REPORT DOCUMENTATION PAGE	Form Approved OMB No. 0704-0188
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comment of information, including suggestions for reducing this burden to Washington Headquarters Service, Directorate for Info 1215 Jefferson Davis Highway, Suite 1204, Artington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188) Washington, DC 20503.	 for reviewing instructions, searching data sources, its regarding this burden estimate or any other aspect of this collection smation Operations and Reports,
PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.	2 DATES COVEDED (From Ta)
1. REPORT DATE (DD-MM-YYYY) 2. REPORT DATE	3. DATES COVERED (From - To)
4. TITLE AND SUBTITLE	1 May 1998 - 31 Dec. 1999
Harvesting Energy from Redox Potential Gradient	
in Sediments and Soils	-5
in Sediments and Solls	5b. GRANT NUMBER
	N00014-98-1-0690
	5c. PROGRAM ELEMENT NUMBER
S. AUTHOR(S)	5d. PROJECT NUMBER
Reimers, Clare, E.	
Kermers, Grafe, E.	5e. TASK NUMBER
	5f. WORK UNIT NUMBER
. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)	8. PERFORMING ORGANIZATION
Institute of Marine and Coastal Sciences	REPORT NUMBER
Rutgers, The State University of New Jersey	
71 Dudley Road	
New Brunswick, NJ 50000 SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)	10. SPONSOR/MONITOR'S ACRONYM(S)
Office of Naval Research	
800 N. Quincy St.	
Arlington, VA 22217-5000	11. SPONSORING/MONITORING AGENCY REPORT NUMBER
2. DISTRIBUTION AVAILABILITY STATEM DISTRIBUTION STATEM	TENTA
Approved for Public Re	
Distribution Unlimited Distribution Unlimited	
	30
3. SUPPLEMENTARY NOTES	
4. ABSTRACT	
	odes, one embedded in marine sedime
Pairs of platinum mesh or graphite fiber electro	
Pairs of platinum mesh or graphite fiber electre (anode), the other in proximal seawater (cathod	e), have been used to harvest low
Pairs of platinum mesh or graphite fiber electr (anode), the other in proximal seawater (cathod levels of power from natural, microbe establish	e), have been used to harvest low ed, voltage gradients at marine
Pairs of platinum mesh or graphite fiber electr (anode), the other in proximal seawater (cathod levels of power from natural, microbe establish sediment _{$\overline{2}$} seawater interfaces. The sustained power	e), have been used to harvest low ed, voltage gradients at marine wer harvested has been on the order
Pairs of platinum mesh or graphite fiber electr (anode), the other in proximal seawater (cathod levels of power from natural, microbe establish sediment $\overline{2}$ seawater interfaces. The sustained pow 0.01 W/m of electrode geometric area but is dep	e), have been used to harvest low ed, voltage gradients at marine wer harvested has been on the order pendent on electrode design, sedime:
Pairs of platinum mesh or graphite fiber electr (anode), the other in proximal seawater (cathod levels of power from natural, microbe establish sediment _{$\overline{2}$} seawater interfaces. The sustained power	e), have been used to harvest low ed, voltage gradients at marine wer harvested has been on the order pendent on electrode design, sedime hat the sediment/anode - seawater/
Pairs of platinum mesh or graphite fiber electr (anode), the other in proximal seawater (cathod levels of power from natural, microbe establish sediment ₂ seawater interfaces. The sustained pow 0.01 W/m of electrode geometric area but is dependent composition, and temperature. It is proposed to	e), have been used to harvest low ed, voltage gradients at marine wer harvested has been on the order pendent on electrode design, sedime hat the sediment/anode - seawater/ uel cell in which power results
(anode), the other in proximal seawater (cathod levels of power from natural, microbe establish sediment $\frac{1}{2}$ seawater interfaces. The sustained pow 0.01 W/m ² of electrode geometric area but is dep composition, and temperature. It is proposed the cathode configuration constitutes a microbial for	e), have been used to harvest low ed, voltage gradients at marine wer harvested has been on the order pendent on electrode design, sedime hat the sediment/anode - seawater/ uel cell in which power results
Pairs of platinum mesh or graphite fiber electr (anode), the other in proximal seawater (cathod levels of power from natural, microbe establish sediment $\overline{2}$ seawater interfaces. The sustained pow 0.01 W/m ² of electrode geometric area but is de composition, and temperature. It is proposed to cathode configuration constitutes a microbial for from the net oxidation of sediment organic matter	e), have been used to harvest low ed, voltage gradients at marine wer harvested has been on the order pendent on electrode design, sedime hat the sediment/anode - seawater/ uel cell in which power results
Pairs of platinum mesh or graphite fiber electr (anode), the other in proximal seawater (cathod levels of power from natural, microbe establish sediment $\overline{2}$ seawater interfaces. The sustained pow 0.01 W/m ² of electrode geometric area but is de composition, and temperature. It is proposed to cathode configuration constitutes a microbial for from the net oxidation of sediment organic matter	e), have been used to harvest low ed, voltage gradients at marine wer harvested has been on the order pendent on electrode design, sedimen hat the sediment/anode - seawater/ uel cell in which power results er by dissolved seawater oxygen.
Pairs of platinum mesh or graphite fiber electr (anode), the other in proximal seawater (cathod levels of power from natural, microbe establish sediment ₂ seawater interfaces. The sustained pow 0.01 W/m ² of electrode geometric area but is de composition, and temperature. It is proposed the cathode configuration constitutes a microbial for from the net oxidation of sediment organic matter 5. SUBJECT TERMS marine sediment, fuel cell, electrode, redox por estimates a subject to the sediment of the sediment of the sediment sediment, fuel cell, electrode, redox por	e), have been used to harvest low ed, voltage gradients at marine wer harvested has been on the order pendent on electrode design, sedimen hat the sediment/anode - seawater/ uel cell in which power results er by dissolved seawater oxygen.
Pairs of platinum mesh or graphite fiber electr (anode), the other in proximal seawater (cathod levels of power from natural, microbe establish sediment ₂ seawater interfaces. The sustained por 0.01 W/m of electrode geometric area but is de composition, and temperature. It is proposed to cathode configuration constitutes a microbial for from the net oxidation of sediment organic matter 5. SUBJECT TERMS marine sediment, fuel cell, electrode, redox por S. SECURITY CLASSIFICATION OF: 17. LIMITATION OF ABSTRACT 18. NUMBER OF PAGES	e), have been used to harvest low ed, voltage gradients at marine wer harvested has been on the order pendent on electrode design, sedimer hat the sediment/anode - seawater/ uel cell in which power results er by dissolved seawater oxygen. tential, microbial
Pairs of platinum mesh or graphite fiber electr (anode), the other in proximal seawater (cathod levels of power from natural, microbe establish sediment ₂ seawater interfaces. The sustained por 0.01 W/m of electrode geometric area but is de composition, and temperature. It is proposed to cathode configuration constitutes a microbial for from the net oxidation of sediment organic matter 5. SUBJECT TERMS marine sediment, fuel cell, electrode, redox por S. SECURITY CLASSIFICATION OF: 17. LIMITATION OF 18. NUMBER OF PAGES	e), have been used to harvest low ed, voltage gradients at marine wer harvested has been on the order pendent on electrode design, sedimer hat the sediment/anode - seawater/ uel cell in which power results er by dissolved seawater oxygen. tential, microbial
Pairs of platinum mesh or graphite fiber electr (anode), the other in proximal seawater (cathod levels of power from natural, microbe establish sediment ₂ seawater interfaces. The sustained por 0.01 W/m of electrode geometric area but is de composition, and temperature. It is proposed to cathode configuration constitutes a microbial for from the net oxidation of sediment organic matter 5. SUBJECT TERMS marine sediment, fuel cell, electrode, redox por S. SECURITY CLASSIFICATION OF: 17. LIMITATION OF ABSTRACT 18. NUMBER OF PAGES	e), have been used to harvest low ed, voltage gradients at marine wer harvested has been on the order pendent on electrode design, sedimer hat the sediment/anode - seawater/ uel cell in which power results er by dissolved seawater oxygen. tential, microbial 19a. NAME OF RESPONSIBLE PERSON Clare E. Reimers

20010831 089

2

•

Final Report

GRANT #: N00014-98-1-0690

. .

PRINCIPAL INVESTIGATOR: Clare E. Reimers

INSTITUTION: Rutgers, The State University of New Jersey

<u>GRANT TITLE</u>: Harvesting Energy from Redox Potential Gradients in Sediments and Soils

AWARD PERIOD: 1 May 1998 - 31 December 1999

<u>OBJECTIVE</u>: To harvest on the order of 1 Watt of electrical power from depth-dependent potential gradients in natural marine sediments and saturated soils; to use this energy source to continuously power small, unattended, sensor systems in remote environments.

<u>APPROACH</u>: Pairs of platinum mesh or graphite fiber electrodes were placed across sediment-seawater interfaces created in laboratory aquaria. After an equilibration time of a few days, voltages and currents sustained by these twoelectrode devices under variable loads were monitored for experimental periods ranging from minutes to months. The sediments and the circulating aerated overlying seawater were electrochemically characterized by profiling (adjacent to the devices) with Pt-redox, voltammetric and pH microelectrodes and sampled with 7.5 cm diameter core tubes. The cored sediments were sectioned into vertical intervals of 0.25-0.5 cm under N_2 , and the pore waters extracted for chemical analyses of a number of reduced species such as sulfide and ammonia.

<u>ACCOMPLISHMENTS</u>: The amount of sustainable power harvested during the experiments of this grant period was ~0.01 W/m² of electrode geometric area. However this power was found to be dependent on electrode design, sediment composition and temperature. A working model for the observed power generation proposes that two electrode cells, straddling the sediment-seawater interface, depend on a net oxidation of sediment organic matter by dissolved seawater oxygen. Further, half-cell reactions may be catalyzed by sediment microbes and mediated by one or more secondary electrontransfer mediator (such as dissolved sulfide in the sediment pore water).

<u>CONCLUSIONS</u>: The concept of harvesting power from a fuelcell device at the sediment-seawater interface has been proven in the laboratory. Ongoing investigations will focus on identifying electrode reactions, understanding microbial involvement, optimizing electrodes with respect to power density, and examining prototype devices interfaced with environmental sensors in natural marine settings. <u>SIGNIFICANCE</u>: Our studies have demonstrated that low levels of power can be harvested from natural, microbe established, voltage gradients at marine sediment-seawater interfaces. Optimized power supplies based on this phenomenon could be developed to power autonomous marine-deployed instrumentation such as hydrophones and chemical sensors.

<u>PATENT INFORMATION</u>: A patent application related to using two electrode devices to harvest power from seafloor potential gradients has been filed.

PUBLICATIONS AND ABSTRACTS:

1 14

Reimers, C.E. and Tender, L. M. (1999) A fuel cell for harvesting power from the marine sediment-water interface. EOS 80(49), OS76.

Tender, L.M., Reimers, C.E., Fertig, S. and Wang, W. (2000) Harvesting energy from natural benthic voltage gradients. 198th meeting of the Electrochemical Society, Phoenix, AZ.

Reimers, C.E., Tender, L.M., Fertig, S., and Wang, W. (2001) Harvesting energy from the marine sediment-water interface. Environ. Sci. Technol. 35, 192-195.