

# REPORT DOCUMENTATION PAGE

*Form Approved*  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. **PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.**

<b>1. REPORT DATE (DD-MM-YYYY)</b> 28 Nov 2000		<b>2. REPORT TYPE</b> Abstract		<b>3. DATES COVERED (From - To)</b> 28 Nov 2000	
<b>4. TITLE AND SUBTITLE</b> In-Situ acoustic and laboratory ultrasonic sound speed and Attenuation measured in heterogeneous seabed sediments: Eel Margin, CA				<b>5a. CONTRACT NUMBER</b>	
				<b>5b. GRANT NUMBER</b>	
				<b>5c. PROGRAM ELEMENT NUMBER</b> 062435N	
<b>6. AUTHOR(S)</b> Michael D. Richardson, Kevin B. Briggs, T.J. Gorgas, R.H. Wilkens, N.L. Frazer, H. Lee				<b>5d. PROJECT NUMBER</b>	
				<b>5e. TASK NUMBER</b>	
				<b>5f. WORK UNIT NUMBER</b>	
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> Naval Research Laboratory Marine Geosciences Division Stennis Space Center, MS 39529-5004				<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>  AB/7430-00-2007	
<b>9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> Office of Navy Research 800 N. Quincy St. Arlington, VA 22217-5000				<b>10. SPONSOR/MONITOR'S ACRONYM(S)</b>	
				<b>11. SPONSOR/MONITOR'S REPORT NUMBER(S)</b>	
<b>12. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for Public Release; Distribution Unlimited					
<b>13. SUPPLEMENTARY NOTES</b>					
<b>14. ABSTRACT</b> <p><b>AB:</b> We calculated in-situ and laboratory measurements of sound speed and attenuation in seafloor sediments from the shallow water delta of the Eel River, California. This region receives a substantial volume of fluvial sediment that is discharged annually onto the shelf. Additionally, high input of fluvial sediments during storms generates flood deposits characterized by thin-beds of variable grain-sizes in water depths between 40 and 90 m. Main objectives of this study were (1) to investigate signatures of seafloor processes on geoacoustic and physical properties, and (2) to evaluate differences between geoacoustic parameters measured in-situ at acoustic (7.5 kHz) and in the laboratory at ultrasonic (400 kHz) frequencies. The in-situ acoustic measurements were conducted between the 60 and 100 isobath. Wet-bulk density and porosity profiles were obtained to 1.15 meters below seafloor (mbsf) using gravity cores of the mostly cohesive fine-grained sediments across- and along-shelf. Our physical and geoacoustic property measurements from six selected sites on the Eel margin showed: (1) Sound speed and wet-bulk density strongly correlated.</p>					
<b>15. SUBJECT TERMS</b> In-situ, attenuation, heterogeneous seabed sediments, Eel Margin, CA, sound speed					
<b>16. SECURITY CLASSIFICATION OF:</b> Abstract Unclassified			<b>17. LIMITATION OF ABSTRACT</b>  SAR	<b>18. NUMBER OF PAGES</b>  1	<b>19a. NAME OF RESPONSIBLE PERSON</b> Michael Richardson
<b>a. REPORT</b> Unclassified	<b>b. ABSTRACT</b> Unclassified	<b>c. THIS PAGE</b> Unclassified			<b>19b. TELEPHONE NUMBER (include area code)</b> 228-688-4621

Standard Form 298 (Rev. 8-98)  
Prescribed by ANSI Std. Z39.18

20010907 073

SC: T  
MN: Fall Meeting 2000

HR: 0830h  
AN: T61A-10

TI: **In-situ Acoustic and Laboratory Ultrasonic  
Sound Speed and Attenuation Measured in  
Heterogeneous Seabed Sediments: Eel Margin,  
California**

AU: \* Gorgas, T J  
EM: tgorgas@soest.hawaii.edu  
AF: T.J. Gorgas, Department of Geology and Geophysics, University of  
Hawaii, 1680 East-West Road, Honolulu, HI 96822 United States

AU: Wilkens, R H  
EM: Roy.Wilkens@onr.navy.mil  
AF: R.H. Wilkens, Hawaii Institute of Geophysics and Planteology,  
University of Hawai'i, 2525 Correa Road Stennis Space Center, Honolulu, HI  
96822 United States

AU: Fu, S  
EM: ssfu@soest.hawaii.edu  
AF: R.H. Wilkens, Hawaii Institute of Geophysics and Planteology,  
University of Hawai'i, 2525 Correa Road Stennis Space Center, Honolulu, HI  
96822 United States

AU: Frazer, N L  
EM: neil@soest.hawaii.edu  
AF: T.J. Gorgas, Department of Geology and Geophysics, University of  
Hawaii, 1680 East-West Road, Honolulu, HI 96822 United States

AU: Richardson, M D  
EM: mike.richardson@nrlssc.navy.mil  
AF: Mike D. Richardson, Marine Geosciences Division, Naval Research  
Laboratory, Stennis Space Center, Stennis, MS 39529-500 United States

AU: Briggs, K B  
EM: kevin.briggs@nrlssc.navy.mil  
AF: Mike D. Richardson, Marine Geosciences Division, Naval Research  
Laboratory, Stennis Space Center, Stennis, MS 39529-500 United States

AU: Lee, H  
AF: H. Lee, Department of Geology and U.S. Geological Survey; Mail  
Stop 999, 345 Middlefield Road, MS 999, Menlo Park, CA 94025 United States

AB: We calculated in-situ and laboratory measurements of sound speed and attenuation in seafloor sediments from the shallow water delta of the Eel River, California. This region receives a substantial volume of fluvial sediments during storms generates flood deposits characterized by thin-beds of variable grain-sizes in water depths between 40 and 90 m. Main objectives of this study were (1) to investigate signatures of seafloor processes on geoacoustic and physical properties, and (2) to evaluate differences between geoacoustic parameters measured in-situ at acoustic (7.5 kHz) and in the laboratory at ultrasonic (400 kHz) frequencies. The in-situ acoustic measurements were conducted between the 60 and 100 isobath. Wet-bulk density and porosity profiles were obtained to 1.15 meters below seafloor (mbsf) using gravity cores of the mostly cohesive fine-grained sediments across- and along-shelf. Our physical and geoacoustic property measurements from six selected sites on the Eel margin showed: (1) Sound speed and wet-bulk density strongly correlated. (2) In most cases, sediment compaction with depth led to increased sound speed and density and decreased porosity and in-situ attenuation values. (3) Scattering effects due to inhomogeneities caused higher ultrasonic attenuation when

measured in coarse-grained sediments. (4) Sound speed was higher in coarser- than finer-grained sediments on an average by 80  $\text{msec}^{-1}$ . (5) In coarse-grained sediments higher sound speed was measured in the laboratory (1560  $\text{msec}^{-1}$ ) than in-situ (1520  $\text{msec}^{-1}$ ). In contrast, average ultrasonic and in-situ sound speed in fine-grained sediments showed only little differences (both approx. 1480  $\text{msec}^{-1}$ ). (6) Higher attenuation was commonly measured in the laboratory (0.4 and 0.8  $\text{dBm}^{-1}\{\text{kHz}\}^{-1}$ ) than in-situ (0.02 and 0.65  $\text{dBm}^{-1}\{\text{kHz}\}^{-1}$ ), and remained almost constant below 0.4 mbsf. We attributed discrepancies between laboratory ultrasonic and in-situ acoustic measurements to frequency dependence of velocity and attenuation. In addition, laboratory attenuation was most likely enhanced due to scattering of sound waves at heterogeneities that were on the scale of ultrasonic wavelengths, while high in-situ attenuation values were linked to stratigraphic scattering at thin-bed layers that form along with flood deposits.

DE: 4219 Continental shelf processes  
SC: T  
MN: Fall Meeting 2000

HR: 0830h  
AN: T61A-01

TI: **Intricate BSR and Bright Spot distribution of the Yaquina Forearc Basin, Peru**

AU: \* Huebscher, C P  
EM: huebscher@dkrz.de  
AF: University of Hamburg, Bundesstrasse 55, Hamburg, 20146  
Germany

AU: Greinert, J  
EM: jgreinert@geomar.de  
AF: GEOMAR, Wischhofstrasse 1-3, Kiel, 24148 Germany  
AU: Kukowski, N  
EM: nina@gfz-potsdam.de  
AF: GeoForschungsZentrum GFZ, Telegrafenberg, Potsdam, 14473  
Germany

AU: Pecher, I A  
EM: ingo@ig.utexas.edu  
AF: University of Texas, 412 Spicewood Springs Rd., Bldg. 600, Austin, tx 78759-8500 United States

AU: Wagner, M  
AF: University of Hamburg, Bundesstrasse 55, Hamburg, 20146  
Germany

AU: Bialas, J  
EM: jbialas@geomar.de  
AF: GEOMAR, Wischhofstrasse 1-3, Kiel, 24148 Germany

AB: In order to study the interaction between BSR occurrence, gas abundance, tectonic uplift, and sedimentation in the Yaquina Basin we carried out a high-resolution reflection seismic survey in the frame of the GEOPECO project (SONNE Leg 146). The Yaquina Basin is located between 8 deg. S and 10 deg. S on the mid-slope of the Andean Continental Margin. This part of the Peruvian Margin has undergone tectonic uplift and, subsequently subsidence by the oblique subduction of the Nazca Ridge. The seismic lines were tied to the ODP sites of Leg 112, which allows correlation between seismic data and core stratigraphy. We used GI-Gun sources to avoid misinterpretations due to bubble generation. The most striking observations have been made at the widest part of the basin at 8 deg. 30 min. S in water depth of about 900 m. Perpendicular to the slope a bright spot changes abruptly into a weak BSR. Several disrupted bright spots are resolved some 10 ms beneath the BSR, indicating strong vertical