



TEAM

FUZZING

SEI

DAYRON

KDI

RAYMOND

www.teamfuzzing.com

Report Documentation Page

Report Date 16Apr2001	Report Type N/A	Dates Covered (from... to) -
Title and Subtitle Mitigation of FMU-139 Component Obsolescence	Contract Number	
	Grant Number	
	Program Element Number	
Author(s) Minnich, John N.; Lewis, Ted	Project Number	
	Task Number	
	Work Unit Number	
Performing Organization Name(s) and Address(es) KDI Electrical Engineer	Performing Organization Report Number	
Sponsoring/Monitoring Agency Name(s) and Address(es) NDIA (National Defense Industrial Association) 211 Wilson BLvd., Ste. 400 Arlington, VA 22201-3061	Sponsor/Monitor's Acronym(s)	
	Sponsor/Monitor's Report Number(s)	
Distribution/Availability Statement Approved for public release, distribution unlimited		
Supplementary Notes Proceedings from The 45th Annual Fuze Conference, 16-18 April 2001 Sponsored by NDIA, The original document contains color images.		
Abstract		
Subject Terms		
Report Classification unclassified	Classification of this page unclassified	
Classification of Abstract unclassified	Limitation of Abstract UU	
Number of Pages 19		



TEAM FUZING

Programme Objectives

- Obsolescence
- Tooling
- Test Gear
- Safety
- Reliability
- Qualification
- 1st Article
- Production



SEI

DAYRON

KDI

RAYMOND






TEAM FUZING

Qualification Programme

Sub System Tests



SEI

DAYRON

KDI

RAYMOND





TEAM FUZING

FMU-139B/B

- Further contract for 3000 FMU139B/B fuzes for a European country.
- Need to address the Power consumption issue to meet the FFCS requirement for the Navy.
- Potential further orders for other European and Middle/Far East Countries.



SEI

DAYRON

KDI

RAYMOND





TEAM FUZING

FMU-139 B/B



SEI

DAYRON

KDI

RAYMOND



Mitigation of FMU-139 Component Obsolescence

John N. Minnich, KDI Electrical Engineer

Ted Lewis, KDI Sr. Staff Engineer



SEI

DAYRON

KDI

RAYMOND



FMU-139 Chronology

- FMU-139A/B
 - Full scale procurement commenced in 1985
 - Last procurement was in 1993
- SAU - A FMU-139A/B derivative
 - Original build circa 1989-1992
 - Team Fuzing awarded contract in 1999, delivered units in 2000.



SEI

DAYRON

KDI

RAYMOND



Two Major Design Challenges

- Replacing the obsolete 4-bit microcontroller.
 - Reverse engineering the logic without source code.
- Improving the operating duration when powered in FFCS mode.



SEI

DAYRON

KDI

RAYMOND



Replacing the Microcontroller

- FMU-139 A/B based upon COP320C
 - 4 bit, CMOS design
 - Industrial temp range (-40 °C to 85 °C)
 - Low current: 100 μ A at 5V with $f_{clk} = 32$ KHz
- KDI evaluated 8-bit μ controllers and FPGAs
 - Architecture A: 8-bit μ controller + ASIC
 - Architecture B: Two FPGAs / ASICs



SEI

DAYRON

KDI

RAYMOND



Reverse engineering the fuze logic.

- Drawing package did not include source code.
 - ROM Object code available as printed media only !
- KDI attempted to reverse assemble this ROM
 - Output is uncommented assembly code.
 - Output appeared to have reverse assembly errors.
- KDI abandoned the μ controller approach due to these issues.



SEI

DAYRON

KDI

RAYMOND



What legacy documentation was available to KDI?

- FMU-139A/B Mil. spec. MIL-F-85815A(AS)
 - FFCS and Turbine operating modes
 - High & low drag arm times
 - Impact or proximity detection requirements
 - Impact or Prox function delay timing
- Navy DWG package 1379ASxxx
- SAU DWG package SK105xxxx



SEI

DAYRON

KDI

RAYMOND



What information was missing ?

- Drawing package did not include source code.
 - Internal self tests
 - Detailed DUD logic requirements
 - Digital filtering / signal conditioning of inputs

To address these “holes” KDI requested a Commercial Service Agreement with the Navy



SEI

DAYRON

KDI

RAYMOND



SAU Implementation

- 2 FPGAs replace the μ controller and ASIC
 - FPGA, U₄₀₂ initiates Gag rod and DET circuitry
 - FPGA, U₄₀₁ initiates Bellows circuitry
- Switching regulator based on FMU-139 A/B
“JANTX” implementation rather than SAU
- Components are predominantly “through-hole”



SEI


DAYRON

KDI


RAYMOND



FPGA Partitioning



SAU Production Panel



FMU-139B/B Implementation

- 2 ASICs replace the SAU FPGAs
- KDI improved the switching regulator
 - Higher efficiency toroidal inductor
 - All 3 select resistors eliminated
- Components are predominantly surface mount



SEI


DAYRON

KDI

RAYMOND



FMU-139 B/B Prototype Panel



FFCS Mode Energy Balance

$$\frac{1}{2} C_1 V_1^2 = \frac{3}{2} C_2 V_2^2 + (V_{\text{bus}}) (i_{\text{ave}}) (t)$$

C1 → Main energy storage capacitor

C2 → PAF capacitor

Let: $C_1 = 4.0 \mu\text{F}$, $C_2 = 47 \mu\text{F}$

$V_1 = 195$, $V_2 = 9$, $V_{\text{bus}} = 3.8$

For: $t = 60$ seconds, $i_{\text{ave}} = 308 \mu\text{A}$



SEI

DAYRON

KDI

RAYMOND





TEAM FUZING

Benefits of the Team Fuzing Design Changes

- Operating duration when powered in FFCS mode exceeds the original FMU-139 A/B
- Extended operating duration facilitates higher altitude bomb release
- Modern and reliable manufacturing process.
- Potential cost reduction.
- Based on proven design.



SEI

DAYRON

KDI

RAYMOND

