# **AFRL-ML-WP-TP-2002-407**

# HIGH TEMPERATURE COMPOSITES Work Unit Directive (WUD) 53

**Ronald J. Kerans** 



Approved for public release; distribution is unlimited.

This material is declared a work of the U.S. Government and is not subject to copyright protection in the United States.

# 20030121 119

# MATERIALS AND MANUFACTURING DIRECTORATE AIR FORCE RESEARCH LABORATORY AIR FORCE MATERIEL COMMAND WRIGHT-PATTERSON AIR FORCE BASE, OH 45433-7750



#### NOTICE

WHEN GOVERNMENT DRAWINGS, SPECIFICATIONS, OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY GOVERNMENT-RELATED PROCUREMENT, THE UNITED STATES GOVERNMENT INCURS NO RESPONSIBILITY OR ANY OBLIGATION WHATSOEVER. THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA, IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE IN ANY MANNER CONSTRUED, AS LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR AS CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE, OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

THIS REPORT IS RELEASABLE TO THE NATIONAL TECHNICAL INFORMATION SERVICE (NTIS). AT NTIS, IT WILL BE AVAILABLE TO THE GENERAL PUBLIC, INCLUDING FOREIGN NATIONS.

THIS TECHNICAL REPORT HAS BEEN REVIEWED AND IS APPROVED FOR PUBLICATION.

RÓNALD J. KERANS Ceramics Branch Metals, Ceramics & NDE Division

ALLAN P. KATZ, Chief Ceramics Branch Metals, Ceramics & NDE Division

WALTER M. GRIFFITH, Chief Metals, Ceramics & NDE Division Materials & Manufacturing Directorate

IF YOUR ADDRESS HAS CHANGED, IF YOU WISH TO BE REMOVED FROM OUR MAILING LIST, OR IF THE ADDRESSEE IS NO LONGER EMPLOYED BY YOUR ORGANIZATION, PLEASE NOTIFY, AFRL/MLLN, WRIGHT-PATTERSON AFB OH 45433-7817 TO HELP US MAINTAIN A CURRENT MAILING LIST.

COPIES OF THIS REPORT SHOULD NOT BE RETURNED UNLESS RETURN IS REQUIRED BY SECURITY CONSIDERATIONS, CONTRACTUAL OBLIGATIONS, OR NOTICE ON A SPECIFIC DOCUMENT.

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
The public reporting burden for this collection of information is sources, gathering and maintaining the data needed, and com information, including suggestions for reducing this burden, to Davis Highway, Suite 1204, Artington, VA 22202-4302. Resp collection of information if it does not display a currently valid	pleting and reviewing the collection Department of Defense, Washingto ordents should be aware that notwit	of information. Send comr n Headquarters Services, I hstanding any other provis	ments regarding this Directorate for Inforn ion of law, no persor	burden estimate or any other aspect of this collection of nation Operations and Reports (0704-0188), 1215 Jefferson shall be subject to any penalty for failing to comply with a	
1. REPORT DATE (DD-MM-YY)	2. REPORT TYPE		3. DA	TES COVERED (From - To)	
September 2002	Bibliography		10	0/01/1995 - 09/03/2002	
4. TITLE AND SUBTITLE HIGH TEMPERATURE COMPOSITES Work Unit Directive (WUD) 53				5a. CONTRACT NUMBER IN-HOUSE	
			F	5b. GRANT NUMBER	
			-	5c. PROGRAM ELEMENT NUMBER 61102F	
				5d. PROJECT NUMBER	
6. AUTHOR(S)				2306	
Ronald J. Kerans				2300 5e. TASK NUMBER	
			BW		
				5f. WORK UNIT NUMBER	
				0P 8. PERFORMING ORGANIZATION	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)				REPORT NUMBER	
Ceramics Branch (MLLN)				AFRL-ML-WP-TP-2002-407	
Metals, Ceramics & Nondestructive Evaluation Division					
Materials and Manufacturing Directorate Air Force Research Laboratory, Air Force Materiel Command					
Wright-Patterson AFB, OH 45433-7750					
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSORING/MONITORING AGENCY	
Materials and Manufacturing Directorate				ACRONYM(S)	
Air Force Research Laboratory				AFRL/MLLN	
Air Force Materiel Command			F	11. SPONSORING/MONITORING AGENCY	
Wright-Patterson AFB, OH 45433-7750				REPORT NUMBER(S) AFRL-ML-WP-TP-2002-407	
12. DISTRIBUTION/AVAILABILITY STATEM	ENT	• • • • • • • • • • • • • • • • • • •			
Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES					
This material is declared a work of the U.S. Government and is not subject to copyright protection in the United States.					
This technical paper contains a summary of the technical effort and a bibliography.					
14. ABSTRACT					
There were numerous interrelated issues that were addressed as a part of the composite interface control effort. Crack deflection is a					
complex function of the fracture properties of the constituents. Hence, in addition to designed oxide coatings for both oxide and non-					
oxide fibers, substantial activity has pursued understanding and controlling fiber degradation, isolating and understanding aspects of the					
failure process, designing processes, and tests that provide definitive criteria for evaluation. These efforts have resulted in the					
identification and solution of a persistent and pervasive problem with fiber degradation during coating. This has finally enabled					
evaluation of the coatings in real composites made both in-house and as part of numerous collaborations with industry, academe, and					
other government laboratories. This in turn led to the recent definitive proof of the viability of oxide coating approaches in real					
composites. With this recent definitive demonstration of oxide coating viability, the specific focus is shifting towards understanding how best to design the overall composite system to best employ the new coatings. The word "design" is used in the sense of the choice of the					
basic constituents of the composites and the choice and execution of the nano and microstructures of the constituents, and the micro and					
macrostructures of the composites.					
15. SUBJECT TERMS					
Ceramics, High Temperature Composites					
16. SECURITY CLASSIFICATION OF:	17. LIMITATION	18. NUMBER	19a. NAME C	F RESPONSIBLE PERSON (Monitor)	
				Ronald J. Kerans	
Unclassified Unclassified Unclassifi	ed SAR	20		ONE NUMBER (Include Area Code)	
	<u> </u>		(937)2	55-9823 Standard Form 298 (Rev. 8-98)	
HES&S 31-15093-1				Prescribed by ANSI Std. Z39-18	
		•			

# Ceramics Research Group WUD 53 (AFOSR Task 2306BL) Final Report August 2002

# Ronald J. Kerans Ceramics Research Group WUD 53 Leader High Temperature Composites Task Leader

#### **1. INTRODUCTION AND BACKGROUND**

The ability to exploit the unique balance of properties offered by the wide variety of compounds and mixtures of compounds that fall under the heading of ceramics has enabled many technological changes, and will enable many more in coming years. The microelectronic revolution, or "Silicon Age", would not be possible without the concurrent advances in ceramic substrate materials and processing. The future of "smart materials" will depend heavily on advanced ceramic systems, as will micromachines for high temperature and chemically aggressive environments. One of the most pervasive and attractive, yet most elusive, objectives has been use of ceramics in high temperature structural applications. The higher operating temperatures thereby enabled will provide substantial increases in efficiency and performance with reduced environmental impact.

The primary problem has been the low fracture toughness that comes with the array of more attractive properties of monolithic ceramics. This problem was effectively dealt with by the introduction of continuous-fiber ceramic composites. However, the toughness of composites was found to be dependent on controlled low-strength fiber-matrix interfaces, which was in turn dependent on fiber coatings that unfortunately also imparted environmental resistance problems. There were also problems with the stability of the fibers themselves; however, while there is still room for improvement, significant progress on improved fibers has been made. The Ceramics Group chose to focus effort on the problem of oxidation resistant interface control. This was both the most difficult problem -- probably requiring a long term, comprehensive attack -- and the one receiving the least attention.

There are numerous interrelated issues that must be addressed as part of the composite interface control effort. The crack deflection event has a complex dependence on the fracture properties of the constituents. Hence, in addition to designed oxide coatings for both oxide and non-oxide fibers, substantial activity has pursued understanding and controlling fiber degradation, isolating and understanding aspects of the failure process, designing processes and tests that provide definitive criteria for evaluation. We strive to focus our attack on basic issues that make a permanent contribution to the literature in ways that are more broadly meaningful than simply composite development. We have built the capabilities to meaningfully address these issues and have become the world leaders in this effort. Recently, progress has become quite rapid and we hope to see significant transition to practice in the near future.

# **OBJECTIVE**

The overall objective of the Ceramics Research Group is to provide the key missing scientific links necessary to enable the development of new materials systems for applications of major importance to the Air Force. Our current objective is the establishment of the foundation of knowledge and understanding to enable the development of fibrous ceramic composites with properties that sum to no less than a revolution high temperature materials.

# 3. APPROACH

(a) Deduce and evaluate approaches to oxidation resistant control of the fiber/matrix interface.

(b) Determine factors controlling mechanical response of brittle-matrix composites through interactive theoretical and experimental studies in mechanics.

(c) Determine strategies for the design and practical fabrication of high temperature composites.

(d) Design and evaluate innovative microstructures for tough "in-situ" composites.

## 4. RESULTS

## 4.1 Summary

There are numerous interrelated issues that are being addressed as part of the composite interface control effort. Crack deflection is a complex function of the fracture properties of the constituents. Hence, in addition to designed oxide coatings for both oxide and non-oxide fibers, substantial activity has pursued understanding and controlling fiber degradation, isolating and understanding aspects of the failure process, designing processes and tests that provide definitive criteria for evaluation.

These efforts have resulted in the identification and solution of a persistent and pervasive problem with fiber degradation during coating. This has finally enabled evaluation of the coatings in real composites made both in-house and as part of numerous collaborations with industry, academe and other government laboratories. This in turn led to the recent definitive proof of the viability of oxide coating approaches in real composites.

With this recent definitive demonstration of oxide coating viability, the specific focus is shifting towards understanding how best to design the overall composite system to best employ the new coatings. The word "design" is used in the sense of the choice of the basic constituents of the composites and the choice and execution of the nano and microstructures of the constituents, and the micro and macrostructures of the composites.

Collaborative research with the Combustion Research Group of PRSF has indicated that oxideoxide composites are viable candidates, with respect to the most basic requirements, for an

innovative new turbine engine combustor, but will require careful design to control thermal stresses. This work has been considering current technology coatingless composites, but coated-fiber composites will be introduced as appropriate. This work has led to several innovations (including one patent, one patent pending) on materials approaches to thermal stress control.

#### 4.2 Narrative

The following narrative attempts to touch on a few high points and give a flavor for the nature and overall flow of the work done. It is by no means comprehensive, sacrifices rigor for brevity and is meant to provide context for the accompanying bibliography and the review.

Our early research in this area was concentrated in three areas: identification of the required coating properties and associated governing mechanics, identification of viable coating schemes, and coating processing by solution chemistry and CVD. This work was successful in establishing criteria that coatings must meet and in developing the science base to measure them. It was also successful in identifying and screening numerous concepts and in establishing potential viability of several. Furthermore, it was successful in developing a new, practical, solution-based process for coating fiber tows (subject of several patents).

The first of these areas, measurement and interpretation of interface properties, provides an example of the synergistic interaction between analytical and experimental work. It is also a fine example of the power of asking the right question. We developed an analytical model for fiber pushout/pullout behavior while simultaneously devising an experimental protocol. When we compared friction values obtained from two different regions of the experiment with one derived using the model, they were significantly different. We initially suspected the model, but eventually asked the right question: Suppose both values are correct? That led us to postulate a progressive contribution of roughness to the friction, which was immediately borne out by an inspired experiment devised by Dr. Jero; again growing out of the discussions comparing experiments and models.

A second model addressing progressive roughness produced yet another fine example of the power of concurrent modeling and experiment. This analysis predicted significantly different pushout load-deflection curves for some cases, but such curves had never been reported or observed in our lab. Subsequently collaborators at the University of Bordeaux were found to be enthusiastic about a new family of composites with higher than usual interfacial friction and very good composite properties, but perplexing pushout curves. A variation of our analysis fully explained the curves and enabled reduction of data from them. Recent work on Nextel-reinforced Blackglas composites with monazite, BN, or porous  $Zr_xSi_yO$  interfacial coatings demonstrated behavior atypical of conventional composites, but completely consistent with the progressive roughness model. It appears that nearly all of the latest oxide coatings require the progressive roughness analysis to reduce the data to materials properties; hence, the investment in modeling of a postulated phenomenon ultimately paid off well.

A related aspect of this work centered on anticipating issues that would be raised by the substitution of new fiber coatings in composites. We introduced the entire topic of composite design in the sense of adjusting microstructural-level geometry and constituent elastic properties in a complimentary fashion to achieve the desired composite behavior. We also applied these insights to

existing studies and devised simple means to introduce previously overlooked factors into existing models.

As noted above, a number of different approaches to interface control have been evaluated to varying degrees. The fugitive coating concept was demonstrated to be a viable approach for oxide composites, though not without limitations. The sacrifice in off-axis properties was felt to limit possible application and placing the results in the literature was felt to be sufficient transition. Several other approaches had shown promise, but there were lingering questions or significant challenges remaining for most of them. For example, hexaluminates were found to cleave easily enough on basal planes to deflect cracks, and processes to obtain the correct microstructure were developed. However, despite remarkable progress in identifying phase stabilizers to reduce process temperatures, they remain a little too high for the current generation of polycrystalline fibers. By late FY98, it was decided to focus additional effort on a single coating approach and move it to a definitive determination. LaPO<sub>4</sub> monazite, originally proposed by researchers at the Rockwell Science Center, was chosen as being somewhat ahead of other approaches in terms of all aspects of the problem, in part due to our own efforts on the coating process in support of an ML managed DARPA funded activity.

During the course of experimental work on coatings, it was quickly discovered that both oxide and non-oxide ceramic fibers are much less robust to the seemingly relatively benign coating processes than previously thought. This led to a significant research activity investigating the mechanisms of degradation, an inherently interesting and important question, and to the elimination of the problem in coating. Research to identify the source of fiber degradation identified stress-corrosion cracking from vapor phase intermediates during coating as a probable cause. A set of experiments to test this hypothesis was designed. The vapor phase components were determined by mass spectrometry. Fibers were then exposed in a manner mimicking the coating process but with isolated combinations of the gases. Significant differences were observed, but the results do not correspond to straightforward models. Nevertheless, this work led to a new approach involving a refined process leading to a much purer sol, and a new variation of the chemistry. This approach yielded remarkably improved results. The substantial degradation previously observed was completely absent for both oxide and SiC based fibers. The processing/fiber degradation breakthrough was confirmed for LaPO<sub>4</sub> monazite coatings on a wide variety of fibers. Multiple coating passes were found to be effective in obtaining a variety of thicknesses of coating over a realistic range for composite use, and coverage was found to be essentially complete. As noted above, rather than each coating cycle severely degrading the fiber, each pass actually increases the strength. This result is surprising because investigation confirms that it is extremely unlikely that the coating carries significant load. Evaluation of coated-fiber composite performance implies that the coatings may play a significant role in protecting the fibers from forms of environmental degradation that were not even known to exist, and this may be the source of the effect. Research on mechanisms is briefly addressed in a paragraph below.

Surprising room-temperature fiber pushout results reported by RSC researchers led to TEM investigations at ML that uncovered substantial plasticity in LaPO<sub>4</sub> (monazite) coatings. Related results and general questions on the details of debonding and sliding led to an experiment that produced a remarkable sequence of TEM images detailing the entire length of the debonding crack in a partially debonded pushout specimen. This specimen has exploded assumptions about the basic

character of the debonding process in monazite coatings and is providing considerable new insight into the process. Moreover, it is providing abundant evidence for the surprising role of true plasticity via dislocations and deformation twinning. Details of the twinning and dislocation processes have been determined. The analysis of deformation twinning is groundbreaking in that it is the first on such a complex compound and shows that the governing energetic factor is indeed different than in simpler materials.

Dense Nextel<sup>™</sup> 720/monazite/Blackglas<sup>™</sup> minicomposites were fabricated and tensile tested, revealing improved strength over control samples with no interfacial coatings. Although little fiber pullout was seen on the fracture surfaces of these minicomposites, push-in testing demonstrated that the monazite did debond readily. Applying the progressive roughness model to the push-in data revealed a low debond energy (1 J/m<sup>2</sup>), a friction coefficient of 0.2, and an interfacial shear stress in the sliding regime of 18 MPa. The absence of significant pullout lengths may be attributed, in part, to the roughness of the monazite coatings. Nevertheless, the results for this coating continue to be very promising. By the end of FY99 we believed proof-of-principal to be in-hand, though there were no results on true tow-reinforced composites with thin fiber coatings.

In FY00, we began focussing on exploiting the breakthrough in fiber coating to pursue definitive evaluation of new coatings in true composites. Initial focus remained on monazite as the fiber coating. The solution of the fiber degradation problem has proven to be the expected watershed development in that the proper evaluation of oxide coatings is now proceeding at a faster pace. Coated fibers of six different types, two oxides and four SiC based, have been provided to industry, academia and other government labs for incorporation into composites and mini-composites for evaluation of coating performance (Appendix C). This hands-on experience also provides a mechanism for rapid and effective transition of technology. Composites and micro/mini composites have been fabricated in-house to the same end. Internal composite processing research has very recently generated a new system better suited for the evaluation and use of the new coatings. Preliminary results of both internally produced and collaborative composites imply an immediate 100C improvement in composite use temperature, though much refinement will be required to fully exploit the new coatings. Most importantly, these composites have finally provided definitive proof that oxide coatings can perform the vital role of deflecting cracks and activating distributed damage failure in real, yarn reinforced composites.

While the tow coating process is straightforward and relatively economical, cloth/preform coating could bring down the cost of processing durable ceramic composites, and reduce the possibility of coating damage, particularly in complex architectures. We have undertaken several modest exploratory efforts to evaluate approaches to cloth coating. These have included investigations of manipulation of the surface charges on fibers and colloidal particles, and freeze-gelation and sublimation: an innovative process studied in earlier work. However, while there were some promising aspects of the results, they have failed to achieve even modest levels of uniformity and coverage of fibers.

As part of the evaluation of coated fibers, both uncoated and monazite coated Tyranno-SA SiC fibers were exposed to oxidizing conditions. Monazite coated fibers apparently oxidized at a much lower rate than uncoated fibers. The scales were far thinner than accountable by diffusivity in the monazite coating, and far more uniform than the coatings, implying some other mechanism. More rigorous investigation including thermogravimetric analysis (TGA), analytical microscopy and

surface doping has been conducted to confirm the effect and investigate kinetics mechanisms. The evidence points to effects of very dilute fiber dopants that are negated by the coating, but definitive proof of the mechanisms has not yet been obtained. This finding could also be of great importance in areas other than fibrous composites. We have initiated an invention disclosure.

For the last three years we have been engaged in an AFOSR Entrepreneurial Research collaborative program with the AFRL Propulsion and Power Directorate (PRSF) entitled "Ultra Compact Ceramic Combustor (UC<sup>3</sup>)". The ML half has been collaborative with the Behavior & Life Prediction Group and the Mechanics Group. This investigation of an innovative composite combustor and enabling materials led to three innovative ideas for thermal stress control in oxide composites. Two of these led to invention disclosures and, so far, one patent. The activity has moved forward on several parallel fronts. A critical subelement and suitable boundary conditions were identified, and modeled by RG 2.3, in order to evaluate the viability of oxide composites for such applications. For example, it was determined that a single piece shell design would have excessive thermal stresses, but relatively simple design approaches can manage the stresses. For example, a multi-piece approach that breaks the component into three regions spanning smaller temperature differentials reduces the stresses to quite low levels.

The  $UC^3$  activity will finish devising a strategy for the evaluation and introduction of a substantially new material – oxide composites – for a turbine engine part using a much more integrated approach than is convention. It will identify the critical issues and best subelements for benchmark tests. In addition, it will have determined a preliminary conclusion on viability of oxides and a strategy for introduction of suitable composite components.

Related studies have been performing experimental evaluation of the barrier layer and mixed fiber composite approaches to thermal stress management. A patent application was filed on the latter, along with a subsequent one on a broader interpretation of the idea (see hybrid composites below). We have also been active in the task to integrate the simulation activities in the two Directorates. This will greatly facilitate a more integrated approach to materials evaluation and application. Microstructural and mechanistic evaluations have progressed on a continuing basis in support of all the  $UC^3$  tasks.

A spin-off of a porous oxide coating study has demonstrated an improved porous-matrix composite system. Preliminary testing has shown a 100 C advantage over current systems using the same fiber. Transition discussions are underway.

We will continue to pursue applications for near-term composites, such as improved porous-matrix materials. We will develop such ideas on an opportunistic basis, but will continue to focus on determining the viability of ceramic composites for the more aggressive, broadest payoff applications.

In summary, our substantial effort in this area is beginning to pay off in rapid progress toward multifaceted evaluation of the technology in multiple organizations. We will continue to aggressively pursue that end, and to simultaneously pursue transition-to-practice and anticipation of problems associated with actual application. If progress continues in the current positive direction, real impact of our research on Air Force systems may not be far away.

## **6.** Publications, Invited Presentations and Inventions

## **Publications**

<sup>1</sup>M. K. Cinibulk, T. A. Parthasarathy, K. Keller, and T. Mah, "Porous Yttrium-Aluminum Garnet Fiber Coatings for Oxide Composites," J. Am. Ceram. Soc. (in review).

<sup>2</sup>J. B. Davis, R. S. Hay, D. B. Marshall, P. E. D. Morgan, and A. Sayir, "The Influence of Interfacial Roughness on Fiber Sliding in Oxide Composites with La-Monazite Interphases," J. Am. Ceram. Soc. (in review).

<sup>3</sup>T. Mah, H. D. Lee, T. A. Parthasarathy, and M. Cinibulk, "Processing, Microstructure and Properties of YAG-based Ceramic Cutting Tool for Titanium Alloy Machining," J. Am. Ceram. Soc. (in review).

<sup>4</sup>P. Mogilevsky, R. S. Hay, E. E. Boakye, and K. A. Keller, "Texture of Rhabdophane Derived Monazite Coatings," J. Am. Ceram. Soc. (In review).

<sup>5</sup>T. A. Parthasarathy, R. J. Kerans, K. Keller, T. Mah, and S. Butner, "Thermal Stress Management in Oxide CMCs using Mixed Fibers," J. Am. Ceram. Soc. (in review).

<sup>6</sup>L. P. Zawada, R. S. Hay, J. Staehler, and S. S. Lee, "High Temperature Mechanical Properties and Characterization of an Oxide/Oxide Ceramic Fiber/Matrix Composite," J. Am. Ceram. Soc. (in review).

<sup>7</sup>K. A. Keller, T. Mah, T. A. Parthasarathy, E. E. Boakye, P. Mogilevsky, and M. K. Cinibulk, "Effectiveness of Monazite Coatings in Oxide/Oxide Composites in Extending Life after Long-Term Exposure at High-Temperature," J. Am. Ceram. Soc. (in press.).

<sup>8</sup>M. K. Cinibulk, K. A. Keller, T. Mah, and T. A. Parthasarathy, "Nextel 610 Fiber-Reinforced Alumina-YAG Porous Matrix Composites," Cer. Eng. Sci. Proc. (in press).

<sup>9</sup>R. J. Kerans, R. S. Hay, T. A. Parthasarathy, and M. K. Cinibulk, "Interface Design for Oxidation Resistant Ceramic Composites," J. Am. Ceram. Soc. (in press).

<sup>10</sup>R. S. Hay, E. E. Boakye, and P. Mogilevsky, "Stress Corrosion of Ceramic Fibers from Fiber Coating Decomposition Products," Corrosion Science Proceedings in press (2002).

<sup>11</sup>P. D. Jero, F. Rebillat, D. J. Kent, and J. G. Jones, "Crystallization of Lanthanum Hexaluminate from MOCVD Precursors," Ceram. Eng. Sci. Proc. in press (2002).

<sup>12</sup>P. Mogilevsky, "Preparation of Thin Ceramic Monofilaments for Characterization by TEM," Ultramicroscopy in Press (2002).

<sup>13</sup>E. E. Boakye, R. S. Hay, P. Mogilevsky, and L. M. Douglas, "Monazite Coatings on Fibers: II, Coating without Strength Degradation," J. Am. Ceram. Soc. **84** (12) 2793-2801 (2001).

<sup>14</sup>R. S. Hay and E. E. Boakye, "Monazite Coatings on Fibers: I, Effect of Temperature and Alumina-Doping on coated Fiber Tensile Strength," J. Am. Ceram. Soc. **84** (12) 2783-2792 (2001).

<sup>15</sup>M. K. Cinibulk and T. A. Parthasarathy, "Characterization of Oxidized Polymer-Derived SiBCN Fibers," J. Am. Ceram. Soc. **84** (10) 2197-2202 (2001).

<sup>16</sup>T. A. Parthasarathy, E. Boakye, K. Keller, and R. S. Hay, "Evaluation of Porous ZrO<sub>2</sub>-SiO<sub>2</sub> and Monazite coatings using Nextel 720 Fiber-Reinforced Blackglas Matrix Minicomposites," J. Am. Ceram. Soc. **84** (7) 1526-32 (2001).

<sup>17</sup>M. K. Cinibulk, K. Keller, T. Mah, and T. A. Parthasarathy, "Nextel 610 and 650 Fiber Reinforced Porous Alumina-YAG Matrix Composites," Cer. Eng. Sci. Proc. **22** (3) 677-686 (2001).

<sup>18</sup>K. A. Keller, T. Mah, T. A. Parthasarathy, E. E. Boakye, and M. K. Cinibulk, "Evaluation of All-Oxide Composites Based on Coated Nextel 610 and 650 Fibers," Ceram. Eng. Sci. Proc. **22** (3) 667-675 (2001).

<sup>19</sup>T. A. Parthasarathy, "Extraction of Weibull Parameters of Fiber Strength from Means and Standard Deviations of Failure Loads and Fiber Diameters," J. Am. Ceram. Soc. **84** (3) 588-92 (2001).

<sup>20</sup>S. G. Steel, L. P. Zawada, and S. Mall, "Fatigue Behavior of a Nextel 720/Alumina Composite (N720/A) at Room and Elevated Temperature," Ceram. Eng. Sci. Proc. **22** (3) 695-702 (2001).

<sup>21</sup>T. Mah, T. A. Parthasarathy, and R. J. Kerans, "Processing, Microstructure and Strength Alumina-YAG Eutectic Polycrystals," J. Am. Ceram. Soc. **83** (8) 2088-2090 (2000).

<sup>22</sup>M. K. Cinibulk, "Synthesis of Yttrium-Aluminum Garnet from a Mixed-Metal Citrate Precursor," J. Am. Ceram. Soc. **83** (5) 1276-1278 (2000).

<sup>23</sup>R. S. Hay, E. Boakaye, and M. D. Petry, "Effect of Coating Deposition Temperature on Monazite Coated Fiber," J. Eur. Ceram. Soc. **20** (5) 589-597 (2000).

<sup>24</sup>E. E. Boakye, M. D. Petry, and R. Hay, "Monazite Coatings on Nextel 720, 610, and Tyranno-SA Fiber Tows: Effects of Precursors on Fiber Strength," Ceram. Eng. Sci. Proc. **21** (4) 229-236 (2000).

<sup>25</sup>M. K. Cinibulk, T. A. Parthasarathy, K. A. Keller, and T. Mah, "Porous Rare-Earth Aluminate Fiber Coatings for Oxide-Oxide Composites," Ceram. Eng. Sci. Proc. **21** (4) 219-228 (2000).

<sup>26</sup>R. S. Hay, "Monazite and Scheelite Deformation Mechanisms," Ceram. Eng. Sci. Proc. **21** (4) 203-217 (2000).

<sup>27</sup>T. Huang, M. N. Rahaman, T.-I. Mah, and T. A. Parthasarathy, "Effect of SiO<sub>2</sub> and Y<sub>2</sub>O<sub>3</sub> additives on the

anisotropic grain growth of dense mullite," J. Mater. Res. 15 (3) 718-726 (2000).

<sup>28</sup>K. A. Keller, T. Mah, E. E. Boakye, and T. A. Parthasarthy, "Gel-casting and Reaction Bonding of Oxide-Oxide Minicomposites with Monazite Interphase," Ceram. Eng. Sci. Proc. **21** (3) 525-534 (2000).

<sup>29</sup>K. A. Keller, T. Mah, T. A. Parthasarathy, and C. M. Cooke, "Fugitive Interfacial Carbon Coatings for Oxide-Oxide Composites," J. Am. Ceram. Soc. 83 (2) 329-336 (2000).

<sup>30</sup>R. E. Dutton, N. J. Pagano, R. Y. Kim, and T. A. Parthasarathy, "Modeling the Ultimate Tensile Strength of Unidirectional Glass Matrix Composites," J. Am. Ceram. Soc. **83** (1) 166-174 (2000).

<sup>31</sup>T. Huang, M. N. Rahaman, T. Mah, and T. A. Parthasarathy, "Anisotropic Grain Growth and Microstructural Evolution of Dense Mullite above 1550C," J Am. Ceram. Soc. **83** (1) 204-210 (2000).

<sup>32</sup>M. K. Cinibulk, "Hexaluminates as a Cleavable Fiber-Matrix Interphase: Synthesis, Texture Development and Phase Compatibility," J. Eur. Ceram. Soc. **20** 569-582 (2000).

<sup>33</sup>V. R. Katta, R. Anthenien, R. Mantz, W. M. Roquemore, R. A. Brockman, R. John, L. P. Zawada, T. A. Parthasarathy, and R. Kerans, "Influence of Ceramic-Matrix-Composite Wall Plates on Combustor Performance," 36th AIAA/ASME/SAE/ASEE Joint Conference Proceedings **AIAA 2000-3351** 1-10 (2000).

<sup>34</sup>M. N. Rahaman, T. Huang, T. Mah, and T. A. Parthasarathy, "In-situ Reinforced Mullite," Ceramic Transactions, Advances in Ceramic-Matrix Composites V **103** 211-222 (2000).

<sup>35</sup>S. M. Sim, K. A. Keller, and T. Mah, "Phase Formation in Yttrium Aluminum Garnet Powders Synthesized by Chemical Methods," J. Mater. Sci. **35** 713-717 (2000).

<sup>36</sup>T. A. Parthasarathy, E. E. Boakye, M. K. Cinibulk, and D. M. Petry, "Fabrication and Testing of Oxide/Oxide Microcomposites with Lanthanum Phosphate and Calcium Hexaluminate as Interlayers," J. Am. Ceram. Soc. **82** (12) 3575-3583 (1999).

<sup>37</sup>D. Petry and T. Mah, "Effect of Thermal Exposures on the Strengths of Nextel<sup>TM</sup> 550 and 720 Filaments," J. Am. Ceram. Soc **82** (10) 2801-2807 (1999).

<sup>38</sup>E. Boakye, R. S. Hay, and M. D. Petry, "Continuous Coating of Oxide Fiber Tows Using Liquid Precursors: Monazite Coatings on Nextel 720," J. Am. Ceram. Soc. **82** (9) 2321-2331 (1999).

<sup>39</sup>R. J. Kerans and T. A. Parthasarathy, "Crack Deflection in Ceramic Composites and Fiber Coating Design Criteria," Composites Part A **30A** (4) 521-524 (1999).

<sup>40</sup>E. Boakye, R. S. Hay, M. D. Petry, and T. A. Parthasarathy, "Sol-gel Synthesis of Zircon-Carbon Precursors and Coatings on Nextel 720 Fiber Tows," Ceram. Eng. Sci. Proc. **20** (3) 165-172 (1999).

<sup>41</sup>R. S. Hay, E. E. Boakye, M. D. Petry, Y. Berta, K. V. Lehmden, and J. Welch, "Grain Growth and Tensile Strength of 3M Nextel 720 after Thermal Exposure," Ceram. Eng. Sci. Proc. **20** (3) 153-163 (1999).

<sup>42</sup>K. A. Keller, T. A. Parthasarathy, T. Mah, M. K. Cinibulk, and E. E. Boakye, "Evaluation of Monazite Fiber Coatings in a Dense Matrix Composite," Ceram. Eng. Sci. Proc. **20** (3) 451-461 (1999).

<sup>43</sup>T. A. Parthasarathy, R. J. Kerans, and N. J. Pagano, "Effective Fiber Properties to Incorporate Coating Thermoelastic Effects in to Fiber/Matrix Composite Models," J. Am. Ceram. Soc. **82** (3) 579-584 (1999).

<sup>44</sup>R. J. Kerans, R. S. Hay, and T. A. Parthasarathy, "Structural Ceramic Composites," Curent Opinion in Solid State and Materials Science **4** 445-451 (1999).

<sup>45</sup>L. E. Matson and N. L. Hecht, "Microstructural Stability and Mechanical Properties of Directionally Solidified Alumina/YAG Eutectic Monofilaments," J. Eur. Ceram. Soc. **PII: S0955-2219** 2487-2501 (1999).

<sup>46</sup>M. K. Cinibulk, "Effect of Precursors and Dopants on the Synthesis and Grain Growth of Calcium Hexaluminate," J. Am. Ceram. Soc. **81** (12) 3157-3168 (1998).

<sup>47</sup>B. K. Ahn, W. A. Curtin, T. A. Parthasarathy, and R. E. Dutton, "Criteria for Crack Deflection/Penetration critera for Fiber-Reinforced Ceramic Matrix Composites," Composite Sci. & Tech. **58** (11) 1775-1784 (1998).

<sup>48</sup>M. K. Cinibulk, "Reactions between Hot–Pressed Calcium Hexaluminate and Silicon Carbide in the Presence of Oxygen," J. Am. Ceram. Soc. **81** (11) 2789-2798 (1998).

<sup>49</sup>M. K. Cinibulk, "Effect of Divalent Cations on the Synthesis of Citrate-Gel-Derived Lanthanum Hexaluminate Powders and Films," J. Mater. Res. **14** (9) 3581-3593 (1998).

<sup>50</sup>R. J. Kerans, T. A. Parthasarathy, F. Rebillat, and J. Lamon, "Interface Properties in High Strength Nicalon/C/SiC Composites as Determined by Rough Surface Analysis of Fiber Pushout Tests," J. Am. Ceram. Soc. **81** (7) 1881-1887 (1998).

<sup>51</sup>T. A. Parthasarathy, C. A. Folsom, and L. P. Zawada, "Combined Effects of Exposure to Salt (NaCl) Water and Oxidation on The Strength of Uncoated and BN-Coated Nicalon Fibers," J. Am. Ceram. Soc. **81** (7) 1812-1818 (1998).

<sup>52</sup>M. K. Cinibulk, "Synthesis of Calcium Hexaluminate and Lanthanum Hexaluminate Fiber Coatings," Ceram. Eng. Sci. Proc. **19** (3) 27-35 (1998).

<sup>53</sup>T. Mah, J. I. Lee, and N. L. Hecht, "In-situ Processing and Properties of SiC/MoSi<sub>2</sub> Nanocomposites," J. Am. Ceram. Soc **81** (2) 421-424 (1998).

<sup>54</sup>E. Boakye, R. S. Hay, and D. Petry, "Zircon-Carbon Sol Precursor and Coatings of Nextel 720 Fiber Tows," Mater. Res. Soc. Symp. Proc. (1998).

<sup>55</sup>P. D. Jero, "MOCVD of Lanthanum Hexaluminate at Atmospheric Pressure," (1998).

<sup>56</sup>J. G. Jones, P. D. Jero, and P. H. Garrett, "In-situ control of chemical vapor deposition for fiber coating," Engineering Applications of Artificial Intelligence **11** 619-626 (1998).

<sup>57</sup>T. Mah and T. A. Parthasarathy, "Effects of Temperature, Environment and Orientation on the Fracture Toughness of Single Crystal YAG," J. Am. Ceram. Soc. **80** (10) 2730-2734 (1997).

<sup>58</sup>M. D. Petry, T. Mah, and R. J. Kerans, "Validity of Using Average Diameter for Determination of Tensile Strength and Weibull Modulus of Ceramic Filaments," J. Am. Ceram. Soc. **80** (10) 2741-2744 (1997).

<sup>59</sup>T. A. Parthasarathy and R. J. Kerans, "Predicted Effects of Interfacial Roughness on the Behavior of Selected Ceramic Composties," J. Am. Ceram. Soc. **80** (8) 2043-2055 (1997).

<sup>60</sup>E. H. Moore, T. Mah, and P. W. Brown, "Carbon Coating of Nextel 550 and 720 by Pitch-Toluene Pyrolysis," J. Am. Ceram. Soc. **80** (5) 1285-88 (1997).

<sup>61</sup>T. Mah, K. A. Keller, S. Sambasivan, and R. J. Kerans, "High-Temperature Environmental Stability of the Compounds in the Al<sub>2</sub>O<sub>3</sub>-Y<sub>2</sub>O<sub>3</sub> System," J. Am. Ceram. Soc. **80** (4) 874-878 (1997).

<sup>62</sup>R. Ruh, K. S. Mazdiyasni, and J. W. Adams, "Young's Modulus, Flexural Strength, and Fracture of Yttria-Stabilized Zirconia versus Temperature," J. Am. Ceram. Soc. **80** (4) 903-908 (1997).

<sup>63</sup>M. K. Cinibulk, "Deposition of Oxide Coatings on Fiber Cloths by Electrostatic Attraction," J. Am. Ceram. Soc. **80** (2) 453-460 (1997).

<sup>64</sup>R. J. Kerans, F. Rebillat, and J. Lamon, "Fiber-matrix Interface Properties of Single-Fiber Microcomposites as Measured by Fiber Pushin Tests," J. Am. Ceram. Soc. **80** (2) 506-508 (1997).

<sup>65</sup>E. Boakye, R. S. Hay, and M. D. Petry, "Mixed Carbon-Aluminum Oxide Coatings from Aqueous Sols and Solutions," Mater. Res. Soc. Symp. Proc. **432** 363-368 (1997).

<sup>66</sup>M. K. Cinibulk, J. Welch, and R. S. Hay, "Transmission Electron Microscopy Specimen Preparation of Ceramic Coatings on Ceramic Fibers," Mater. Res. Soc. Symp. Proc. **480** 3-17 (1997).

<sup>67</sup>R. S. Hay, J. Welch, and M. Cinibulk, "TEM Specimen Preparation and Characterization of Ceramics Coatings on Fiber Tows," Thin Solid Films **308-309** 389-392 (1997).

<sup>68</sup>R. J. Kerans and T. A. Parthasarathy, "Debond Crack Roughness, Interface Properties and Fiber Coating Design in Ceramic Composites," Key Eng. Mater. **127-131** 51-62 (1997).

<sup>69</sup>T. Mah and P. Chen, "Synthesis and Characterization of Lanthanum Phosphate Sol for Fiber Coating," J. Mater. Sci. **32** 3863-3867 (1997).

<sup>70</sup>T. A. Parthasarathy and R. S. Hay, "Effect of Yttria Concentration on the Low Strain Rate Flow Stress of Cubic Zirconia Single Crystals," J. Am. Ceram. Soc. 44 (12) 4663-4676 (1996).

<sup>71</sup>M. K. Cinibulk, J. R. Welch, and R. S. Hay, "Preparation of Thin Sections of Coated Fibers for Characterization By Transmission Electron Microscopy," J. Am. Ceram. Soc. **79** (9) 2481-2484 (1996).

<sup>72</sup>R. J. Kerans, "Viability of Oxide Fiber Coatings in Ceramic Composites for Accomodation of Misfit Stresses," J. Am. Ceram. Soc. **79** (6) 1664-1668 (1996).

<sup>73</sup>M. K. Cinibulk and R. S. Hay, "Textured Magnetoplumbite Fiber-Matrix Interphase Derived from Sol-Gel Fiber Coatings," J. Am. Ceram. Soc. **79** (5) 1233-1246 (1996).

<sup>74</sup>E. Boakye, M. D. Petry, and R. S. Hay, "Porous Aluminum Oxide and Lanthanum Phosphate Fiber Coatings," Ceram. Eng. Sci. Proc. **17** (4) 53-60 (1996).

<sup>75</sup>M. K. Cinibulk, "Sol–Gel Coating of Nicalon<sup>™</sup> Fiber Cloths," Ceram. Eng. Sci. Proc. **17** (4) 241-249 (1996).

<sup>76</sup>R. E. Dutton, N. J. Pagano, and R. Y. Kim, "Crack Initiation in Borosilicate Glass-SiC Fiber Composites," J. Am. Ceram. Soc. **79** (4) 865-72 (1996).

<sup>77</sup>R. S. Hay, D. Petry, and E. Boakye, "Fiber Strength with Coatings from Sols and Solutions," Ceram. Eng. Sci. Proc. **17** (4) 43-52 (1996).

<sup>78</sup>T. A. Parthasarathy, R. S. Hay, and R. Ruh, "High Temperature Deformation Behavior of SiC-Whisker Reinforced MgO-PSZ/Mullite Composites," J. Am. Ceram. Soc. **79** (2) 475-483 (1996).

<sup>79</sup>N. J. Pagano and G. P. Tandon, "Matrix Crack Impinging on a Frictional Interface in Undirectional Brittle Matrix Composites," International Journal of Solids and Structures **00** (0) 1-18 (1996).

<sup>80</sup>N. J. Pagano and G. P. Tandon, "Effective Thermoelastic Moduli of a Unidirectional Fiber Composite Containing Interfacial Arc Microcracks," Trans. of the ASME 63 210-217 (1996).

<sup>81</sup>N. J. Pagano, A. K. Kaw, and S. Kunchithapatham, "The Stress Field in a Cracked Brittle Matrix Composite Cylinder with a Frictional Interface," International Journal Solid Structures **32** (15) 2127-2154 (1995).

<sup>82</sup>R. S. Hay, "The Use of Solid-State Reactions with Volume Loss to Engineer Stress and Porosity into the Fiber-Matrix Interface of a Ceramic Composite," Acta Metallurgica Materialia **43** (9) 3333-3347 (1995).

<sup>83</sup>T. A. Parthasarathy, T. Mah, A. P. Katz, and C. A. Folsom, "Microstructural Stability of Nicalon Fibers at 1000°C in air after Salt (NaCl) Exposure," J. Am. Ceram. Soc. **78** (7) 1992-1996 (1995).

<sup>84</sup>R. Berriche and R. E. Dutton, "Elastic Moduli Of TiB<sub>2</sub> and C Layers in a Fiber Reinforced Glass Ceramic Composite," Scripta Met. **33** (5) 789-794 (1995).

<sup>85</sup>M. K. Cinibulk, "Microstructure and Mechanical Behavior of an Hibonite Interphase in Alumina-Based Composites," Ceram. Eng. Sci. Proc. **16** (5) 633-641 (1995).

<sup>86</sup>P. W. Brown, "Metalorganic Chemical Vapor Deposition of LaAl<sub>11</sub>O<sub>18</sub> by a Liquid Precursor Route," Ceram. Eng. Sci. Proc. **16** (4) 385-387 (1995).

<sup>87</sup>A. J. Eckel, J. D. Cawley, and T. A. Parthasarathy, "Oxidation Kinetics of a Continuous Carbon Phase in a Nonreactive Matrix," J. Am. Ceram. Soc. **78** (4) 972-980 (1995).

<sup>88</sup>R. J. Kerans, "The Role of Coating Compliance and Fiber/Matrix Interfacial Topography on Debonding in Ceramic Composites," Scripta Metallurgica et Materialia **32** (4) 505-509 (1995).

<sup>89</sup>N. J. Pagano and G. P. Tandon, "Use of Composite Cylinder Model as Representative Volume Element for Unidirectional Fiber Composites," Journal of Composite Materials **29** (3) 388-422 (1995).

<sup>90</sup>M. K. Cinibulk, "Synthesis and Characterization of Sol-Gel Derived Lanthanum Hexaluminate Powders and Films," J. Mater. Res. **10** (1) 71-76 (1995).

<sup>91</sup>M. K. Cinibulk, "Thermal Stability of some Hexaluminates at 1400 C," J. Mat. Sci. Let. 14 651-654 (1995).

<sup>92</sup>R. S. Hay, "Orientation Relationships and Interfaces between low Symmetry Phases in the Yttria-Alumina System," Mat. Res. Soc. **357** 145-151 (1995).

<sup>93</sup>N. J. Pagano and A. K. Kaw, "Asymptotic stresses around a crack tip at the interface between planar or cylindrical bodies," International Journal of Fracture **71** 151-164 (1995).

<sup>94</sup>N. J. Pagano, Yuan, and X. Cai, "Elastic Moduli of Brittle Matrix Composites with Interfacial Debonding," International Journal of Solids and Structures (1995).

<sup>95</sup>T. A. Parthasarathy, D. Barlage, P. D. Jero, and R. J. Kerans, "Effects of Interfacial Roughness Parameters on Fiber Push-out Behavior of a Model Composite," J. Am. Ceram. Soc. **77** (12) 3232-3236 (1994).

<sup>96</sup>T. A. Parthasarathy, D. B. Marshall, and R. J. Kerans, "Analysis of the Effect of Interfacial Roughness on Fiber Debonding and Sliding in Brittle Matrix Composites," Acta Metall et Mater. **42** (11) 3772-3784 (1994).

<sup>97</sup>R. J. Kerans, "Issues in the Control of Fiber-Matrix Interface Properties in Ceramic Composites," Scripta Met. **31** (8) 1079-1084 (1994).

<sup>98</sup>R. S. Hay, "Kinetics and Deformation during the Reaction of Yttrium-Aluminum Perovskite and Alumina to Yttrium-Aluminum Garnet," J. Am. Ceram. Soc. **77** (6) 1473-1485 (1994).

<sup>99</sup>J. D. Cawley, A. J. Eckel, and T. A. Parthasarathy, "Oxidation of Carbon in Fiber-Reinforced Ceramic Matrix Composites," Ceram. Eng. Sci. Proc. **15** (5) 967-976 (1994).

<sup>100</sup>M. K. Cinibulk, "Magnetoplumbite Compounds as a Fiber Coating in Oxide/Oxide Composites," Ceram. Eng. Sci. Proc. **15** (5) 721-729 (1994).

<sup>101</sup>R. S. Hay, T. Mah, and C. Cooke, "Molybdenum-Palladium Fiber-Matrix Interlayers for Ceramic Composites," Ceram. Eng. Sci. Proc. **15** (5) 760-768 (1994).

<sup>102</sup>E. H. Moore, T. Mah, and K. A. Keller, "3D Composite Fabrication Through Matrix Slurry Pressure Infiltration," Ceram. Eng. Sci. Proc. **15** (4) 113-120 (1994).

<sup>103</sup>I. Tanaka, H.-J. Kleebe, M. K. Cinibulk, J. Bruley, D. R. Clarke, and M. Rühle, "Calcium Concentration Dependence of the Intergranular Film Thickness in Silicon Nitride Ceramics," J. Am. Ceram. Soc. **77** (4) 911-914 (1994).

<sup>104</sup>P. W. Brown and S. Sambasivan, "MOCVD of Beta Alumina," Ceram. Eng. Sci. Proc. 15 (3) 729-730 (1994).

<sup>105</sup>R. J. Kerans, P. D. Jero, and T. A. Parthasarathy, "Issues in the Control of Fiber/Matrix Interfaces in Ceramic Composites," Composites Science and Technology **51** (2) 291-296 (1994).

<sup>106</sup>G. N. Frantziskonis, P. Karpur, T. E. Matikas, S. Krishnamurthy, and P. D. Jero, "Fiber-matrix interface-information from experiments via simulation," Composite Structures **29** 231-247 (1994).

<sup>107</sup>R. J. Kerans, P. N. Kumpta, P. D. Jero, and T. Mah, "Processing of 3D interconnected porous aluminum nitride composites for electronic packaging," Mater. Lett. **21** 329-333 (1994).

<sup>108</sup>N. J. Pagano and H. M. Kim, "Progressive Microcracking in Unidirectional Brittle Matrix Composites," Mechanics of Composite Material and Structures **1** 3-29 (1994).

<sup>109</sup>S. Sambasivan, P. W. Brown, and L. E. Matson, "Metal-Organic Chemical Vapor Deposition (MOCVD) of layered Aluminates", , (1994).

<sup>110</sup>L. M. Butkus, J. W. Holmes, and T. Nicholas, "Thermomechanical Fatigue Behavior of a Silicon Carbide Fiber-Reinforced Calcium Aluminosilicate Composite," J. Am. Ceram. Soc. **76** (11) 2817-2825 (1993).

<sup>111</sup>M. Cinibulk, H.-J. Kleebe, G. A. Schneider, and M. Rühle, "Amorphous Intergranular Films in Silicon Nitride Ceramics Quenched from High Temperatures," J. Am. Ceram. Soc. **76** (11) 2801-2808 (1993).

<sup>112</sup>K. A. Keller, T. Mah, T. A. Parthasarathy, and C. Cooke, "Fugitive Interfacial Carbon Coatings for Oxide/Oxide Composites," Ceram. Eng. Sci. Proc. **14** (9-10) 878-879 (1993).

<sup>113</sup>P. D. Jero, T. A. Parthasarathy, and R. J. Kerans, "A Comparison of Single and Multi-Fiber Push-out Techniques," Ceram. Eng. Sci. Proc. **14** (7-8) 147-155 (1993).

<sup>114</sup>T. Mah, T. A. Parthasarathy, D. Petry, and L. E. Matson, "Processing, Structure and Properties of Alumina-YAG Eutectic Fibers," Ceram. Eng. Sci. Proc. **14** (7-8) 622-638 (1993).

<sup>115</sup>S. Sambasivan, T. A. Parthasarathy, F. J. Scheltens, and R. J. Kerans, "Tailoring of Interfacial Properties in Ceramic Matrix Composites Using Segregants," Ceram. Eng. Sci. Proc. **14** (7-8) 873-877 (1993).

<sup>116</sup>R. J. Kerans, T. A. Parthasarathy, P. D. Jero, A. Chatterjee, and N. J. Pagano, "Fracture and Sliding in the Fiber/Matrix Interface and Failure Processes in Ceramic Composites," Brit. Ceram. Trans. **92** (5) 181-196 (1993).

<sup>117</sup>M. K. Cinibulk, H.-J. Kleebe, and M. Rühle, "Quantitative Comparison of TEM Techniques for Determining Amorphous Intergranular Film Thickness," J. Am. Ceram. Soc. **76** (2) 426-432 (1993).

<sup>118</sup>T. A. Parthasarathy, T. Mah, and L. E. Matson, "Deformation Behavior of an Al<sub>2</sub>O<sub>3</sub>-Y<sub>3</sub>Al<sub>5</sub>O<sub>12</sub> Eutectic

Composite in Comparison with Sapphire and YAG," J. Am. Ceram. Soc. 76 (1) 29-32 (1993).

<sup>119</sup>M. K. Cinibulk and H.-J. Kleebe, "Effects of Oxidation on Intergranular Phases in Silicon Nitride Ceramics," J. Mater. Sci. **28** 5775-5782 (1993).

<sup>120</sup>R. S. Hay, "Phase Transformations and Microstructure Evolution in Sol-Gel Derived Yttrium-Aluminum Garnet Films," J. Mater. Res. **8** 578-604 (1993).

<sup>121</sup>R. S. Hay, "Fiber-Matrix Interfaces for Oxide Fiber-Oxide Matrix Composites," Ceram. Eng. Sci. Proc. 385-391 (1993).

<sup>122</sup>P. D. Jero, T. A. Parthasarathy, and R. J. Kerans, "Interface Evaluation In Ceramic Composites", Report No. 795, (1993).

<sup>123</sup>H.-J. Kleebe and M. K. Cinibulk, "TEM Characterization of a Ceria-Fluxed Silicon Nitride," J. Mater. Sci. Lett. **12** 70-72 (1993).

<sup>124</sup>H.-J. Kleebe, M. K. Cinibulk, I. Tanaka, J. Bruley, R. M. Cannon, D. R. Clarke, M. J. Hoffmann, and M. Rühle, "High-Resolution Electron Microscopy of Grain-Boundary FIlms in Silicon Nitride Ceramics," Mater. Res. Soc. Symp. Proc. **287** 65-78 (1993).

<sup>125</sup>T. Mah and T. A. Parthasarathy, "Fracture Toughness of Single Crystal YAG," Scripta Metall. et Materialia 28 1383-1385 (1993).

<sup>126</sup>T. Mah, T. A. Parthasarathy, M. D. Petry, and L. E. Matson, "Development of Continuous Refractory Oxide Eutectic Fibers", Report No. WL-TR-94-4087, (1993).

<sup>127</sup>T. Mah and M. D. Petry, "Feasibility Study of Refractory Oxide Fiber through the Melt Spinning Technique", Report No. U.S. Army Missile Command Under Contract Number DAAHO1-92-C-R056, AD-B174261, (1993).

<sup>128</sup>T. Mah, P. R. Subramanian, and L. E. Matson, "Solid State Reactions between selected Intermetallics and Oxides in the Al-Y-O System," Scripta Met. **28** 961-966 (1993).

<sup>129</sup>C. A. Folsom, F. W. Zok, F. F. Lange, and D. B. Marshall, "Mechanical Behavior of a Laminar Ceramic/Fiber-Reinforced Epoxy Composite," J. Am. Ceram. Soc. **75** (11) 2969-2975 (1992).

<sup>130</sup>R. S. Hay and B. Evans, "The Coherency Strain Driving Force for CIGM in Non-cubic Crystals: Comparison with IN SITU Observations in Calcite," Acta Met. 40 (10) 2581-2593 (1992).

<sup>131</sup>R. Ruh, K. Y. Donaldson, and D. P. H. Hasselman, "Thermal Conductivity of Boron Carbide-Boron Nitride Composites," J. Am. Ceram. Soc. **75** (10) 288-290 (1992).

<sup>132</sup>M. K. Cinibulk, G. Thomas, and S. M. Johnson, "Oxidation Behavior of Rare-Earth Disilicate-Silicon Nitride Ceramics," J. Am. Ceram. Soc. **75** (8) 2044-2049 (1992).

<sup>133</sup>M. K. Cinibulk, G. Thomas, and S. M. Johnson, "Fabrication and Secondary-Phase Crystallization of Rare-Earth Disilicate-Silicon Nitride Ceramics," J Am. Ceram. Soc. **75** (8) 2037-2043 (1992).

<sup>134</sup>M. K. Cinibulk, G. Thomas, and S. M. Johnson, "Strength and Creep Behavior of Rare-Earth Disilicate-Silicon Nitride Ceramics," J. Am. Ceram. Soc. **75** (8) 2050-2055 (1992).

<sup>135</sup>P. D. Jero, T. A. Parthasarathy, and R. J. Kerans, "Measurement of Interface Properties from Push-out Tests," Ceram. Eng. Sci. Proc. **13** (7-8) 54-63 (1992).

<sup>136</sup>P. D. Jero, T. A. Parthasarathy, and R. J. Kerans, "Interfacial Roughness in Ceramic Matrix Composites," Ceram. Eng. Sci. Proc. **13** (7-8) 64-69 (1992).

<sup>137</sup>T. Mah and M. D. Petry, "Eutectic Composition in the Pseudobinary of  $Y_4Al_2O_9$  and  $Y_2O_3$ ," J. Am. Ceram. Soc. **75** (7) 2006-2009 (1992).

<sup>138</sup>T. A. Parthasarathy, T. Mah, and K. Keller, "Creep Mechanism of Polycrystalline Yttrium Aluminum Garnet," J. Am. Ceram. Soc. **75** (7) 1756-1759 (1992).

<sup>139</sup>R. Ruh, J. E. Ritter, K. Jakus, and M. H. Godin, "Comparison of High-Temperature Crack Growth in SiC-Whisker-Reinforced Mullite and Si<sub>3</sub>N<sub>4</sub>," J. Am. Ceram. Soc. **75** (7) 1760-1766 (1992).

<sup>140</sup>R. Ruh, A. Zangvil, and C. C. Lin, "Microstructural Studies in Alkoxide-Derived Mullite/Zirconia/Silicon Carbide-Whisker Composites," J. Am. Ceram. Soc. **75** (5) 1254-1262 (1992).

<sup>141</sup>R. Ruh, M. Kearns, A. Zangvil, and Y. Xu, "Phase and Property Studies of Boron Carbide-Boron Nitride Composites," J. Am. Ceram. Soc. **75** (4) 864-872 (1992).

<sup>142</sup>L. M. Butkus, L. P. Zawada, and G. A. Hartman, "Fatigue Test Methodology and Results for Ceramic Matrix Composites at Room and Elevated Temperatures," ASTM **STP 1157** 52-68 (1992).

<sup>143</sup>J. Guth, "CVD Coating of Ceramic Monofilaments," Mater. Res. Soc. Symp. Proc. 250 263-268 (1992).

<sup>144</sup>R. S. Hay, "Coherency Strain Energy and Thermal Strain Energy of Thin Films in any Chrystal System," Scripta Met. **26** 535-540 (1992).

<sup>145</sup>J. Wolfenstine and T. A. Parthasarathy, "Elevated Temperature Deformation of a Fine-grained Y<sub>3</sub>Al<sub>5</sub>O<sub>12</sub>-YAlO<sub>3</sub> (20 vol%) Material," Scripta Metall. et Mater. **26** 1649-1653 (1992).

<sup>146</sup>P. D. Jero, R. J. Kerans, and T. A. Pathasarathy, "Effect of Interfacial Roughness on the Frictional Stress Measured Using Pushout Tests," J. Am. Ceram. Soc. **74** (11) 2793-2801 (1991).

<sup>147</sup>T. A. Parthasarathy, P. D. Jero, and R. J. Kerans, "Extraction of Interface Properties from the Fiber Push-out Test," Scripta Metall. et Mater. **25** (11) 2457-2462 (1991).

<sup>148</sup>L. P. Zawada, L. M. Butkus, and G. A. Hartman, "Tensile and Fatigue Behavior of Silicon Carbide Fiber-Reinforced Aluminosilicate Glass," J. Am. Ceram. Soc. **74** (11) 2851-2858 (1991).

<sup>149</sup>T. Mah, K. A. Keller, T. A. Parthasarathy, and J. Guth, "Fugitive Interface Coating in Oxide-Oxide Composites: A Viability Study," Ceram. Eng. Sci. Proc. **12** (9-10) 1802-1815 (1991).

<sup>150</sup>T. A. Parthasarathy, T. Mah, and K. Keller, "High Temperature Deformation Behavior of Polycrystalline YAG," Ceram. Eng. Sci. Proc. **12** (9-10) 1767-1773 (1991).

<sup>151</sup>R. S. Hay and L. E. Matson, "Alumina/Yttrium-Aluminium Garnet Crystallographic Orientation Relationships and Interphase Boundaries: Observations and Interpretation by Geometric Criteria," Acta Metall. **39** (8) 1981-1994 (1991).

<sup>152</sup>R. S. Hay, "Sol-Gel Coating of Fiber Tows," Ceram. Eng. Sci. Proc. **12** (7-8) 1064-1074 (1991).

<sup>153</sup>P. D. Jero and H. L. Walls, "Effect of Probe Geometry on Push-Out Test Results in Some SiC/Borosilicate Glass Composites," Ceram. Eng. Sci. Proc. **12** (7-8) 1115-1126 (1991).

<sup>154</sup>R. J. Kerans and T. A. Parthasarathy, "Theoretical Analysis of the Fiber Pullout and Pushout Tests," J. Am. Ceram. Soc. **74** (7) 1585-1596 (1991).

<sup>155</sup>L. P. Zawada and R. C. Wetherhold, "The effects of thermal fatigue on a SiC fibre/aluminosilicate glass composite," J. Mater. Sci. **26** 648-654 (1991).

<sup>156</sup>R. S. Hay and E. E. Hermes, "Sol-Gel Coatings on Continuous Ceramic Fibers," Ceram. Eng. Sci. Proc. **11** (9-10) 1526-1532 (1990).

<sup>157</sup>T. Mah, T. A. Parthasarathy, and L. E. Matson, "Processing and Mechanical Properties of Al<sub>2</sub>O<sub>3</sub>-Y<sub>3</sub>Al<sub>5</sub>O<sub>12</sub> Eutectic Composite," Ceram. Eng. Sci. Proc. **11** (9-10) 1617-1627 (1990).

<sup>158</sup>T. A. Parthasarathy, T. Mah, and L. E. Matson, "Creep Behavior of an Alumina- YAG Eutectic Composite," Ceram. Eng. Sci. Proc. **11** (9-10) 1628-1638 (1990).

<sup>159</sup>K. Keller, T. Mah, and T. A. Parthasarathy, "Processing and Mechanical Properties of Polycrystalline Y<sub>3</sub>Al<sub>5</sub>O<sub>12</sub> (Yttrium Aluminum Garnet)," Ceram. Eng. Sci. Proc. **11** (7-8) 1122-1133 (1990).

<sup>160</sup>L. E. Matson, R. S. Hay, and T. Mah, "Characterization of Alumina/Yttrium-Aluminum Garnet and Alumina/Yttrium-Aluminum Perovskite Eutectics," Ceram. Eng. Sci. Proc. **11** (7-8) 995-1003 (1990).

<sup>161</sup>M. K. Cinibulk, G. Thomas, and S. M. Johnson, "Grain-Boundary-Phase Crystallization and Strength of Silicon Nitride Sintered with a YSiAlON Glass," J. Am. Ceram. Soc **73** (6) 1606-1612 (1990).

<sup>162</sup>T. Mah, "Fiber Reinforced Ceramic Composites :OVERVIEW," J. Kor. Composite Materials 3 (1) 70-82 (1990).

<sup>163</sup>R. S. Hay, "HRTEM Observations of Sol-Gel derived YAG and Alumina/YAG Thin Films," Mat. Res. Soc. **183** 279-285 (1990).

<sup>164</sup>R. S. Hay and B. Evans, "Coherency Strain Energy in any Crystal System: Applications to In Situ Observations of CIGM Calcite," Acta Metall. (1990).

<sup>165</sup>R. S. Hay and L. E. Matson, "Interpretation of Alumina/Yttrium-Aluminum Garnet Orientation Relationships by Geometric Criteria," Acta Metall (1990).

<sup>166</sup>P. D. Jero and R. J. Kerans, "The Contribution of Interfacial Roughness to Sliding Friction of Ceramic Fibers in a Glass Matrix," Scripta Met. **24** 2315-2318 (1990).

<sup>167</sup>R. J. Kerans, P. D. Jero, T. A. Parthasarathy, and A. Chatterjee, "Determination of Fiber-Matrix Interface Mechanical Properties in Brittle Matrix Composites," MRS Symposium Proc. **194** 263-270 (1990).

<sup>168</sup>T. Mah, T. A. Parthasarathy, L. Boothe, M. D. Petry, and L. E. Matson, "Directional Solidification of Refractory Oxide Ceramic Eutectic Composites", Report No. WRDC-TR-90-4081, (1990).

<sup>169</sup>T. A. Parthasarathy, N. J. Pagano, and R. J. Kerans, "A Technique to Measure the Interfacial Bond Strength," Ceram. Eng. Sci. Proc. **10** (7-8) 872-881 (1989).

<sup>170</sup>S. Mall, "Characterization of Fracture in Fiber-Reinforced Ceramic Composites under Shear Loading," J. Am. Ceram. Soc. **72** (7) 1175-1178 (1989).

<sup>171</sup>R. J. Kerans, R. S. Hay, N. J. Pagano, and T. A. Parthasarathy, "The Role of the Fiber-Matrix Interface in Ceramic Composites," Am. Ceram. Soc. Bull. **68** (2) 429-442 (1989).

<sup>172</sup>T. Mah, M. Chen, and M. Battison, "Interface Analysis of Si-C-O Fiber/Magnesium Aluminosilicate Matrix Composites," J. Mater. Sci. **24** 3213 (1989).

<sup>173</sup>L. E. Matson, R. S. Hay, and T. Mah, "Stability of Sapphire/Yttrium Aluminum Garnet Composite System," Ceram. Eng. Sci. Proc. **10** 764 (1989).

<sup>174</sup>P. D. Jero and W. M. Kriven, "Formation and Properties of 2Tb2O3Al2O," J. Am. Ceram. Soc. **71** (11) 454-455 (1988).

<sup>175</sup>R. Ruh and A. Zangvil, "Phase Relationships in the Silicon Carbide-Aluminum Nitride System," J. Am. Ceram. Soc. **71** (10) 884-890 (1988).

<sup>176</sup>A. P. Katz and R. J. Kerans, "Structural Ceramics Program at AFWAL Materials Laboratory," Am. Ceram. Soc. Bull. **67** (8) 1360-1366 (1988).

<sup>177</sup>K. Cho, R. J. Kerans, and K. A. Jepsen (Keller), "Selection, Fabrication, and Failure Behavior of SiC Monofilament-Reinforced Glass Composites," Ceram. Eng. Sci. Proc. **9** (7-8) 815-824 (1988).

<sup>178</sup>R. J. Kerans, "Dependence of Composite Properties Upon Statistical Variations in Fiber Length," Ceram. Eng. Sci. Proc. **9** (7-8) 613-620 (1988).

#### **Invited Presentations**

R.J. Kerans, R.S. Hay, E.E. Boakye, M.K. Cinibulk and T.A. Parthasarathy, "Oxide Fiber-Coatings for Controlled Fracture in Robust Ceramic Composites", International Congress of Fracture (ICF), Honolulu, HI, 3-7 December 2001

R.J. Kerans, "Progress in Oxidation Resistant Interface Control in Ceramic Composites" High Temperature Ceramic Matrix Composites (HT-CMC 4), Munich, Germany, 1-3 October 2001

R.J. Kerans, "Oxidation Resistant Interface Control in Fiber Reinforced Ceramics" Annual Meeting, American Ceramic Society, Indianapolis, IN, 1-4 May 2001

R.J. Kerans, "Oxidation Resistant Ceramic Composites: How 'Weak Interfaces' Became 'Designed Failure Processes," Materials Research Society Annual Meeting, Boston, MA, 1 December 2000

M. K. Cinibulk and T.A. Parthasarathy, "Characterization of Oxidized Bayer SiBCN Fiber," Ultra High-Temperature Ceramics Workshop, University of Colorado, Boulder, CO, August 2000.

M.K. Cinibulk, "AFRL's Fiber-Matrix Interface Activities for All-Oxide CMCs," Ultra High-Temperature Ceramics Workshop, University of Colorado, Boulder, CO, August 2000.

R.J. Kerans, "Designed Failure Processes and the Development of Oxidation Resistant Ceramic Composites," 10<sup>th</sup> Iketani Conference on Materials Research, Karuizawa, Japan, 29 June 2000

R.J. Kerans, "Lightweight Power and Selected Materials Innovations At the Beginning and End of the Century," Graduate Seminar, University of Dayton, 23 March 2000

R.J. Kerans, "Lightweight Power and Selected Materials Innovations At the Beginning and End of the Century," Graduate Seminar, Case Western Reserve University, 22 February 2000 R.J. Kerans, "High Temperature Applications of Ceramic Composites", 1999 International Mechanical Engineering Congress and Exposition (ASME), Nashville, TN, 14–19 Nov. 1999

R. S. Hay, 2nd Acta Materialia Workshop on "Ceramic and Bimaterial Interfaces: Designing for Properties," Seville, Spain, Sep 1999

R. S. Hay, "Solid State Studied in Ceramics," 1999 Gordon Conference, Aug 1-6, Kimball Union Academy, NH

T.A.Parthasarathy and R.J.Kerans, "Modeling Cracks for Material Design and Life Prediction in Ceramic Matrix Composites", NIST workshop on Reliability of Ceramics, Gaithersberg, MD, August 31, 1999.

M. K. Cinibulk, "Synthesis of Hexaluminates for Coatings on Polycrystalline Oxide Fibers," IMA Seminar, University of Bayreuth, Germany, July 1999.

R. J. Kerans, "Crack Deflection in Ceramic Composites and Fiber Coating Design Criteria," JFCC International Workshop on Fine Ceramics '98, Nagoya, Japan, Mar 12-13 1999

R. J. Kerans, "Damage Tolerant Ceramic Composites," Gordon Research Conference on Composites, Ventura, California, Jan 10-15 1999

R. J. Kerans, "Design for Damage Accumulation and the Development of Ceramic Composites," International Meeting on Thermo-Mechanical and Electrical Properties of High-Temperature Materials, Renaissance Wailea Beach Resort, Maui, Hawaii, Jan 4-9 1999.

R. S. Hay, "Fiber Coatings and Fiber Strength", Recent Advances in Ceramic Matrix Composites - Structural Design, Fabrication, and Long Term Use, MRS Fall 1998, Boston, MA

T. A. Parthasarathy, "Successes and Challenges in Ceramic Matrix Composites", Graduate Seminar, University of Dayton, October 1998

R. J. Kerans, "Interface Control For Durable Ceramic Composites", TMS-AIME Fall Meeting, Chicago IL, 11-15 October 1998

R. J. Kerans, "Issues in the Design of Selected Advanced Ceramic Systems," Advanced Materials for Extreme Environments: New Experimental Opportunities in Neutron Scattering, Argonne National Laboratory, Argonne IL, September 11-12 1998.

R. S. Hay, "Fiber Coating Issues for Oxide-Oxide Matrix Composites," Oxide/Oxide Workshop 98, June 22-24, Irmsee, Germany

T. A. Parthasarathy, R. J. Kerans and R.S.Hay, "Challenges in Design and Evaluation of Advanced Interface Control Strategies in CMCs, Mardi Gras Conference on 'Challenges in Materials Design for Extreme Environments', Baton Rouge, LA, February 1998

T. A. Parthasarathy, R. J. Kerans, T. Mah, "The Outer Limits : Selection of Materials for Structural Use in Combustion Environments at V.High Temperatures", International Workshop on Ultrahigh Temperature Ceramics, Boulder CO, July 1998

T. A. Parthasarathy, M. G. Mendiratta, D. M. Dimiduk, "Creep Behavior of PST and Fully Lamellar Polycrystals of Ti-48Al", TMS Annual Meeting, San Antonio, TX, 1998

R. J. Kerans, "Damage Development, Toughening, and the Design and Performance of Ceramic Composite Systems (Keynote Presentation)," ASME Annual Meeting, Dallas TX, Nov 16-21 1997.

R. J. Kerans, T. A. Parthasarathy and R. S. Hay, "Crack Deflection in Ceramic Composites and Fiber Coating Design Criteria," 5<sup>th</sup> Japan International SAMPE Symposium & Exhibition (JISSE-5), Tokyo Big Sight, Tokyo, Japan, October 28-31 1997.

R. S. Hay, J. R. Welch, and M. K. Cinibulk, "Characterization of Ceramic Coatings on Ceramic Fiber Tows," ICMCTF, April, 1997

M. K. Cinibulk, J. R. Welch, and R. S. Hay, "Preparation of TEM Thin Sections of Coated Ceramic Fibers," MRS Spring, SF 1997

R.J. Kerans and T.A. Parthasarathy, "Debond Crack Roughness, Interface Properties and Fiber Coating Design in Ceramic Composites", International Conference on Ceramic and Metal Matrix Composites CMMC-96, San Sebastian, Spain, 9-12 September 1996

R. S. Hay, "Characteristics of Sol and Solution Derived Ceramic Fiber Coatings," 2nd Int. Mtg. Pacific Rim Cer. Soc., July 15-17, 1996

R.J Kerans, "Fiber Coating Design Parameters for Ceramic Composites as Implied by Considerations of Debond Crack Roughness" Ceramic Microstructures '96: Control at the Atomic Level, Berkeley, CA 24-27 June

R. J. Kerans and R. S. Hay, "Oxidation Resistant Fiber/Matrix Interface Control for Ceramic Composites," AEROMAT '96, June 5, 1996.

R.J. Kerans, "Fiber/Matrix Interface Properties and the Design of Fiber Coatings for Ceramic Composites" ICCI-V Microphenomena in Advanced Interfaces, Zichron Yaacov, Israel, 5-8 May 1996

R. S. Hay, "Fiber-Matrix Interface Concepts for CMCs," Materials Science Seminar, U. Dayton, Feb. 1, 1996

R. S. Hay, "Fiber-Matrix Interfaces for CMCs,", National Materials Advisory Board, Committee on Advanced Fibers for High-Temperature Ceramic Composites, Cocoa Beach, FL, Jan 1996

R. S. Hay, "Progress in Oxidation Resistant Fiber Coatings," Materials Science Seminar, U. Illinois, Oct. 26, 1995.

R. J. Kerans, "The Role of Fiber/Matrix Interfacial Topography in Determining Composite Design Parameters", Keynote Lecture, 4th International Conference on Interfacial Phenomena in Composite Materials, Eindhoven, The Netherlands, 10-13 September 1995.

R.J. Kerans, "Design of Fiber Coatings for Control of Interface properties in Ceramic Composites", ASME 1995 Summer Mechanics and Materials Joint Meeting, Univ. Calif. Los Angeles, 28-30 June 1995

R. J. Kerans, "Design of Fiber Coatings for Control of Interface Properties in Ceramic Composites," 97th Annual Meeting of the American Ceramic Society", Cincinnati, OH, 29 April-4 May 1995

R. J. Kerans, "Design of Fiber Coatings for Control of Interface Properties in Ceramic Composites," Graduate Seminar, Carnegie Mellon University, 14 March 1995

R. J. Kerans, "Design of Fiber Coatings for Control of Interface Properties in Ceramic Composites," Graduate Seminar, University of Cincinnati, 3 Feb 1995

R. J. Kerans, "Progress and Challenges in Fiber/Matrix Interface Control in Ceramic Composites," Graduate Seminar, Pennsylvania State Univ., 17 Nov 1994

R. J. Kerans, "Progress and Challenges in Fiber/Matrix Interface Control in Ceramic Composites," Keynote Lecture, Basic Sciences Div. Annual Meeting, Am. Ceram. Soc., Louisville, KY, 26-29 September 1994.

R. J. Kerans, "Control of Fiber-Matrix Interface Properties in Ceramic Composites," First International Conference on Composite Engineering, New Orleans, LA, USA, 28 - 31 August 1994.

M.K. Cinibulk, "Magnetoplumbite-Type Compounds as a Fiber Coating in Oxide/Oxide Composites," Structural Ceramics Group Seminar, Rockwell Science Center, Thousand Oaks, CA, May 1994.

R. J. Kerans, "Control of Fiber-Matrix Interface Properties in Ceramic Composites," Graduate Seminar, University of Illinois, 18 March 1994.

R. J. Kerans, "Effects of Fiber/Matrix Interface Topography and Debonding in Ceramic Composites", ARPA University Research Initiative Review, University of California at Santa Barbara, 7 January 1994.

R. J. Kerans, "Control of Fiber Matrix Interface Properties in Ceramic Composites", ARPA, University Research Initiative Review, University of California at Santa Barbara, 6 January 1994.

R. S. Hay, "Deformation During Solid-State Reactions with Volume Expansion," Materials Science Colloquium, Case Western Reserve University, Aug. 5 (1993).

T.A. Parthasarathy, R. J. Kerans, P.D. Jero and D.B. Marshall, "Friction in Fiber/Matrix Interfaces in Ceramic Composites", PAC Rim Meeting, Am. Ceram. Soc., Honolulu, HI, 7-10 November 1993.

P.D Jero, R.J. Kerans and T.A. Parthasarathy, "Interface Evaluation in Ceramic Composites", Symposium on Mechanics and Ultrasonic Characterization of Interfaces", ASME Winter Meeting, New Orleans, LA, 28 November

R.J. Kerans, "Control of Fiber-Matrix Interface Properties in Ceramic Composites," International Conference on High Temperature Ceramic Matrix Composites, 6th European Conference on Composite Materials, Bordeaux, France, 21 September 1993.

R. J. Kerans, "Issues in the Control of Fiber/Matrix Interfaces in Ceramic Composites", 2nd International Workshop on Interfaces, Santiago, Galicia, Spain, 27-29 September 1993.

R. S. Hay, "Deformation During Solid-State Reactions with Volume Expansion," Materials Science Colloquium, Case Western Reserve University, Aug. 5 (1993).

R.J. Kerans, "Effects of the Fiber-Matrix Interface on Measured Interface Properties and the Behavior of Ceramic Composites," Gordon Research Conference on Solid State Studies in Ceramics, August 1993.

R.J. Kerans, "Fiber-Matrix Interface Control in Ceramic Composites," 95th Annual Meeting of the American Ceramic Society, Cincinnati, OH, 24 April 1993.

M. Ruhle, H.-J. Kleebe, M.K. Cinibulk, and I. Tanaka, "High-Resolution Electron Microscopy of Grain-Boundary Films in Silicon Nitride Ceramics," Fall Meeting of Materials Research Society, December 1992.

M.K. Cinibulk, "Intergranular Phases in Silicon Nitride Ceramics and Their High-Temperature Stability," Institut für Keramik im Maschinenbau Seminar, Universität Karlsruhe, Germany, December 1992.

M.K. Cinibulk, "Intergranular Phases and Their Influence on the High-Temperature Behavior of Silicon Nitride Ceramics," Materials Science Division Seminar, Lawrence Livermore National Laboratory, October 1992.

R.J. Kerans, "Issues in the Control of Fiber-Matrix Interface Properties in Ceramic Composites," International Workshop on Advances in Inorganic Fiber Technology, Melbourne, Australia, 13 August 1992.

R.J. Kerans, "Fracture and Sliding in the Fiber-Matrix Interface in Composites," Graduate Seminar, The University of Dayton, 19 October 1992.

M.K. Cinibulk, "Experimental Studies on Intergranular Films in Silicon Nitride Ceramics," Advanced Ceramics Research Laboratory, Dow Chemical Co., Midland, MI, April 1992.

M.K. Cinibulk, "Effects of Oxidation on Microstructure and Properties of Silicon Nitride Ceramics," Center for Materials Science Seminar, Los Alamos National Laboratory, Los Alamos, NM, April 1992

P.D. Jero, T.A. Parthasarathy and R.J. Kerans, "Measurement of Interface Properties from Fiber Pushout Experiments," Graduate Seminar, University of Illinois, 20 March 1992.

R.J. Kerans, "Fracture and Sliding in the Fiber-Matrix Interface in Composites," Seminar, National Institute of Standards and Technology, 2 December 1991

R.J. Kerans, "Fracture and Sliding in the Fiber-Matrix Interface in Composites," Graduate Seminar, The Pennsylvania State University, 20 November 1991.

R. S. Hay, "Phase and Microstructure Evolution in Sol-Gel Derived Yttrium-Aluminum Garnet Thin Films," Materials Science Colloquium, Case Western Reserve University, Nov. 5 (1991).

R.J. Kerans, "Issues in the Development of Structural Ceramic Composites," Centennial Symposium on Materials Science and Engineering, Centennial Annual Meeting of the Ohio Academy of Sciences, The Ohio State University, 28 April 1991.

R.J. Kerans, "Fracture and Sliding in the Fiber-Matrix Interface," Seminar, Laboratoire des Composites Thermostructuraux (University of Bordeaux), Bordeaux, France, 18 April 1991.

R.J. Kerans, "Oxidation of Non-Oxide Reinforcements in Oxide-Matrix Composites," Seminar, Laboratoire des Composites Thermostructuraux (University of Bordeaux), Bordeaux, France, 18 April 1991.

R.J. Kerans, "Fracture and Sliding in the Fiber-Matrix Interface," Seminar, LERMAT (University of Caen), Caen, France, 17 April 1991.

R.J. Kerans, "Fracture and Sliding in the Fiber-Matrix Interface," Seminar, Rolls-Royce Advanced Ceramics Laboratory, (University of Warwick), Warwick, England, 13 April 1991.

R.J. Kerans, "Oxidation of Non-Oxide Reinforcements in Oxide-Matrix Composites," Seminar, Rolls-Royce Advanced Ceramics Laboratory, (University of Warwick), Warwick, England, 13 April 1991.

R.J. Kerans, "Fracture and Sliding in the Fiber-Matrix Interface and Failure Processes in Ceramic Composites," Plenary Lecture, Annual Convention of The Institute of Ceramics (UK), Oxford University, Oxford England, 10 April 1991.

R. S. Hay, "Chemically Induced Grain Boundary Migration," Materials Science Colloquium, Ohio State University, May 10 (1990).

R.J. Kerans, "The Role of the Fiber-Matrix Interface in Brittle-Matrix Composites," Graduate Seminar, University of Cincinnati, 25 May 1990.

R.J. Kerans, R. S. Hay, N. J. Pagano, and T. A. Parthasarathy, "The Role of the Fiber-Matrix Interface in Ceramic Composites," Short Course/Workshop on High Temperature Ceramic and Metallic Matrix Composites", Michigan State University, 12 December 1989.

R.J. Kerans, "Processing of Ceramic Composites: The State of the Art and the Challenges," Symposium on The State of the Art in Materials Processing, ASM Materials Week, 5 October 1989.

#### **Inventions and Patents**

<sup>1</sup>R. Kerans and T. A. Parthasarathy, Hybrid Composite Materials, Patent No. Air Force Invention No. AFD 552, USA Patent Filed (2002).

<sup>2</sup>D. M. Dimiduk, T. A. Parthasarathy, M. Uchic, and S. Rao, Comprehensive Design Tool Methodology for Rapid Assessment of Structural Capability of Materials, Patent No. AF Invention Disclosure AFD 594, USA - Patent Filed (2002).

<sup>3</sup>T. A. Parthasarathy and R. J. Kerans, Thermal Gradient Resistant Ceramic Composite, Patent No. Patent No. 6,251,815, USA (2001).

<sup>4</sup>T. Mah, T. A. Parthasarathy, and M. K. Cinibulk, Ceramić Matrix Composite Cutting Tool, Patent No. US Patent, USA (2001).

<sup>5</sup>M. K. Cinibulk and R. S. Hay, Method of Forming Tubular Inclusions in Single-Crystal Alumina, Patent No. US Patent No. 5894035, USA (1999).

<sup>6</sup>R. S. Hay and M. D. Petry, Coating Apparatus for Continuous Tow, Patent No. U. S. Patent #5,951,764, USA (1999).

<sup>7</sup>E. Boakye, R. S. Hay, and M. D. Petry, Ceramic Composite, Patent No. U. S. Patent #5,759,632, USA (1998).

<sup>8</sup>R. S. Hay, Method for Coating Continuous Tows, Patent No. U. S. Patent #5,217,533, USA (1993).

<sup>9</sup>R. S. Hay and E. E. Hermes, Coating Apparatus and Method for Continuous Fibers, Patent No. U. S. Patent #5,217,533, USA (1993).

#### **Selected Professional Activities and Awards**

Associate Editors, Jl of Amer. Ceram. Soc., T.A.Parthasarathy and R.J.Kerans

Fellow of the American Ceramic Society, R.J. Kerans

Fellow of the Air Force Research Laboratory, R.J. Kerans

AFRL/ML John J. Cleary Awards for Excellence in Research, R.S. Hay 1996, P.D. Jero and R.J. Kerans, 1993, (2 Finalists)

AFRL/ML Robert T. Schwartz Award for Excellence in Engineering, L.E. Matson, 1994

Affiliate Societies Council Scientist of the Year, R.J. Kerans

Air Force Basic Research Award Runner-Up

Organized and Co-Sponsored with NASA/GRC and DoE/ORNL the Interfaces Working Group

Gordon Conference Presentations (3), Gordon Conference Moderator (2)

Feature Article in J. Am. Ceram. Soc. (in press)

Invited Article in Current Opinion in Solid State and Materials Science, R.J. Kerans, R.S. Hay and T.A. Parthasarathy

Organizing or Advisory Boards for 3 International Conferences