

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY) 21 April 2003		2. REPORT TYPE View Graphs		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE Investigating the Effects of Confining Pressure on Cumulative Damage and the Constitutive Behavior of a Particulate Composite Material				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) C.T. Liu, M. Yen				5d. PROJECT NUMBER 2302	
				5e. TASK NUMBER 0378	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/PRSM 10 E. Saturn Blvd. Edwards AFB, CA 93524				8. PERFORMING ORGANIZATION REPORT NUMBER AFRL-PR-ED-VG-2003-099	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/PRS 5 Pollux Drive Edwards AFB CA 93524-7048				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S NUMBER(S) AFRL-PR-ED-VG-2003-099	
12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
20030616 050					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE	A		Sheila Benner
Unclassified	Unclassified	Unclassified			19b. TELEPHONE NUMBER (include area code) (661) 275-5963

FILE

MEMORANDUM FOR PRS (In-House Publication)

FROM: PROI (STINFO)


23 Apr 2003

SUBJECT: Authorization for Release of Technical Information, Control Number: **AFRL-PR-ED-VG-2003-099**
5642 C.T. Liu; M. Yen, "Investigating the Effects of Confining Pressure on Cumulative Damage and the Constitutive Behavior of a Particulate Composite Material"

International Conference on Mechanical Behavior of Materials
(Geneva, Switzerland, 25-29 May 2003) (Deadline: 14 May 2003)


(Statement A)

Investigating the Effects of Confining Pressure on the Cumulative Damage and the Constitutive Behavior of a Particulate Composite Material




C.T. Liu
10 East Saturn Blvd.
Edwards AFB CA 93524

M. Yen
Material Technology Center
Southern Illinois University at Carbondale
Carbondale, IL USA



A0913.ppt


Objectives



- Investigate the Effects of Strain Rate and Confining Pressure on Cumulative Damage and the Constitutive Behavior of a Particulate Composite Material.



— Strain Rates: 0.73 cm/cm/min, 18.18 cm/cm/min, and 72.73 cm/cm/min


— Confining Pressures: Ambient and 1000 psi



A0913.ppt



Specimen Geometry






A0913.ppt


Fracture Surface Under Different Confining Pressures



Pressure = 72.7 psi






Pressure = 1744 psi



A0913.ppt



Applied Load Vs. Strain (Strain Rate=18.8 min⁻¹)






A0913.ppt


Applied Load Vs. Strain (Confining Pressure=1000 psi)






A0913.ppt



Engineering Stress and Volume Dilatation Vs. Applied Strain (Strain Rate=0.73 min⁻¹ and Ambient Pressure)








A0913.ppt


Volume Dilatation Vs. Confining Pressure






Damage Parameter Vs Time, semi-log scale







Relative Change in Acoustic Attenuation Versus Strain



(constant strain rate loading)







A0913.ppt

Relative Attenuation of Acoustic Energy Versus Volume Dilatation




(monotonic loading)








Under A High Confining Pressure, Microcracks Can Develop in the Highly Filled Particulate Composite Material




- * The development of micro-cracks under multi-axial loading conditions results in a decrease in modulus.
- * For a given number of defects (micro-cracks or micro-voids), the modulus (volume dilatation) is insensitive (sensitive) to the type of defects.





Conclusions



- For a given strain rate, confining pressure has significant effects on the maximum stress and the applied strain for the onset of dilatation.
- For a given strain rate, confining pressure has no effect on the Modulus and insignificant effect on the rupture strain.
- For a given time, the strain rate has a significant effect on the damage intensity.
- The critical damage intensity is insensitive to the strain rate.