# AFRL-VA-WP-TP-2003-315 UAV TASK ASSIGNMENT WITH TIMING CONSTRAINTS

Corey Schumacher Phillip Chandler Meir Pachter



**JULY 2003** 

Approved for public release; distribution is unlimited.

This material is declared a work of the U.S. Government and is not subject to copyright protection in the United States.

AIR VEHICLES DIRECTORATE AIR FORCE RESEARCH LABORATORY AIR FORCE MATERIEL COMMAND WRIGHT-PATTERSON AIR FORCE BASE, OH 45433-7542

# 20030822 055

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188
The public reporting burden for this collection of informat sources, gathering and maintaining the data needed, and information, including suggestions for reducing this burde Davis Highway, Suite 1204, Artington, VA 22202-4302. H collection of information if it does not display a currently	on is estimated to average 1 hour per response completing and reviewing the collection of in n, to Department of Defense, Washington He Respondents should be aware that notwithstar alid OMB control number. PLEASE DO NOT	se, including the time fr formation. Send comm adquarters Services, I nding any other provisi RETURN YOUR FOR	r reviewing ents regard irectorate fi on of law, n M TO THE	Instructions, searching existing data sources, searching existing data ding this burden estimate or any other aspect of this collection of or Information Operations and Reports (0704-0188), 1215 Jefferson o person shall be subject to any penalty for failing to comply with a ABOVE ADDRESS.
1. REPORT DATE (DD-MM-YY)	2. REPORT TYPE		DATES COVERED (From - To)	
July 2003	Conference Paper	Preprint		
4. TITLE AND SUBTITLE UAV TASK ASSIGNMENT WITH TIMING CONSTRAINTS			5a. CONTRACT NUMBER	
			In-house	
				5b. GRANT NUMBER
				5c. PROGRAM ELEMENT NUMBER N/A
6. AUTHOR(S)				5d. PROJECT NUMBER
Corey Schumacher and Phillip Chandler (AFRL/VACA) Meir Pachter (AFIT/ENG)			N/A	
			5e. TASK NUMBER	
			N/A	
			5f. WORK UNIT NUMBER	
				N/A
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)				8. PERFORMING ORGANIZATION REPORT NUMBER
Control Theory Optimization Branch (AFRL/VACA) AFIT/ENG Control Sciences Division				AFRL-VA-WP-TP-2003-315
Air Vehicles Directorate				
Air Force Research Laboratory, A	ir Force Materiel Command	1		
Wright-Patterson Air Force Base,	OH 45433-7542			
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSORING/MONITORING AGENCY ACRONYM(S)
Air Vehicles Directorate				AFRL/VACA
Air Force Research Laboratory				11. SPONSORING/MONITORING AGENCY
Air Force Materiel Command				REPORT NUMBER(S)
wright-Patterson Air Force B	ase, OH 43433-7342			AFRL-VA-WF-IF-2003-313
<ol> <li>DISTRIBUTION/AVAILABILITY STAT Approved for public release; c</li> </ol>	<b>TEMENT</b> listribution is unlimited.	<u></u>		
13. SUPPLEMENTARY NOTES To be presented at the AIAA ( This material is declared a wo	Guidance Navigation and C rk of the U.S. Government	ontrol Confer and is not sub	ence, A ject to	Austin, TX, August 11-14, 2003. copyright protection in the United States.
4. ABSTRACT	<u></u>			
This paper addresses the prob for, classify, attack, and verify communicated between all ele Mixed Integer Linear Program time to a UAV's path, and veh with variable arrival times pro coupled tasks involving timing	em of task allocation for wire the destruction of potential ments of the swarm. We ge h, or MILP format. MILP can hicle paths are then recalcul- wides an optimal solution to g and task order constraints.	ide area searc l targets. We s merate a tour an assign task ated to match o multiple-ass	n muni assume of optin that lo the rec gnmer	tions. The munitions are required to search that target field information is mal assignments for each vehicle using a pok infeasible, due to timing, by adding puired arrival times. The MILP formulation at problems for groups of UAVs with
15. SUBJECT TERMS	untrol wide area search mu	nitions		
task anotation, cooperative co				
16. SECURITY CLASSIFICATION OF:	17. LIMITATION 1	8. NUMBER	19a. N/	AME OF RESPONSIBLE PERSON (Monitor)
A. REPORT b. ABSTRACT c. THIS Unclassified Unclassified Unclass	PAGE         OF ABSTRACT:           sified         SAR	OF PAGES	Pl 19b. Tl	hillip Chandler ELEPHONE NUMBER (Include Area Code)

Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std. Z39-18

# UAV Task Assignment with Timing Constraints

Corey Schumacher, Phillip Chandler Control Sciences Division Air Force Research Laboratory (AFRL/VACA) Wright-Patterson AFB, OH 45433-7531

Meir Pachter Department of Electrical and Computer Engineering Air Force Institute of Technology (AFIT/ENG) Wright-Patterson AFB, OH 45433-7765

#### Abstract

This paper addresses the problem of task allocation for wide area search munitions. The munitions are required to search for, classify, attack, and verify the destruction of potential targets. We assume that target field information is communicated between all elements of the swarm. We generate a tour of optimal assignments for each vehicle using a Mixed Integer Linear Program, or "MILP" format. MILP can assign tasks that look infeasible, due to timing, by adding time to a UAV's path, and vehicle paths are then recalculated to match the required arrival times. The MILP formulation with variable arrival times provides an optimal solution to multiple-assignment problems for groups of UAV's with coupled tasks involving timing and task order constraints.

#### 1 Introduction

Autonomous wide area search munitions (WASM) are small, powered air vehicles, each with a turbojet engine and sufficient fuel to fly for a short period of time. They are deployed in groups, or "swarms," from larger aircraft flying at higher altitudes. They are individually capable of searching for, recognizing, and attacking targets. Cooperation between munitions has the potential to greatly improve their effectiveness in many situations. The ability to communicate target information to one another will greatly improve the capability of future search munitions.

In [1], a time-phased network optimization model was used to perform task allocation for a group of powered munitions. The model is run simultaneously on all munitions at discrete points in time, and assigns each vehicle one or more tasks each time it is run. The model is solved each time new information is brought into the system, typically because a new target has been discovered or an already-known target's status has been changed. The network optimization model is run iteratively so that all of the known targets will be completely serviced by the resulting allocation. Classification, attack, and battle damage assessment tasks can all be assigned to different vehicles when a target is found, resulting in the target being more quickly serviced. A single vehicle can also be given multiple task assignments to be performed in succession, if that is more efficient than having multiple vehicles perform the tasks individually. In [2], variable path lengths are added to guarantee that feasible trajectories will be calculated for all tasks. This method is computationally efficient and can quickly assign all of the needed tasks to the available vehicles, however the iterative procedure is heuristic and does not guarantee that the solution is near optimal.

This paper proposes an optimal formulation for solving the coupled multiple-assignment problem. Formulating the problem in a Mixed Integer Linear Program, or MILP format, will allow the optimal solution to be found. MILP can assign tasks that look infeasible, due to timing, by adding time to a UAV's path. This allows all the tasks to be assigned giving an optimal solution. Solution times for non-trivial problems are much longer than for the heuristic iterative method used in [2], but the optimal solution can be used to evaluate the heuristically based solutions. This will help determine the value of solutions from other assignment procedures. The solution to this

ASE 63.1448

formulation will likely require too much computation and time for real-time use in a vehicle, except for extremely simple cases, but it can be used as a benchmarking and comparison tool to evaluate faster but non-optimal assignment methodologies. Details of the path-planning and pathlengthening algorithms used in this work can be found in [2,3].

### 2 MILP Model

The MILP model uses a discrete approximation of the real world based on nodes that represent discrete start and end positions for segments of a UAVs path. Nodes representing target positions range from 1...n and nodes for UAV positions range from 1+n...w+n. There is also an additional logical node for the sink n+w+1. The sink node is used when a UAV is not assigned to attack a target; it goes to the sink when it is done with all of its tasks. When a UAV enters the sink it is then used for searching the battlefield. The MILP model requires the costs or times for a UAV to fly from one node to another node. These flight times are constants represented by  $t_{vij}$ , the time it takes UAV v to fly from node i to node j. The flight times are positive real numbers,  $t_{vij} \ge 0$ .

In this MILP model the variable representations are as follows:

- n the number of targets
- w the number of UAVs
  - $\circ$  w  $\ge$  n + 1 One or more UAVs than targets required in the model.
- v = 1...w UAVs index
- k = 1,2,3 Task index

o

- o 1 Classify
  - Identify if the target is actually an eligible target.
- o 2 Attack
  - Attempt to destroy the target. Attacks are terminal events.
  - 3 Verification (Battle Damage Assessment)
    - Did we actually destroy the target?
- i = 1...n, n+v Initial nodes for UAVs
  - A UAV can start at any target node, 1...n, and only its original start node n+v. It would not make sense for a UAV to start at any other UAVs start node because there are no tasks at start nodes.
- j = 1...n Target nodes
- $k\neq 2 \Rightarrow i\neq j$  If k does not equal an attack task node i cannot equal node j.
  - The nodes represent start and end positions for a segment of a UAVs path. If a UAV were attacking a target it just classified it would fly from a node to the same node to do the attack. This allows a UAV to do a classify/attack task at a single target. During a classify or VERIFICATION task the UAV would never fly from a node to the same node, hence the restriction on i and j.
- $x_{vkij} = \{0,1\}$  Binary Decision Variables
  - o If UAV v is assigned to do task k fling from node i to node j,
  - Then  $x_{vkij} = 1$ , otherwise it is zero
- $\mathbf{x}_{vi,n+w+1} = \{0,1\} \text{Binary Sink Variables}$ 
  - o If UAV v is assigned to go to the sink from node i
  - Then  $x_{vi,n+w+1} = 1$ , otherwise it is zero
  - $t_{kj} = R^{+1} Continuous Timing Variables$ 
    - The time task k is performed on target j
- 3 MILP Formulation

The basic MILP formulation consists of three main parts: an optimization function, upper and lower bounds on all variables, and constraints using the variables. The variables are binary integer decision variables or continuous timing variables. The optimization function is the total time for all UAVs to do all tasks.

$$y = \sum_{\nu=1}^{w} \sum_{k=1}^{3} \sum_{\substack{i=1\\k\neq 2 \Rightarrow i\neq j}}^{1,\dots,n,n+\nu} \sum_{j=1}^{n} (t_{\nu i j} * x_{\nu k i j})$$

As described above  $t_{vij}$  is a constant describing the time for a UAV v to fly from node i to node j, this is multiplied by the binary decision variable  $x_{vkij}$ . Also from above  $x_{vkij}$  is either 0 or 1, if a UAV is flying from i to j and performing task k at j then the  $x_{vkij}$  will be 1 and the constant time multiplied by 1, will be added to the total time optimization function. If the UAV is not doing a task the  $x_{vkij}$  will be 0 and the constant  $t_{vij}$  will be multiplied by 0, which removes that time from the optimization function. There are other options for the optimization function such as maximizing the benefits, which would be similar to the benefit function used in [X].

The lower and upper bounds on variables describe the range of valid values for each variable. The ranges for the variables are described in Section 2. For example, the binary decision variables can take the values 0 or 1, and the continuous timing variables can take the values of the positive real numbers.

The formulation of the MILP is primarily based on the constraints. The constraints use the variables to make equations that describe the problem. For this research the constraints are as follows:

1. All tasks must be performed on all targets. This constraint is related to requiring,  $w \ge n + 1$  or, that the number of UAVs is 1 more than the number of targets. If less then or equal number of UAVs to targets is used this constraint will fail and no solution will be found.

$$\sum_{\substack{\nu=1\\k\neq 2 \Rightarrow i\neq j}}^{w} \sum_{\substack{i=1\\k\neq 2 \Rightarrow i\neq j}}^{1,...,n,n+\nu} x_{\nu k i j} = 1 \quad \substack{k=1,2,3\\j=1,...,n}$$

2. A UAV can only visit a target twice, to prevent looping. The UAV can do a classify task and then an attack task or a classify task and a verification task or a single one of these tasks at any target. But keeping in mind the attack task is a terminal event and that the attack has to occur before a verification can happen. A UAV does not have to visit a target any times so the times visited can be less then or equal to two or greater than or equal to zero.

$$\sum_{k=1}^{3} \sum_{\substack{i=1\\k\neq 2 \Rightarrow i\neq j}}^{1,...,n,n+\nu} x_{vkij} \le 2 \quad v = 1,...,w$$

3. A UAV can only enter the sink once. When a UAV is in the sink it is searching the battlefield for new targets, but it can't stop searching unless a reassignment occurs. This prevents inconsistencies with a UAV entering the sink and then immediately leaving the sink at a different target.

$$\sum_{i=1}^{1,\dots,n,n+\nu} x_{\nu i,(n+w+1)} \le 1 \quad \nu = 1,\dots,w$$

4. If a UAV is doing a verification on a target it can't be assigned to also attack that target. The verification must occur after the attack at a target, and the attack is a terminal event. It is impossible for a UAV to attack a target and then to verification that target after it has attacked.

$$\sum_{\substack{i=1\\k\neq2\Rightarrow i\neq j}}^{1,\dots,n,n+\nu} x_{\nu_{2ij}} \le 1 - \sum_{\substack{i=1\\k\neq2\Rightarrow i\neq j}}^{1,\dots,n,n+\nu} x_{\nu_{3ij}} \quad v = 1,\dots,w$$

5. If a UAV attacks a target it cannot attack any other target. These vehicles are munitions and are destroyed in an attack. The UAVs do not have to attack a target if it goes to the sink it is searching and can't leave the sink until a reassignment occurs. The UAV can do less then or equal to one attack.

$$\sum_{\substack{l=1\\k\neq 2 \Rightarrow i\neq j}}^{1,...,n,n+\nu} \sum_{j=1}^{n} x_{\nu_{2ij}} \le 1 \ \nu = 1,...,w$$

1

6. If a UAV enters a target to perform task k = 1 or 3 it must also exit that target. Targets have flow in and out for keeping track of UAVs. If a UAV performs the classify or verification task at a target it must leave the target when it is done to do another task or go to the sink. If a UAV does an attack at a target it can't leave because an attack is a terminal event.

$$\sum_{\substack{k=1,3\\k\neq2\Rightarrow i\neq j}}\sum_{\substack{i=1\\k\neq2\Rightarrow i\neq j}}^{n} x_{vkij} = \sum_{\substack{k=1,3\\k\neq2\Rightarrow i\neq j}}\sum_{\substack{i=1\\k\neq2\Rightarrow i\neq j}}^{n} x_{vkji} + \sum_{\substack{i=1\\i=1}}^{n} x_{v2ji} + x_{vj,(n+w+1)} \quad \substack{j=1,...,n\\k=1,2,3}$$

7. If a UAV attacks a target it cannot be sent to any other targets to do any other tasks. This constraint is similar to constraint six. The attack is a terminal event and a UAV can't do anything after it attacks a target.

$$\sum_{k=1}^{3} \sum_{\substack{i=1\\k\neq2 \Rightarrow i\neq j}}^{n} x_{\nu k j i} \le 1 - \sum_{\substack{i=1\\k\neq2 \Rightarrow i\neq j}}^{1,...,n,n+\nu} x_{\nu 2 i j} \quad \nu = 1,..., n$$

8. All UAVs must be assigned to leave the source node. A UAV has to do something either go to the sink immediately and search the battle field or do tasks that lead to an attack or go to the sink when the UAV is done with all of its non-attack tasks.

$$\sum_{k=1}^{3} \sum_{j=1}^{n} x_{\nu k(n+\nu)j} + x_{\nu(n+\nu)(n+w+1)} \quad \nu = 1, ..., w$$

9. A UAV cannot do tasks if it goes to the sink from its start node. This helps prevent looping. A UAV could be assigned to go to the sink from its start node and to do a non-attack task at several targets.

$$\begin{array}{ll} x_{vkij} \leq 1 - x_{v(v+n)(n+w+1)} \\ v = 1, \dots, w \quad k = 1, 3 \quad i = 1, \dots, n \quad j = 1, \dots, n \\ i = 1, \dots, n \quad j = 1, \dots, n \quad i \neq j \end{array}$$

10. The segments of a UAVs path cannot be greater than the UAVs Endurance. Again the  $t_{vij}$  is multiplied by the binary decision variable  $x_{vkij}$  to determine if the constant value is added to the total UAV path.

$$T_{v} = \text{UAV Endurance}$$

$$\sum_{k=1}^{3} \sum_{\substack{i=1\\k\neq 2 \Rightarrow i\neq j}}^{1,\dots,n,n+\nu} \sum_{j=1}^{n} \left( t_{\nu i j} * x_{\nu k i j} \right) \le T_{\nu} \quad \begin{array}{c} \nu = 1,\dots,w \\ T_{\nu} > 0 \end{array}$$

11. Timing for tasks performed after the UAV leaves the start node. These constraints only represent the first leg of a UAVs path after it leaves the start node.

$$\begin{array}{ll} t_{kj} \leq t_{1i} + t_{vij} + (1 - x_{vkij}) * T_v & v = 1, ..., w \\ t_{kj} \leq t_{3i} + t_{vij} + (1 - x_{vkij}) * T_v & k = 1, 2, 3 \\ t_{kj} \geq t_{1i} + t_{vij} - (1 - x_{vkij}) * T_v & i = n + 1, ..., n + w \\ t_{kj} \geq t_{3i} + t_{vij} - (1 - x_{vkij}) * T_v & i \neq j \end{array}$$

12. Timing for tasks performed on subsequent targets. These are the most complex attempt at coupling the paths of the UAVs from the first segment to the subsequent segments. These are soft constraints which have no effect, except when vehicle v is flying from node I to node j to perform task k – in that case the upper and lower bounds meet, enforcing an equality constraint on the timing for the task.

13. The time a classify task is performed on a target is ≤ the time an attack task is performed on a target which is ≤ the time the VERIFICATION is performed on a target. This constraint also prevents the VERIFICATION from happening before the classify and attack or the attack happening before the classify.

$$\begin{array}{l} t_{1j} \leq t_{2j} \\ t_{2j} \leq t_{3j} \end{array} j = 1, \dots, n$$

Using these constraints the MILP solver can find an optimal assignment for the tasks that are to be done on a set of targets, with the timing variables also telling us if any of the pre-computed paths need to be lengthened.

4 Simulation Results

The iterative network flow task assignment methodology described above has been implemented in our multi-vehicle, multi-target coordinated-control simulation. The scenario has eight Wide Area Search Munitions performing a search for targets in a rectangular area. The WASM are using a simple "mowing the grass" search pattern. There are up to 5 different target types possible in the simulation, including a "non-target" target type for objects that appear similar to targets but which may be distinguishable as non-targets by the ATR.

For the simulation results presented, eight vehicles are searching an area containing two targets. The targets have an orientation (facing) that has an impact on the ATR process and desired viewing angles, but this will not be discussed as it does not directly affect the task allocation. The search vehicles are initialized in a staggered row formation, with fifteen minutes of flight time remaining, out of a maximum thirty minutes. This assumes that the vehicles have been searching for fifteen minutes and then find a cluster of potential targets.

Figure 1 shows vehicle flight paths and target locations with variable-length paths. Targets are the grey objects numbered 1 and 2. UAV's are represented by small colored numbers and colored flight paths. The colored rectangles are vehicle sensor footprints. Whenever the minimum-length path does not satisfy the timing constraints, a new path that satisfies the constraints, and is near the minimum possible path length that satisfies the constraints, is calculated for each vehicle. All of the tasks assigned and completed successfully. There is, however, no guarantee that the method has produced a near-optimal result. The method does not give any quantification of how close to optimal the assignment might be.

## 5 Conclusions

We have presented a method for using a Mixed Integer Linear Program (MILP) formulation to find the optimal solution to a multipe-task assignment problem where the tasks are coupled by timing, precedence, and task order constraints. This formulation allows variation of vehicle flight paths to guarantee that timing constraints are satisfied, and directly incorporates the varying task completion times into the optimization. This is a promising formulation, which allows a true optimal solution for a very challenging problem. The MILP formulation results in a large optimization problem with many constraints that is not amenable to real-time solution, but it is usable for off-line assignment calculations, and for determining optimal solutions to evaluate the performance of more computationally tractable sub-optimal methods.

#### References

- 1. Schumacher, C, Chandler, P. R, Rasmussen, S. J., "Task Allocation for Wide Area Search Munitions Via Iterative Network Flow", Proceedings of the 2002 AIAA Guidance, Navigation, and Control Conference.
- Schumacher, C, Chandler, P. R, Rasmussen, S. J., "Task Allocation for Wide Area Search Munitions with Variable Path Length", Proceedings of the 2003 American Control Conference
- 3. Schumacher, C, Chandler, P. R, Rasmussen, S. J., "Path Elongation for Task Assignment", to appear in the Proceedings of the 2003 AIAA Guidance, Navigation, and Control Conference.
- 4. P. R. Chandler, S. Rasmussen, and M. Pachter, "UAV Cooperative Control," in AIAA GNC, (Denver, Colorado), 2000.

Page 7 of 7



