					Form Approved
]	REPORT DOC	CUMENTATIO	N PAGE	aviawing instructions	OMB No. 0704-0188
Public reporting burden for th data needed, and completing this burden to Department of 4302. Respondents should be	is collection of information is e and reviewing this collection of Defense, Washington Headqua aware that notwithstanding an ICASE DO NOT BETURN YOU	stimated to average 1 hour per res information. Send comments rega rters Services, Directorate for Info y other provision of law, no person IR FORM TO THE ABOVE ADDRE	ponse, including the time for i rding this burden estimate or rmation Operations and Repo shall be subject to any penal SS	any other aspect of this c rts (0704-0188), 1215 Jeff y for failing to comply wit	ollection of information, including suggestions for reducing erson Davis Highway, Suite 1204, Arlington. VA 22202- h a collection of information if it do" not display a currently
1. REPORT DATE (DL	D-MM-YYYY)	2. REPORT TYPE		3.	DATES COVERED (From - To)
	,	Confere	nce Proceeding	g	14-18 January 2002
4. TITLE AND SUBTI	TLE			5a	
The Role	of Marine Bac	teria in Stainle	ess Steel Pit	ting 5b). GRANT NUMBER
				50	PROGRAM ELEMENT NUMBER
					PE601153N
6. AUTHOR(S)	······································			5d	. PROJECT NUMBER
Richar	d I. Ŕay, Bren	ıda J. Little an	d Jason S. Le	e 5e	TASK NUMBER
				5f.	WORK UNIT NUMBER
7. PERFORMING ORG	GANIZATION NAME(S)	AND ADDRESS (ES)		8.	PERFORMING ORGANIZATION REPORT NUMBER
Naval Researc	h Laboratory				NRL/JA/7303/02/0001
Oceanography Stennis Spac	Division e Center, MS (39529-5004			
9. SPONSORING / MC	DNITORING AGENCY N	AME(S) AND ADDRESS(ES)		. SPONSOR/MONITOR'S ACRONYM(S)
Office of Nav	al Research				
800 N Ouincy	St			11	. SPONSOR/MONITOR'S REPORT
Arlington, VA 22217-5660					NUMBER(S)
12. DISTRIBUTION / /	AVAILABILITY STATE	MENT	· · · · · · · · · · · · · · · · · · ·		
Approved for	public releas	e, distribution	is unlimited		
13. SUPPLEMENTAR	Y NOTES				
14. ABSTRACT Flat plate and potential micr plate of welde of Nitronic 50 large numbers located on fla	l welded stain obiologically d AL6XN under and 316L stai of bacteria we t plate coupor	less steel coupo influenced corr the exposure co inless steels af ere associated w ns of 316L or Ni	ons (316L, Nit cosion in seav ondition after fter six- and with the corro itronic 50.	ronic 50 an water. No pi cone year. eight-week osion produc	AL6XN) were evaluated for tting was observed in flat Pits were located at welds exposures. In all cases, ets. No corrosion was
				·	
					3000/ 0/4
				200	50826 061 🗍
15. SUBJECT TERMS	3		······································		
316L, Nitronio	c 50, AL6XN				
16. SECURITY CLAS	SIFICATION OF:		17. LIMITATION	18. NUMBER	19a. NAME OF RESPONSIBLE PERSON
			UF ADSIKAUI		Richard I. Ray
a. REPORT	b. ABSTRACT	Unclassified	SAR		code)
OUCTUBBILIEU	SHOTOSSITION			14	228-688-4690
					Standard Form 298 (Rev. 8-98)

١,

٠.

PUBLICATION OR PRESE	NTATION RELEASE REQUEST		Pubkey: 3179 NRLINST 5600.2				
1. REFERENCES AND ENCLOSURES	2. TYPE OF PUBLICATION OR PRESENTA	ION ³	3. ADMINISTRATIVE INFORMATION				
Ref: (a) NRL Instruction 5600.2 (b) NRL Instruction 5510.40D Encl: (1) Two copies of subject paper (or abstract	 Abstract only, published Book Book Conference Proceedings Conference Proceedings Conference Proceedings Conference Conference Invited speaker Invited speaker Journal article (refereed) Journal article (refereed) Journal Presentation, published Oral Presentation 	act only, not published chapter rence Proceedings efereed) ledia report al article (not refereed) resentation, not publish	STRN <u>NRL/PP/7303-02-1</u> Route Sheet No.7303/ Job Order No. Classification X Sponsor approval obtained X				
		1. N. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.					
Title of Paper or Presentation		A A A A A A A A A A A A A A A A A A A					
The Role of Marine Bacteria in Stain	less Steel Pitting		·				
Author(s) Name(s) (First, MI, Last), C	ode, Affiliation if not NRL						
Richard I. Ray, Brenda J. Little, J	ason S. Lee						
It is intended to offer this paper to $5\alpha n$, $14-19$	the 2002 Tri-Service	me of Conference)	n Conference				
	in a cf 2002 Tri Service Correction Confe						
and/or for publication in Proceed	langs of 2002 Tri-Service Corrosion Conte- lame and Classification of Publication)		(Name of Publisher)				
After presentation or publication, pertinent publication/presentation data will be entered in the publications data base, in accordance with reference (a). It is the opinion of the author that the subject paper (is) (is not \underline{X}) classified, in accordance with reference (b). This paper does not violate any disclosure of trade secrets or suggestions of outside individuals or concerns which have been communicated to the Laboratory in confidence. This paper (does) (does not \underline{X}) contain any militarily critical technology.							
I his subject paper (has) (ha	s never <u>A</u>) been incorporated in an officia		n DV a				
Ric	Richard I. Ray, 7330 Whand A. Huy						
	d Code (Principal Author)	1					
5. ROUTING/APPROVAL		an 199					
CODE	SIGNATURE	DATE	COMMENTS				
Ray	Kuband & Kay	2-15-02					
	2						
	Lu I. O Ville	0-19-00	· · · · · · · · · · · · · · · · · · ·				
Branch Head	phenda Stitle	2-19-62	· · · · · · · · · · · · · · · · · · ·				
Payne	NIL	2.19.02	1 Release of this paper is approved				
Division Head			2. To the best knowledge of this Division, the subject matter of this paner (has				
William J. Jobst, 7300	W. Ast	2-19-02	(has never <u>X</u>) been classified.				
Security, Code	De la compañía de la comp	7/70/03	1. Paper or abstract was released, 2. A copy is filed in this office.				
Office of Counsel,Code	ANIN Date	51,1102					
1008.3 ADOR/Director NCST E.O. Hartwig, 7000	Verdroes	3/1/0-					
Public Affairs (Unclassified/ Unlimited Only), Code 7030.4	Deeke Robenle	2/22/01					
Division, Code	0	- 1					
Author, Code							

HQ-NRL 5511/6 (Rev. 12-98) (e)

THIS FORM CANCELS AND SUPERSEDES ALL PREVIOUS VERSIONS

A - Approved for public release, distribution is unlimited.				
B - Distribution authorized to U.S. Govern	ment agencies only (check reason below):			
Foreign Government Information	Contractor Performance Evaluation	Critical Technology		
Proprietary Information	Administrative/Operational Use	Premature Dissemination		
Test and Evaluation	Software Documentation	Cite "Specific Authority "		
Date statement applied	·	(Identification of valid documented authority)		
Other requests for this document sha	all be referred to			
	(Insert Controlling DC	D Office")		
C - Distribution authorized to U.S. Govern	ment agencies and their contractors (check r	eason below):		
Foreign Government Information	Software Documentation			
Administrative/Operational Use	Critical Technology	Cite "Specific Authority"		
Date statement applied		(Identification of valid documented authority)		
Other requests for this document sha	all be referred to	· · · · · · · · · · · · · · · ·		
	(Insert Controlling DO	D Office*)		
D - Distribution authorized to DOD and DO	D contractors only (check reason below):			
Foreign Government Information	Critical Technology			
Software Documentation	Cite "Specific Authority			
Administrative/Operational Use	(identification	or valid documented authonty)		
Date statement applied				
Other requests for this document sha	Il be referred to			
	(Insert Controlling DO	D Office*)		
E - Distribution authorized to DOD compo	nents only (check reason below):			
Proprietary Information	Premature Dissemination	Critical Technology		
Foreign Government Information	Software Documentation	Direct Military Support		
Administrative/Operational Use	Contractor Performance Evaluation	Test and Evaluation		
Date statement applied		Cite "Specific Authority "		
Other requests for this document sha	Il be referred to	(Identification of valid documented authority)		
	(Insert Controlling DO	D Office*)		
F - Further dissemination only as directed	by			
Dete statement surely d	(Insert Controlling	DOD Office*)		
	or higher DOD authority			
G - Distribution authorized to U.S. Govern	ment agencies and private individuals or ent	erprises eligible to obtain export-controlled		
technical data in accordance with regu	lations implementing 10 U.S.C. 140c.			
Date statement applied	84. Ary Company			
Other requests for this document shal	be referred to			
For NRL publications, this is usually the	(Insert Controlling DO	D Office)		
	Seminanding Officer, Naval Research Labo			
Classific	ation NOFORN	DTIC exempt (explain)		
Classification Review Substantive	changes made in this document after approv	al by Classification Review and Public Release invalidate		
(initial/Date) the documer	s. Therefore, if any substantive changes are to must be returned for another Classification	made by the author, Technical information, or anyone else,		
Author completes and submits this form wit	h the manuscript via line channels to the divi	sion head for review and approval according to		
1. NRL Reports	Submit the	e diskette (if available), manuscript, typed double-spaced,		
	complete v proposed o	vith tables, illustrations, references, draft SF 298, and listribution list.		
2. NRL Memorandum Reports	Submit a	copy of the original, typed manuscript complete with		
3. NRI. Publications or other books	distribution	n list.		
proceedings, or any other printed p	ublications.	a on a per case basis by Site Technical Information Office.		
HQ-NRL 5219/1 (Rev. 5-97) (e) (Back)				

Read and the second

THE ROLE OF MARINE BACTERIA IN STAINLESS STEEL PITTING

and a same

Richard I. Ray, Brenda J. Little and Jason S. Lee

Naval Research Laboratory/Code 7330 & 7303 Stennis Space Center, MS 39529-5004 ray@nrlssc.navy.mil blittle@nrlssc.navy.mil jason.lee@nrlssc.navy.mil

ABSTRACT

Flat plate and welded stainless steel coupons (316L, Nitronic 50 an AL6XN) were evaluated for potential microbiologically influenced corrosion in seawater. No pitting was observed in flat plate or welded AL6XN under the exposure condition after one year. Pits were located at welds of Nitronic 50 and 316L stainless steels after six- and eight-week exposures. In all cases, large numbers of bacteria were associated with the corrosion products. No corrosion was located on flat plate coupons of 316L or Nitronic 50.

INTRODUCTION

Microbiologically influenced corrosion (MIC) is used to designate corrosion due to the presence and activities of microorganisms. The spatial relationship between bacterial cells and pitting of weldments in austenitic stainless steels exposed in fresh water is well documented. ¹⁻¹¹ However, the reason for preferential microbial colonization at weldments has not been satisfactorily explained. Several case histories document selective attack at 316L stainless steel weldments exposed in marine environments.¹²⁻¹⁴ It is generally accepted that the weld material is less resistant to pitting than the base metal because of differences in composition and structure resulting from heating and cooling. Welds typically contain ferrite, not found in the base metal. Little et al.¹⁵ demonstrated that marine bacteria are co-located with iron corrosion product even when the bacteria were not responsible for the corrosion. Experiments in this paper were

DISTRIBUTION STATEMENT A Approved for Public Release Distribution Unlimited designed to determine the potential for MIC in stainless steel weldments and to document the electrochemical impact of marine organisms on welded austenitic stainless steels.

MATERIALS AND METHODS

EXPOSURE CONDITIONS

Flat coupons (10 cm x 10 cm x 3.2 mm) were prepared of three stainless steels (316L, Nitronic 50 and AL6XN). Coupons were also prepared with a tungsten inert gas butt weld across the width in the center of the coupon. The welds on the coupons were not burnished and no attempt was made to remove surface oxides. 316L and Nitronic® coupons were welded with matching fillers. AL6XN was welded with Inconel 625 and Hastelloy C-276. See Table 1 for USN numbers and alloy compositions. Samples were cleaned and degreased by rinsing consecutively in isopropyl alcohol, acetone, and blown dry with nitrogen gas. Experiments were conducted in natural seawater in Key West, Florida and in abiotic artificial seawater with a salinity of 35 ppm. Two coupons of each material were exposed to flowing seawater for one year. Serial dilutions of the natural seawaters were tested with MICkit V[®] (BioIndustrial Technologies, Georgetown, TX) to quantify aerobic bacteria (AERO), acid-producing bacteria (APB), sulfate-reducing bacteria (SRB), iron-related bacteria (IRB), and low-nutrient bacteria (LNB). Coupons were examined monthly until the end of the test period (one year). Location and general description of corrosion was noted.

Name	USN #	Nominal Concentration (wt%)
316L	S31603	Cr(16.0-18.0), Mo(2.0-3.0), Ni(10.0-14.0), C(0.035 max), Fe(bal)
AL6XN	N08367	Cr(20-22), Mo(6-7), Ni(23.5-25.5), Cu(0.75 max), N(0.18-0.25), C(0.03 max),
		Fe(bal)
Nitronic 50	520910	Cr(22), Mo(2.25), Ni(12.5), Mn(5), Si(1 max), N(0.3), Fe(bal)
Inconel	N06625	Cr(21.5), Mo(9.0), Nb + Ta (3.6), Ni(bal) (61.0)
Hastelloy	N10276	Cr(15.5), Mo(16.5), W(3.8), Fe(5.5), Ni(bal) (57.0)

 TABLE 1.

 USN Numbers and Alloy Compositions

MICROSCOPY.

At the end of the exposure periods, surface topography and chemistry (i.e., corrosion products, biological deposits, and inorganic deposits) were documented using an ElectroScan[®] Model E-3 environmental scanning electron microscope (ESEM). Stainless steel samples were removed from the exposure medium, fixed in 4% glutaraldehyde in abiotic seawater, carried through a series of water washes with a final distilled water wash and examined directly from distilled water. Samples were attached to a Peltier® stage, maintained at 4 °C and imaged in a water vapor environment at 2-5 torr to maintain samples in a hydrated state. Coupons were x-rayed for 20 minutes at 100 kV/3 mAmps.

ELECTROCHEMISTRY.

Anodic polarization scans were performed on 316L samples using a PAR horizontal flat cell with a defined working electrode area of 1 cm^2 with a knife-edge crevice-free gasket. Duplicate scans were performed at sites along the weld and approximately 2.5 cm away from the weld on the flat plate. A Pt-Nb mesh (2.5 cm²) and a saturated calomel electrode (SCE) were used as counter and reference electrodes, respectively. The open-circuit potential (OCP) was recorded for 10 minutes before scans were initiated. Scan range was from OCP to 0.7 V vs. SCE at a scan rate of 1 mV/sec.

Corrosion of the weld area was initiated by polarizing to 200 mV above OCP for 20 minutes in a Princeton Applied Research (PAR) Tait corrosion cell where the 316L coupon was at the bottom of the cell facing up. A glass tube (6.25 cm diameter) was placed on top of the sample with a rubber gasket seal. The top was sealed and the entire cell was clamped together using exterior bolts. Significant tightening was required to seal the bottom of the cell due to the height difference of the weld and the rest of the sample. The cell was filled with 200 mL of artificial seawater. The value of 200mV was chosen to drive active corrosion along the weld but not on the unwelded plate. Polarizations of welded and flat plate areas were conducted in duplicate. At the conclusion of the 20-minute polarization, OCP was monitored vs. SCE for two days. After two days, 20 mL of natural seawater were added to each system. Coupons were allowed to corrode freely for an additional four days.

RESULTS

EXPOSURE TESTING.

Key West natural seawater contained low levels (10 cells mL⁻¹) of AERO, APB, SRB, IRB, LNB. Flat coupons of Nitronic 50 and 316L exposed in natural seawater showed no signs of corrosion (Figure 1). Nitronic 50 and 316L showed visible corrosion in welds at six weeks in flowing seawater. Through-wall pitting was observed for 316L after an eight-week exposure (Figures 2a-c). In all cases corrosion was limited to weld areas. ESEM micrographs of the well-developed corrosion products demonstrated the presence of numerous microorganisms (Figure 3). There were no accumulations of bacteria on the unwelded plates or in areas away from the welds. Flat plate and welded AL6XN coupons did not show any visible corrosion after one-year exposures.



FIGURE 1. Nitronic 50 flat coupon exposed to flowing seawater.





FIGURE 2. 316L stainless steel coupon with a center weld exposed to flowing seawater for 10 weeks:

(A)Pit with corrosion product

(B) Penetration through the wall

(C) X-ray of the weld after exposure



FIGURE 3. 316L welded coupon exposed to flowing seawater for 10 weeks.

OCP values for the welded 316L were ~70 mV lower than the ones recorded for the plate (Figure 4). The polarization scans of the welds indicate that there is a lack of passive behavior and that active corrosion initiated immediately above the OCP with a steady increase in current density with increasing potential. Anodic polarization scans of the flat plate indicated a distinct passive region between 0 and 450 mV where the maximum current density increased one order of magnitude with a maximum of $0.1 \,\mu\text{A/cm}^2$. Current densities measured at the weld started at $0.1 \,\mu\text{A/cm}^2$ and increased five orders of magnitude over the same range. Breakdown potentials were observed at 450 and 550 mV in scans for the two flat plate samples. No discernable breakdown potential was observed for the welded metal.



FIGURE 4. Anodic polarization scans of welded and as-received 316L plate.

Polarization at 200 mV produced varying amounts of corrosion on duplicate samples — heavy corrosion in one sample and less corrosion in a second sample as demonstrated in time transient OCP (vs. SCE) (Figure 5). OCP for the sample with less corrosion started at 155 mV and fluctuated in the initial 15 minutes of exposure with a minimum value of 60 mV. After 15 minutes, OCP returned to 155 mV and remained relatively stable over the next hour. During this hour, only a slight orange-red discoloration was observed at the weld indicating light corrosion. In contrast, the sample with more corrosion had an initial OCP of -50 mV. OCP dropped over the first 25 minutes of exposure with a minimum value of -90 mV. OCP returned to the initial value of -50 mV over the next hour. Over this period, significant orange-red discoloration was observed on the weld surface, indicating significant corrosion.

The time transient OCP for the two previously polarized samples (Figure 6) indicate two different responses after addition of natural seawater. The immediate impact of the additions can be seen on the figure as two small fluctuations in the first 0.25 hour. Over the next two days increases were observed in OCP for both samples. OCP for the lightly corroding sample increased from 150 mV to 210 mV, while the OCP for the sample with more corrosion increased from -50 mV to 0 mV. Addition of viable cells to the electrolyte of the sample with heavier corrosion had no influence on the OCP over 40 hours and OCP remained at 0 mV. In contrast the OCP for the sample with minor corrosion fluctuated over the next 40 hours with a minimum value of 160 mV. During this time, the weld continued to discolor. Over the next three days (six days after the initial anodic polarization) OCP increased for both samples — 250 mV and 160 mV for the lightly corroding and heavily corroding samples, respectively.



FIGURE 5. OCP measured after potential holds at 200 mV above the initial OCP.



FIGURE 6. OCP measured two days after the anodic potential holds. Natural seawater was added at 0.25 hours as indicated by the vertical arrows.

There are many reports of MIC localized at welds in 300 series stainless steels exposed in fresh natural and chlorinated waters.¹⁻¹¹ In these cases MIC is attributed to biomineralized deposits, resulting from oxidation of ferrous to ferric and accumulation of tubercle-like deposits of ferric hydroxide [Fe(OH)₃].¹⁶ The oxidation can be carried out by a variety of organisms including bacteria, yeast, and fungi, but is particularly associated with genera of the so-called iron and manganese bacteria, *Siderocapsa, Gallionella, Leptothrix, Sphaerotilus, Crenothrix,* and *Clonothrix.* All are common in soil and groundwater. Deposits of cells and metal ions create oxygen concentration cells that effectively exclude oxygen from the area immediately under the deposit and initiate a series of events that are individually or collectively very corrosive. In an oxygenated environment, the area immediately under individual deposits becomes deprived of

oxygen. That area becomes a relatively small anode compared to the large surrounding oxygenated cathode. Cathodic reduction of oxygen may result in an increase in pH of the solution in the vicinity of the metal. Metal cations form at anodic sites. If the metal hydroxide is the thermodynamically stable phase in the solution, metal ions will be hydrolyzed by water with the formation of H⁺ ions. If cathodic and anodic sites are separated from one another, the pH at the anode will decrease, and that at the cathode will increase. In addition, Cl⁻ ions from the electrolyte will migrate to the anode to neutralize any charge buildup, forming heavy metal chlorides that are extremely corrosive. Under these circumstances, pitting involves the conventional features of differential aeration, a large cathode to anode surface area, and the development of acidity and metallic chlorides.

This widely accepted mechanism does not account for the specificity of the attack at weldments. Several theories have been advanced, but none has been accepted. The two-phase weld metal appears to be the most susceptible, although the relative susceptibilities of ferrite and delta phases have not been clearly defined.¹ Garner¹⁷ reported that the pitting potential and the critical pitting temperature were lower for welded than unwelded steel. Stein² determined that sensitization of the 300 series stainless steels does not affect susceptibility to MIC. The higher tendency for MIC of welds compared to unwelded material has been attributed to surface roughness or chemical composition that facilitates colonization. Pope et al.¹⁸ speculated that more nutrients accumulated at roughened areas i.e., welds, causing increased biofilm formation. However, Holthe¹⁹ showed that the increase in potential that accompanies biofilm development is just slightly more rapid on a rough surface than on a polished one. Eashwar and Dexter²⁰ published a paper entitled "Relation of Bacterial Settlement Patterns to Anodic Activity on Stainless Steel Weldments," but there are no data in the paper to support the title. Franklin et

al.,²¹ working with a phosphate-buffered freshwater medium, demonstrated that an aerobic bacterium was attracted to anodic sites on flat plate carbon steel coupons and that pit propagation was related to microbial settlement.

Preferential attack at welds is common to both freshwater and marine exposures. However, there are fewer reports of MIC localized at welds in 300 series stainless steels exposed in seawater, possibly because there are fewer applications of 300 series stainless steels in chloride-rich media. Little et al.¹² reported MIC localized at weldments of 300 series stainless steel causing through wall pitting of .032 cm plate after six to eight weeks exposed to flowing or stagnant seawater. They further demonstrated that in the absence of microorganisms anodic sites initiated at welds but those sites were not sustained and did not develop into pits. In the presence of marine bacteria stable anodic sites formed within four weeks.

Despite the attraction of bacteria to anodic sites on steel substrata in both fresh and marine waters the mechanism for pit propagation may differ in the two environments. Freshwater contains a higher concentration of reduced iron, a lower concentration of chloride, and a different population of microorganisms. The concentration of total iron in open marine waters is in the nM range. The generally cited causative organisms are not prevalent in seawater environments. The chemical oxidation rate of iron in seawater at pH 8.2 is so high that microbial oxidation is not competitive. In the ocean, iron-oxidizing bacteria are found primarily in bottom waters and seeps, where ferrous iron is seeping into the ocean from anaerobic groundwater, or where it is being produced in the sediments by iron-reducing organisms.

CONCLUSIONS

Experiments presented in this paper demonstrate that welded 316L corrodes at a lower potential than does the unwelded plate, and that over short exposure times the electrochemical impact of marine bacteria varies between aggressively corroding sites and those that are producing lower current densities. It appears that under all circumstances marine bacteria are attracted to anodic sites that occur preferentially at welds. Under some circumstances the attraction produces an electrochemical impact and in other cases the cells have no impact.

ACKNOWLEDGEMENTS

This work was funded under program element 0601153N and by the Office of Naval Research (Dr. John Sedriks). NRL Contribution Number NRL/PP/7303/02/0001.

REFERENCES

- 1. S.W. Borenstein, Microbiologically Influenced Corrosion Handbook, (New York, NY: Industrial Press Inc, 1994), p. 152.
- 2. A. Stein, "Microbiologically Influenced Corrosion-An Overview, Third International Symposium on Environmental Degradation of Materials in Nuclear Reactors, held August 30-September 3, 1987, (Traverse City, MI: 1987).
- 3. S.W. Borenstein, P.B. Lindsay, "Microbiologically Influenced Corrosion Failure Analyses," CORROSION/87, paper no. 381 (Houston, TX: NACE, 1987).
- 4. R.E. Tatnall, MP 19 (1980): p.88.
- 5. G. Kobrin, MP 15 (1976): p. 38.
- 6. G. Kobrin, Biologically Induced Corrosion (Houston, TX: NACE International, 1986), p. 33.
- J. Kearns, S. Borenstein, "Microbiologically Influenced Corrosion of Welded Stainless Alloys for Nuclear Power Plant Service Water Systems," CORROSION/91, paper no. 279, (Houston, TX: NACE, 1991).

- 8. S.W. Borenstein, P.B. Lindsay, "Why Does Microbiologically Influenced Corrosion Occur preferentially at Welds?," CORROSION/91, paper no. 286 (Houston, TX: NACE, 1991).
- 9. J. Kearns, S.W. Borenstein, "Microbiologically Influenced Corrosion of Welded Stainless Alloys for Nuclear Power Plant Service Water Systems," CORROSION/91, paper no. 279, (Houston, TX: NACE, 1991).
- 10. S.W. Borenstein, MP 27, 8 (1998): p. 62.
- 11. S.W. Borenstein, MP 30, 1 (1991): p. 52.
- 12. R.I. Ray, B.J. Little, J. Jones-Meehan, "A Laboratory Evaluation of Stainless Steels Exposed to Tap Water and Seawater," Research Technical Symposium: Corrosion 2002, (Houston, TX: NACE International, 2002).
- 13. W.R.N. Howell, Jr., "An Analysis of Possible Microbiologically Influenced Crevice Corrosion of 316 Stainless Steel in a Seawater Environment," (Thesis, Massachusetts Institute of Technology, 1996).
- 14. N.J.E. Dowling, M. Franklin, D.C. White, C.H. Lee, C. Ludin, "The Effect of Microbiologically Influenced Corrosion on Stainless Steel Weldments in Artificial Sea Water," CORROSION/89, paper no. 187, (Houston, TX: NACE International, 1989).
- 15. B.J. Little, P.A. Wagner, K.R. Hart, R.I. Ray, "Spatial Relationships Between Bacteria and Localized Corrosion," CORROSION/96, paper no. 278, (Houston, TX: NACE International, 1996).
- 16. B. Little, P. Wagner, F. Mansfeld, Inter. Mater. Rev. 36 (1991): p. 253.
- 17. A. Garner, Corrosion 35, 3 (1979) p. 108.
- D.H. Pope, D.J. Duquette, D.C. Wagner, Jr., A.H. Johannes, "Microbiologically Influenced Corrosion: A State of the Art Review," (Columbus, OH: Materials Technology Institute of the Chemical Process Industries, 1984) p. 76.
- 19. R. Holthe, "The Cathodic and Anodic Properties of Stainless Steels in Seawater," (Ph.D. diss., Norwegian University of Science and Technology, 1988).
- 20. M. Easwar, S.C. Dexter, "Relation of Bacterial Settlement Patterns to Anodic Activity on Stainless Steel Weldments," Corrosion/99, paper no. 174, (Houston, TX: 1999).
- 21. M. Franklin, B.J. Little, D.C. White, R. Ray, R. Pope, Biofouling 15, 1-3, (2000) p. 23.