

REPORT DOCUMENTATION PAGE			Form Approved OMB NO. 0704-0188	
Public Reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comment regarding this burden estimates or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188,) Washington, DC 20503.				
1. AGENCY USE ONLY (Leave Blank)		2. REPORT DATE July 8, 2002		3. REPORT TYPE AND DATES COVERED Final Progress Report: May 1, 1999 –April 30,2002
4. TITLE AND SUBTITLE Nonlinear Solvers for Subsurface Flow Problems			5. FUNDING NUMBERS DAAD19-99-1-0186	
6. AUTHOR(S)				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) North Carolina State University Office of Sponsored Programs, Box 7514			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U. S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211			10. SPONSORING / MONITORING AGENCY REPORT NUMBER 39199.11-MA	
11. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.				
12 a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12 b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The aims of this project are development of linear and nonlinear solvers and temporal integration methods in the context of three-dimensional simulations of subsurface flow and transport. In the period covered by this report the PI and his students completed the initial phase of development of a two-level preconditioner, applied those results to unsaturated and multiphase flow problems, and derived condition number estimates. We have also applied our work on simulation to problems in optimal design.				
14. SUBJECT TERMS			15. NUMBER OF PAGES	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OR REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION ON THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

Final Progress Report
Nonlinear Solvers for Subsurface Flow Problems
ARO Grant # DAAD19-99-1-0186
May 1, 1999 – April 30, 2002

1. Problem Studied. This project was for basic research in numerical methods for solving linear and nonlinear equations and related problems in time-dependent simulations. The motivating application was simulation of flow through porous media, in particular the unsaturated zone in the subsurface. The nature of the nonlinearities and the physical properties of the equations make standard methods for solution of equations perform in ways not predicted by current theory [17]. Our objective was to understand these effects and design and analyze new solvers. By doing this the new solvers can be incorporated in production codes and adapt to changes in the solution as the simulation progresses. This ability to adapt is crucial to an efficient simulation.

The basic research issues in nonlinear equation solvers arise from the nature of the nonlinearities. These do not have the smoothness properties that a traditional Newton's method code requires to converge in the usual way. Our group performed research directed toward understanding of how the nonlinearity can be approximated in a way that improves the performance of the solver and, at the same time, does not affect the accuracy of the simulation. The nonlinearities also affect the way in which the nonlinear solver and the time-dependent part of the simulator communicate. This communication is important for temporal adaption. This part of the project is the central component in Kathleen Kavanagh's Ph. D. work.

The research questions for linear solvers arise from the size of the problem. In general terms, the linear solver is used to compute an approximation to the Newton step for the nonlinear solver. This part of the overall simulation takes most of the computational time. Only a large distributed-memory parallel computer can store the data for large-scale ground and surface- water simulations in three space dimensions. Linear solvers that are efficient in this environment and can effectively use the complex data structures needed for an adaptive spatial discretization must be designed. In collaboration with the group at WES we have designed and implemented in ADH an efficient iterative method for large linear systems [4, 6–8]. This method has given good parallel scalability and is now [8] supported by theoretical analysis.

This research was done in collaboration with a group (Charlie Berger, Stacy Howington, and Jackie Hallberg) at the US Army Engineer Research and Development Center (ERDC). The **Adaptive Hydrology** model (ADH), a production groundwater modeling code, was used as both a testbed for the algorithmic work in the project and as a source for new research topics. The PI and his students have an very productive collaboration A DH team.

In addition to the group at ERDC, the PI collaborates a group led by Professor C. T. Miller at the University of North Carolina on work related to this project.

2. Most Important Results. The most significant results from the project are connected with the development, implementation, analysis, and tech transfer of a two-level Schwarz preconditioner for Richards' equation (RE) and related problems. Richards' equation is a simple model of flow in the unsaturated zone. In three space dimensions, letting z be the vertical direction and ∇ the spatial gradient operator, the pressure head form of RE is

$$(2.1) \quad [c(\psi) + S_s S_a(\psi)] \frac{\partial \psi}{\partial t} = \nabla \cdot (K(\psi) \nabla \psi) + \frac{\partial K(\psi)}{\partial z}$$

In (2.1), ψ is pressure head, $c(\psi) = \partial\theta/\partial\psi$ is the specific moisture capacity, $\theta(\psi)$ is the volumetric fraction of water, S_s is the specific storage, $S_a(\psi) = \theta(\psi)/n$ is the aqueous-phase saturation, n is the porosity, and $K(\psi)$ is the hydraulic conductivity. We will assume that appropriate initial and boundary conditions have been imposed.

The equation must be closed with constitutive equations for $\theta(\psi)$ and $K(\psi)$. One common way to do this is to define the effective saturation S_e with the van Genuchten formula [19],

$$(2.2) \quad S_e(\psi) = \frac{\theta - \theta_r}{\theta_s - \theta_r} = \begin{cases} (1 + |\alpha_\nu \psi|^{n_\nu})^{-m_\nu}, & \psi < 0 \\ 1, & \psi \geq 0 \end{cases}.$$

In (2.2), θ_r is the residual volumetric water content, θ_s is the saturated volumetric water content, n_ν is an experimentally determined measure of pore size uniformity, $m_\nu = 1 - 1/n_\nu$, and α_ν is an experimentally-determined coefficient that is related to the mean pore size. Note that (2.2) also defines θ as a function of ψ . If the van Genuchten formula is used for the saturation, it is standard to define the conductivity with the Mualem model, [15],

$$(2.3) \quad K(\psi) = K_s S_e^{1/2} \left[1 - \left(1 - S_e^{1/m_\nu} \right)^{m_\nu} \right]^2$$

where K_s is the water-saturated hydraulic conductivity. One can see from (2.2) and (2.3) that the nonlinearity is not differentiable if $1 < n_\nu < 2$. Values of n_ν in this range are physically realistic and solvers must be prepared to deal with nonsmooth nonlinearities.

Discretization in time and space of RE leads to a sequence of nonlinear equations that must be solved at each time step. To see this in a simple way we define the accumulation term

$$A(\psi) = c(\psi) + S_s S_a(\psi),$$

and suppress the spatial variables to obtain

$$A(\psi) \frac{\partial \psi}{\partial t} = \mathcal{N}(\psi)$$

where the nonlinear term $\mathcal{N}$ contains all spatial derivatives. The semi-discretized problem (*i. e.* discrete in space only) has the same form,

$$(2.4) \quad A(u) u_t = \mathcal{N}(u),$$

where $\mathcal{N}$ is the discrete form of $\mathcal{N}$ and u the approximation to ψ . Our work on this project seeks efficient solvers for (2.4).

One must integrate (2.4) implicitly in time. If, for example one uses the backward Euler method one obtains

$$(2.5) \quad A(u^{n+1})(u^{n+1} - u^n) = h_n \mathcal{N}(u^{n+1})$$

which leads to a nonlinear equation that must be solved to advance in time

$$(2.6) \quad F(u) = A(u)(u - u^n) - h_n \mathcal{N}(u) = 0.$$

We solved (2.6) with a Newton-iterative method. This means that we approximate the Newton step

$$s = -F'(u_c)^{-1} F(u_c)$$

by solving the linear equation,

$$(2.7) \quad F'(u_c)s = -F(u_c),$$

with an iterative method.

The problems of interest here are too large for a Jacobian factorization to be computed and stored. Hence (2.7) must be solved by an linear (inner) iterative method. The termination criteria for the iterative method is typically coupled to the state of the nonlinear (outer) iteration by the *inexact Newton condition* [1, 13],

$$(2.8) \quad \|F'(u_c)s + F(u_c)\| \leq \eta_c \|F(u_c)\|.$$

This is simply the standard relative linear residual termination criterion for iterative methods.

In our computational work on RE [4, 6, 7] and two-phase flow [12] we use a preconditioned Krylov method for the linear equation and terminate that inner iteration when (2.8) holds. The problems are large enough that distributed memory computers are needed both to store the data and to do the computations rapidly. The Jacobian matrix is nonsymmetric for most of the problems we consider and we solve the nonsymmetric linear equation for the Newton step with a preconditioned Bi-CGSTAB [18] linear iteration.

Let $Ax = b$ be the linear system to be solved. We seek a (left) preconditioner M such that the condition number

$$\kappa(MA) = \|MA\| \|(MA)^{-1}\|$$

is significantly smaller than that of A . Krylov methods usually perform better if the condition of the linear system can be improved. The preconditioner is used by applying the method to the preconditioned system $MAx = Mb$. Krylov methods take one or two matrix-vector products per iteration. The matrix-vector product is usually the most significant cost in cpu time. Hence a good preconditioner, by reducing the number of linear iterations, will reduce the cost of the solve. However, one must keep in mind that the MA -vector product could be much more expensive than the A -vector product. Hence, the preconditioner is useful if the reduction in the number of iterations offsets the increased cost from the application of the preconditioner with each matrix-vector product.

The combination of a Newton-Krylov method with a Schwarz domain decomposition preconditioner is called a Newton-Krylov-Schwarz (NKS) method [14]. We have implemented both one and two level Schwarz preconditioners in ADH. Both of these preconditioners are domain decomposition preconditioners, which means that the original physical domain is split into several subdomains, and the solutions of the original problem restricted to the subdomains are combined to form the preconditioner for the original system.

We now describe additive the kind of Schwarz preconditioners we use in ADH. If we define a matrix R_i to be the restriction matrix for subdomain i so that $R_i = [0 \ I \ 0]$, where I is an $n_i \times n_i$ identity matrix and n_i is the size of subdomain i , then the one-level additive Schwarz preconditioner can be written as

$$M = \sum_{i=1}^p R_i^T (R_i A R_i^T)^{-1} R_i$$

where p is the number of subdomains.

The coarse mesh component of the preconditioner is formed by defining one aggregate element per subdomain. The resulting coarse mesh basis function is constant except in the elements shared between subdomains. The contribution of the subdomain to the coarse matrix is computed locally and then communicated to all of the processors. Thus every processor solves the coarse mesh problem. The subdomain solves are performed using a profile solver [2] and the coarse grid problem is solved using a dense LU factorization. The two-level additive Schwarz preconditioner is formed by adding the coarse mesh problem to the one-level preconditioner, so that

$$M = R_0^T (R_0 A R_0^T)^{-1} R_0 + \sum_i^p R_i^T (R_i A R_i^T)^{-1} R_i$$

where R_0 and R_0^T are the restriction and interpolation operators from the fine to coarse meshes, respectively.

If h is the scale of the fine mesh and H the scale of the subdomains, we have shown, at least for model elliptic problems [5, 8], that the two-level preconditioner satisfies,

$$(2.9) \quad \kappa(MA) \leq C\omega(1 + (H/h)^2).$$

In practical terms, (2.9) means that if the number of subdomains grows as the mesh is refined, then the condition number of MA will be independent of h , hence the number of iterations needed to satisfy (2.8) should also be independent of h and the scalability of the solver should be good. While the link between condition number and iteration count is only a heuristic for nonsymmetric systems [3, 13, 16], the computational results in [4, 6–8, 12] show good-to-excellent scalability in terms of iteration counts and nonlinear function evaluations.

To illustrate this scalability, we present a table of iteration statistics from [8]. The findings in [6, 12] are similar, with the one-level method performing less well in the three dimensional simulations from [6]. The data are from a temporal integration of RE in two space dimensions, using a regular spatial mesh. In the table we report on the average number of linear iterations per Newton step over a complete simulation. The linear solver was BiCGSTAB [18] and the temporal integration was done with the BDF code from [10]. Table 2.1 shows how the performance of the preconditioned linear solver depends on H and h . The constant numbers along the diagonals indicate almost perfect scalability.

TABLE 2.1
RE Iteration Statistics, 2-level Schwarz Preconditioner

$H \backslash h$	1/16	1/32	1/64	1/128	1/256
1/8	7	8	9	12	15
1/16		7	9	11	14
1/32			7	9	11
1/64				7	9
1/128					7

In [12] we apply the solver technology developed for RE in [5, 6, 8] to a model [9, 11] for two phase flow. The model is a coupled system of equations of the same form as (2.1). The preconditioning and temporal integration methods that have been designed for Richards' equation also performed well in this context.

In [4, 7] the group at ERDC and the PI's group applied the multilevel preconditioner to problems in surface water and in ground-surface water interaction. The long-term goal is that the preconditioner be applicable to the entire range of problems that ADH is intended to solve.

3. Publications.

3.1. Refereed Journal Publications.

1. E. W. JENKINS, C. T. KELLEY, C. T. MILLER, AND C. E. KEES, *An aggregation-based domain decomposition preconditioner for groundwater flow*, SIAM J. Sci. Comp., 23 (2001), pp. 430–441.
2. C. T. MILLER, C. E. KEES, E. W. JENKINS, AND C. T. KELLEY. **Versatile two-level Schwarz preconditioners for multiphase flow**. Technical Report CRSC-TR01-32, NCSU, CRSC, December 2001. Finished in late Dec., Submitted to Computational Geosciences.
3. J. F. KANNEY, C. T. MILLER, AND C. T. KELLEY. **Convergence of iterative split operator approaches for approximating nonlinear reactive transport problems**. Technical Report CRSC-TR02-06, NCSU, CRSC, March 2002. Submitted to Advances in Water Resources.
4. A. S. MAYER, C. T. KELLEY, AND C. T. MILLER. **Optimal design for problems involving flow and transport phenomena in saturated subsurface systems**. Technical Report CRSC-TR01-33, North Carolina State University, Center for Research in Scientific Computation, December 2001. To appear in Advances in Water Resources.
5. A. BATTERMANN, J. M. GABLONSKY, A. PATRICK, C. T. KELLEY, T. COFFEY, K. KAVANAGH, AND C. T. MILLER. **Solution of a groundwater control problem with implicit filtering**. Technical Report CRSC-TR00-30, North Carolina State University, Center for Research in Scientific Computation, December 2000. To appear in Optimization and Engineering.
6. E. W. JENKINS, R. C. BERGER, J. P. HALLBERG, S. E. HOWINGTON, C. T. KELLEY, J. H. SCHMIDT, A. STAGG, AND M. D. TOCCI. **Newton-Krylov-Schwarz methods for Richards' equation**. Technical Report CRSC-TR99-32, NCSU, CRSC, October 1999. submitted for publication.

3.2. Proceedings Publications.

1. C. T. MILLER, M. W. FARTHING, C. E. KEES, AND C. T. KELLEY, *Higher order, locally conservative, temporal integration methods for multiphase flow in porous media*, in Computational Methods in Water Resources XIV, Vol. 1, S. M. Hassanizadeh, R. J. Schotting, W. G. Gray, and G. F. Pinder, eds., Amsterdam, 2002, Elsevier, pp. 249–256.
2. K. R. KAVANAGH, C. T. KELLEY, R. C. BERGER, J. P. HALLBERG, AND S. E. HOWINGTON, *Nonsmooth nonlinearities and temporal integration of Richards' equation*, in Computational Methods in Water Resources XIV, Vol. 2, S. M. Hassanizadeh, R. J. Schotting, W. G. Gray, and G. F. Pinder, eds., Amsterdam, 2002, Elsevier, pp. 947–954.
3. E. W. JENKINS, R. C. BERGER, J. P. HALLBERG, S. E. HOWINGTON, C. T. KELLEY, J. H. SCHMIDT, A. STAGG, AND M. D. TOCCI, *A two-level aggregation-based Newton-Krylov-Schwarz method for hydrology*, in Parallel Computational Fluid Dynamics 1999, D. E. Keyes, A. Ecer, J. Periaux, and N. Satofuka, eds., North Holland, 2000, pp. 257–264.

4. S. E. HOWINGTON, R. C. BERGER, J. P. HALLBERG, J. F. PETERS, A. K. STAGG, E. W. JENKINS, AND C. T. KELLEY. *A model to simulate the interaction between groundwater and surface water*, 1999. Proceedings of the High Performance Computing Users' Group Meeting, Monterrey, CA, June 7–10.

3.3. Unpublished Presentations at Meetings.

1. K. R. Kavanagh, **Solving Groundwater Remediation Problems With Implicit Filtering**, SIAM 7th Conference on Optimization, Toronto, Canada, May 20–23, 2002.
2. K. R. Kavanagh, **Implicit Temporal Integration for Richards' Equation**, 7th Copper Mountain Iterative Methods Conference, Copper Mountain, Colorado, March 24–29, 2002.
3. K. R. Kavanagh, **Subsurface Control With Implicit Filtering**, Sixth SIAM Conference on Mathematical and Computational Issues in the Geosciences, Boulder, CO, June 11–14, 2001.
4. C. T. Kelley, **Nonlinear solvers and preconditioners in groundwater flow simulations**, September 28 1999. Workshop on Parallel Algorithms, U.S. Army Engineer Research and Development Center, Vicksburg MS.

3.4. Technical Reports.

- E. W. JENKINS, *The Application of Two-Level Domain Decomposition Preconditioners to Problems in Hydrology*, PhD thesis, North Carolina State University, Raleigh, North Carolina, 2000.

4. Scientific Personnel.

1. C. T. Kelley: Principal Investigator
2. E. W. Jenkins: Graduate Student
Ph. D. in Mathematics, August, 2000
3. K. R. Kavanagh: Graduate Student
MS in Mathematics, December, 2000; Ph. D. expected, 2003

REFERENCES

- [1] R. DEMBO, S. EISENSTAT, AND T. STEIHAUG, *Inexact Newton methods*, SIAM J. Numer. Anal., 19 (1982), pp. 400–408.
- [2] I. S. DUFF, A. M. ERISMAN, AND J. K. REID, *Direct Methods for Sparse Matrices*, Oxford University Press, New York, NY, 1986.
- [3] A. GREENBAUM, *Iterative Methods for Solving Linear Systems*, no. 17 in Frontiers in Applied Mathematics, SIAM, Philadelphia, 1997.
- [4] S. E. HOWINGTON, R. C. BERGER, J. P. HALLBERG, J. F. PETERS, A. K. STAGG, E. W. JENKINS, AND C. T. KELLEY, *A model to simulate the interaction between groundwater and surface water*, Tech. Rep. CRSC-TR99-27, North Carolina State University, Center for Research in Scientific Computation, August 1999. Proceedings of the High Performance Computing Users' Group Meeting, Monterrey, CA, June 7–10.
- [5] E. W. JENKINS, *The Application of Two-Level Domain Decomposition Preconditioners to Problems in Hydrology*, PhD thesis, North Carolina State University, Raleigh, North Carolina, 2000.
- [6] E. W. JENKINS, R. C. BERGER, J. P. HALLBERG, S. E. HOWINGTON, C. T. KELLEY, J. H. SCHMIDT, A. STAGG, AND M. D. TOCCI, *Newton-Krylov-Schwarz methods for Richards' equation*, Tech. Rep. CRSC-TR99-32, North Carolina State University, Center for Research in Scientific Computation, October 1999. submitted for publication.
- [7] ———, *A two-level aggregation-based Newton-Krylov-Schwarz method for hydrology*, in Parallel Computational

- Fluid Dynamics 1999, D. E. Keyes, A. Ecer, J. Periaux, and N. Satofuka, eds., North Holland, 2000, pp. 257–264.
- [8] E. W. JENKINS, C. T. KELLEY, C. T. MILLER, AND C. E. KEES, *An aggregation-based domain decomposition preconditioner for groundwater flow*, SIAM J. Sci. Comp., 23 (2001), pp. 430–441.
 - [9] C. E. KEES, *Multiphase Flow Modeling with DAE/MOL Methods*, PhD thesis, University of North Carolina, Chapel Hill, North Carolina, 2001.
 - [10] C. E. KEES AND C. T. MILLER, *C++ implementations of numerical methods for solving differential-algebraic equations: Design and optimization considerations*, ACM Trans. Math. Soft., 25 (2000), pp. 377–403.
 - [11] ———, *Higher order time integration methods for two-phase flow*, 2001. submitted for publication.
 - [12] C. E. KEES, C. T. MILLER, E. W. JENKINS, AND C. T. KELLEY, *Versatile two-level Schwarz preconditioners for multiphase flow*, Tech. Rep. CRSC-TR01-32, North Carolina State University, Center for Research in Scientific Computation, December 2001.
 - [13] C. T. KELLEY, *Iterative Methods for Linear and Nonlinear Equations*, no. 16 in Frontiers in Applied Mathematics, SIAM, Philadelphia, 1995.
 - [14] D. E. KEYES, *Aerodynamic applications of Newton-Krylov-Schwarz solvers*. to appear in Proc. of 14th International Conference on Num. Meths. in Fluid Dynamics. (R. Narishima et al. eds), Springer, NY 1995.
 - [15] Y. MUALEM, *A new model for predicting the hydraulic conductivity of unsaturated porous media*, Water Resources Research, 12 (1976), pp. 513–522.
 - [16] N. M. NACHTIGAL, S. C. REDDY, AND L. N. TREFETHEN, *How fast are nonsymmetric matrix iterations?*, SIAM J. Matrix Anal. Appl., 13 (1992), pp. 778–795.
 - [17] M. D. TOCCI, C. T. KELLEY, AND C. T. MILLER, *Accurate and economical solution of the pressure head form of Richards’ equation by the method of lines*, Advances in Water Resources, 20 (1997), pp. 1–14.
 - [18] H. A. VAN DER VORST, *Bi-CGSTAB: A fast and smoothly converging variant to Bi-CG for the solution of nonsymmetric systems*, SIAM J. Sci. Statist. Comput., 13 (1992), pp. 631–644.
 - [19] M. T. VAN GENUCHTEN, *Predicting the hydraulic conductivity of unsaturated soils*, Soil Science Society of America Journal, 44 (1980), pp. 892–898.