Abstract for 40-minute invited talk at the URSI General Assembly in 2005 (URSI= International Union of Radio Science)

Near-term Time Transfer Technologies and International Atomic Time (TAI)

Demetrios Matsakis U.S. Naval Observatory Washington, DC USA

While there are many forms of time-transfer, the most precise long-distance forms currently used for the generation of TAI and Coordinated Universal Time (UTC) involve either GPS or Two Way Satellite Time Transfer (TWSTT). This paper will give a brief description of their current and future capabilities, with emphasis on their uncertainties. Some of these uncertainties are due to inherent modeling or receiver instabilities, while others can be reduced through temperature and humidity stabilization, electronic impedance matching, and multipath minimization. The residual time-transfer uncertainties directly affect the uncertainties in each individual laboratory's realization of UTC.

GPS is the best-known means of precise time transfer, and the introduction of Common-View GPS contributed significantly to the great increase in the stability of TAI over the last 15 years. GPS pseudorange observations are currently adjusted by correcting the broadcast orbital and ionosphere delay information with post-processed values, and reduced in common-view mode, however "melting-pot" techniques have been shown to be more precise over long baselines. The continuous GPS observations are supplemented by periodic receiver calibrations, which have accuracies of several-ns. Greater precision (20 ps), but not significantly greater accuracy, would be attainable if carrier-phase GPS techniques were employed. Several institutions, and in particular the International GNSS Service (IGS), routinely provide publicly available carrier-phase based timing solutions in near-real time. Other institutions will reduce any laboratory's data for free via an automated procedure. A few institutions, such as JPL/NASA and NRCan, provide realtime carrier-phase based time transfer as well.

Beginning in 2000, time-transfer links using Two Way Satellite Time Transfer (TWSTT) began to replace GPS links, and currently over half the clocks are linked to TAI via TWSTT. TWSTT links can be calibrated so to achieve slightly subnanosecond absolute time transfer, while the precision is in the range of a few hundred picoseconds. Carrier-phase TWSTT holds the promise of ps-level precision, but this promise has not yet been realized in any system. The theory relevant to carrier-phase TWSTT will be presented, as will some experimental data.

The generation of TAI involves merging information via dissimilar links, which greatly complicates the relevant statistical approach and strongly increases the dependence of TAI upon the stability of the time-transfer equipment at those "pivot sites", which are

Report Documentation Page				Form Approved OMB No. 0704-0188		
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.						
1. REPORT DATE 2. REPORT TYPE 2005 N/A				3. DATES COVERED		
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER		
Near-Term Time Transfer Technologies and International Atomic Time (TAI)				5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NUMBER		
				5e. TASK NUMBER		
				5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) US Naval Observatory 3450 Massachusetts Ave, NW Washington, DC 20392				8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited						
13. SUPPLEMENTARY NOTES						
14. ABSTRACT						
15. SUBJECT TERMS						
16. SECURITY CLASSIFICATION OF: 17. LIMITATION OF				18. NUMBER	19a. NAME OF	
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	ABSTRACT UU	OF PAGES 2	RESPONSIBLE PERSON	

Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std Z39-18 linked to some laboratories via TWSTT but linked to other laboratories via GPS. In order to correctly model the processes, the correlation and anti-correlation of time-transfer links that share common sites must be estimated and accounted for. The relevant mathematics will be developed and presented. Taking into consideration the dominant importance of robustness, it is possible to optimally combine all available information, and a method of achieving this will be presented.