

**UNITED STATES AIR FORCE
311th Human Systems Wing**



Human Factors Considerations in Migration of Unmanned Aircraft System (UAS) Operator Control

20060406003

Anthony P. Tvaryanas, Major, USAF

February 2006

*Approved for public release;
distribution unlimited.*

**311th Performance Enhancement Directorate
Performance Enhancement Research Division
2485 Gillingham Drive
Brooks City-Base TX 78235-5105**

NOTICES

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely Government-related procurement, the United States Government incurs no responsibility or any obligation whatsoever. The fact that the Government may have formulated or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication, or otherwise in any manner construed, as licensing the holder or any other person or corporation; or as conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

The mention of trade names or commercial products in this publication is for illustration purposes and does not constitute endorsement or recommendation for use by the United States Air Force.

The Office of Public Affairs has reviewed this report, and it is releasable to the National Technical Information Service, where it will be available to the general public, including foreign nationals.

This report has been reviewed and is approved for publication.

Government agencies and their contractors registered with Defense Technical Information Center (DTIC) should direct requests for copies to: Defense Technical Information Center, 8725 John J. Kingman Rd., STE 0944, Ft. Belvoir, VA 22060-6218.

Non-Government agencies may purchase copies of this report from: National Technical Information Services (NTIS), 5285 Port Royal Road, Springfield, VA 22161-2103.



ANTHONY P. TVARYANAS
Maj, USAF, MC, FS
Chief, Unmanned Aircraft Systems (UAS)
Human Systems Integration Branch



STEFAN H. CONSTABLE
Director, Performance Enhancement Research
Division

REPORT DOCUMENTATION PAGE**Form Approved**
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Service, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188) Washington, DC 20503.

PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY) 02-07-2006		2. REPORT TYPE Final		3. DATES COVERED (From - To) Aug 2005 - Jan 2006	
4. TITLE AND SUBTITLE Human Factors Considerations in Migration of Unmanned Aircraft System (UAS) Operator Control				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Anthony P. Tvaryanas				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) 311 th Performance Enhancement Directorate Performance Enhancement Research Division 2485 Gillingham Drive, Brooks City-Base, TX 78235-5105				8. PERFORMING ORGANIZATION REPORT NUMBER HSW-PE-BR-TR-2006-0002	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S) 311 HSW/PE	
				11. SPONSORING/MONITORING AGENCY REPORT NUMBER	
12. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT Unmanned aircraft system (UAS) operator control can be migrated within temporal, physical, and functional domains. Although such control migrations occur in current UAS operations, there are no human factors studies specifically addressing this issue in UASs. This work sought to identify reasons for migrating UAS operator control and summarize the human factors literature with inferential bearing on this topic. Migration of UAS operator control is necessary to overcome limitations of the human operator, current technology, or both. There are potential advantages to control migration to include mitigating operator vigilance decrements and fatigue, facilitating operator task specialization, and optimizing workload during multi-aircraft and payload control tasks. However, there are also significant disadvantages to include transient degraded operator situational and systems awareness and more complex and potentially distributed teams of operators. Future work should focus on improving the empirical knowledge base on UAS human factors so evidence-based recommendations can be made when incorporating control migration in UAS design and operations.					
15. SUBJECT TERMS Unmanned air vehicle, UAV, remotely piloted aircraft, RPA, remotely piloted vehicle, RPV, crew changeover, vehicle handoff, human factors					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UL	18. NUMBER OF PAGES 34	19a. NAME OF RESPONSIBLE PERSON Maj Anthony P. Tvaryanas
a. REPORT UNCLASSIFIED	b. ABSTRACT UNCLASSIFIED	c. THIS PAGE UNCLASSIFIED			19b. TELEPHONE NUMBER (Include area code) 210-536-4446; DSN 240-4446

THIS PAGE INTENTIONALLY LEFT BLANK

TABLE OF CONTENTS

	<u>Page</u>
Executive Summary	iv
Acknowledgements	v
Introduction	1
Reasons for Control Migration	2
Temporal	2
Physical	3
Functional	4
Advantages of Control Migration	5
Vigilance and Fatigue	5
Functional Specialization	6
Workload and Multiple Vehicle Control	8
Payload Control	9
Disadvantages of Control Migration	10
Situational Awareness	10
Complex Teaming Situations	11
Aeromedical Implications	12
Conclusion	13
References	15

EXECUTIVE SUMMARY

Purpose: To identify the potential human factors concerns in migration of unmanned aircraft system (UAS) operator control.

Background: UAS operator control can be migrated within temporal, physical, and functional domains. Although such control migrations occur routinely in current UAS operations, they constitute a critical and potentially high workload phase of flight. Despite this fact, there are currently no relevant human factors studies in the literature specifically addressing this issue in UASs.

Methodology: The technical approach involved identifying reasons which might necessitate the migration of UAS operator control and exploring the potential advantages and disadvantages of control migration. The existing human factors literature was reviewed for studies with inferential bearing on this topic.

Overall Assessment: There is a very limited scope of work to date on migration of UAS operator control requiring the application of findings from research in other task domains to that of the UAS environment. Based on the synthesis of the available literature:

- Migration of UAS operator control is necessary to overcome limitations of the human operator, current technology, or both.
- There are potential advantages to control migration to include the maintenance of operator performance by mitigating fatigue and vigilance decrements through optimum shift lengths (e.g., 6-10 hours) and the provision of work breaks, facilitating enhanced operator functional specialization, and allowing for the adjustment of workload during multi-aircraft and payload control tasks via control migration strategies.
- Possible significant disadvantages to control migration include transient degraded operator situational and systems awareness and more complex and potentially distributed teams of operators.
- Future work should focus on improving the empirical knowledge base on UAS human factors so evidence-based recommendations can be made when incorporating control migration in UAS design and operations.

ACKNOWLEDGEMENTS

The author expresses thanks to Col (Dr) Lex Brown at the 311th Human Systems Wing's Performance Enhancement Directorate for his technical and financial support in conducting this research. The views and opinions are those of the author, and do not necessarily represent the views of the U.S. Air Force, the Department of Defense, or any other government agency.

THIS PAGE INTENTIONALLY LEFT BLANK

HUMAN FACTORS CONSIDERATIONS IN MIGRATION OF UNMANNED AIRCRAFT SYSTEM (UAS) OPERATOR CONTROL

INTRODUCTION

The advent of unmanned aircraft systems (UASs) has created a host of new human factors challenges¹⁸ arising primarily because the air vehicle and operator(s) are no longer necessarily co-located.²⁶ One of the most unique of these human factors challenges concerns migration of UAS operator control. While the term migration simply implies movement, the construct of control migration used in this work is similar to that described by Kahne²⁰ and includes changes in the locus of control within temporal, physical, and functional domains. For example, in current long endurance UASs, control may be transferred between operators in a single control station (e.g., crew changeover), between control stations (e.g., vehicle handoff), or among members of a crew (e.g., task execution).^{27,49} While the ability to migrate operator control adds a new dimension of flexibility in operating UASs, it also comes at a cost in terms of increased complexity and has been a factor in several UAS mishaps.^{51,66} Additionally, there are currently no relevant human factors studies in the literature specifically addressing this issue in UASs.²⁷ For autonomous UASs requiring only supervisory control, studies of air traffic control (ATC) might serve as an analog supervisory control domain.⁶ However, an important distinction is the fact ATC's instructions to aircraft are ultimately advisory rather than mandatory since legal responsibility for the safety of an aircraft rests with the pilot.¹⁹ Nevertheless, issues related to the human factors of migration of operator control are likely to be of particular concern in the near future in establishing guidelines for the certification and safe operation of UASs in civil airspace. The goal of the current work was to examine the existing human factors literature and summarize the state of knowledge which might have inferential bearing on the discussion of migration of UAS operator control. The technical approach involved identifying reasons which might necessitate the migration of UAS operator control and exploring the potential advantages and disadvantages of control migration.

REASONS FOR CONTROL MIGRATION

Temporal

Many current human-machine operations are continuous in character and the nature of these operations often preclude a temporary shutdown because of economical, operational, or other constraints.²¹ Such operations have the potential to create situations in which people are driven to work continuously. This has certainly been the case in military operations where technological advances in night vision devices and other sensors coupled with a global battle space has led to a doctrine of continuous, around-the-clock operations.^{3,23} Therefore, current military medium and high altitude endurance UASs have been designed to operate at distances requiring beyond line-of-sight (LOS) communications and remain airborne for nearly 1-2 days. Future military and civil UASs are projected to operate for even longer durations of time on the order of days to months.^{8,27,36}

A critical problem for endurance UASs is the predictable decrements experienced by individuals continuously performing cognitive tasks for sustained periods.^{21,23} In a study comparing the effects of fatigue versus alcohol intoxication, Dawson and Reid¹⁰ found the hourly performance decrement for each hour of wakefulness between 10 and 26 hours was equivalent to the performance decrement observed with a 0.004 percent rise in blood alcohol concentration. After 17 hours of sustained wakefulness, cognitive psychomotor performance decreases to a level equivalent to the performance impairment observed at a blood alcohol concentration of 0.05 percent. This is the proscribed level for alcohol intoxication in many western industrialized countries^{3,10} and exceeds the 0.04 percent limit established by the Federal Aviation Administration (FAA) for aircrew.¹⁶ Mullaney et al³³⁻³⁵ conducted several studies of continuous performance on monotonous tasks requiring sustained attention and found such performance produced rapid fatigue effects after only six hours. More than half of the study participants experienced psychological disturbances such as mild hallucinations, illusions, disorientation, and derealizations, mostly after 18 hours. Beyond the laboratory environment, an Air Force Safety Center study found fatigue-related performance decrements were present in 12.7 percent of the most serious class of Air Force mishaps occurring during fiscal years 1972-2000,⁵⁶ costing the Air Force an estimated 54 million dollars each year.³

While it is obviously unreasonable to expect a single operator to control a UAS with an endurance greater than one day, it is also evident operators will need to be changed during UAS operations spanning more than the majority of a day. Summarizing NASA's experience testing UASs, Del Frante and Cosentino¹¹ stressed the importance of adhering to established crew rest requirements, implying UAS operations are not immune to fatigue-related operator performance decrements. Additionally, studies of personnel working 8, 10, and 12 hour shifts³⁹⁻⁴³ have shown increased fatigue and poorer performance with 12-hour versus eight or ten hour shifts. Collectively, these studies suggest migration of operator control is desirable as UAS endurances routinely exceed 12 hours, although more optimally it should be considered after 6-10 hours.

Physical

As previously mentioned, some military endurance UASs operate at great distances from the control station, necessitating beyond line-of-sight (LOS) communications.^{27,36} As satellites or other UASs are used to relay signals over the horizon, variable time delays or latencies of one or more seconds are introduced. However, latencies greater than one second mean real-time feedback necessary for effective manual control is not available.⁶⁴ Additionally, many UAS operators are dependent on real-time imagery from cameras mounted on the remote vehicle in order to manually control the vehicle.⁵⁹ This requires data transmission links between the vehicle and control station with high bandwidths and low latencies. However, increasing distance between the vehicle and control station, especially beyond LOS, necessarily forces constraints on data link bandwidth and increases latency.^{26,31,59} Such data link constraints can result in limited temporal resolution, spatial resolution, color, and field of view of imagery irrespective of onboard sensor capabilities.^{59,60} With great enough distance, the frequency and immediacy of transmitted images may decrease to the point where direct manual control of the vehicle is significantly degraded.^{26,31} Besides vehicle control, experimental evidence has also shown visual tasks such as target detection and identification, tracking, and orientation are adversely affected by degraded image quality, slow update rates (< 2 Hz) and high latency (> 2 sec).^{59,61}

Increased automation (e.g., supervisory control) and predictive displays have been utilized to mitigate the effects of control latency,^{31,64} but there are situations where manual control modes may be preferred over supervisory control or a fully automated vehicle.⁵⁹ In such situations, an alternative strategy may be to handoff control to more proximate control stations. This approach has relative merit over supervisory control in situations where concerns over control latency and quality of visual imagery or sensor information are critical, such as in highly dynamic and changing environments where near-real time data is required for complex decision-making.^{26,59} Such situations might include weapons employment³¹ when there is a risk for fratricide or responding to a malfunctioning or damaged remote vehicle. Additionally, some current military UASs by design must be manually controlled during takeoff and landing.^{26,27,59} In these circumstances, a control station needs to be located in LOS distance of the airfield to minimize data transmission delays and optimize manual control. However, once airborne, control can be handed off to a geographically remote control station where the UAS is then operated via supervisory control, minimizing the equipment and personnel which must be sent to a potentially vulnerable forward base of operations.

Functional

Migration of control within a crew may occur when a UAS is designed such that control is functionally divided between non-equivalent operators. Current military UASs are typically operated by at least two operators with one responsible for vehicle control and the other for payload control.^{26,59} While the payload operator usually does not directly control the vehicle, it may be possible for this individual to exercise indirect control of a UAS if the program logic automatically adjust the flight path to stabilize camera or sensor images. For example, current MQ-1 Predator UAS multi-aircraft control (MAC) ground control station design allows sensor operators limited control of the vehicle within a sensor operator container (SOC) predefined by the pilot.⁴⁶ Functional migration of control also occurs in some small military tactical UASs where responsibility for takeoff/landing and en route control is divided between two operators. In this situation, the external pilot (EP) interacts with the UAS while in direct visual contact at the site of takeoff or landing. In contrast, the air vehicle operator (AVO) is inside a control station and interacts with the UAS through an interface of sensor displays and controls during the

en route phase of flight.^{1,27,66} While control is functionally divided out of necessity because of task-specific human-machine interfaces (HMIs), Barnes et al¹ also demonstrated differences between EPs and AVOs with regards to operator abilities across multiple cognitive skill sets.

ADVANTAGES OF CONTROL MIGRATION

Vigilance and Fatigue

Much of an operator's task load in highly automated systems such as UASs is supervisory in nature, consisting mainly of passive monitoring of system parameters and remaining alert for malfunctions.^{32,59} This trend towards placing the operator in the role of passive monitor has continued despite years of vigilance research demonstrating such roles make maintaining a constant level of alertness exceedingly difficult^{9,25,37,65} and predispose to "hazardous states of awareness."^{38(p. 449)} Studies of vigilance tasks have consistently demonstrated a vigilance decrement beginning as early as 20-35 minutes after task initiation and characterized by declining numbers of correct responses, increasing response times, or both.^{9,23,64} One study found declining response rates after only 2-3 minutes of task performance, with response rates eventually plateauing at 70-80 percent of initial rates.²⁴ Prolonged vigilance work generally invokes subjective feelings of boredom and monotony and invariably induces decreased levels of physiologic arousal. Boredom in particular can become apparent within minutes of the onset of a monotonous task and is associated with decreased performance efficiency and increased drowsiness. However, when coupled with the need to maintain high levels of alertness, boring vigilance tasks can be perceived as quite stressful.^{23,47} This stress predisposes to short term fatigue which typically manifests as long response times, missed signals, and brief interruptions in performance due to gaps or lapses in attention⁴⁴ as well as increased decision errors or decreased throughput.²³ This was born out in a study of U.S. Air Force MQ-1 Predator UAS operators which found a 7.1-17.8% increase in reaction times associated with more frequent lapses in attention as well as increased subjective ratings of fatigue and decreased ratings of alertness over the course of an 8-hour shift. Ninety-two percent of these operators also reported "moderate" to "total" boredom.⁵⁵ Thus, it should be expected

tasks requiring the sustained attention of UAS operators will be susceptible to degraded performance and increased risk for operator error.³²

Although initial research^{21,45} with complex monitoring tasks typical of the ATC task environment suggested vigilance decrements did not occur, more recent studies are supportive of the vigilance decrement in both simple and complex monitoring tasks.^{9,30,44,48} The validity of these concerns in the UAS task environment was demonstrated in a study of Army UAS operator performance under two experimental conditions involving 8-10 hour versus three hour flights.² Target detection and recognition performance as well as crew reaction times were significantly degraded during nocturnal operations involving the longer flights while no nocturnal changes were observed for the shorter flights. Likewise, two studies^{44,48} using an ATC task found the time to detect and the frequency of missed traffic conflicts increased significantly over the course of just two hours. These vigilance decrements were attributed to increasing lapses in attention rather than a generalized fatigue effect.

One of the best ways to overcome these effects is change, whether using work breaks, rest pauses, or split shifts, although the benefits of rest pauses may derive more from subjective factors such as relief of boredom.²³ Warm⁶² in particular recommended continuous vigilance monitoring tasks be kept to less than four hours in duration. Irregardless of the method of change, it will necessarily involve the migration of control to another operator, whether in the same or another control station. Thus, control migration plays a potentially critical role in the maintenance of optimum operator performance and in decreasing the risk for operator errors.

Functional Specialization

Unlike traditional manned aircraft where crew size is limited by vehicle payload constraints and all human functional capabilities must be resident in the onboard crew, UASs offer the advantage of allowing these functional capabilities to be distributed over a multitude of potentially geographically dispersed specialists. In essence, a UAS crew is limited only by data transmission link accessibility. Given the massive amounts of information currently down-linked from UASs³² and the information processing constraints imposed by the sequential

decision-making of human operators,²⁰ it is key to distribute this information so it can be more efficiently processed for mission accomplishment.³² This point was highlighted by a study of human systems integration (HSI) issues in military UAS mishaps which found an association between failures in the cognitive domain and operator errors.⁵³

Beyond the issue of information processing, UASs offer the opportunity to employ task specialization beyond the level hereto seen in manned aircraft. The potential need for task specialization in UAS operations may be appreciated given the current military experience with UASs in which training and attentional issues are frequent causal factors in human error-related mishaps.⁵⁴ As noted by Barnes et al¹ in their study of Army UAS operators, experience improves operators' cognitive throughput, allowing them to devote limited attentional resources to future problems while automatically attending to immediate perceptual and motor tasks. This was echoed in NASA's lessons learned testing UASs that "even more important than practicing the emergency procedures is practicing the normal procedures to the point that they are second nature."^{11(p. 8)} Thus, experience serves to increase an operator's cognitive efficiency in problem solving by effectively increasing available attentional resources.⁶⁴ Unfortunately, the cognitive efficiency obtained via experience is specific to the tasks experienced and not broadly generalizable.¹

Given the task-centric nature of expertise, consideration should be given to the creation of specialty teams to intervene and handle uncommon or off-nominal events. Such teams could rehearse infrequent tasks and explore potential outcomes, thereby developing proficiency in situational problem solving prior to encountering the actual event. For example, rather than training all operators to handle emergencies, specialty teams could be trained to take control and troubleshoot a malfunctioning or damaged UAS. These emergency teams could operate from remote control stations equipped with enhanced displays to aid diagnosis and allow predictive simulation. Such methods have been used successfully in the U.S. space program.³²

Functional specialization could also be utilized in non-emergent, nominal situations to optimize the central role of the human decision-maker within the system. In traditional manned combat aircraft, the pilot has the responsibility to authenticate targets and trigger weapons

because they are presumed to be in the best position to assess the situation and make timely decisions. However, UASs allow this function to be migrated to other team members possessing higher levels of technical or combat expertise such as a target detection specialist or experienced mission commander, thereby improving the confidence level of information presented to higher authorities.³² Additionally, functional specialization allows for increased training program efficiency since all personnel don't necessarily need to receive equal training given non-uniform task environments across worksites. The FAA has explored this issue with regards to training air traffic control specialists (ATCS)⁵⁰ and the U.S. Air Force has adopted this approach in training MQ-1 Predator UAS operators on takeoff and landing.

Workload and Multiple Vehicle Control

There currently is limited human factors research suggesting one operator may control more than one UAS under relatively idealized conditions to include closely coordinated and correlated vehicle activities, a stable environment, and reliable automation.^{6,13,14,27} Other research has demonstrated operator performance controlling even a single vehicle is significantly degraded when heavy demands are imposed by payload operations.^{2,61,63} This would suggest the ability of an operator to attend to multiple UASs may be severely compromised under non-idealized conditions, especially if one vehicle is malfunctioning or damaged.²⁷ Feedback from testing of the MQ-1 Predator UAS MAC ground control station which utilizes one pilot and four sensor operators to control four UASs found dynamic taskings may require two pilots.⁴⁶ Additional human factors research is available examining situational awareness in ATC, an analog for supervisory control of multiple vehicles. Endsley and Rodgers¹⁵ found ATCS accuracy was significantly impacted by the number of aircraft being controlled and situational awareness declined dramatically when the number of aircraft exceeded 8-10. This is consistent with the magic number " 7 ± 2 " in memory research,²⁹ suggesting there are finite limits on human information processing beyond which people tend to forget. Two studies^{17,28} examining ATCS performance while passively monitoring aircraft under free flight conditions found a significant decrement in situational awareness when controllers had to handle 17 versus 11 aircraft. Another study examining control of multiple retargetable missiles⁶ found operators could effectively control 8-12 missiles, but performance degraded with 16 missiles. Overall, the

preponderance of evidence suggests greater than 12 vehicles potentially represents a cognitive saturation state for operators interacting with semi-autonomous vehicles requiring only the setting of new goals.⁷

Given the limits of an operator's ability to manage multiple UASs, migration of control may need to be utilized as a workload mitigation strategy. For example, an operator controlling multiple UASs under high workload conditions (e.g., multiple vehicle requests for operator attention) could transfer control of one or more UASs to other operators under low workload conditions, even as part of normal operations. In cases where a single UAS requires sustained attention because of a backlog of vehicle requests for operator attention or off-nominal operating conditions, control of this high workload UAS could be transferred to an on-call operator or supervisor akin to current ATC practices. The ability to transfer control of UASs based on workload prevents a single operator controlling multiple UASs from having to adopt triage-like procedures for handling multiple attentional demands.³²

Payload Control

As already alluded to during the discussion of multiple vehicle control, performing payload tasks can significantly increase operator workload and degrade operator performance. In current military reconnaissance UASs, vehicle and payload control are typically divided between a vehicle operator and a payload operator.^{26,61} Van Erp and Van Breda⁶¹ concluded such a crew structure was reasonable in light of findings that consolidating vehicle and payload control within a single operator substantially degraded performance. Likewise, Barnes and Matz² studied a prototype UAS control station configuration which allowed a single operator to perform both vehicle control and target acquisition functions. They found operators became focused on the targeting function to the detriment of situational awareness and vehicle control, leading the authors to question the wisdom of using a single operator. Two additional studies demonstrated attentional fixation and cognitive tunneling during target analysis which degraded performance on other tasks irrespective of level of automation or use of auditory cueing.^{13,63} The task of manipulating a camera image, analyzing targets, and keeping track of cardinal directions appears to be sufficiently challenging that timesharing with other tasks such as vehicle control

becomes virtually impossible. Van Breda and Passenier⁵⁸ also noted operator performance was poor when utilizing “double-stick” controls where one joystick controls airframe heading and speed and the other camera heading and pitch. However, this is not surprising given such control arrangements predispose to perceptual confusion which increases the potential for action slip errors.⁶⁴

Nevertheless, for optimal flexibility and cost effectiveness, it is desirable to allocate both vehicle and payload control to one operator.⁵⁸ It may therefore be necessary to delineate circumstances under which vehicle and payload control can be safely performed by a single UAS operator and when control of the payload should be transferred to another operator.²⁷ This may be decided prior to a mission or payload control may need to be transferred during a mission in response to a dynamically evolving situation. As previously discussed, a UAS operator’s ability to perform payload-oriented visual tasks such as target detection and identification, tracking, and orientation is impaired by low temporal update rates and long transmission delays.^{59,61} If vehicle control is adequate for the task using some form of supervisory control, it may only be necessary to handoff payload control to a more proximate control station, potentially eliminating the need for full control stations in forward locations. Additionally, the ability to handoff payload control to those directly requesting the camera imagery or sensor data (e.g., target detection specialists or fielded forces) could increase the efficiency of data collection and eliminate the need for coordination with an intermediate payload operator. At the extreme, control of weapons could be transferred to the forces requesting their employment, hopefully decreasing the risk for fratricide.

DISADVANTAGES OF CONTROL MIGRATION

Situational Awareness

While there are good reasons to consider utilizing migration of operator control in UASs, it is important to also explore the potential pitfalls. Indeed, migration of control may well constitute a critical and potentially high workload phase for UAS operators.²⁷ For example, several military UAS mishaps have occurred either directly during or indirectly as the result of

changeovers or handoffs.^{27,51,66} In handing off control between stations, mishaps have resulted when the station receiving control was improperly configured.⁶⁶ During changeovers, mishaps have resulted because of the new operator's decreased systems awareness.⁵¹ More broadly, there is concern for an acute decrement in crew situational awareness when control is transferred to a crew not currently involved in the ongoing mission. Kidd and Kinkade²¹ demonstrated the existence of such an operator change-over performance decrement in the ATC environment. Controller performance was markedly decreased over the first five minute period following assumption of controller duties. This change-over performance decrement was mitigated by about 50 percent if either parallel control or auditory-plus-visual monitoring was employed as a pretransition condition. Another study examining operational errors in ATC¹² found errors were most frequent during the first 15 minutes after assuming controller duties and nearly half occurred within the first 30 minutes on position. An analysis of U.S. Air Force MQ-1 Predator UAS mishaps revealed a similar predominance of operator error-related mishaps relatively early in the duty period suggestive of a changeover effect.⁵² Likewise, a study of Army UAS operators² found operators preferred longer over shorter rotations because they perceived the longer rotations allowed for better situational awareness of the tactical environment.

Complex Teaming Situations

Migrating operator control can create distributed crews with dynamically changing membership which may have significant associated costs in terms of the increased complexity of crew coordination and communication.^{22,27} Moving from the individual to multiple operators introduces an additional layer of cognitive requirements in the form of the associated demands for working together effectively as a team. Additionally, the effects of physical dispersion on team workload and performance have not been well evaluated.⁵ However, breakdowns in team performance, cooperation, and communication do occur in military UAS operations and have been a contributing factor in UAS mishaps.⁵⁴

Studies of team dynamics in the UAS task environment are limited. Kiekel et al²² used a UAS synthetic task environment to assess team cognition by evaluating the flow of communications among team members. They found communication patterns were less stable

when team members were geographically dispersed as compared to co-located. Cooke et al⁵ also used a UAS synthetic task environment to evaluate the effects of distributed mission environments and workload on team performance, process, and cognition. While they did not find any detrimental effects of physical dispersion on team processes, knowledge, and situational awareness, the composition of their teams limits the validity of the results when extrapolated to the context of migration of operator control. Specifically, in their study a team consisted of a UAS crew comprised of three members: an air vehicle operator, payload operator, and data exploitation, mission planning, and communications (DEMPC) operator. This makes it difficult to infer how teams consisting of more than one UAS crew would function in the context of UAS handovers or handoffs, especially given the membership of such teams may not be predetermined and generally exist for only short periods of time. This is important given the findings of Cooke et al that teams generally required four 40-minute missions to reach asymptotic levels of performance and teamwork knowledge developed with mission experience. This suggests those phases of UAS operations involving migration of control may well be vulnerable to diminished team performance.

AEROMEDICAL IMPLICATIONS

Human factors issues are central to the current practice of aerospace medicine, especially with the recent increased focus on ensuring humans have the capacity to perform under conditions associated with current aerospace operations. As noted by a U.S. Air Force Scientific Advisory Board report, *Human Systems Integration in Air Force Weapons System Development and Acquisition*, “the roles of human operators are undergoing qualitative changes driven by technological changes...because of these transformational factors, the considerable base of human factors knowledge derived from cockpit experience may have limited applicability to future systems.”^{57(p. v)} The importance of this finding is self evident given UASs currently comprise 81 percent of all the U.S. military’s aviation hours flown per year⁴ and the U.S. UAS inventory is expected to grow from 250 vehicles today to 675 by 2010 and 1,400 by 2015.³⁶ Since UASs represent the engineering solution to such traditional aeromedical human factors concerns as barotrauma and hypoxia, acceleration, vibration, thermal stress, and those forms of

spatial disorientation associated with acceleration, human cognitive and information processing capabilities are the main limiting factor for the performance of this significant and growing subset of aerospace systems. As demonstrated in this review, there is currently a lack of aeromedical research addressing these capabilities, particularly as applied to UASs. Some initial work has been started as part of the U.S. Air Force's UAS Performance Analysis Project which will document the workflow, major accomplishments, and supporting tasks to include the knowledge, skills, and abilities associated with the roles of MQ-1 Predator and RQ-4 Global Hawk UAS pilots and sensor operators (Constable S, 311th Performance Enhancement Directorate. Personal communication; 2006). The capability to migrate operator control and potentially for operators to task specialize will have significant ramifications for future operator selection, certification, and training. Additionally, the ability to migrate control may drive new perspectives on more traditional aeromedical concerns such as fatigue, workload, and acceptable levels of risk for operator incapacitation.

CONCLUSION

Current UASs encompass a broad range of military mission capabilities and offer great promise in potentially serving a host a civil applications. Transformational technologies and operational necessity has led UAS designers and operators to step out of the one crew-aircraft-mission paradigm of traditional manned aircraft systems and allowed for the routine migration of UAS control between operators across temporal, physical, and functional domains. This has in part been driven by limitations of the human operator, the technology, or both. However, this capability also offers aerospace human factors practitioners the potential to redesign UAS operator tasks and jobs in order to capitalize on the inherent strengths of human operators while limiting the impact of their natural weaknesses. It is also equally important these same human factors practitioners identify the potential pitfalls of control migration and design appropriate administrative or engineering countermeasures. As this review has demonstrated, the limited scope of work to date on this topic requires the application of findings from research in other task domains to that of the UAS environment. The immediate challenge therefore is to verify the generalizability of existing research to UASs. However, future work should focus on improving

the empirical knowledge base regarding UAS human factors so improved cost-benefit analyses can be made when considering incorporating control migration in UAS design and operations.

REFERENCES

- (1) Barnes MJ, Knapp BG, Tillman BW, et al. Crew systems analysis of unmanned aerial vehicle (UAV) future job and tasking environments. Aberdeen Proving Ground, MD: Army Research Laboratory; 2000 Jan. Report No.: ARL-TR-2081.
- (2) Barnes MJ, Matz MF. Crew simulations for unmanned aerial vehicle (UAV) applications: sustained effects, shift factors, interface issues, and crew size. Proceedings of the Human Factors and Ergonomics Society 42nd Annual Meeting; 1998 Oct 5-9; Chicago. Santa Monica, CA: Human Factors and Ergonomics Society; 1998.
- (3) Caldwell JA. Fatigue in aviation operations. Retrieved August 9, 2005, from the World Wide Web: <http://www.afrlhorizons.com/Briefs/Jun03/HE0301.html>
- (4) Child J. The UAV gold rush. COTS Journal. Retrieved December 18, 2005, from the World Wide Web: <http://www.cotsjournalonline.com/home/article.php?id=100432>
- (5) Cooke NJ, DeJoode JA, Pedersen HK, et al. The role of individual and team cognition in uninhabited air vehicle command-and-control. Mesa, AZ: Arizona State University East, Applied Psychology Program; 2004 Mar. Report No.: AFRL-SR-AR-TR-04-0220.
- (6) Cummings ML, Guerlain S. Human performance issues in supervisory control of autonomous airborne vehicles. Retrieved August 9, 2005, from the World Wide Web: http://web.mit.edu/aeroastro/www/people/missyc/pdfs/AUVSI_Cummings.pdf
- (7) Cummings ML, Mitchell PJ. Management of multiple dynamic human supervisory control tasks for UAVs. Retrieved August 9, 2005, from the World Wide Web: http://web.mit.edu/aeroastro/www/labs/halab/papers/HCI2005_cummings2.pdf
- (8) Curry M. NASA – past projects – Helios prototype. Retrieved July 30, 2005, from the World Wide Web: <http://www.nasa.gov/centers/Dryden/history/pastprojects/Erast/helios.html>

- (9) Davies DR, Parasuraman R. The psychology of vigilance. London: Academic Press, 1982: 208-227.
- (10) Dawson D, Reid K. Fatigue, alcohol and performance impairment. *Nature* 1997;338:235.
- (11) Del Frate JH, Cosentino GB. Recent flight test experience with uninhabited aerial vehicles at the NASA Dryden Flight Research Center. Edwards AFB, CA: Dryden Flight Research Center; 1998 Apr. Report No. NASA/TM-1998-206546.
- (12) Della Rocco P, ed. The role of shift work and fatigue in air traffic control operational errors and incidents. Oklahoma City, OK: Department of Transportation, Federal Aviation Administration; 1999 Jan. Report No.: DOT/FAA/AM-99/2:11-21.
- (13) Dixon SR, Wickens CD. Control of multiple-UAVs: a workload analysis. Retrieved August 9, 2005, from the World Wide Web: <http://www.humanfactors.uiuc.edu/Reports&PapersPDFs/isap03/dixwic.pdf>
- (14) Dixon SR, Wickens CD. Imperfect automation in unmanned aerial vehicle flight control. Retrieved August 9, 2005, from the World Wide Web: <http://www.humanfactors.uiuc.edu/Reports&PapersPDFs/TechReport/03-17.pdf>
- (15) Endsley MR, Rodgers MD. Distribution of attention, situational awareness, and workload in a passive air traffic control task: implications for operational errors and automation. Oklahoma City, OK: Department of Transportation, Federal Aviation Administration; 1997 Jul. Report No.: DOT/FAA/AM-97/13.
- (16) Federal Aviation Administration. Guide for aviation medical examiners. Retrieved August 9, 2005, from the World Wide Web: http://www.faa.gov/avr/aam/game/Version_2/03AMEMANUAL/Home/HOME.htm

(17) Galster SM, Duley JA, Masalonis AJ, et al. Air traffic controller performance and workload under mature free flight: conflict detection and resolution of aircraft self-separation. *International Journal of Aviation Psychology* 2001;11:71-93.

(18) Gawron VJ. Human factors issues in the development, evaluation, and operation of uninhabited aerial vehicles. *Proceedings AUVSI '98*; 1998 Jun 8-12; Huntsville. Arlington: Association of Unmanned Vehicle Systems International, 1998.

(19) Hopkins VD. Human factors in the ground control of aircraft. Neuilly-sur-Seine, France: North Atlantic Treaty Organization, Advisory Group for Aerospace Research & Development; 1970. Report No.: AGARD-AG-142.

(20) Kahne S. Control migration: a characteristic of C3 systems. *Control Systems Magazine* 198;15-19.

(21) Kidd JS, Kinkade RG. Operator change-over effects in a complex task. Wright-Patterson AFB, OH: Wright Air Development Center, Aerospace Medical Laboratory; 1959 Aug. Report No.: WADC TR 59-235.

(22) Kiekel PA, Gorman JC, Cooke NJ. Measuring speech flow of co-located and distributed command and control teams during a communication channel glitch. Retrieved August 12, 2005, from the World Wide Web:
[http://www.certt.com/publications/Measuring%20speech%20flow%20of%20collocated%20and%20distributed\[1\].pdf](http://www.certt.com/publications/Measuring%20speech%20flow%20of%20collocated%20and%20distributed[1].pdf)

(23) Krueger GP. Sustained military performance in continuous operations: combatant fatigue, rest and sleep needs. In: Gal R, Mangelsdorff, AD, eds. *Handbook of Military Psychology*. New York: Wiley; 1991:255-277.

- (24) Makeig S, Elliott FS, Inlow M, et al. Predicting lapses in vigilance using brain evoked responses to irrelevant auditory probes. San Diego, CA: Naval Health Research Center; 1990. Report No.: TR 90-39.
- (25) Makeig S, Elliott FS, Postal M. First demonstration of an alertness monitoring management system. Bethesda, MD: Naval Health Research Center; 1993. Report No. TR 93-36.
- (26) McCarley JS, Wickens CD. Human factors concerns in UAV flight. Retrieved July 30, 2005, from the World Wide Web: <http://www.hf.faa.gov/docs/508/docs/uavFY04Planrpt.pdf>
- (27) McCarley JS, Wickens CD. Human factors implications of UAVs in the national airspace. Retrieved July 30, 2005, from the World Wide Web: <http://www.humanfactors.uiuc.edu/Reports&PapersPDFs/TechReport/05-5.pdf>
- (28) Metzger U, Parasuraman R. The role of the air traffic controller in future air traffic management: an empirical study of active control versus passive monitoring. *Human Factors* 2001;43:519-528.
- (29) Miller GA. The magical number seven plus or minus two: some limits on our capacity for processing information. *Psychological Review* 1956;63:81-87.
- (30) Molloy R, Parasuraman R. Monitoring an automated system for a single failure: vigilance and task complexity effects. *Human Factors* 1996;38:311-322.
- (31) Mouloua M, Gilson R, Daskarolis-KringvE, et al. Ergonomics of UAV/UCAV mission success: consideration for data link, control, and display issues. Proceedings of the Human Factors and Ergonomics Society 45th Annual Meeting, 2001 Oct 8-12; Minneapolis. Santa Monica, CA: Human Factors and Ergonomics Society; 2001.
- (32) Mouloua M, Gilson R, Kring J, et al. Workload, situation awareness, and teaming issues for UAV/UCAV operations. Proceedings of the Human Factors and Ergonomics Society 45th

Annual Meeting, 2001 Oct 8-12; Minneapolis. Santa Monica, CA: Human Factors and Ergonomics Society; 2001.

(33) Mullaney DJ, Fleck PA, Okudaira N, et al. An automated system for administering continuous workload and for measuring sustained continuous performance. *Behavior Research Methods, Instruments, and Computers* 1985;17:16-18.

(34) Mullaney DJ, Kripke PA, Fleck PA, et al. Sleep loss and nap effects on sustained continuous performance. *Psychophysiology* 1983;20:643-651.

(35) Mullaney DJ, Kripke DF, Fleck PA, et al. Effects of sustained continuous performance on subjects working alone and in pairs. *Perceptual and Motor Skills* 1983;57:819-832.

(36) Office of the Under Secretary of Defense for Acquisition, Technology, and Logistics. Unmanned aircraft systems roadmap 2005-2030. Retrieved December 18, 2005 from the World Wide Web: <http://www.acq.osd.mil/usd/Roadmap%20Final2.pdf>

(37) Parasuraman R. Human-computer monitoring. *Human Factors* 1987;29:695-706.

(38) Pope AT, Bogart EH. Identification of hazardous awareness states in monitoring environments. *SAE 1992 Transactions: Journal of Aerospace* 1992;101:448-457.

(39) Rosa RR. Performance, alertness and sleep after 3-5 years of 12 h shifts: a follow-up study. *Work and Stress* 1991;5:107-116.

(40) Rosa RR, Bonnet MH. Performance and alertness on 8 h and 12 h rotating shifts at a natural gas utility. *Ergonomics* 1993;36:1177-1193.

(41) Rosa RR, Colligan MJ, Lewis P. Extended workdays: effects of 8-hour and 12-hour rotating shift schedules on performance, subjective alertness, sleep patterns, and psycho-social variables. *Work and Stress* 1989;3:21-32.

(42) Rosa RR, Wheeler DD, Warm JS, et al. Extended workdays: effects on performance and ratings of fatigue and alertness. Behavior Research Methods, Instruments, and Computers 1985;17:6-15.

(43) Schroder DJ, Rosa RR, Witt LA. Some effects of 8- vs. 10-hour work schedules on the test performance/alertness of air traffic control specialists. Oklahoma City, OK: Department of Transportation, Federal Aviation Administration; 1995 Dec. Report No.: DOT/FAA/AM-95/32.

(44) Schroder DJ, Touchstone RM, Stern JA, et al. Maintaining vigilance on a simulated ATC monitoring task across repeated sessions. Oklahoma City, OK: Department of Transportation, Federal Aviation Administration; 1994 Mar. Report No.: DOT/FAA/AM-94/6.

(45) Shaw WJ. The effects of continued performance in a task of air traffic control. Perceptual and Motor Skills 1955;5:167.

(46) Tanner SC. Predator MAC OUE summary. Third Annual Remotely Piloted Aircraft Conference; 2005 Nov 15-17; Chantilly. Washington: Department of Defense; 2005.

(47) Thackray RI. Boredom and monotony as a consequence of automation: a consideration of the evidence relating boredom and monotony to stress. Oklahoma City, OK: Department of Transportation, Federal Aviation Administration; 1980 Feb. Report No.: DOT/FAA/AM-80/1.

(48) Thackray RI, Touchstone RM. An evaluation of the effects of high visual taskload on the separate behaviors involved in complex monitoring performance. Oklahoma City, OK: Department of Transportation, Federal Aviation Administration; 1988 Jan. Report No.: DOT/FAA/AM-88/1.

- (49) Theunissen E, Goossens AAHE, Bleeker OF, et al. UAV mission management functions to support integration in a strategic and tactical ATC and C2 environment. AIAA Modeling and Simulation Technologies Conference and Exhibit; 2005 Aug 15-18; San Francisco. Reston: American Institute of Aeronautics and Astronautics, 2005.
- (50) Thompson RC, Agen RA, Broach DM. Differential training needs and abilities at air traffic control towers: should all controllers be trained equally? Oklahoma City, OK: Department of Transportation, Federal Aviation Administration; 1998 Mar. Report No.: DOT/FAA/AM-98/8.
- (51) Tvaryanas AP. USAF UAV mishap epidemiology, 1997-2003. Brooks City-Base, TX: United States Air Force School of Aerospace Medicine; 2003.
- (52) Tvaryanas AP, Thompson WT. The role of fatigue in USAF MQ-1 Predator operator error-related mishaps. Brooks City-Base, TX: 311th Performance Enhancement Directorate; 2005. (In press.)
- (53) Tvaryanas AP, Thompson WT, Constable SH. The U.S. military unmanned aerial vehicle (UAV) experience: evidence-based human systems integration (HSI) lessons learned. RTO Meeting Proceedings. Retrieved from the World Wide Web at:
<http://www.rta.nato.int/Pubs/RDP.asp?RDP=RTO-MP-HFM-124>
- (54) Tvaryanas AP, Thompson WT, Constable SH. U.S. military unmanned aerial vehicle mishaps: assessment of the role of human factors using the human factors analysis and classification system (HFACS). Brooks City-Base, TX: United States Air Force, 311th Human Systems Wing; 2005 Mar. Report No.: HSW-PE-BR-TR-2005-0001.
- (55) Tvaryanas AP, Thompson WT, Lopez N, et al. Effects of shift work and sustained operations: operator performance in remotely piloted aircraft (OP-REPAIR). Brooks City-Base, TX: United States Air Force, 311th Human Systems Wing; 2006 Jan. Report No.: HSW-PE-BR-TR-2006-0001.

- (56) United States Air Force. Summary of fatigue in U.S. Air Force aviation mishaps, fiscal years 1972 through 2000. Kirtland AFB: Air Force Safety Center, 2002.
- (57) United States Air Force Scientific Advisory Board. Human systems integration in Air Force weapon systems development and acquisition. Washington, DC: Department of the Air Force, Department of Defense; 2004 Jul. Report No. SAB-TR-04-04.
- (58) Van Breda L, Passenier PO. An exploratory study of the human-machine interface for controlling a maritime unmanned air vehicle. Soesterberg, The Netherlands: TNO Institute for Perception; 1993. Report No.: IZF 1993 A-10.
- (59) Van Erp JBF. Controlling unmanned vehicles: the human factors solution. RTO Meeting Proceedings 2000;44 (RTO-MP-44):B8.1-B8.12.
- (60) Van Erp JBF, Kappé B. Computer generated environment for steering a simulated unmanned aerial vehicle. Soesterberg, The Netherlands: TNO Human Factors Research Institute; 1996. Report No.: TM-96-A039.
- (61) Van Erp JBF, Van Breda L. Human factors issues and advanced interface design in maritime unmanned aerial vehicles: a project overview. Soesterberg, The Netherlands: TNO Human Factors Research Institute; 1999. Report No.: TM-99-A004.
- (62) Warm JS, ed. Sustained attention in human performance. New York: John Wiley & Sons, 1984. Cited in: Gal R, Mangelsdorff, AD, eds. Handbook of Military Psychology. New York: Wiley; 1991:257.
- (63) Wickens CD, Dixon S. Workload demands of remotely piloted vehicle supervision and control: single vehicle performance. Urbana-Champaign, IL: University of Illinois, Aviation Research Lab; 2002. Sep. Report No.: AHFD-02-10/MAD-02-1.

(64) Wickens CD, Hollands JG. Engineering psychology and human performance: 3rd rev. ed. Upper Saddle River: Prentice Hall, 2000.

(65) Wiener EL. Application of vigilance research: rare, medium, or well done? Human Factors 1987;27:75-90.

(66) Williams KW. A summary of unmanned aerial aircraft accident/incident data: human factors implications. Oklahoma City, OK: Department of Transportation, Federal Aviation Administration; 2004 Dec. Report No.: DOT/FAA/AM-04/24.