

UNCLASSIFIED

AD

**FINAL REPORT ON THE EXPERIMENTAL ASSESSMENT OF POROUS SCREENS
FOR PROTECTION AGAINST SHOCK EFFECTS**

**Final Technical Report
by**

**Dr IM Snyman
(September 2005)**

**United States Army
EUROPEAN RESEARCH OFFICE OF THE U.S. ARMY
London, England**

CONTRACT NUMBER: N62558-05-P-0155

CSIR DPSS

Approved for Public Release; distribution unlimited

UNCLASSIFIED

UNCLASSIFIED

REPORT DOCUMENTATION PAGE				<i>Form Approved OMB No. 0704-0188</i>	
<p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</p>					
1. REPORT DATE (DD-MM-YYYY) 31 August 2005		2. REPORT TYPE Interim Report		3. DATES COVERED (From - To) August to December 2005	
4. TITLE AND SUBTITLE SECOND INTERIM REPORT ON THE EXPERIMENTAL ASSESSMENT OF POROUS SCREENS FOR PROTECTION AGAINST SHOCK EFFECTS				5a. CONTRACT NUMBER N62558-05-P-0155	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Dr IM Snyman				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) CSIR, DPSS				8. PERFORMING ORGANIZATION REPORT NUMBER DPSS 2005/158	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Aero-Mechanics Branch, European Research Office, Army Research Laboratory 223 Old Marylebone Road, London, NW1 5TH UK				10. SPONSOR/MONITOR'S ACRONYM(S) AMB, ERO, ARL	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for Public Release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT Use the theoretical knowledge of shock attenuation and advance with experimental evidence to the point where the results can be used in practical scenario. Our first objective is to characterise the material with respect to shock attenuation from a blast load. This achieved by the design and development of a test rig that can be used to evaluate, analyse and eventually understand the parameters in a material that influence shock attenuation with verification of the existing theory.					
15. SUBJECT TERMS Shock attenuation, mitigation, ballistic pendulum, blast wave					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT None	18. NUMBER OF PAGES 17	19a. NAME OF RESPONSIBLE PERSON Dr IM Snyman
a. REPORT None	b. ABSTRACT None	c. THIS PAGE None			19b. TELEPHONE NUMBER (Include area code) +27 12 841 4187

UNCLASSIFIED



REPORT

DPSS 2005/158 ISSUE NO:3

**FINAL REPORT ON THE EXPERIMENTAL ASSESSMENT OF
POROUS SCREENS FOR PROTECTION AGAINST SHOCK
EFFECTS**

by

DR IM SNYMAN

JANUARY 2006




APPROVAL SHEET

DPSS 2005/158

Title	FINAL REPORT ON THE EXPERIMENTAL ASSESSMENT OF POROUS SCREENS FOR PROTECTION AGAINST SHOCK EFFECTS		
Project Name	SHOCK SCREEN EVALUATION		
Prepared for	Dr SG Sampath		
DLP Project No	GLCE500		
Contract File No			
by	Dr IM Snyman	Signature	Date
Designation	Simulation Specialist		
Approved for (Programme)			
by	D Engels	Signature	Date
Designation	Acting Competency Area Manager: Landwards Sciences		
<p>Abstract Use the theoretical knowledge of shock attenuation and advance with experimental evidence to the point where the results can be used in practical scenario. Our first objective is to characterise the material with respect to shock attenuation from a blast load. This achieved by the design and development of a test rig that can be used to evaluate, analyse and eventually understand the parameters in a material that influence shock attenuation with verification of the existing theory</p> <p>Keywords Shock attenuation, mitigation, ballistic pendulum, blast wave</p> <p>final report on shock screening.doc/ 16/01/2006 09:30:00</p> <p style="text-align: center;">Your Technology Partner</p>			

EXECUTIVE SUMMARY

Document:	<hr/> <div>Title: FINAL REPORT ON THE EXPERIMENTAL ASSESSMENT OF POROUS SCREENS FOR PROTECTION AGAINST SHOCK EFFECTS</div> <div>Report No: DPSS 2005/158</div> <div>Date: November 2006</div> <hr/>
Objective:	<hr/> <div>The objective of this project is to use the theoretical knowledge of shock attenuation and advance with experimental evidence to the point where the results can be used in practical scenario. Our first objective is to characterise the material with respect to shock attenuation from a blast load.</div> <hr/>
Methodology:	<hr/> <div>Design and develop a test rig that can be used to evaluate, analyse and eventually understand the parameters in a material that influence shock attenuation with verification of the existing theory.</div> <hr/>
Conclusions:	<hr/> <div>The first phase of the design of the rig was successful with regard to the fitment and usage with the ballistic pendulum.</div> <hr/>
Recommendations:	<hr/> <div>The next phase to commence so that different foams can be evaluated.</div> <hr/>
Risks:	<hr/> <div>None.</div> <hr/>

		DOCUMENT CHANGE HISTORY	
Author	Issue	Date	Description
This page will only be updated starting from: Rev 1			
Dr IM Snyman	1	June 2005	Original
Dr IM Snyman	2	Sept 2005	Updated
Dr IM Snyman	3	Jan 2006	Updated

DISTRIBUTION PAGE

COPY NO	NAME	ORGANISATION	DISTRIBUTION ADDRESS
1	Dr SG Sampath	AMB, ERO, ARL	223 Old Marylebone Road, London, NW1 5TH UK
2	Dr IM Snyman	CSIR, DPSS	Meiring Naudé Road, Brummeria
3	Prof G Nurick	BISRU, UCT	Rondebosch, Cape Town

CONTENTS

Executive Summary	2
Abbreviations List	7
1 INTRODUCTION	8
2 DESIGN OF THE TEST RIG	9
3 EFFECT OF POLYSTYRENE ON BLAST LOADED CIRCULAR PLATES	12
4 REFERENCES	20

FIGURES LIST

Figure 1:	The pendulum, test rig and extension tubes	9
Figure 2:	The ballistic pendulum with the test rig fitted	10
Figure 3:	Different extension tubes can be attached to the test rig	10
Figure 4:	The design of the test tube (length 25 mm) and clamped plates	11
Figure 5:	Different loading conditions used in experiments	13
Figure 6:	Photograph of black soot observed for test plate subjected to load condition LC-1, Test plate Number NJ210405a, S = 300mm, I = 13.32Ns and Mid-point deflection = 7.01mm	15
Figure 7:	Photograph of translucent soot observed for test plate subjected to load condition LC-2, Test plate Number NJ210405b, S=300mm, I=13.20Ns and Mid-point deflection = 7.38mm	15
Figure 8:	Photograph of polystyrene residue visible for test plate subjected to load condition LC-3, Test plate Number NJ210405c, S = 300mm, I = 12.24Ns and Mid-point deflection = 7.87mm	16
Figure 9:	Photograph showing a close up view of the polystyrene residue visible for test plate (NJ210405c) subjected to load condition LC-3	16
Figure 10:	Photograph of plate profile for test plate subjected to same charge mass (5g) but different load conditions (LC-1, LC-2 and LC-3) Test plate Numbers, NJ210405a, NJ210405b, NJ210405c	17
Figure 11:	Photograph of plate profile for test plate subjected to same charge mass (7g) but different load conditions (LC-1, LC-2 and LC-3) Test plate Numbers, NJ220405c, NJ220405e, NJ220405f	17
Figure 12:	Graph of mid-point deflection - thickness ratio versus dimensionless impulse ϕ_{cs} for data given in Table 1	18

Abbreviations List

BISRU	Blast Impact and Survivability Research Unit
CSIR	Council for Scientific and Industrial Research
DPSS	Defence Peace Safety Security
mm	Millimetre
MPa	Megapascal
PE4	Plastics Explosive formulation 4
UCT	University of Cape Town

1 INTRODUCTION

The objective of this project is to use the theoretical knowledge (as set out by Gelfand in [4]) and advance with experimental evidence to the point where the results can be used in practical scenario.

Our first objective is to characterise the material with respect to shock attenuation from a blast load. This will entail the design and development of a test rig to be used to evaluate, analyse and eventually understand the parameters in a material that influence shock attenuation with verification of the existing theory.

Our second objective is to use the knowledge and the theory to update or create a mathematical model to be used in finite element software to provide a design tool for engineers. This is typical work that can be done in conjunction with a PhD student at the University of Cape Town

The final objective is to design a prototype application that can be used in the industry.

The outcomes from this research can then be applied to the development and testing of various concepts around the use of porous and other filler materials to effect protection for both vehicles and humans against blast events. Communication of the results will be with technical reports and publications in the open literature.

We are contracted to meet the first objective this financial year. This is the final report and conclude the work done to achieve the first objective.

2 DESIGN OF THE TEST RIG

The test rig has been designed to fit the impulse measurement apparatus at BISRU. The impulse is measured by a ballistic pendulum shown in Figure 1 together with the attachments for this project. The ballistic pendulum consists of a horizontal structure that is accelerated by the explosive on the one side and at the other end the motion is recorded.



Figure 1: The pendulum, test rig and extension tubes

The test rig (attached to the pendulum shown in Figure 2) consist of two flat mild steel plates each with a cylindrical hole, that are bolted together to hold a thinner plate (target plate) in between. On to the one side extension tubes of different lengths can be attached. The other side is attached to the ballistic pendulum. The explosive is placed at the open end of the extension tube and detonated. Various materials can be inserted between the explosive and the target plate.

The impulse on the system is recorded by the ballistic pendulum and the indentation of the plate is measured. The indentation and the impulse measure the energy and shock absorption of the material between the explosive and the target plate.





Figure 2: The ballistic pendulum with the test rig fitted



Figure 3: Different extension tubes can be attached to the test rig

The number of test tubes represents the different stand off distance from the target plate. The lengths are 25, 30, 40, 50, 100, 150, 200, 250 and 300 mm. The inner diameter is 106 mm and the outer diameter is 150 mm, shown in Figure 4.



Issue No 3

3 EFFECT OF POLYSTYRENE ON BLAST LOADED CIRCULAR PLATES

Nurick and Martin [1] report on experiments conducted by Jones, Uran and Tekin (1970) using various materials (sponge rubber and neoprene) to separate the explosive charge and the test plate to prevent spallation of fully clamped rectangular plates. A significant result of this work was that the type of attenuator, *i.e.* foam or neoprene, did not appear to influence the outcome of the tests, except that the impulsive velocity varied according to the attenuator used [1].

Polystyrene has been used extensively in experiments reported by Nurick et al [1 – 3]. It is used primarily as a stand-off buffer to prevent spalling. It was deemed necessary to understand the possible effects of using polystyrene to separate the explosive charge and plate on measured impulse and plate deformation. Different loading conditions are used in this investigation as shown in Figure 5 and classified as follows,

- **Loading condition 1 (LC-1)** – The plastic explosive is attached to a 13mm thick polystyrene pad using a strip of double sided tape and the pad is pushed into place on the end of a tube. Stand off distance is varied using different lengths of tube. This arrangement is shown in Figure 5(a).
- **Loading condition 2 (LC-2)** – Double sided tape is used to secure the plastic explosive at one end of the tube, as shown in Figure 5(b).
Note: No polystyrene is used.
- **Loading condition 3 (LC-3)** – Double sided tape is used to secure the plastic explosive at one end of the tube. A 13mm polystyrene pad is placed directly against the test specimen as shown in Figure 5(c).

Two charge masses of 5g and 7g were used in this investigation on three stand-off distances 150mm, 200mm and 300mm. The experimental results from the tests for the different loading conditions are given in Table 1.




Figure 5: Different loading conditions used in experiments

The experimental observation of the loaded side of the plates for load conditions LC-1, LC-2 and LC-3 at stand-off distance of 300mm are shown in Figure 6 to Figure 8 respectively. The loaded side of a test plate subjected to load condition LC-1 shows an even coating of black soot on the surface of the plate as shown in Figure 6. The charge mass was kept constant and the polystyrene was replaced with double sided tape for load case LC-2, as shown in Figure 7. The loaded side exhibited significantly less black soot than the LC-1 plate. The plate surface was visible and covered with a thin coating of semi-transparent soot which can be easily wiped away as shown in Figure 7. Residue of the polystyrene was visible on the loaded side of the test plate for load case LC-3 as shown in Figure 8. A detailed photograph of the residue is shown in Figure 9. The cross-sectional view of plates subjected to LC-1, LC-2 and

LC-3 for charge mass of 5g and 7g are shown in Figure 10 and Figure 11 respectively.

Table 1 Experimental data for investigation into the influence of polystyrene as a stand-off buffer

Test number	Loading condition	Charge mass (g)	Stand-off distance (mm)	Impulse (Ns)	% variation in impulse from average	Mid-point deflection (mm)	% variation in mid-point deflection from average
NJ230405a	LC-1	5	150	11.47	1.0	7.83	3.0
NJ230405b	LC-2	5	150	12.03	6.0	8.50	5.4
NJ230405c	LC-3	5	150	10.56	7.0	7.87	2.4
			Average	11.35	Average	8.07	
NJ230405d	LC-1	7	150	15.30	0.4	11.76	2.6
NJ230405e	LC-2	7	150	15.11	0.8	12.18	0.9
NJ230405f	LC-3	7	150	15.30	0.4	12.28	1.7
			Average	15.24	Average	12.07	
NJ220405a	LC-1	5	200	11.91	2.2	7.65	2.5
NJ220405b	LC-2	5	200	11.67	0.1	7.82	0.3
NJ220405d	LC-3	5	200	11.38	2.3	8.07	2.8
			Average	11.65	Average	7.85	
NJ220405c	LC-1	7	200	16.18	3.1	10.72	3.2
NJ220405e	LC-2	7	200	15.66	0.3	11.38	2.7
NJ220405f	LC-3	7	200	15.26	2.8	11.14	0.6
			Average	15.70	Average	11.08	
NJ210405a	LC-1	5	300	13.32	3.1	7.01	5.6
NJ210405b	LC-2	5	300	13.20	2.2	7.38	0.5
NJ210405c	LC-3	5	300	12.24	5.3	7.87	6.1
			Average	12.92	Average	7.42	
NJ210405d	LC-1	7	300	16.74	3.1	10.43	0.6
NJ210405e	LC-2	7	300	16.30	0.4	10.27	0.9
NJ210405f	LC-3	7	300	15.65	3.6	10.41	0.4
			Average	16.23	Average	10.37	




Figure 6: Photograph of black soot observed for test plate subjected to load condition LC-1, Test plate Number NJ210405a, S = 300mm, I = 13.32Ns and Mid-point deflection = 7.01mm




Figure 7: Photograph of translucent soot observed for test plate subjected to load condition LC-2, Test plate Number NJ210405b, S=300mm, I=13.20Ns and Mid-point deflection = 7.38mm




Figure 8: Photograph of polystyrene residue visible for test plate subjected to load condition LC-3, Test plate Number NJ210405c, S = 300mm, I = 12.24Ns and Mid-point deflection = 7.87mm



Figure 9: Photograph showing a close up view of the polystyrene residue visible for test plate (NJ210405c) subjected to load condition LC-3



**Figure 10: Photograph of plate profile for test plate subjected to same charge mass (5g) but different load conditions (LC-1, LC-2 and LC-3)
Test plate Numbers, NJ210405a, NJ210405b, NJ210405c**



**Figure 11: Photograph of plate profile for test plate subjected to same charge mass (7g) but different load conditions (LC-1, LC-2 and LC-3)
Test plate Numbers, NJ220405c, NJ220405e, NJ220405f**

The results indicate negligible influence on impulse and plate mid-point deflection. The data given in Table 1 are plotted in the graph of mid-point deflection – thickness ratio versus dimensionless impulse ϕ_{cs} as shown in Figure 12. The results show variation in mid-point deflection is less than ± 1 deflection – thickness ratio and all the data points fall within the ± 1 confidence lines of the empirical prediction equation proposed by Nurick and Martin [1]. The derivation of dimensionless impulse ϕ_{cs} is discussed in detail in the thesis [3].

The measured impulses for loading conditions LC-1, LC-2 and LC-3, in general, show less than 5% variation on the average impulse value for a given charge mass and stand-off distance. The impulse measured for test number NJ230405c shows the largest variation from the average impulse value for that particular charge mass and stand-off distance. The variation in measured impulse (10.56Ns) from the average

impulse value of 11.35Ns is 7%. This translates to a difference in impulse of 0.8Ns from the average impulse value.




Figure 12: Graph of mid-point deflection - thickness ratio versus dimensionless impulse ϕ_{cs} for data given in Table 1

The experimental results have shown that the effect of polystyrene on plate mid-point deflection and impulse is within experimental error with the experimental set-up used in this investigation.

4 CONCLUSION AND RECOMMENDATIONS

The test rig was designed and commissioned successfully by the student Mr N Jacobs under the leadership of Prof GN Nurick at BISRU, University of Cape Town. In the thesis [3] the design and commissioning are dealt with in detail.

The use of polystyrene as a shock screen material was investigated. The polystyrene has no effect on the impulse delivered by the explosive. The deviations on the measurement of the impulse lie within experimental variation.

Different foam materials (such as metal or aluminium foams) can now be compared with the results of the polystyrene tests.

5 REFERENCES

1. NURICK, GN and MARTIN, JB, Deformation of thin plates subjected to impulsive loading - a review; Part II - Experimental studies, International journal of impact engineering. Vol. 8 (2), pp 170 - 186, 1989.
2. NURICK, GN and RADFORD, AM, Deformation and tearing of clamped circular plates subjected to localised central blast loads, Recent developments in computational and applied mechanics: a volume in honour of John B. Martin, International centre for numerical methods in engineering (CIMNE), Barcelona, Spain, pp 276 – 301, 1997.
3. JACOB, N, The effect of stand-off distance on deformation of thin plates subjected to blast loads, MSc thesis, University of Cape Town, 2005.
4. GELFAND, B, Translation from Russian to English the book “*Blast Effects Caused by Explosions*” authored by B Gelfand and M Silnikov. *Final Technical report, US Army, European Research Office of the US Army, London, N62558-04-M-0004, 2004.*