# AFRL-VA-WP-TM-2006-3197

# MULTIDISCIPLINARY COMPUTATIONAL RESEARCH

Miguel R. Visbal, Ph.D.



Computational Sciences Branch (AFRL/VAAC) Aeronautical Sciences Division Air Vehicles Directorate Air Force Materiel Command, Air Force Research Laboratory Wright-Patterson Air Force Base, OH 45433-7542

## **JULY 2006**

## Interim Report for 01 July 2005 – 31 July 2006

Approved for public release; distribution is unlimited.

**STINFO COPY** 

AIR VEHICLES DIRECTORATE AIR FORCE MATERIEL COMMAND AIR FORCE RESEARCH LABORATORY WRIGHT-PATTERSON AIR FORCE BASE, OH 45433-7542

# NOTICE AND SIGNATURE PAGE

Using Government drawings, specifications, or other data included in this document for any purpose other than Government procurement does not in any way obligate the U.S. Government. The fact that the Government formulated or supplied the drawings, specifications, or other data does not license the holder or any other person or corporation; or convey any rights or permission to manufacture, use, or sell any patented invention that may relate to them.

This report was cleared for public release by the Air Force Research Laboratory Wright Site (AFRL/WS) Public Affairs Office and is available to the general public, including foreign nationals.

Copies may be obtained from the Defense Technical Information Center (DTIC) (http://www.dtic.mil).

AFRL-VA-WP-TR-2006-3197 HAS BEEN REVIEWED AND IS APPROVED FOR PUBLICATION IN ACCORDANCE WITH ASSIGNED DISTRIBUTION STATEMENT.

\*//Signature//

MIGUEL R. VISBAL, Ph.D. Technical Area Lead Computational Sciences Branch //Signature//

REID B. MELVILLE, Ph.D. Chief Computational Sciences Branch

//Signature//

MICHAEL J. STANEK, Ph.D. Technical Advisor Aeronautical Sciences Division

This report is published in the interest of scientific and technical information exchange, and its publication does not constitute the Government's approval or disapproval of its ideas or findings.

\*Disseminated copies will show "//signature//" stamped or typed above the signature blocks.

REPOR	Form Approved OMB No. 0704-0188				
The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. <b>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS</b> .					
1. REPORT DATE (DD-MM-YY)	2. REPORT TYPE		3. DAT	ES COVERED (From - To)	
July 2006	Interim		07/	01/2005 - 07/31/2006	
4. TITLE AND SUBTITLE			5	a. CONTRACT NUMBER	
MULTIDISCIPLINARY CO		In-house			
	51	D. GRANT NUMBER			
				AFOSR 2304N400,	
		2304N402, and 2307N61A			
			5	c. PROGRAM ELEMENT NUMBER 0601102	
6. AUTHOR(S)			5	d. PROJECT NUMBER	
Miguel R. Visbal, Ph.D.				N/A	
			5	e. TASK NUMBER	
				N/A	
	5	f. WORK UNIT NUMBER			
				N/A	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)				PERFORMING ORGANIZATION REPORT NUMBER	
Computational Sciences Bran Aeronautical Sciences Divisio		AFRL-VA-WP-TM-2006-3197			
Air Vehicles Directorate					
Air Force Materiel Command	, Air Force Research La	boratory			
Wright-Patterson Air Force B					
9. SPONSORING/MONITORING AGENC	10	). SPONSORING/MONITORING			
Air Valialas Directoreta				AGENCY ACRONYM(S)	
Air Force Research Laborator		AFRL-VA-WP			
Air Force Materiel Command	1	1. SPONSORING/MONITORING			
Wright-Patterson Air Force B		AGENCY REPORT NUMBER(S) $\Delta FRI_V \Delta_W P_T M_2006_3197$			
12. DISTRIBUTION/AVAILABILITY STATEMENT					
Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES PAO Case Number: AFRL/W	7S 06-1227 (cleared May	22, 2006).			
14. ABSTRACT	· · · · ·	. ,			
The purpose of this work is to develop advanced multidisciplinary numerical simulation capabilities for aerospace vehicles with emphasis on highly accurate, massively parallel computational methods for Direct and Large-Eddy simulation of turbulence, flow control, aero-acoustics and nonlinear fluid/structure interactions. These technical objectives directly support AFRL Air Vehicles Directorate's Capability Focused Tech Investment in persistent ISR, Strike and Multi-Role Mobility thrusts.					
Computational fluid dynamics, multidisciplinary computations, higher-order methods, direct numerical simulation, large- addy simulations, agent acoustics, fluid structure interactions,					
16. SECURITY CLASSIFICATION OF:a. REPORTb. ABSTRACTc. THISUnclassifiedUnclassifiedUnclassified	17. LIMITATION   PAGE OF ABSTRACT   ssified SAR	18. NUMBER OF PAGES 14	19a. NAME OF Miguel 19b. TELEPHO N/A	RESPONSIBLE PERSON (Monitor) R. Visbal, Ph.D. DNE NUMBER (Include Area Code)	

Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std. Z39-18
•

#### MULTIDISCIPLINARY COMPUTATIONAL RESEARCH

Miguel R. Visbal Air Force Research Laboratory Air Vehicles Directorate Wright-Patterson AFB, OH 45433

#### **Objectives**

To develop advanced multidisciplinary numerical simulation capabilities for aerospace vehicles with emphasis on highly accurate, massively parallel computational methods for Direct and Large-Eddy simulation of turbulence, flow control, aero-acoustics and nonlinear fluid/structure interactions. These technical objectives directly support AFRL Air Vehicles Directorate's Capability Focused Tech Investment in persistent ISR, Strike and Multi-Role Mobility thrusts.

#### **Progress**

During this reporting period, significant progress has been achieved in several research areas pertinent to the present task. These include: (i) flow control of external and internal flows employing plasma actuators, (ii) development and validation of a hybrid high-order RANS/ILES technique, (iii) investigation of the flow structure over non-slender delta wings and a generic UCAV configuration, and (iv) non-linear fluid-structure interactions on a highly flexible wing. Only some research highlights for plasma-based flow control are included in this summary.

#### **Control of Transitional and Turbulent Flows Using Plasma-Based Actuators**

Control of separated flows using simulated plasma (DBD) actuators was investigated. Since the flows are typically characterized by transition and turbulence, a high-fidelity three-dimensional viscous methodology is required. This high-end simulation technique is computationally intensive, and therefore, a first-principles fully-coupled approach of the plasma effects, even if available, becomes prohibitive. For this reason, at this stage, the plasma-induced body forces are represented using either a phenomenological model [1] or a loosely-coupled first-principles approach [2]. These methods represent respectively the averaged and instantaneous force introduced by the actuator in a specified plasma region above the device. Strategies for the effective control of separation were explored. Emphasis was placed on the greater importance of unsteady forcing rather than pure streamwise momentum injection as the primary control mechanism. With the exception of very low freestream velocities or very strong wall jet effects, transition/turbulence enhancements are found to be the dominant mechanism. The present emphasis also dictates the use of a high-fidelity three-dimensional computational approach capable of describing the impact of unsteady forcing on the spatio-temporal transition/turbulence structure. A comprehensive set of applications was considered, including suppression of wing stall, control of boundary layer transition on a plate, control of vortex breakdown over a delta wing, control of laminar separation over a ramp, and turbulent separation over a wall-mounted hump.

#### Control of Wing Stall

Control of the stalled flow past a NACA 0015 airfoil section was investigated [1]. The Mach number, chord Reynolds number and angle of attack were chosen as M = 0.1,  $Re_c = 45,000$  and  $\alpha = 15^{\circ}$ , respectively. This particular case was previously considered in Ref. [2]. However, in the present work, both pulsed co-flow and counter-flow actuators are used, and much smaller plasma

forces are prescribed in order to demonstrate control effectiveness by promoting transition and turbulence. The actuator origin was located at x/c = 0.024, just downstream of the mean boundary-layer separation point for the baseline flow. The geometric parameters of the simulated plasma region, as well as the corresponding actuator strength (D<sub>c</sub>), orientation and duty-cycle primary frequency are provided in Ref. [1].

The global structure of the baseline and controlled flow fields is shown in Fig. 1 in terms of streamwise velocity and spanwise vorticity contours. At this high incidence, the baseline flow is observed to be fully stalled. The time-averaged velocity contours (Fig. 1b) display a separation zone which extends significantly in the direction normal to the wing section. Control of the stalled airfoil flow was investigated employing both steady and pulsed, as well as co-flow and counterflow DBD actuators.

The use of a steady (i.e. continuous) co-flow actuator was first considered. Examination of the transient response of the flow following the onset of actuation indicated that, initially, a significant downstream displacement of the separation point takes place due to the actuator-induced streamwise wall jet. However, despite this beneficial transient effect, the flow eventually returns to a completely stalled condition (Figs. 1a,b). Comparison of the C<sub>p</sub>-distributions and velocity profiles near midchord (x/c = 0.42) shows no significant improvement with control (Fig. 2). Therefore, steady actuation (modeled with the phenomenological approach) is found to be ineffective for the actuator strength parameters considered. It should be noted that for a value of D<sub>c</sub> an order-of-magnitude larger, the simulated steady actuator was previously found [2] to fully attach the flow due to the formation of a very strong wall jet. The present results suggest that a steady actuator force of limited magnitude is not an effective means of flow control, and attempts to attach the boundary layer through pure streamwise momentum injection are therefore of limited applicability.

In order to exploit the receptivity of the flow to unsteady disturbances, a pulsed co-flow actuator with a primary duty-cycle non-dimensional frequency St = fc/U = 4.0 was considered. As shown in Fig. 1, the pulsed actuation reattaches the separated flow. The mean surface pressure (Fig. 2) exhibits a well-defined suction peak, and the velocity profile near mid-chord displays a fully-attached character. Examination of the instantaneous vorticity contours (Fig. 1c) indicates that the pulsed force engenders a rapid transition to turbulence of the initially laminar shear layer.

In order to contrast the relative importance of transition and turbulence enhancement mechanisms relative to simple wall-jet momentum injection arguments, the impact of a counter-flow actuator was also explored. As shown in Fig. 1, a pulsed counter-flow actuator was found to be equally effective in eliminating stall. This control is again achieved by the rapid transition downstream of a small separation bubble generated by the counter-flow actuator. The pulsed counter-flow actuator was found to be even more effective when doubling the strength parameter, which further emphasizes the importance of unsteady forcing rather than momentum injection as the primary control mechanism.

The effect of pulsing frequency was also considered for the counter-flow actuator with a fixed strength parameter. A comparison of the instantaneous flow fields obtained with the lowest (St = 1.0) and highest (St = 8.0) pulsing frequencies is shown in Fig. 3. Although with St = 1.0 the flow

begins to transition downstream of the actuator, the process is not as effective as for the case of high-frequency pulsing. With St = 8.0, the shear layer quickly breakdowns due to spanwise instabilities, and much higher values of vorticity are observed near the wing surface. In each cycle of the pulsing, a dynamic-stall-like vortex is generated near the leading edge downstream of the actuator. For the higher frequency, this leading-edge vortex forms closer to the actuator and to the airfoil surface. The actuator-induced vortex is observed to be initially coherent but quickly breakdowns due to spanwise instabilities. It therefore appears that the increased control effectiveness of the pulsed actuator derives from the process of modulated vorticity injection. The time-averaged surface pressure and velocity profiles are displayed for all values of St in Fig. 4. The mean surface pressure exhibits the development of a stronger suction peak with increasing frequency, however this effect seems to saturate after St = 4.0. Comparison of the velocity profiles shows also a marked reduction of the boundary layer displacement with increasing St.

Finally, results computed with a loosely-coupled first-principles approach for a co-flow actuator showed that the high-frequency forcing (radio frequency) associated with continuous actuator operation promoted transition to turbulence [1]. For this case, the phenomenological approach, which assumes a time-invariant force, could not reproduce the transition/turbulence enhancements associated with the inherent unsteady forcing. Comparison of the results obtained with the first-principles high-frequency (monochromatic) forcing with the pulsed cases indicated that the duty cycle (with sufficiently high pulsing frequency) provided a significant improvement in control effectiveness. This is due to the fact that the flow is more receptive to the intermediate forcing frequencies rather that the extremely high radio frequency itself. Future computations with a duty cycle using the first-principles approach are required to validate this conclusion and to further assess the merits of the phenomenological model for the case of pulsed actuation.

#### Control of Laminar Separation Over a Ramp

Control of boundary-layer separation over a generic ramp configuration was also considered. This simple geometry is taken as a model problem of separation near the trailing edge of a natural laminar flow wing section. The flow conditions were Mach number M = 0.1 and Reynolds number  $Re_c = 6.0 \times 10^4$  (based on ramp length). The incoming boundary layer was assumed to be laminar upstream of the ramp, with a nominal thickness  $\delta/c = 0.0625$ .

The baseline instantaneous and time-averaged flow field structure is shown in Figs.5 and 6, respectively. The incoming laminar boundary layer is observed to separate immediately upon encountering the ramp, and a large time-averaged re-circulation region is formed. Downstream of separation, a laminar free shear layer is formed which subsequently rolls up into coherent spanwise vortices and abruptly breakdowns just upstream of re-attachment. In order to control this massive separation region, we first considered a pulsed co-flow DBD actuator (St = 3.2) located just upstream of the ramp (x/c = -0.13). With the actuator on, the breakdown process of the shear layer is observed to move closer to the separation point due to the unsteady forcing. As a result of this turbulence enhancement, a significant reduction is achieved in the size of the mean separation region.

As was shown in our previous work [1, 3], a low-power counter-flow DBD actuator can be used as an effective on-demand boundary-layer tripping device. Therefore, we considered the use of this strategy for the control of laminar separation over the ramp. For this purpose, instead of employing a co-flow pulsed actuator near the separated laminar shear layer, we use a steady counter-flow actuator to promote boundary-layer transition to turbulence upstream of the ramp. As observed in Fig. 5, the laminar boundary layer begins to transition downstream of the counter-flow actuator. This allows the flow to turns downward upon encountering the ramp without significant boundary-layer separation (Fig. 6). The flow is now practically re-attached, with the exception of a much smaller time-averaged separation bubble at the end of the ramp.

These exploratory results clearly demonstrate that for separated laminar flows, encountered in offdesign operation of laminar flow wings and low-pressure turbines, improved control may be achieved through modification of the boundary layer sufficiently upstream of the adverse pressure gradient region. In this manner, suppression of massive separation can be obtained with a significant reduction in the actuator power requirements. This strategy may also provide scalability to higher freestream velocities encountered in practical applications. This approach is currently being used for separation control of a low-pressure turbine at low Reynolds number.

## References

- 1. Visbal, M., Gaitonde, D. and Roy, S., "Control of Transitional and Turbulent Flows Using Plasma-Based Actuators," AIAA Paper 2006-3230, Jun 2006.
- 2. Gaitonde, D., Visbal, M. and Roy, S., "A Coupled Approach for Plasma-Based Flow Control Simulations of Wing Sections," AIAA Paper 2006-1205, Jan 2006.
- *3.* Visbal, M. and Gaitonde, D., "Control of Vortical Flows Using Simulated Plasma Actuators," AIAA Paper 2006-0505, Jan. 2006.

## **Personnel Supported**

Dr. Peter Attar (NRC)	Dr. Raymond Gordnier	Dr. Philip Morgan (OAI)
Dr. Donald Rizzetta	Dr. Scott Sherer	Dr. Miguel Visbal (Team Leader)

## Honors/Awards, Professional Activities

<u>Visbal, M</u>., AIAA Applied Aerodynamics Best Paper Award (2006), Royal Aeronautical Society Silver Award and Busk Prize (2006);USAF Basic Research Award (2004); AFRL Fellow (1995); Outstanding Scientist of Dayton (2003); Gen. B. Foulois Award, Air Vehicles Directorate (1990,1999); NRC Mentor; Invited Speaker AIAA Aerospace Sciences Meeting (2006); AIAA Aero-acoustics Technical Committee; Co-organizer of LES/DNS, Algorithm Development and Fluid-Structure Interaction Symposia, ASME 2006 Summer Conference.

<u>Gordnier, R.</u>, AFRL Fellow (2003); Gen. B. Foulois Award, Air Vehicles Directorate (1997); AIAA Structural Dynamics Technical Committee; NRC Mentor; Keynote Speaker, ASME 2006 Fluids Engineering Conference; Royal Aeronautical Society Silver Award and Busk Prize (2006). <u>Rizzetta, D.</u>, Gen. B. Foulois Award, Air Vehicles Directorate (2001); NRC Mentor; AIAA Fluid Dynamics Technical Committee.

#### **Interactions / Transitions**

- C. Liu, Univ. of Texas at Arlington; high-order-methods, DNS
- D. Hixon, Univ. of Toledo, high-order methods, aero-acoustics
- V. Golubev, Embry-Riddle Univ.; gust-airfoil interactions

- F. Laidende, SUNY; high-order methods, aero-acoustics
- S. Lele, Stanford Univ.; high-order overset solver
- R. Moser, Univ. of Illinois; LES
- Gursul, Bath Univ., UK; vortical flows, flexible delta wings
- P. Seshaiyer, Texas Tech Univ.; flexible MAV's
- J. Li, Univ. of Nevada, LV.; high-order schemes
- D. Rockwell, Lehigh Univ.; vortical flows

#### **Publications**

- 1. Gordnier, R. and Visbal, M., "Compact Difference Scheme Applied to Simulation of Low-Sweep Delta Wing Flows," *AIAA Journal*, Vol. 43, No. 8, Aug 2005.
- Gursul, I., Gordnier, R. and Visbal, M., "Unsteady Aerodynamics of Non-Slender Delta Wings," *Progress in Aerospace Sciences*, 41, 2005.
- 3. Gordnier, R. and Visbal, M., "High-Fidelity Computational Simulation of nonlinear Fluid-Structure Interactions", *The Aeronautical Journal*, Paper No. 2919, July 2005.
- Gordnier, R., Visbal, M. and Sherer, S., "Higher-Fidelity Simulations of Maneuvering Unmanned Combat Air Vehicle Configurations", Proceedings of the 2006 DoD HPC Users Group Conference, June, 2006.
- 5. Attar, P. and Gordnier, R., "Aeroelastic Prediction of the Limit Cycle Oscillations of a Cropped Delta Wing", *J. of Fluids & Structures*, No. 22, 2006.
- Gaitonde, D., Visbal, M. and Roy, S., "A Coupled Approach for Plasma-Based Flow Control Simulations of Wing Sections," AIAA Paper 2006-1205, Jan 2006.
- 7. Attar, P., Dowell, E. and Tang, D., "Modeling the LCO of a Delta Wing with an External Store Using a High-Fidelity Structural Model," *J. of Aircraft*, Vol. 42, No. 5, Sep-Oct 2005.
- 8. Gordnier, R. and Visbal, M., "High-Order Simulation of Low Sweep Delta Wing Flows Using a Hybrid RANS/ILES Model", AIAA Paper 2006-0504, Jan. 2006.
- 9. Visbal, M. and Gaitonde, D., "Control of Vortical Flows Using Simulated Plasma Actuators," AIAA Paper 2006-0505, Jan. 2006.
- 10. Morgan, P., Rizzetta, D. and Visbal, M., "High-Order Numerical Simulation of Turbulent Flow over a Wall-Mounted Hump," *AIAA Journal*, Vol. 44, No.2, Feb 2006.
- 11. Morgan, P., Visbal, M. and Rizzetta, D., "A Parallel Overset Grid High-Order Flow Solver for Large-Eddy Simulation," *Journal of Scientific Computing*, in press.
- 12. Sherer, S. and Scott, J., "High-Order Compact Finite-Difference Methods on General Overset Grids", *Journal of Computational Physics*, No. 210, 2005.
- 13. Attar, P., Gordnier, R. and Visbal, M., "Numerical Simulation of the Buffet of a Full-Span Delta Wing at High Angle of Attack," AIAA Paper 2006-2075.
- 14. Visbal, M., Gaitonde, D. and Roy, S., "Control of Transitional and Turbulent Flows Using Plasma-Based Actuators," AIAA Paper 2006-3230, Jun 2006.
- 15. Golubev, V., Mankbadi, R. and Visbal, M., "A Parametric Study of Nonlinear Gust-Airfoil Interaction," AIAA Paper 2006-2426, May 2006.
- 16. Liu, C., Jiang, L., Visbal, M. and Xie, P., "Smart Weighted Compact Scheme for Shock Tube and Shock-Entropy Interaction," AIAA Paper 2006-3708, Jun 2006.
- 17. Rizzetta, D. and Visbal, M., "Numerical Simulation of Separation Control for Transitional Highly-Loaded Low-Pressure Turbines," *AIAA Journal*, Vol. 43, No. 9, Sep 2005.
- Morgan, P. and Visbal, M., "Application of Hybrid RANS/ILES to Geometries with Separated Flows," AIAA Paper 2006-3028, Jun 2006.
- 19. Gordnier, R. and Visbal, M., "High-Order Computational Techniques for Unsteady Vortical Flows Over Delta Wings," FEDSM2006-98559, Proceedings of ASME Fluids Engineering Conference, Jul 2006.
- 20. Sherer, S and Visbal, M., "Multi-resolution Implicit Large Eddy Simulations Using a High-Order Overset Grid Approach," submitted to *International Journal for Numerical Methods in Fluids*, 2005.



Figure 1. Effect of DBD actuator on stalled flow above a NACA 0015 wing section : (a) instantaneous and (b) mean streamwise velocity on vertical plane, and (c) spanwise vorticity on plane parallel to airfoil surface.



Figure 2. Effect of co-flow actuator on NACA 0015 airfoil flow: (a) mean surface pressure, and (b) time-averaged velocity profile near mid-chord.



Figure 3. Effect of pulsing frequency of counter-flow DBD actuator on stalled flow above a NACA 0015 wing section: (a) iso-surface of vorticity magnitude; instantaneous vorticity magnitude on (b) a plane parallel to airfoil surface and (c) on vertical plane.



Figure 4. Effect of pulsing frequency of counter-flow DBD actuator on NACA 0015 airfoil flow: (a) mean surface pressure and (b) mean streamwise velocity profile near mid-chord.



Figure 5. Effect of DBD actuator on instantaneous flow structure over a separation ramp: (a) streamwise velocity, and vorticity magnitude on (b) vertical plane and on (c) computational surface above the wall.



Figure 6. Effect of DBD actuator on time-averaged flow structure over a separation ramp: (a) static pressure, (b) streamwise velocity, (c) Reynolds stress, and (d) streamlines in separation region.