

AFRL-RX-WP-TP-2008-4005

COMPOSITES AFFORDABILITY INITIATIVE (Preprint) CANCOM 2007, Winnipeg, Manitoba, 15 Aug 07

Dr. John Russell Processing and Fabrication Branch Manufacturing Technology Division

AUGUST 2007 Final Report

> Approved for public release; distribution unlimited. See additional restrictions described on inside pages

> > **STINFO COPY**

AIR FORCE RESEARCH LABORATORY MATERIALS AND MANUFACTURING DIRECTORATE WRIGHT-PATTERSON AIR FORCE BASE, OH 45433-7750 AIR FORCE MATERIEL COMMAND UNITED STATES AIR FORCE

	REP	Form Approved OMB No. 0704-0188							
The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS .									
1. REPORT DA	TE (DD-MM-YY)	2. REPORT TYPE		3. DATES C	OVERED (From - To)			
August 2	2007		Conference Pa	per Preprint					
4. TITLE AND	SUBTITLE	·	•	•		5a. CONTRACT NUMBER			
COMPC	SITES AFFO	RDABILITY	INITIATIVE (Pre	print)		F33615-98-3-5103			
CANCO	OM 2007, Win	nipeg, Manito	ba, 15 Aug 07			5b. GRANT NUMBER			
						5c. PROGRAM ELEMENT NUMBER 78011F			
6. AUTHOR(S)						5d. PROJECT NUMBER			
Dr. John	Russell	2865							
						5e. TASK NUMBER			
						01			
						5f. WORK UNIT NUMBER			
						28650138			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)						8. PERFORMING ORGANIZATION REPORT NUMBER			
	ng and Fabric	AFRL-RX-WP-TP-2008-4005							
	•	ology Division		atanin a Dinastan	- 4 -				
		•	erials and Manufa H 45433-7750	cluring Director	ate				
			d States Air Force						
			E(S) AND ADDRESS(E			10. SPONSORING/MONITORING			
				- /		AGENCY ACRONYM(S)			
	e Research La					AFRL/RXMP			
		cturing Direct				11. SPONSORING/MONITORING			
•	e Materiel Co		H 45433-7750			AGENCY REPORT NUMBER(S) AFRL-RX-WP-TP-2008-4005			
	States Air Forc					AFRL-RA- WF-1F-2008-4003			
		-	ition unlimited.						
PAO cas	13. SUPPLEMENTARY NOTES PAO case number AFRL/WS07-0344, 28 February 2007. To be presented at CANCOM 2007, Winnipeg, Manitoba, 15 Aug 07. This is a work of the U.S. Government and is not subject to copyright protection in the United States. Document contains color.								
14. ABSTRAC	 14. ABSTRACT In the mid 1990's, the United States Air Force Research Laboratory (AFRL) recognized that despite the potential of advanced 								
	composites to drastically reduce aircraft structural weights compared to conventional metal structures, the aircraft industry was								
	reluctant to implement them in new aircraft. As a result, AFRL launched the Composites Affordability Initiative (CAI) to address								
these concerns. CAI found that the key to affordability in composites was to reduce assembly costs through the integration of parts									
and by bonding parts, structural assembly costs could be drastically reduced. As a result, CAI's objective was to establish the confidence to fly large integrated and bonded structures. A partnership between AFRL, the Office of Naval Research, Bell									
Helicopter, Boeing, Lockheed Martin, and Northrop Grumman was established to develop technologies to meet this objective. This									
initiative required a multidisciplinary approach: maturation of materials and processes, an understanding of the structural behavior of									
bonded joints, quality assurance and nondestructive evaluation to ensure bonded joints remain bonded throughout an aircraft's									
service life, and the buy off of U.S. Department of Defense (DoD) aircraft certification authorities. An assessment will be provided									
of the technical achievements, technology transition successes and failures, and the program structure and teaming arrangements. 15. SUBJECT TERMS									
IJ. JUBJECI									
16. SECURITY	CLASSIFICATIO	N OF:	17. LIMITATION	18. NUMBER	19a. NAME OF F	RESPONSIBLE PERSON (Monitor)			
a. REPORT	b. ABSTRACT	c. THIS PAGE	OF ABSTRACT:	OF PAGES	Dr. John	Russell			

16. SECURITY CLASSIFICATION OF:			17. LIMITATION	18. NUMBER	19a. NAME OF RESPONSIBLE PERSON (Monitor)
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified	OF ABSTRACT: SAR	OF PAGES 26	Dr. John Russell 19b. TELEPHONE NUMBER (Include Area Code) (937) 255-7279

COMPOSITES AFFORDABILITY INITIATIVE

CANCOM 2007 Winnipeg, Manitoba 15 Aug 07



Dr. John D. Russell

1

Senior Materials Engineer Materials and Manufacturing Directorate Air Force Research Laboratory








- Introduction/motivation
- Objective and program structure
- Technical achievements
 - Integrated structures
 - Bonded structures
- Technology transition
- Summary







Unacceptable cost & risk for new structures & applications






RISK REDUCTION FOR AFFORDABLE STRUCTURES



Structures



Quality Assurance: Documented Quality




BUSINESS MODEL



- Funding
 - USAF-US Navy funded program
 - 50-50 cost share with airframe industry
 - Bell, Boeing, Lockheed Martin, Northrop Grumman
- Technology sharing
 - Pre-competitive technology
 - Government industry integrated product teams
 - Shared data rights among industry partners
- Technology transition
 - Customer involved at all levels of CAI
 - Government and industry
 - Cost share gives industry added incentive to transition

KEY TECHNOLOGIES TO ADDRESS STRUCTURAL INTEGRITY

- Structurally sound bonded joints
- VARTM & Co-VARTM for integrated structures
- Validated analysis methods
- Bondline validation testing
- Quantifiable in-process QA / NDE
- Material & process specifications
- Certification plans
- Guidelines
- Database to support and validate technologies



Establish the confidence to fly large integrated and bonded structures



- Vacuum Assisted Resin Transfer Molding (VARTM)
 - Non autoclave process for making large yacht hulls was transitioned to the aerospace industry (ex. SCRIMP)
 - Uses a lower than atmospheric pressure (typically full vacuum) to pull a liquid resin into a fiber bed.
 - Advantages
 - Autoclave is not needed
 - Reduced capital equipment costs
 - Expands suppler base for part fabrication
 - Typical VARTM resins cure at a low enough temperature to enable the use of inexpensive tooling such as medium density fiberboard




- CAI has significantly reduced the risk on VARTM
 - Part sizes over 50 ft²
 - Aerospace quality fiber volumes
 - High consistency (per ply thickness)
 - EX1510, SI-ZG-5A, and VRM-34 resins



AEROSPACE QUALITY COMPOSITES WITHOUT AN AUTOCLAVE




- "Pi" Joint
 - Provides structural redundancy
 - Acts as two independent bondlines
 - Stronger than a double lap shear joint
 - Takes advantage of the excellent shear properties of EA 9394 adhesive, the pi joint of the material
 - EA 9394 performs better in shear than in tension loaded bonds
 - Paves the way for much reduced assembly times
 - Determinate assembly feature
 - Minimizes outtime issues when compared to faying surface bonds
 - Eliminates need for verifilm to correct tolerances





BONDED STRUCTURES DEMONSTRATIONS

















- CAI has significantly reduced the risk on bonded structures (pi joints)
 - Easier and much faster to assemble structures than with faying surface bonds
 - Eliminates verifilm checks, adhesive out time issues
 - Robust (effects of defects), predictable performance
 - Room temperature paste bond is stronger than composite base material
 - Demonstrated a ballistically survivable, mostly composite wingbox
 - Demonstrated manufacturing of several realistic structures with bonding
 - Enables a significant reduction in the number of fasteners from the outer mold line
 - ASC/EN, NAVAIR, FAA concurrence on certification methods for large integrated/bonded structures



- Tools
 - Conventional analysis methods for bonded joints were limited in capabilities and accuracy
 - A4EI only applicable to adhesive failures in shear-loaded joints, does not account for peel stresses or for potential adherend failures
 - Only alternative to these limitations has been to develop detailed finite element models of a joint
 - Time consuming
 - Requires great skill and care
 - Small errors in modeling can lead to substantial errors in joint performance prediction
 - No NDE technique to assess the strength of a bonded joint
 - Detect "kissing" bonds
 - Weight based cost models can't accurately/credibly estimate the cost of composite structures manufactured w/ emerging technologies



- Advanced Tools
 - Demonstrated ability to measure the strength of bonded joints via non-destructive inspection
 - 2 SBIRs ongoing to build a system
 - Validated improved structural analysis tools for bonded joints
 - Static and DaDT
 - Validated an advanced bottoms-up cost analysis tool for improved accuracy on new processes
- Database
 - Gathered a comprehensive database with pedigree attached
 - Standing up AMMTIAC as the permanent host

CAI TECHNOLOGY ACHIEVEMENTS



TECHNOLOGY GUIDELINE MANUALS

Design and Manufacturing

- Pi Preform Design
- Pi Preform Allowables
- Back-to-Back L
- Aluminum-Composite Bonding
- Pi Preform Cobonded Structure Process
- Pi Preform Cocured Structure Process
- VARTM Process
- Stitching
- Pi Joint Design and Manufacturing (*)
- Secondary Bonded Structure Process (*)
- Damage Level and Types (*)
- K-Spar and T-Joint (*)

Analytical Methods

- Durability and Damage Tolerance (DaDT)
- StressCheck Analysis and Modeling Guide
- Strain Invariant Failure Theory (SIFT) (*)

Quality Assurance

- Bonded Joint Evaluation
- Bonding QA Process Control
- Angle Beam Ultrasonic Spectroscopy (ABUS)
- Composite Detailed UT Evaluation
- Laser UT
- Laser Bond Inspection Local Proof Test
- Surface Preparation Procedures
- Surface Wetting Tension
- Surface Texture Measurement
- Solvent Wipe FTIR Surface Measurement
- Wing Witness Proof Test
- Field Inspection Guidelines

Repair Methods

- Bonded Wing Repair Concepts
- 3-D Pi Preform Bonded Joint Repair Concepts

(*) In Review






- Significant technical successes
- Large number of demo articles and huge database of test results
- Surprisingly small number of technical failures
 - E-beam, CoVARTM
- Documented procedures on how to employ these technologies
- CAI has significantly reduced the risk on large integrated and bonded structures
- Does industry have the confidence to implement large integrated and bonded structures?




CAI TECHNOLOGY TRANSITION PERVASIVE TOOLS







- WBS based structure
 - Define processes for parts/assembly



• Define cost based on simple engineering data

Advanced cost analysis tools commercialized Cost estimates validated with actual production data to prove accuracy of tools In use to cost numerous DoD weapon systems and commercial aircraft





Advanced structural analysis tools commercialized In use to design numerous DoD weapon systems and commercial aircraft Reduced design times, improved design accuracy



CAI TECHNOLOGY TRANSITION C-17







- VARTM, Stitched landing gear doors
- One piece main landing gear doors adopted by C-17
- Eliminates numerous field repair issues
- \$6M life cycle cost savings (before AF decision to limit production to 180 aircraft)





- No other hardware transitions at this time
 - Parallel path development needs MAJOR cost or performance improvements to replace the baseline
 - Program issues (schedule, cancellation, lack of transition funding, etc.) are impossible for a technology development program to overcome
- Being strongly considered by several companies for new military and commercial applications





- CAI has made tremendous technical strides to advance the state of the art in design and manufacture of aircraft structure
- DoD certification community concurs that bonded structure is technically feasible
- CAI has established the confidence to fly large integrated and bonded structures
- In 10 to 20 years, CAI methods will be commonplace for building aircraft structure