Report Documentation Page				Form Approved OMB No. 0704-0188			
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.							
1. REPORT DATE 18 APR 2004		2. REPORT TYPE Technical, Success	s Stories	3. DATES COVE 10-10-2003	RED 3 to 18-04-2004		
4. TITLE AND SUBTITLE			5a. CONTRACT	NUMBER			
Inconel 713 Turbine N			5b. GRANT NUN	/IBER			
		5c. PROGRAM ELEMENT NUMB		ELEMENT NUMBER			
6. AUTHOR(S)			5d. PROJECT NU 03-0011-10	JMBER			
			5e. TASK NUME	BER			
			5f. WORK UNIT NUMBER				
7. PERFORMING ORGANIZAT National Center for D Technology Way,Latr	DRESS(ES) uring & Machining	s,1600	8. PERFORMING ORGANIZATION REPORT NUMBER				
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/M	ONITOR'S ACRONYM(S)		
		11. SPONSOR/M NUMBER(S)		ONITOR'S REPORT			
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited							
13. SUPPLEMENTARY NOTES							
14. ABSTRACT Technical Directions Inc. (TDI) in Ortonville, Michigan, was commissioned to produce a small jet engine for the Loitering Attack Missile (LAM). This system is currently being reviewed by the Army at Redstone Arsenal for use in the NLOS-LS (Non-Line of Site Launch System) system. TDI in turn enlisted Extreme Precision Screw Products of Flint, Michigan, to machine key engine components. The high-temperature materials used in jet engines present machining challenges that include limited metal removal rates and frequent tool failure. For a turbine nozzle made of Inconel 713 nickel-base alloy, Extreme Precision sought ways to increase productivity in drilling and turning perations and also overcome problems encountered when using taps to thread small-diameter holes.							
^{15. SUBJECT TERMS} Loitering Attack Missile; Redstone Arsenal; NLOS-LS; Technical Directions Inc.; Extreme Precision Screw Products; National Center for Defense Manufacturing and Machining; NCDMM							
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF	18. NUMBER	19a. NAME OF		
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified		1	RESPONSIBLE PERSON		

Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std Z39-18



Inconel 713 Turbine Nozzle

NCDMM Project No. 03-0011-10



PROBLEM / OBJECTIVE

Technical Directions Inc. (TDI) in Ortonville, Michigan, was commissioned to produce a small jet engine for the Loitering Attack Missile (LAM). This system is currently being reviewed by the Army at Redstone Arsenal for use in the NLOS-LS (Non-Line of Site Launch System) system. TDI in turn enlisted Extreme Precision Screw Products of Flint, Michigan, to machine key engine components. The high-temperature materials used in jet engines present machining challenges that include limited metal removal rates and frequent tool failure. For a turbine nozzle made of Inconel 713 nickel-base alloy, Extreme Precision sought ways to increase productivity in drilling and turning operations and also overcome problems encountered when using taps to thread small-diameter holes.

ACCOMPLISHMENTS / PAYOFF



NCDMM created a "proof-of-concept" simulation using Predator verification software supplied by software provider, COM 1 Information Technologies, an NCDMM alliance partner.

TDI supplied NCDMM with Inconel castings so the proof of concept machining could take place on the actual material used in the nozzle.

Process Improvement

After analyzing the machining operations, the NCDMM recommended replacing the cobalt drills used previously with physical vapor deposition (PVD) coated solid-carbide drills. PVD-coated carbide inserts were suggested for turning processes. The tools permitted higher cutting speeds (surface feet per minute/sfm) and feed rates (inches per revolution/ipr). NCDMM also suggested milling the threads with high-performance PVDcoated solid-carbide thread mills. Unlike taps, thread mills will not jam in the hole if breakage should occur. Thread milling eliminated the need to transfer a nozzle to an electric discharge machining (EDM) unit to burn out a jammed tap, a process that can take eight hours or longer. Eliminating the workhandling and time for that secondary operation

lowered overall part cost. The thread mills also reduced threading time and boosted productivity.

Implementation and Technology Transfer

A limited supply of castings has delayed full implementation of the NCDMM recommendations, but results to date are highly positive. They include an increase in metal removal rate in turning from 0.006 cubic inches per minute (in^3/min) to .014 in^3/min . Cutting speed was increased 50 percent, from 100 sfm to 150 sfm. The high-performance solid carbide drills enabled machining parameters to be increased from 25 sfm at 0.002" ipr to 70 sfm and 0.0025" ipr. Overall, machining time for the turbine nozzle dropped from 51 minutes to 31 minutes.

Expected Benefits

In summary, full implementation will produce:

- A 40 percent average increase in turning and drilling productivity.
- Elimination of tap breakage and the need to rework nozzles on an EDM unit to remove broken taps.
- Reduction in threading time from 10 seconds to 5 seconds (50 percent).
- A better understanding of the benefits of thread milling and high performance tools in the machining of high temperature alloys.

At an estimated machine cost savings per turbine nozzle of \$20.00, savings in machining time alone over the entire intended production run of 20,000 engines will amount to \$400,000.

TIME LINE / MILESTONE

Start Date	October 03
End Date	April 04

PROJECT FUNDING

NCDMM funding\$< 5K

PARTICIPANTS

Extreme Precision Screw Products Com 1 Information Technologies, Inc. NCDMM Kennametal Inc.

For additional information concerning this project, contact the NCDMM at www.ncdmm.org