FY08 Bi-Annual Report

WIRELESS COOPERATIVE NETWORKS: SELF-CONFIGURATION AND OPTIMIZATION

Liuqing Yang (Technical Point of Contact) Dept. of Electrical and Computer Engineering P.O. Box 116130 University of Florida Gainesville, FL 32611 Tel: (352) 392-9469 Fax: (352) 392-0044 Email: lqyang@ece.ufl.edu

> Ms. Roslyn S. Heath (Administrative Point of Contact) Office of Engineering Research College of Engineering P.O. Box 116550 University of Florida Gainesville, FL 32611-6550 Tel: (352) 392-9447 ext. 7 Fax: (352) 846-1471 Email: roleson@ufl.edu

20080626 289

| REPORT DOCUMENTATION PAGE | | | | | Form Approved OMB No. 0704-0188 | | |
|--|-----------|-----------|----------------------|---------------------------------|------------------------------------|-----------------------------------|--|
| The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS. | | | | | | | |
| 1. REPORT DATE (DD-MM-YYYY) 2. REPORT TYPE | | | | | | 3. DATES COVERED (From - To) | |
| 06-15-2008 | | Per | formance/Technical R | eport (Bi-anni | ual) | Jan 2008 - Jun 2008 | |
| 4. TITLE AND SUBTITLE | | | | | 5a. CON | ITRACT NUMBER | |
| Wireless Cooperative Networks: Self-Configuration and Optimization | | | | | | | |
| FY08 Bi-Annual Report | | | | · · · | 5b. GRANT NUMBER | | |
| | | | | | N00014-07-1-0868 | | |
| | | | | | 5c. PROGRAM ELEMENT NUMBER | | |
| | | | | | | | |
| | | | | | 5d. PROJECT NUMBER | | |
| b. AUTHORISI | | | | | | | |
| Ludure rang | | | | | | | |
| | | | | | be. TASK NUMBER | | |
| | | | | | | | |
| | | | | | 5f. WORK UNIT NUMBER | | |
| | | | | | | | |
| 7. PERFORMING ORGAN | IZATION N | AME(S) AM | ID ADDRESS(ES) | | | 8. PERFORMING ORGANIZATION | |
| University of Florida | | | | | | H2 | |
| Office of Engineering Research | | | | | #2 | | |
| 343 Weil Hall, PO Box 116550 | | | | | | | |
| Gainesville, FL 32011 | | | | | | 10. SPONSOR/MONITOR'S ACRONYM(S) | |
| 9. SPONSORING/MONITORING AGENCY NAME(3) AND ADDRESS(25) | | | | | | ONR | |
| 875 North Randolph Street | | | | | onit | | |
| Arlington, VA 22203-1995 | | | | | 11. SPONSOR/MONITOR'S REPORT | | |
| | | | | | | NOMBER(S) | |
| | | | | | | | |
| 12. DISTRIBUTION/AVAILABILITY STATEMENT | | | | | | | |
| Approved for Public Release, distribution is Offinitied. | | | | | | | |
| | | | | | | | |
| 13. SUPPLEMENTARY NOTES | | | | | | | |
| | | | | | | | |
| 14 ARSTRACT | | | | | | | |
| Distributed multi-input multi-output (MIMO) system is a promising architecture to provide reliable | | | | | | | |
| Distributed multi-input multi-output (winvio) system is a promising architecture to provide reliable | | | | | | | |
| communications over spanany separated relaying nodes. In this paper, we will investigate the optimum | | | | | | | |
| resource allocation techniques in distributed MIMO systems, employing differential (de)modulation and | | | | | | | |
| various relaying protocols. Instead of limiting to energy optimization, we solve this problem via a two- | | | | | | | |
| dimensional energy and location optimization. Benefits of our resource optimization approaches are illustrated | | | | | | | |
| through extensive analysis and simulations. Comparisons between different optimization techniques and | | | | | | | |
| systems with different protocols are also included. | | | | | | | |
| 15. SUBJECT TERMS | | | | | | | |
| wireless sensor networks, wireless cooperative networks, resource optimization, ultra-wideband, localization, ranging | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| 16. SECURITY CLASSIFICATION OF: 17. LIMITATION OF ABSTRACT OF | | | | 19a. NAME OF RESPONSIBLE PERSON | | | |
| a. REPORT D. ABSTR | ACT C. TI | HIS PAGE | TITI | PAGES | 19h TE | FPHONE NUMBER (Include area code) | |
| U U | | U | 00 | 4 | TOD. TEL | (352)392-9469 | |
| Standard Form 298 (Rev. 8/98) | | | | | | | |

Prescribed by ANSI Std. Z39.18

A Abstract

Distributed multi-input multi-output (MIMO) system is a promising architecture to provide reliable communications over spatially separated relaying nodes. In this paper, we will investigate the optimum resource allocation techniques in distributed MIMO systems, employing differential (de)modulation and various relaying protocols. Instead of limiting to energy optimization, we solve this problem via a two-dimensional energy and location optimization. Benefits of our resource optimization approaches are illustrated through extensive analysis and simulations. Comparisons between different optimization techniques and systems with different protocols are also included.

B Technical Results

Based on our previous work, we provide an upper bound of the symbol error rate (SER) for decodeand-forward (DF) systems and an approximated SER for amplify-and-forward (AF) systems. We proved that the system SER is a convex function in both the transmit energy and the relay location, and then carried out the two-dimensional energy and location optimization through numerical search. As we know, system energy is a limited resource, especially for mobile terminals, and the coverage area is a critical factor to judge the system performance. Therefore, we evaluate the benefits of our optimization techniques in terms of the system energy saving and the coverage distance extension.

The simulations reveal several interesting results. For both DF and AF protocols, the optimized systems always outperform the unoptimized systems with either less energy consumption or longer transmission range. It is also noticed that the benefits of both energy and location optimizations vary a lot for different protocols, and with different system configurations. Uniform energy allocation and midpoint relay location are normally chosen as an initial system setup. For such a configuration with DF protocol, location optimization is more critical than energy optimization, and the unoptimized system receives prominent benefits from both optimizations, and tremendous system resources savings. For AF protocol, however, location and energy optimizations are equally important for the unoptimized system. It turns out that the uniform energy allocation and the midpoint relay location result in fairly good system performance, since it is reasonably close to the global optimum.

For other initial system setups, the optimization benefits are also distinct in AF and DF systems. In DF systems, more optimization benefits can be achieved when the relays are either close to the destination or have more transmit energy allocated to the relay(s). On the contrary, in AF systems, remarkable optimization benefits will be achieved when the relays are far from the midpoint, or when the relays are only able to transmit at low energy levels.

To enable the implementation of such an optimum strategy in wireless sensor networks, the sensor nodes need to know their precise (absolute or relative) locations. In the past, the Global Positioning System (GPS) has been the major method for wireless localization and navigation. However, its application is constrained since the GPS signal is not available in indoor, metropolitan and heavy-foliage scenarios which, more often than not, are where the sensor networks are deployed. Therefore, we need to exploit alternative terrestrial wireless signals for positioning and navigation. In our work, we consider both the ultra-wideband (UWB) signals that are intentionally set up, and the wireless local area network (WLAN) IEEE 802.11a/g signals that are widely available and are known as the "signal-of-opportunity." For both signals, we investigate the time-difference-of-arrival (TDoA) based ranging and localization.

The Cramer-Rao Bound (CRB) analysis reveals that broadband signals can provide high accuracy timing and localization. In order to exploit this capability, we propose a high-precision time-of-arrival (ToA) estimator for broadband wireless systems. By *focusing on the first arrival* (FoFa), our approach has the advantage of high resolution and low complexity, in comparison with existing alternatives. In addition, no analog or oversampled waveform is needed. Our algorithm is built on, and requires minimum modification of, the frequency domain equalizers that are widely adopted for broadband wireless systems. Simulations show that our proposed FoFa estimator outperforms the well-known space alternating generalized expectation maximization estimator in terms of the ToA estimation accuracy for both the line-of-sight and non-line-of-sight channels.

C Publications

- W. Cho, R. Cao and L. Yang, "Optimum Resource Allocation for Amplify-and-Forward Relay Networks with Differential Modulation," *IEEE Transactions on Signal Processing*, 2008 (to appear).
- [2] F. Qu, D. Duan, L. Yang and A. Swami, "Signaling with Imperfect Channel State Information: A Battery Power Efficiency Comparison," *IEEE Transactions on Signal Processing*, 2008 (to appear).
- [3] W. Cho and L. Yang, "Optimum resource allocation for relay networks with differential modulation," *IEEE Transactions on Communications*, vol. 56, no. 4, pp. 531–534, April 2008.

- [4] H. Xu and L. Yang, "Timing with Dirty Templates for Low-Resolution Digital UWB Receivers," *IEEE Transactions on Wireless Communications*, vol. 7, no. 1, pp. 54–59, January 2008.
- [5] D. Duan, F. Qu, L. Yang and A. Swami, "Battery Power Efficiency of PPM and OOK in Wireless Sensor Networks," *IEEE Transactions on Communications*, June 2008 (submitted).
- [6] H. Xu, L. Yang and J. Y. Morton, "Ranging with Multi-Band UWB Signals," *IEEE Transactions on Communications*, June 2008 (submitted).
- [7] H. Xu, L. Yang, C.-C. Chong and I. Guvenc, "Precise ToA Estimation for Broadband Wireless Systems by Focusing on the First Arrival," *IEEE Transactions on Wireless Communications*, June 2008 (submitted).
- [8] H. Xu and L. Yang, "UWB-based precision positioning and navigation," in Proc. of the URSI General Assembly 2008, Chicago, IL, August 7-16, 2008 (invited).
- [9] H. Xu, C.-C. Chong, I. Guvenc, F. Watanabe, and L. Yang, "High-Resolution TOA Estimation with Multi-Band OFDM UWB Signals," in *Proc. of IEEE International Conference on Communications*, pp. 4191–4196, Beijing, China, May 19-23, 2008.
- [10] R. Cao and L. Yang, "Resource Optimization of Distributed MIMO Systems," in Proc. of International Symposium on Advances in Computer and Sensor Networks and Systems, Zhengzhou, China, April 7-10, 2008 (invited).
- [11] W. Cho and L. Yang, "Performance analysis of cooperative networks with differential unitary space time coding," in *Proc. of Intl. Conf. on Acoustics, Speech and Signal Processing*, Las Vegas, NV, March 30-April 4, 2008.
- [12] R. Cao and L. Yang, "Practical Issues in Resource Optimization of Relay Networks," in Proc. of Conference on Info. Sciences and Systems, Princeton University, March 19-21, 2008.
- [13] H. Xu and L. Yang, "Ultra-Wideband Technology: Yesterday, Today, and Tomorrow," in *Proc.* of *IEEE Radio and Wireless Symposium*, pp. 715–718, Orlando, FL, January 22-24, 2008 (invited).