

## REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ORGANIZATION.

1. REPORT DATE (DD-MM-YYYY) 14-01-2010		2. REPORT TYPE Conference Proceeding		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE Limiting factors in Underwater Imaging Applications				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER 0602782N	
6. AUTHOR(S) Weilin Hou, Alan Weidemann				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER 73-6369-09-5	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Research Laboratory Oceanography Division Stennis Space Center, MS 39529-5004				8. PERFORMING ORGANIZATION REPORT NUMBER NRL/PP/7330-09-9289	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Office of Naval Research 800 N. Quincy St. Arlington, VA 22217-5660				10. SPONSOR/MONITOR'S ACRONYM(S) ONR	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution is unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT Applications of a simple underwater imaging model (SUIM) are presented, which help to identify limiting factors in conventional underwater imaging applications, such as diver visibility. The model includes the effects of scattering caused by particles as well as turbulent flow structure. The effect of path radiance is also discussed.					
15. SUBJECT TERMS simple underwater imaging model, OTF, point spread function					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT  UL	18. NUMBER OF PAGES 8	19a. NAME OF RESPONSIBLE PERSON Deric Gray
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (Include area code) 228-688-4237

20100121306

## PUBLICATION OR PRESENTATION RELEASE REQUEST

Pubkey: 6223

NRLINST 5600.2

1. REFERENCES AND ENCLOSURES	2. TYPE OF PUBLICATION OR PRESENTATION	3. ADMINISTRATIVE INFORMATION
Ref: (a) NRL Instruction 5600.2 (b) NRL Instruction 5510.40D  Encl: (1) Two copies of subject paper (or abstract)	<input type="checkbox"/> Abstract only, published <input type="checkbox"/> Book <input type="checkbox"/> Conference Proceedings (refereed) <input type="checkbox"/> Invited speaker <input type="checkbox"/> Journal article (refereed) <input type="checkbox"/> Oral Presentation, published <input type="checkbox"/> Other, explain  <input type="checkbox"/> Abstract only, not published <input type="checkbox"/> Book chapter <input checked="" type="checkbox"/> Conference Proceedings (not refereed) <input type="checkbox"/> Multimedia report <input type="checkbox"/> Journal article (not refereed) <input type="checkbox"/> Oral Presentation, not published	STRN <b>NRL/PP/7330-09-9289</b> Route Sheet No. <b>7330/</b> Job Order No. <b>73-6369-09-5</b> Classification <b>X</b> <b>U</b> <b>C</b> Sponsor <b>ONR</b> approval obtained <b>yes</b> <b>X</b> <b>no</b>

## 4. AUTHOR

Title of Paper or Presentation

Limiting Factors in Underwater Imaging Applications

Author(s) Name(s) (First, MI, Last), Code, Affiliation if not NRL

Weilin Hou, Aian D. Weidemann

It is intended to offer this paper to the **ONW'2009 Conference**

(Name of Conference)

**08- SEP - 12- SEP- 09, St Petersburg, Russia, Unclassified**

(Date, Place and Classification of Conference)

and/or for publication in **ONW'2009 Conference, Unclassified**

(Name and Classification of Publication)

(Name of Publisher)

After presentation or publication, pertinent publication/presentation data will be entered in the publications data base, in accordance with reference (a).

It is the opinion of the author that the subject paper (is ☐) (is not ☒) classified, in accordance with reference (b).This paper does not violate any disclosure of trade secrets or suggestions of outside individuals or concerns which have been communicated to the Laboratory in confidence. This paper (does ☐) (does not ☒) contain any militarily critical technology. This subject paper (has ☐) (has never ☒) been incorporated in an official NRL Report.

Weilin Hou, 7334

Name and Code (Principal Author)

(Signature)

## 5. ROUTING/APPROVAL

CODE	SIGNATURE	DATE	COMMENTS
Author(s) Hou		7/6/2009	Need by <u>21 Jul 09</u> Publicly accessible sources used for this publication
Section Head Weidemann		7/6/09	
Branch Head Robert A Arnone, 7330			
Division Head Ruth H. Preller, 7300		7/8/09	1. Release of this paper is approved. 2. To the best knowledge of this Division, the subject matter of this paper (has <input type="checkbox"/> ) (has never <input checked="" type="checkbox"/> ) been classified.
Security, Code 1226			
Office of Counsel, Code 1008.3		7/9/09	1. Paper or abstract was released. 2. A copy is filed in this office. <u>55C 244-9</u>
ADOR/Director NCST E. R. Franchi, 7000			
Public Affairs (Unclassified/ Unlimited Only), Code 7030.4		7/10/09	
Division, Code			
Author, Code			



## PUBLICATION OR PRESENTATION RELEASE REQUEST

09-1226-2385

Preskey.

NRL INST 5600.2

Ref: (a) NRL Instruction 5600.2 (b) NRL Instruction 5510.40D	<input type="checkbox"/> Abstract only, published <input type="checkbox"/> Book <input type="checkbox"/> Conference Proceedings (refereed) <input type="checkbox"/> Invited speaker <input type="checkbox"/> Journal article (refereed) <input type="checkbox"/> Oral Presentation, published <input type="checkbox"/> Other, explain	<input type="checkbox"/> Abstract only, not published <input checked="" type="checkbox"/> Book chapter <input checked="" type="checkbox"/> Conference Proceedings (not refereed) <input type="checkbox"/> Multimedia report <input type="checkbox"/> Journal article (not refereed) <input type="checkbox"/> Oral Presentation, not published	STRN <u>NRL PP/7330-09-0289</u> Route Sheet No. <u>7330/</u> Job Order No. <u>73-6369-09-5</u> Classification <u>X</u> <u>U</u> <u>C</u> Sponsor <u>ONR</u> <u>Base 6.2 mt</u> approval obtained <u>yes</u> <u>X</u> <u>no</u>
---	---	--	---

Title of Paper or Presentation

Limiting Factors In Underwater Imaging Applications

Author(s) Name(s) (First, M, Last), Code, Affiliation if not NRL

Wellin Hou, Alan D. Weldemann

It is intended to offer this paper to the ONW'2009 Conference

(Name of Conference)

08- SEP - 12- SEP - 09, St Petersburg, Russia, Unclassified

(Date, Place and Classification of Conference)

and/or for publication in ONW'2009 Conference, Unclassified

(Name and Classification of Publication)

(Name of Publisher)

After presentation or publication, pertinent publication/presentation data will be entered in the publications data base, in accordance with reference (a).

It is the opinion of the author that the subject paper (is     ) (is not X) classified, in accordance with reference (b).This paper does not violate any disclosure of trade secrets or suggestions of outside individuals or concerns which have been communicated to the Laboratory in confidence. This paper (does     ) (does not X) contain any militarily critical technology.This subject paper (has     ) (has never X) been incorporated in an official NRL Report.

Wellin Hou, 7334

Name and Code (Principal Author)

(Signature)

CODE	SIGNATURE	DATE	COMMENTS
Author(s) <u>Hou</u>	<u>[Signature]</u>	<u>7/6/2009</u>	Need by <u>21 Jul 09</u>
			Publicly accessible sources used for this publication
			This is a Final Security Review
Section Head <u>Weidemann</u>	<u>[Signature]</u>	<u>7/6/09</u>	Any changes made in the document after approved by Code 1226 nullify the Security Review
Branch Head <u>Robert A Arnone, 7330</u>	<u>[Signature]</u>		
Division Head			1. Release of this paper is approved. 2. To the best knowledge of this Division, the subject matter of this paper (has <u>    </u> ) (has never <u>X</u> ) been classified.
Ruth H. Preller, 7300	<u>[Signature]</u>	<u>7/8/09</u>	
Security, Code <u>1226</u>	<u>[Signature]</u>	<u>7/8/09</u>	1. Paper or abstract was released. 2. A copy is filed in this office. <u>55C244-9</u>
Office of Counsel, Code <u>1008.3</u>	<u>[Signature]</u>	<u>7/8/09</u>	
ADOR/Director NCST <u>E. R. Franchi, 7000</u>	<u>[Signature]</u>	<u>7/10/09</u>	Personally identifying photos may not be posted to publicly accessible DON websites per SECNAVINST 5720.47B, encl. (1); 3.c (2) & 3.c (4).
Public Affairs (Unclassified/ Unlimited Only), Code <u>7030.4</u>	<u>[Signature]</u>	<u>7/10/09</u>	del Email
Division, Code			
Author, Code			


S

Weilin Hou

V International Conference

# **CURRENT PROBLEMS IN OPTICS OF NATURAL WATERS (ONW'2009)**

*St.-Petersburg, Russia, September 8 – 11, 2009*



## **PROCEEDINGS**

*Nizhny Novgorod, 2009*



# LIMITING FACTORS IN UNDERWATER IMAGING APPLICATIONS

W. Hou, A.D. Weidemann

Naval Research Laboratory, Stennis Space Center, MS 39529, USA, hou@nrlssc.navy.mil

## 1. Background

Underwater vision and diver visibility is one of the key research and application topics dating back at least 150 years, when the Secchi disk was believed first put to use to estimate the turbidity of the ocean and lake waters. It is well known that the light attenuation effect of the water, both absorption but more importantly scattering, contributes to the degradation of image transmission. In general, scattering properties of the medium determine the outcome of the image transmission. In ocean and lake environments, such properties are conveniently described and measured by the scattering coefficient ( $b$ ), which determines the probability that a photon will be scattered away from its original traveling direction per unit length by the medium molecules, constituents within the medium (i.e. particles), and turbulence [1]. The scattering parameter ( $b$ ) is an integration of the volume scattering or phase function,  $\beta$ , which details such probabilities by the relative directions of incoming and out-going photons.

The point spread function (PSF) provides a more intuitive and direct measure of the imaging outcome. It gives the system response to a point source, and thus includes the effect of multiple scattering. It is the parameter of choice to study image transmission, optical sounding [2], and retrieval of optical properties [3]. Its Fourier transform, the Optical Transfer Function (OTF), is also widely used and at times considered interchangeable with the PSF. The magnitude of the OTF, the modulation transfer function (MTF), is sufficient for incoherent imaging purposes when phase information can be neglected.

The system response includes those from the imaging system itself, as well as the effects of the medium (water in our case). With known characteristics of the imaging system and correct modeling of the medium, theoretically it is possible to fully recover the original signal by reversion or deconvolution [4]. Mathematically PSF is equivalent to the beam spread function (BSF) [5] which can be modeled and measured more easily. It is apparent that with the knowledge of formed image and PSF, the original image can be restored, especially when the noise can be reduced with improved system setup or optimization [6]. Additionally, with the knowledge of the PSF, one can easily simulate the system outcome. This is valuable to system design, performance prediction, as well as underwater scene simulations, as it is based on the accuracy of the physical model of the system (medium included). Different models of PSF that are based on particulate scattering have been examined and compared [7]. The results show that 3 commonly used inherent optical properties (IOP) should be used in order to adequately describe the imaging transfer through the water. However, the variations of signal due to index of refraction changes in water are not accounted for.

## 2. SUIM: simple underwater imaging model

A simple underwater imaging model (SUIM) has been developed [8], to investigate the relative contribution of particle and turbulence scattering on underwater imaging and transmission. The key steps will be outlined briefly for the convenience of the readers.

Results developed in previous atmosphere research [9–12] are used with modifications to reflect in-water optical conditions. Optical turbulence in the ocean is primarily caused by index of refraction (IOR) variation as functions of temperature and salinity, compared to density variations found in the atmosphere. It has been shown that IOR fluctuations can be expressed as linear combinations of individual elements, both in terms of power spectrum and structure functions [13]. Following the Kolmogorov model [9], for a fully developed turbulent flow, under the inertial or convective regime,  $2\pi/L_0 < \kappa < 2\pi/l_0$  ( $L_0$  and  $l_0$  denote outer and inner scale respectively;  $\kappa$  defines the wavenumber of eddies), the power spectral density of IOR of the ocean waters over the imaging range ( $r$ ) can be expressed in the forms of [13, 14]

$$\Phi_n^K(\kappa, r) = K_3 \kappa^{-11/3}, \quad (1)$$

where  $K_3 = B_1 \chi \epsilon^{-1/3}$ , and reflects the 3-dimensional optical turbulence strength.  $B_1$  is a constant.  $\epsilon$  is the kinetic energy dissipation rate.  $\chi$  relates to the dissipation rate of temperature or salinity [14]. For simplicity

but without losing generality, one can assume only one factor dominates IOR fluctuations, although observations suggest both can contribute simultaneously [15]. It is apparent the above has the usual Kolmogorov form found in atmospheric studies [9-11] as  $\Phi_n^K(\kappa, r) = 0.033 C_n^2(r) \kappa^{-11/3}$ , where again the superscript  $K$  denotes Kolmogorov spectrum.  $C_n^2$  is the structure constant of the IOR fluctuations in atmosphere, which describes the optical turbulence strength at distance  $r$  from the pupil plane (i.e. intensity of IOR fluctuations). We notice that  $K_3$  is the equivalent of  $C_n^2$ , by a constant. The above scalar relationship implies that the turbulence in water can be considered statistically isotropic, homogenous, and wide-sense stationary (WSS) such that spatial autocorrelation function only depends on relative positions. We assume this is true at least in the imaging range.

It is commonly known that spatial coherence functions between optical fields of any two points can be used to describe the irradiance distribution of the source image or object [11, 16]. For a time-varying correlation function under WSS conditions, its ensemble average can be related to the spatial phase structure function, such that the optical transfer function (OTF) of a general incoherent object can be expressed following the approach by Fried [10, 12]. Consider that random phase changes of a wavefront can be described independently as a thin screen which exists only when turbulence exists, the resting or averaging OTF would be that of particles only. This assures linearity of system components, which allows the application of the cascading of optical transfer functions in the frequency domain [16]. From this, we can arrive at a simple underwater imaging equation accounts for particle [17], path radiance and turbulence scattering, in the form:

$$\begin{aligned} OTF(\psi, r)_{total} &= OTF(\psi, r)_{path} OTF(\psi, r)_{par} OTF(\psi, r)_{nr} = \\ &= \left( \frac{1}{1+D} \right) \exp \left[ -cr + br \left( \frac{1 - e^{-2\pi\theta_0\psi}}{2\pi\theta_0\psi} \right) \right] \exp(-S_n\psi^{5/3}r) = \\ &= \left( \frac{1}{1+D} \right) \exp \left\{ - \left[ c - b \left( \frac{1 - e^{-2\pi\theta_0\psi}}{2\pi\theta_0\psi} \right) + S_n\psi^{5/3} \right] r \right\} \end{aligned} \quad (2)$$

where  $\theta_0$  relates to mean scattering,  $c$  is the beam attenuation coefficient,  $D$  is the normalized radiance received by the detector. The first term in the bracket reflects the effect of the path radiance [8]. It is worth pointing out that  $OTF_{par}$  can take many different forms, depending how the scattering phase structure is incorporated [7].

### 3. Application of SUIM

The simple underwater imaging model (SUIM), Eq. (2), accounts for particle, turbulence scattering as well as path radiance effects in the underwater environment. The primary aim of the model is to determine the relative contributions which are essential in assessing limits of conventional passive systems under different underwater conditions.

In an earlier study [18], the SUIM model was applied to diver visibility observations from several divers, and used to explain discrepancies between observations and the particle scattering only model. This model can also help to explain the extreme turbulence situation observed by Gilbert and Honey [15]. One of the targets used in their experiment is the standard USAF 1951 resolution chart, which is shown in Fig. 1. The chart uses black and white bar patterns of horizontal and vertical orientations at different spatial frequencies denoted by the number of line pairs per mm (Table 1). If one converts USAF line pairs to spatial frequencies, the first blurred line pairs, group -1, element 1, correspond to 650 cyc/rad at 1.3 m range. Applying Eq. (2) with  $R_0 \sim 0.0005$ ,  $c \sim 0.3 \text{ m}^{-1}$  which is the likely values in such waters ( $\epsilon = 10^{-5}$ ,  $\chi = 10^{-11}$ ), one can see the total contrast easily decreases to  $< 2\%$  within 1.3 m range (Fig. 2), which explains the complete disappearance of the group in the USAF chart observed at such short distance [15]. From Eq.(2) and Fig. 2, it becomes apparent why Mertens reported no frequency higher than 1 cyc/mrad observed in the




Fig. 1. Standard USAF 1951 chart. Each group consists of different elements, corresponding to different spatial frequencies denoted by number of line pairs per mm.



field, which puzzled Duntley [19], as at such high spatial frequency ( $\sim 10^3$  cyc/rad), the relative contrast decreases rather rapidly towards zero.


**Table 1.** USAF resolution chart, showing number of line pairs per mm of different groups and elements. Notice the spatial frequencies of first 4 elements of groups -2 to 1 at distance 1.3 m are shown in bracketed values

Number of line pairs per mm (USAF 1951)							
Element\Group#	-2	-1	0	1	2	3	4
1	0.250 (325)	0.500 (650)	1.00 (1300)	2.00 (2600)	4.00	8.00	16.00
2	0.280	0.560	1.12	2.24	4.49	8.98	17.95
3	0.315	0.630	1.26	2.52	5.04	10.10	20.16
4	0.353	0.707	1.41	2.83	5.66	11.30	22.62
5	0.397	0.793	1.59	3.17	6.35	12.70	25.39
6	0.445	0.891	1.78	3.56	7.13	14.30	28.50

The SUIM helps to assess the limitations of underwater imaging contributions by particles, turbulence and ambient illumination observed. It is important to observe the differences between particle and turbulence effects on underwater imaging, as shown by Fig. 2. While turbulence scattering can affect low frequency components, especially over longer range, its primary impact is on high frequency or details, which differ from that of particles. It is also worth mentioning that the current SUIM reflects the optical properties of a medium under incoherent cases, although coherent cutoff frequency is often less [11], so it can be used as a crude estimate even under partial coherent sources. Naturally it can be applied directly for conventional imaging and especially diver visibility assuming passive conditions. It is apparent that the SUIM does not include effects of backscattering, nor cases with saturation which only further degrades MTF, although first order this can be neglected since effects on all frequencies remain the same. Needless to say, it is directly applicable to active systems such as gated and modulated, although modifications can be made to reflect shorter integration time, to obtain system limitations similar to approach used in [12].

#### 4. Summary

In this paper the relative contributions by both turbulence induced index of refraction variations as well as particle scattering on imaging outcome in natural environments are examined, using the recently developed SUIM model. Specifically, it is shown that by including turbulence effects which are based on Kolmogorov power spectrum, we are able to explain the blurring of resolution patterns in very short distance in clean waters off the coast of Hawaii, observed by Gilbert and Honey. Further validation of the theory is necessary, especially under different turbulence conditions and particulate concentration. The applicable range of the developed theory should also be tested, along with different turbulence models and subregime



**Fig. 2.** Relative contributions by particle and turbulence scattering on MTF under a condition similar to that of Hawaiian waters during Gilbert and Honey experiment (1972). Notice relative contrast drops to 2% at spatial frequency: 650 cyc/rad.

### Acknowledgement

The authors thank NRL for continuous support through UW Project 73-6369.

### Reference

1. Mobley C.D., *Light and Water: radiative transfer in natural waters*. New York: Academic Press, 1994.
2. Katsev I.L., et al., "Efficient technique to determine backscattered light power for various atmospheric and oceanic sounding and imaging systems," *J. Opt. Soc. Am.*, vol. 14, p. 1338-1346, 1997.
3. Hou W., et al., "Automated underwater image restoration and retrieval of related optical properties," in *IEEE International Geoscience and Remote Sensing Symposium, IGARSS 2007*, p. 1889-1892.
4. Gonzalez R.C. and Woods R.E., *Digital image processing*, 2nd ed. Upper Saddle River, N.J.: Prentice Hall, 2002.
5. Mertens L.E. and Replogle J.F.S., "Use of point spread and beam spread functions for analysis of imaging systems in water," *J. Opt. Soc. Am.*, vol. 67, p. 1105-1117, 1977.
6. Zhang J., et al., "Blind deconvolution: multiplicative iterative algorithm," *Opt. Lett.*, vol. 33, pp. 25-27, 2008.
7. Hou W., et al., "Comparison and validation of point spread models for imaging in natural waters," *Opt. Express*, vol. 16, p. 9958-9965, 2008.
8. Hou W., "A simple underwater imaging model," *Opt. Lett.* (accepted), 2009.
9. Tatarskii, *Wave Propagation in a Turbulent Medium*. New York: Dover Publications, 1967.
10. Roggemann M.C. and Welsh B.M., *Imaging through turbulence*: CRC Press, 1996.
11. Goodman J.W., *Statistical Optics*: John Wiley & Sons, 1985.
12. Fried D.L., "Optical resolution through a randomly inhomogeneous medium for a very long and very short exposures," *J. Opt. Soc. Am.*, vol. 56, p. 1372-1379, 1966.
13. Fields A.S., "Optical Phase and Intensity Fluctuations in a Refractive Index Microstructure: A Mathematical Analysis," vol. 3577, P. a. A. S. Department, Ed., ed: Naval Ship Research and Development Center, 1972.
14. Batchelor G.K., "Small-scale variation of convected quantities like temperature in turbulence fluid," *J. Fluid Mech.*, vol. 5, p. 113-133, 1959.
15. Gilbert G.D. and Honey R.C., "Optical turbulence in the sea," in *Underwater photo-optical instrumentation applications*, 1972, pp. 49-55.
16. Goodman J.W., *Introduction to Fourier Optics*: Roberts & Company Publishers, 2005.
17. Hou W., et al., "Why does the Secchi disk disappear? An imaging perspective," *Opt. Express*, vol. 15, p. 2791-2802, March 19 2007.
18. Hou W. and Weidemann A., "Diver visibility: why one can not see as far?" in *SPIE Proc. 7317*, Orlando, FL, USA, 2009.
19. Duntley S.Q., "Underwater Visibility and Photography," in *Optical Aspects of Oceanography*, N.G. Jerlov, and Nielsen, E.S., Ed., ed New York: Academic Press, 1974.