REPORT DOCUMENTATION PAGE					Form Approved OMB No. 0704-0188	
The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching axisting deta sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden astimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Heedquarters Services, Directorate for information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suita 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shell be subject to any penelty for failing to comply with a collection of information if it does not display a currently valid OM8 control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.						
1. REPORT DA	TE (DD-MM-YY) 05-1967	(Y) 2. REPO	RT TYPE	nen File Ren	ort	3. DATES COVERED (From - To)
4. TITLE AND	SUBTITLE		annisuauve Report, O	peu i ne Rep	5a. COM	ITRACT NUMBER
Reconnaissance Sediment Survey of Kajakai and Arghandab Reservoirs, Helmand River Basin, Afghanistan. Appendix 11. Surface water investigations in Afghanistan: a summary of activities from 1952 to 1969. United States Operations Mission to Afghanistan; International Cooperation			rvoirs, es from operation	5b. GRANT NUMBER 5c. PROGRAM ELEMENT NUMBER		
Administratio	i, Lasiikai Uali	, Aignanistan.				
6. AUTHOR(S) Porterfield, George and Arthur O. Westfall.				5d. PROJECT NUMBER		
				5e. TASK NUMBER		
					5ł. WOł	RK UNIT NUMBER
7. PERFORMIN US Geologica 12201 Sunrise Reston, VA 20	G ORGANIZATI I Survey (USG Valley Drive)192, USA	on name(s) an S)	ID ADDRESS(ES)			8. PERFORMING ORGANIZATION REPORT NUMBER
9. SPONSORIN	G/MONITORING	AGENCY NAM	E(S) AND ADDRESS(ES)			10. SPONSOR/MONITOR'S ACRONYM(S)
						HVA; ICA; USGS; USAID
						11. SPONSOR/MONITOR'S REPORT NUMBER(S)
12. DISTRIBUT	ON/AVAILABILI	TY STATEMENT	7			
Unclassified/Unlimited						
13. SUPPLEME	TARY NOTES					
Appendix 11.						
14. ABSTRACT						
The purpose of this report is to summarize briefly the history of the Surface Water Research project since its inception in 1952, the work accomplished, and the problems encountered. In general, each topic is discussed under two periods of time: 1952-1963, when projects were confined to the Helmand River Valley and was entitled "Helmand Surface Water Investigations (306-12-021, 306-M-12-AD and 306-AC-12-AD5)," and 1963-1969 when activities were expanded to cover most of Afghanistan and title was changed to "Surface Water Research (306-11-190-002)".						
Agriculture and Irrigation, Royal Government of Afghanistan under the auspices of the United States Agency for International Development.						
15. SUBJECT T	ERMS					
Afghanistan. Drainage. Flood control. Helmand River Project. HVA. Helmand Valley Authority. Hydrology. Hydropower. Irrigation. Lashkar Gah. Rainfall Runoff Calculations. Stream-flow Data. Stream gaging stations. Stream measurements. Surface Water, Water supply.						
16. SECURITY	CLASSIFICATIO	N OF:	17. LIMITATION OF	18. NUMBER	19a. NAI	ME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE	THT	PAGES	105 TE	EDHONE NI IMBER (Include and and)
UU	UU	UU	UU	6	100. TEL	LI TOME NUMBER (Include area Code)

Standard	Form	298	(Rev.	8/98)
Prescribed b	y ANSI	Std. Z	39.18	

Appendix (1

(200) WRBwsw appendix 11

Reconnaissance Sediment Survey of Kajakai and Arghandab Reservoirs, Helmand River Basin, Afghanistan

> By George Porterfield and A.O. Westfall U.S. Geological Survey May 1967

A reconnaissance survey of Kajakai and Arghandab Reservoirs was made May 26-28, 1967 to observe the present extent of silting and to determine the optimum method to be used for detailed sediment studies at each reservoir. This preliminary report is not complete, but is only intended to alert the US AID/Kabul to the magnitude of sedimentation observed during this survey. The optimum methods for detailed studies will be given in a later report.

Soundings of water depth at various points in the lake were made with a sonic depth recorder, and an attempt was made to measure sediment thickness at several points with a steel rod.

Arghandab Reservoir

Storage began in Arghandab Reservoir on February 24, 1952 and the initial storage capacity was 388,000 acre-feet. The daily mean inflow to the reservoir for the 17-year period, 1948-64, was 1,398 cubic feet per second (cfs). The annual runoff has varied from a maximum of 2,168,000 acre-feet in 1957 to a minimum of 464,100 acre feet in 1955. The average annual runoff for the period was 1,012,000 acre-feet. The maximum discharge recorded was 35,700 cfs on March 17, 1957 and the minimum recorded was 44 cfs on September 7-8, 1948. The only major source of the sediment deposited in Arghandab Reservoir is that which is transported by the Arghandab River. Deposited sediment now fills the upper 3 miles of the reservoir where water depths were originally as much as 32 feet. Soundings also indicate sediment deposits up to 30 feet thick for an additional 2 miles of reservoir and up to 20 feet thick for one more mile. Although soundings were not taken in the lower part of the reservoir (the reservoir is approximately 10 miles long) silting has undoubtedly occurred.

A rough estimate based on the above observations indicates that up to 25 percent of the reservoir capacity has been lost to sedimentation in the last 15 years and that the present storage capacity of the reservoir is less than 300,000 acre-feet. If the past rate of sediment accumulation continues, the reservoir will probably be filled by sediment in another 45 years.

Kajakai Reservoir

Storage began in Kajakai Reservoir on January 28, 1953 and the initial capacity was 1,495,000 acre-feet. The daily mean inflow to the reservoir for the 17-year period, 1948-64, was 6,977 cfs. The annual runoff has varied from a maximum of 9,059,000 acre-feet in 1957 to a minimum of 3,175,000 acre-feet in 1962. The average annual runoff for the period was 5,051,000 acre-feet. The maximum peak discharge is unknown. The maximum mean daily discharge recorded was 66,200 cfs on May 3, 1957. The minimum discharge recorded was 1,100 cfs on October 1, 1947 (start of record - it may have been lower prior to that date).

2

The only major source of the sediment deposited in Kajakai Reservoir is that which is transported by the Helmand River. In the upper arm of the reservoir soundings indicate sediment deposits of up to 50 feet in thickness. Because of the size, shape, and operational pattern of the reservoir the distribution of sediment is not as readily determined as it is in Arghandab Reservoir. The narrow upper part of Kajakai Reservoir is not as completely filled as the upper part of Arghandab Reservoir because of the large volumes and high velocities of the water entering while the lake is filling. This moves sediment previously deposited much further into the reservoir. The large upper arm of the lake will trap much of the sediment while lake levels are high, but at the start of the storm season when lake levels are low the sediment will pass through the upper arm and into the main body of the lake.

Although the silting of Kajakai Reservoir is not as obvious to the eye as that of Arghandab Reservoir the facts point to a rate of silt accumulation that may be equal to that of Arghandab Reservoir.

3

Recommendations

This preliminary survey indicates a loss of storage from the two reservoirs of about 470,000 acre-feet at the present time, more than the total initial storage of Arghandab Reservoir. At the present rate of silt accumulation, the reservoirs will probably be half filled with sediment in another 15 years. This will seriously affect the flood-storage capacity of the reservoirs and cause increasing problems for the proposed hydro-power installation at Kajakai Reservoir and for the continued expansion of irrigated lands, especially in the Arghandab-Tarnak area.

It is recommended that a complete survey be made of both reservoirs to more accurately determine the present amount and location of sediment deposits, and to establish a system whereby periodic checks can be made to observe the silt-accumulation rate.

Arghandab Reservoir inflow

Water	. 1,000	1,000 cfs		
Year	Acre-Feet	Max. daily	Min. daily	
1948	574.0	6.79	0.044	
1949	873.0	15.0	.149	
1950	1,145	11,8	.243	
1951	1,043	11.1	.283	
1952	816.4	5.86	.232	
1953	493.8	4.79	.071	
1954	1,358	13.5	.145	
1955	464.1	8.64	.064	
1956	1,657	15.5	.136	
1957	2,168	22.0	.492	
1958	1,119	9.00	.205	
1959	1,215	11.9	.280	
1960	987.0	9.90	.267	
1961	1,134	15.0	.296	
1962	539.5	3.02	.117	
1963	640.7	6.50	.183	
1964	977.1	6.04	.180	

Average 1,012 (1,398 cfs)

Note:

1948-51 record from station below reservoir. Storage began February 24, 1952.

Maximum discharge 35,700 cfs, March 17, 1957. Minimum discharge 44 cfs, September 7-8, 1948. Kajakai Reservoir inflow (Dehraout + Tirin)

Water	1,000	1,000 cfs		
Year	Acre-Feet	Max. daily	Min. daily	
1948	3,885	29.2	1.10	
1949	5,193	45.0	1.81	
1950	5,256	36.2	1.98	
1951	6,171	47.5	2.00	
1952	4,827	28.6	1.81	
1953	4,156	23.7	1.75	
1954	5,523	33.9	2.04	
1955	3.796	40.0	1.62	
1956	5,952	48.6	2.00	
1957	9,059	70.8	2.37	
1958	5,549	29.6	2.58	
1959	5,003	27.2	2.37	
1960	4,735	33.7	2.02	
1961	5,135	39.2	2.33	
1962	3,175	17.8	1.70	
1963	3,301	23.5	1.62	
1964	5,155	36.2	1.90	

Average 5,051 (6,977 cfs)

Note:

1948-52 record from station below reservoir Storage began January 28, 1953.

Maximum discharge unknown. Occurred May 3, 1957.

Minimum discharge 1,100 cfs, October 1, 1947 (Start of record - may have been lower prior to that date.)