



MSTV

MODELING AND SIMULATION, TESTING AND VALIDATION



SIMULATION OF VARIOUS ON-BOARD VEHICLE POWER GENERATION ARCHITECTURES FOR STATIONARY APPLICATIONS

Matthew Young

Center for Advanced Vehicular Systems

Mississippi State University

Report Documentation Page

Form Approved
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE 11 AUG 2010	2. REPORT TYPE N/A	3. DATES COVERED -			
4. TITLE AND SUBTITLE simulation of Various On-Board Vehicle Power Generation Architectures for Stationary Applications		5a. CONTRACT NUMBER W56 HZV-08-C-0236 (SimBRS)			
		5b. GRANT NUMBER			
		5c. PROGRAM ELEMENT NUMBER			
6. AUTHOR(S) Matthew Young		5d. PROJECT NUMBER			
		5e. TASK NUMBER			
		5f. WORK UNIT NUMBER			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Center for Advanced Vehicular Systems Mississippi State University		8. PERFORMING ORGANIZATION REPORT NUMBER			
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) US Army RDECOM-TARDEC 6501 E 11 Mile Rd Warren, MI 48397-5000, USA		10. SPONSOR/MONITOR'S ACRONYM(S) TACOM/TARDEC			
		11. SPONSOR/MONITOR'S REPORT NUMBER(S) 21101			
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES Presented at NDIAs Ground Vehicle Systems Engineering and Technology Symposium (GVSETS), 17 22 August 2009, Troy, Michigan, USA, The original document contains color images.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT SAR	18. NUMBER OF PAGES 14	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Outline

MSTV

MODELING AND SIMULATION, TESTING AND VALIDATION



- Motivation
- Selected architectures for simulation
- Simulation environment overview
- Simulation model constraints
- Simulation results
 - Required engine power
 - System efficiency
 - Estimated fuel consumption
- Vehicle demonstration of most efficient architecture



- Increased “in-vehicle” electrical presence
 - C4ISR systems
 - Anti-IED systems
 - Climate control systems
- Higher exportable power demand
 - Mobile command stations
 - Radar systems
- Reduction of audible and heat signature using higher efficiency generation systems
- Exploration of power generation systems for greater than 10 kW electrical output at idle through simulation

Selected Architectures for Simulation

MSTV

MODELING AND SIMULATION, TESTING AND VALIDATION




- Observed three possible architectures
 - Architecture 1: Belt-driven dual alternator system
 - Architecture 2: Belt-driven and PTO-driven alternator system
 - Architecture 3: Belt-driven alternator and PTO-driven Permanent Magnet-Brushless DC (PMDC) Generator
- Selection criteria
 - Serviceability
 - Ease of implementation/integration
 - Utilization of COTS components

Selected Architectures


MSTV

MODELING AND SIMULATION, TESTING AND VALIDATION




- All architectures use 520 A Niehoff alternator
- Use standard alternator to engine pulley ratio of 3:1 with 95% power transfer efficiency
- PTO/Gearbox assembly uses a pulley ratio of 2.54:1 from alternator to engine with an efficiency of 97%

Architecture 1



Architecture 2




UNCLASSIFIED: Dist. A. Approved for public release


Selected Architectures

MSTV

MODELING AND SIMULATION, TESTING AND VALIDATION



Architecture 3



- Architecture 3 uses a belt-driven 520 A Niehoff alternator and 75 kW UQM PMDC motor/generator
- Alternator connected using a 3:1 pulley ratio
- PMDC connected using a combined PTO/Gearbox ratio of 2.15:1 with efficiency of 97%


Simulation Environment

MSTV

MODELING AND SIMULATION, TESTING AND VALIDATION



- Created in MATLAB/Simulink environment
- Environment uses a forward-looking approach
 - Driver requests are passed from Powertrain Controller to the Powertrain Model
 - Powertrain sensors are used to adjust the driver request to match the desired speed request
- Power generation components are controlled using torque command sent from powertrain control subsystem



UNCLASSIFIED: Dist. A. Approved for public release

Simulation Model Constraints

MSTV


MODELING AND SIMULATION, TESTING AND VALIDATION




- Radar load profile used. Requires power levels both above and below the rated output for any single component [1]
- Power train controller limits the minimum power of the alternator to 1 kW to ensure proper charging of battery
- Simulation utilizes a battery SOC target of 80% and an initial SOC of 75%
- SOC mismatch causes the power train controller to provide additional power to charge 28 V battery to desired SOC

[1] Marshall Molen, *R&D Final Report for Advanced Power Distribution Prototyping, Evaluation, and Simulation for the U.S. Army Space and Missile Defense Command Contract #DASG60-00-C-0074*, May 2009.

Electrical Load Profile



28V Battery SOC and Charging Current



UNCLASSIFIED: Dist. A. Approved for public release



Simulation Results

MSTV

MODELING AND SIMULATION, TESTING AND VALIDATION



- Simulation calculates system efficiency defined as ratio of electrical load power to engine output
- Model limits the PMDC output power based on maximum rating of DC/DC converter



UNCLASSIFIED: Dist. A. Approved for public release

Simulation Results


MSTV

MODELING AND SIMULATION, TESTING AND VALIDATION



- Fuel consumption calculated based on the required engine energy output
- Engine efficiency was assumed to be constant at 25%
- Used JP8 energy density to calculate estimated fuel consumption:

Estimated Fuel Consumption



$$\text{Fuel Used} = \frac{\text{Engine Required Energy [BTU]} * \frac{1}{0.25}}{\text{JP8 Energy Density} \left[\frac{\text{BTU}}{\text{gal}} \right]}$$


Simulation Results

MSTV


MODELING AND SIMULATION, TESTING AND VALIDATION



- Architecture 3 was used in a second simulation which employed an additional 10 kW AC load connected to PMDC (better utilization of available load capacity)
- Simulation computed a higher system operating efficiency while under heavier loads
- Adding 10 kW load possible only with Architecture 3



Architecture 3 System Efficiency and Fuel Used



UNCLASSIFIED: Dist. A. Approved for public release

Results Summary

MSTV

MODELING AND SIMULATION, TESTING AND VALIDATION



Architecture	Fuel Consumption	System Efficiency
1 (Dual alternators)	1.14 gals	50.2 %
2 (Belt-driven and PTO-driven alternators)	1.12 gals	53.7 %
3 (Belt-driven alternator and PTO-driven PMDC)	1.09 gals	56.6 %
3+(Belt-driven alternator and PTO-driven PMDC) with additional 10 kW AC load	2.69 gals	67.1 %

UNCLASSIFIED: Dist. A. Approved for public release



- Architecture 3 was selected for a feasibility test on a Mine Resistant Ambush Protected (MRAP)
- Tests were conducted to observe potential issues driving the PMDC via a transmission PTO port
- Architecture was tested from 100 A to 600 A in 50-A steps
- Transit points were selected at 250 A and 400 A to observe system response to load transients
- Excellent performance was observed during “in-vehicle” testing





MSTV

MODELING AND SIMULATION, TESTING AND VALIDATION



Questions

UNCLASSIFIED: Dist. A. Approved for public release