


Testing for Stray Current Corrosion in Earth Covered Magazines with EOP

O. S. Marshall

US Army Engineer Research and
Development Center, Champaign, IL

J. E. Bennett

J. E. Bennett Consultants, Inc.
Chardon, OH



US Army Corps of Engineers
BUILDING STRONG®

Report Documentation Page

Form Approved
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE FEB 2010		2. REPORT TYPE		3. DATES COVERED 00-00-2010 to 00-00-2010	
4. TITLE AND SUBTITLE Testing for Stray Current Corrosion in Earth Covered Magazines with EOP				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Engineer Research and Development Center (ERDC), Construction Engineering Research Laboratory (CERL), PO Box 9005, Champaign, IL, 61822				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES 2010 U.S. Army Corrosion Summit, Huntsville, AL, 9-11 Feb					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			


Outline

- EOP Technology
- Stray Current
- Stray Current Testing
- Test Findings
- Recommended Test Procedures
- Conclusion



Background

- Underground Structures inherently have moisture intrusion problems
- Large volumes of water seep through the concrete
 - ▶ Walls, floors, and ceilings
 - Rising damp
 - Wicking
 - High external head
 - ▶ Joints and cracks




Background


- The water intrusion causes corrosion
 - ▶ Structural steel
 - ▶ Stored assets making many unusable
 - ▶ Mold and poor air quality




Typical EOP Installation




When activated EOP sets up an electric field that creates an osmotic force within the concrete pores that counters head forces




Typical EOP Pulse




EOP Pulse Effect




DC current has potential for causing corrosion of metallic objects between anode and cathode




Stray Current



Cathodic Reaction



Anodic Reaction



(To remote cathode)




EOP Technology Demonstration





BUILDING STRONG®

EOP Technology Demonstration



EOP Technology Demonstration





EOP Technology Demonstration




BUILDING STRONG®

Field Tests and Demonstrations in ECMs


Spark potential of steel arch	None
Spark potential of pallets on floor	None
Spark potential between pallets and arch	None
Hydrogen generation	None
Affects on LPS 	None w/ majority of current to rebar
Water intrusion	Stopped
Electromagnetic radiation	None detected
RF emission	None detected



Typical ECM LPS Layout






Stray Current Test Setup



BUILDING STRONG®

Stray Current Test Setup



Estimated Current Requirements to Steel

X (cm)	Concrete Resistivity, Ω -cm			
	10,000	15,000	20,000	25,000
2.	0.00 mA (0%)	0.00 mA (0%)	0.00 mA (0%)	0.03 mA (2.2%)
4.	0.00 mA (0%)	0.06 mA (4.2%)	0.12 mA (8.0%)	0.18 mA (12.1%)
6.	0.06 mA (4.2%)	0.16 mA (10.3%)	0.24 mA (16.0%)	0.33 mA (21.7%)
8.	0.12 mA (8.0%)	0.24 mA (16.0%)	0.36 mA (23.8%)	0.47 mA (31.6%)


Assumptions:

Current density of 16.15 mA/m²

Steel surface area of 0.5 24 m²/m²



Field Tests




Recommended Field Test Procedure

- Locate “most cathodic” and “most anodic” sites
- Install test probes at “most cathodic” and “most anodic” sites
- Take data with the EOP system off and disconnected
- Take data with the EOP system energized
 - ▶ Selected percentage from 0-100% of the cathodic current diverted to the reinforcing steel
- Plot current and potential data
- Determine potential for Stray Current Corrosion



Plot of Current Measurements



Field Measurements



RF Emission Testing



EM Emission Testing



Conclusions

- A rebar probe placed above the location of the grounding loops shifted in the anodic direction (corrosive) when attached to the EOP system negative. The anodic shift decreased in magnitude as more current was directed to the reinforcing steel.
- Corrosion current was measured to the rebar probe placed above the location of the grounding loops. The corrosion current decreased in magnitude as more current was directed to the reinforcing steel.



Conclusions

- The corrosive potential and corrosion current recorded when a high percentage of current was directed to the reinforcing steel was not a function of EOP system operation. EOP operated in this way will not cause significant stray current corrosion of elements embedded in the soil.
- With a large percentage of cathodic current directed to the reinforcing steel EOP operation will not result in stray current corrosion of the LPS or structural steel of the magazines.



Discussions

