


Performance of FRP Connectors for Seismic Rehab of Michie Stadium

Orange Marshall
USACE ERDC-CERL
Orange.S.Marshall@usace.army.mil



US Army Corps of Engineers
BUILDING STRONG®



Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE FEB 2010		2. REPORT TYPE		3. DATES COVERED 00-00-2010 to 00-00-2010	
4. TITLE AND SUBTITLE Performance of FRP Connectors for Seismic Rehab of Michie Stadium				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Engineer Research and Development Center (ERDC), Construction Engineering Research Laboratory (CERL), PO Box 9005, Champaign, IL, 61822				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES 2010 U.S. Army Corrosion Summit, Huntsville, AL, 9-11 Feb					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 24	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Outline

- Technical Objective
- Background
- Acoustic Guide Wave Technology
- Performance Evaluation
- Results
- Conclusions



Technical Objective

The objective of this project order was to inspect two hundred and fifty (250) FRP composites patches used for service life extension of Michie Stadium at the USAMA, West Point, NY, using Acoustic Guide Wave technology



West Side Bleachers



BUILDING STRONG®

Background



BUILDING STRONG®

Background




BUILDING STRONG®

Background




BUILDING STRONG®

Background



ISOMETRIC DETAIL
Not to Scale



TYPICAL SECTION
Not to Scale

Background



BUILDING STRONG®

Acoustic Guide Wave Technology

- Acousto-Ultrasonic (AU) technology developed Physical Acoustic Corporation (PAC) as an inspection technique for nondestructive evaluation of structures such as FRP composite and graphite epoxy



BUILDING STRONG®

Acoustic Guide Wave Technology


- System based on AU technology
- acoustic waveform bursts (100-500 kHz) directed into the material being inspected
- AU receiver recognizes these waveforms and AGW device processes the results and displays them as A-Scan waveforms and C-Scan image maps.
 - ▶ The acoustic signal features include gated Amplitude and Time of Flight parameters,
 - change when the acoustic bursts travel through the material and encounter defects and discontinuities, cracks, material property changes, delamination and debonding.

▶ Defects can be identified from the C-Scan images.




BUILDING STRONG®


Acoustic Guide Wave Technology



Example A-Scan



Example C-Scan




Performance Evaluation

- Tasks:
 - ▶ Pre Work visit for selection of two hundred and fifty (250) patches
 - ▶ Inspect the preselected patches
 - ▶ Document photographically all the inspected patches
 - ▶ Perform analysis and submit the results





Performance Evaluation




BUILDING STRONG®

Performance Evaluation A-Scan




Performance Evaluation C-Scan


Delamination ↓
↑ Good



Performance Evaluation C-Scan




Results




BUILDING STRONG®

Results



BUILDING STRONG®

Results



BUILDING STRONG®

Results



BUILDING STRONG®

Conclusions

- The results were obtained in the form of C-scan images in which the color pixel of the different areas in the image is related to the amplitude of the acoustic signal reflected from the different areas of the panel.
 - ▶ In this case, the green areas are associated with signals reflected from good areas of the FRP panel, whereas the blue areas of the C-scan are associated with delaminations in the panel.
- Section-6 on lower tier and section-14 on upper tier should be investigated for bond failure.



Conclusions

- The AGW system with rolling sensor probe has been successfully used in the quality inspection of thick composite material on concrete structure rehabilitation with fiber-reinforced concrete polymer.
- The system also has many distinctive features that make it ideally used in the field and in applications where other traditional NDT methods are not practical or successful.



Discussions



BUILDING STRONG®