

# Implementation of Structural Health Monitoring for the USMC CH-53E

Jason Thomas  
Structures Division NAVAIR, Patuxent River, MD

Christopher Neubert  
Ground Station IPT Lead, NAVAIR, Lakehurst, NJ

Mark D. Little  
Condition Based Maintenance & Mechanical Diagnostics Development (4.4.2.4) Lead  
In Service Support Center, Cherry Point, NC

Brian L. Fuller  
Marine and Aviation Division, NSWC Carderock Division, West Bethesda, MD

## Abstract

There is great concern in the U. S. Navy/Marine Corps aviation community regarding out-year operating costs. Simply put, there may not be sufficient funds for the services to execute their mission goals. Studies and initiatives have been undertaken to reduce Operational and Support Costs, with a keen interest in Condition Based Maintenance (CBM) and a re-structuring of the logistics infrastructure. A key artifact of CBM, Structural Health and Usage Monitoring (SHUM), is vital to the Chief of Naval Operations (CNO) vision of “the right readiness, at the right cost.”

The Structural Appraisal of Fatigue Effects (SAFE) program at the Naval Air Systems Command (NAVAIR) has been providing structural tracking information to maintain the structural integrity of US Navy aircraft for over 30 years. The SAFE program uses parametric data from onboard flight recorders to accrue component life consumption via actual flight data vice an assumed usage spectrum. The objective is to determine if an aircraft is flown more or less severely than designed, and to provide benefit in the form of either safety or economy. Although most of the beneficiaries from the SAFE program have been fixed wing aircraft, NAVAIR has been working to implement the first rotorcraft fleet in SAFE, the Integrated Mechanical Diagnostics System (IMDS) equipped CH-53E helicopter. Seven CH-53E components selected upon criticality, perceived benefit, and expense, were evaluated via SAFE.

There are two ways to execute SHUM. The first is to implement a CH-53E SAFE program to provide a Fatigue Life Expended (FLE) metric based upon component specific aircraft usage. The second is to update the aircraft usage spectrum based upon fleet-wide aircraft usage. The CH-53E program has funded both of these paths to maximize benefit. This paper discusses these paths and respective tasks including regime recognition, event counting, damage rate and mapping, and the institution of a novel gross weight prediction tool developed by Naval Surface Warfare Center (NSWC) Carderock. Mitigation strategies for obstacles such as loss-of-data and component configuration management are highlighted in this paper.

## Report Documentation Page

Form Approved  
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE

**MAY 2010**

2. REPORT TYPE

3. DATES COVERED

**00-00-2010 to 00-00-2010**

4. TITLE AND SUBTITLE

**Implementation of Structural Health Monitoring for the USMC CH-53E**

5a. CONTRACT NUMBER

5b. GRANT NUMBER

5c. PROGRAM ELEMENT NUMBER

6. AUTHOR(S)

5d. PROJECT NUMBER

5e. TASK NUMBER

5f. WORK UNIT NUMBER

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

**Naval Air Systems Command (NAVAIR), Structures Division, Patuxent River, MD, 20670**

8. PERFORMING ORGANIZATION REPORT NUMBER

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

10. SPONSOR/MONITOR'S ACRONYM(S)

11. SPONSOR/MONITOR'S REPORT NUMBER(S)

12. DISTRIBUTION/AVAILABILITY STATEMENT

**Approved for public release; distribution unlimited**

13. SUPPLEMENTARY NOTES

14. ABSTRACT

**There is great concern in the U. S. Navy/Marine Corps aviation community regarding out-year operating costs. Simply put, there may not be sufficient funds for the services to execute their mission goals. Studies and initiatives have been undertaken to reduce Operational and Support Costs, with a keen interest in Condition Based Maintenance (CBM) and a re-structuring of the logistics infrastructure. A key artifact of CBM, Structural Health and Usage Monitoring (SHUM), is vital to the Chief of Naval Operations (CNO) vision of "the right readiness, at the right cost." The Structural Appraisal of Fatigue Effects (SAFE) program at the Naval Air Systems Command (NAVAIR) has been providing structural tracking information to maintain the structural integrity of US Navy aircraft for over 30 years. The SAFE program uses parametric data from onboard flight recorders to accrue component life consumption via actual flight data vice an assumed usage spectrum. The objective is to determine if an aircraft is flown more or less severely than designed, and to provide benefit in the form of either safety or economy. Although most of the beneficiaries from the SAFE program have been fixed wing aircraft, NAVAIR has been working to implement the first rotorcraft fleet in SAFE, the Integrated Mechanical Diagnostics System (IMDS) equipped CH-53E helicopter. Seven CH-53E components selected upon criticality, perceived benefit, and expense, were evaluated via SAFE. There are two ways to execute SHUM. The first is to implement a CH-53E SAFE program to provide a Fatigue Life Expended (FLE) metric based upon component specific aircraft usage. The second is to update the aircraft usage spectrum based upon fleet-wide aircraft usage. The CH-53E program has funded both of these paths to maximize benefit. This paper discusses these paths and respective tasks including regime recognition, event counting, damage rate and mapping, and the institution of a novel gross weight prediction tool developed by Naval Surface Warfare Center (NSWC) Carderock. Mitigation strategies for obstacles such as loss-of-data and component configuration management are highlighted in this paper.**

15. SUBJECT TERMS

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>Same as Report (SAR)</b>	18. NUMBER OF PAGES <b>9</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			

**Standard Form 298 (Rev. 8-98)**  
Prescribed by ANSI Std Z39-18

## Introduction

There is great concern in the U.S. Navy/Marine Corps aviation community regarding out-year operating costs. Maintenance activities comprise a major portion of total ownership costs for Navy weapon systems, with a majority of those being attributed to direct maintenance costs (figure 1, Ref 1).




Figure 1: Maintenance Costs for the CH-53E

Premature and unnecessary maintenance are inflating maintenance costs and therefore overall ownership cost. The CH-53E costs more per flight hour than a number of US Navy/Marine Corps aircraft programs (figure 2).




Figure 2: FY04 Program Costs per Flight Hour, by T/M/S

Studies and initiatives have been undertaken to reduce Operational and Support (O&S) Costs, with a keen interest in Condition-Based Maintenance (CBM) and a re-structuring of the logistics infrastructure. CBM utilizes Health and Usage Monitoring Systems (HUMS) and includes maintenance processes and capabilities derived from real-time or near-real-time assessments obtained from embedded sensors and/or external tests and measurements using either portable equipment or actual inspection. The

objective of CBM is to perform maintenance based upon the evidence of need while ensuring safety, reliability, availability, and reduced total ownership cost [Ref. 2 and Ref. 3]. A key artifact of CBM, Structural Health and Usage Monitoring (SHUM) is vital to the Chief of Naval Operations (CNO) vision of, “the right combat readiness...for the right cost” [Ref. 4].

Naval Air Systems Command’s (NAVAIR) answer to SHUM is the Structural Appraisal of Fatigue Effects (SAFE) program. The SAFE program entails using flight data recorders to identify the severity to which the aircraft (and its components) is being utilized in comparison to how it was intended and designed. The recorded usage data is then used to monitor various fatigue critical components and/or locations on the aircraft. The program can then determine how to perform maintenance based on the specific aircraft need and not based on an assumed designed usage.

## Background

In 1997, a team led by the program offices of the H-53 and Executive Helicopters (PMA-261) and the SH-60 Multi-mission Helicopters (PMA-299) were selected to implement the Goodrich Corporation’s Integrated Mechanical Diagnostic – Health Usage and Monitoring System (IMD-HUMS) on the SH-60B and CH-53E aircraft under the Office of Secretary of Defense’s (OSD) Commercial Operations and Support Savings Initiative (COSSI). The system evolved under the Joint Dual-Use Program Office’s (JDUPO) COSSI and is now referred to as the Integrated Mechanical Diagnostics System (IMDS) [Ref. 5].

The first CH-53E was equipped with IMDS in 1998 and was soon followed by three additional aircraft in 1999. These initial installations served as data sources for accelerated system characterization and service suitability evaluations for the remaining fleet aircraft. In 2004 the IMDS successfully completed Operational Test and Evaluation (OTE) which allowed for the full rate procurement and production of the system on the CH-53E [Ref. 6].

The NAVAIR Aircraft Structural Life Surveillance (ASLS) branch, AIR 4.3.3.4, has tracked the structural life on Navy/Marine Corps fixed wing aircraft via the SAFE program since the 1970s. In 2006, discussion between the NAVAIR Structures Division (AIR 4.3.3), PMA-261 and PMA-275 focused on implementing SAFE on their respective rotary wing aircraft, the CH-53E and MV-22B, to meet the emerging CBM initiatives.

This would mark the first time SAFE was performed for rotary winged aircraft. Implementation of SAFE poses several challenges to any aircraft program; the need for flight data, an accurate gross weight association to better increment damage and a gapfilling methodology to account for missing data. In addition to these obstacles, SAFE implementation for a rotary wing fleet introduces additional obstacles; the need to identify the serialized dynamic component history and an even more robust gapfilling methodology to account for variations in load and the fatigue contribution due to ground rotor turn time.

This paper will address the CH-53E SAFE effort, the plans to pursue its CBM benefits, and the technical challenges experienced in the process.

## IMDS

The IMDS consists of an airborne system and a ground based system, both implemented with an open architecture approach. The data used by the system is obtained primarily from state sensors that are part of the basic aircraft (including buses), and specially mounted accelerometers and shaft position sensors [Ref. 5]. The major functionalities incorporated into IMDS are Health Monitoring, Usage Monitoring, and the Maintainer Interface (figure 3).

For the purpose of this paper, the primary components providing data for SAFE CBM related activities are the Usage Monitoring and the Maintainer Interface.



FIGURE 3: Subcomponent Functions to IMDS

## Airborne System

The airborne system consists of the original manufacture helicopter fitted with additional hardware and instrumentation [Ref. 5 and Ref. 7]. During ground and flight operations, the Main Processor Unit (MPU) acquires data at sampling rates ranging from 10 to 40 hertz, storing most data as a 1-second averaged signal. The airborne system can be configured to store parametric data at a higher rate if an exceedance or event occurs. These high-rate data are referred to as a burst data set. In the case of SHUM, some parametric data are stored at a higher rate for regime recognition [Ref. 8]. A sample list of parameters required at higher than 1 hertz for SHUM can be found in table 1 [Ref. 9].

Parameter	Data Rate (Hz)
Vertical Acceleration	8
Pilot Stick Positions (and/or swashplate positions)	8
Roll Rate	8
Rate of Climb	6
Engine Torque	6
Roll Attitude	4
Pitch Rate	4
Yaw Rate	4
Rotor Speed	2
Pitch Attitude	2
Airspeed	2

Table 1: Minimum Data Rates for High Rate Structural Monitoring Parameters.

The data is written and transferred to the Ground Station (GS) via a Personal Computer Memory Card International Association (PCMCIA) card.

## Ground Station

The IMDS incorporates an Information Technology infrastructure made up of a series of networked GS devices providing application user interface tools that support pilot and maintainer activities. For the purposes of SAFE, the key task of the GS is the storage, linking, and archiving of IMDS aircraft data. The maintainer is responsible for downloading the Raw Data Files (RDFs) after each flight, where the aircraft files are stored at the local level to support the IMDS application. The files are copied nightly via secure socket encryption to the Navy's fleet archive at Naval Air Station

(NAS) Patuxent River (PAX) where they are distributed to customer servers such as SAFE.

## SHUM Development

There are two ways to execute SHUM. The first is to implement a CH-53E SAFE program to provide a Fatigue Life Expended (FLE) metric based upon specific aircraft usage exhibited on each serialized dynamic component or airframe location. The second is to update the aircraft usage spectrum based upon fleet-wide aircraft usage and then adjust component retirement times. The CH-53E program office has funded both of these paths to maximize benefit. The following discusses the processes needed to achieve these goals.

## The SAFE System

The SAFE system requires the following fleet data:

- IMDS flight data
- Pilot recorded flight records
- Aircraft dynamic component configuration records (figure 4).

These data are processed to perform:

- Regime Recognition
- Serialized Component Damage

The output of the SAFE system is the SAFE report, which in part contains a component life expended summary of all serialized life limited fleet component.




Figure 4: The SAFE Process

## IMDS Aircraft Data

Once the fleet maintainers download the data to the ground based system, the data file is then sent to the local squadron archive automatically. The data file is then sent to the IMDS fleet archive and subsequently to the SAFE server on a nightly basis. This process is run via a batch file. The batch file checks the IMDS RDF filename to determine if it is a new file or not. Embedded in the filename is the aircraft tail number, aircraft type, the download date and download time. These artifacts are important, as they are used to match up IMDS data with aircraft flight and configuration records. Once a file is retrieved and stored, the data are kept indefinitely in the event reprocessing is ever required.

## Pilot Flight Records

The squadrons are required to provide flight records for every flight. After each flight, the pilot enters the flight date, flight duration, and other information into the flight record tracking application. These data are referred to as Maintenance, Material, and Management (3M) records. The 3M records are compared to submitted RDFs to determine if any flight data files are missing.

In the event that an RDF does not have an accompanying 3M record, or a 3M record does not have a matched RDF file, the squadron is contacted to avoid data loss. Until the discrepancy is rectified, the data is deemed missing. All missing data needs to be gapfilled to account for fatigue damage incurred on flights in which there is no IMDS data. Gapfill methodology will be discussed later in this paper.

## Aircraft Component Configuration

The last piece of data provided by the squadrons is the dynamic component configuration data. These records reside in the Navy's configuration management application, the Optimized Organizational Maintenance Activity Naval Aviation Logistics Command Management Information System (OOMA-NALCOMIS) and are compiled from Assembly Service Record (ASR) cards, Equipment History Record (EHR) cards and Service Removal Component (SRC) cards. These cards document when a particular serial number of a specific part number is removed from one aircraft and placed on another aircraft, moved to storage,

repaired, overhauled, and/or retired. The fleet maintainer selects preloaded part numbers in OOMA-NALCOMIS and moves them between aircraft via Work Unit Codes (WUCs).

These configuration data are entered by all squadrons and then replicated to the OOMA-NALCOMIS top tier server. These configuration data are pulled by the SAFE process nightly and quality controlled with any available data that may have been previously received. These records are then compiled to identify which serial number was installed on which aircraft for what time period. The SAFE process can then identify which RDF data to assign to which component.

It is important to note that the SAFE quality control process has uncovered occasions where the incorrect serial numbers or aircraft tail numbers were assigned to a component. The OOMA-NALCOMIS record sub-system does not have an efficient process to notify the squadrons of discrepant records. Some discrepancies identified by the SAFE quality control process are: incorrect amount of expected parts installed on one aircraft, same serialized component on two different aircraft, and time since new (TSN) data is reset to zero when a component is reinstalled on aircraft. Compiling complete and accurate component history data remains the most difficult task for tracking fatigue life of serialized components in SAFE.

## SAFE Processing

With the above data at the SAFE server, processing of the three types of data is performed with the end product being damage assessments of every life limited, serialized component.

## Regime Recognition

Regime Recognition (RR) is a process in which known flight maneuvers are identified from parametric flight data. These identified flight maneuvers (or regimes) have fatigue damage values associated with them depending on the parametric values. The RR code processes through 6 stages as it identifies the 356 known flight regimes of the CH-53E and categorizes them into 78 fatigue damaging regimes.

The first stage addresses the fact that most parameters used for structural tracking are recorded at different rates; some as low as 1 Hz, while others are recorded at up to 10 Hz. Whether due to IMDS limitations or data storage concerns, some data are recorded at less than optimum frequencies for SHUM; however the minimum frequencies are met. Data that is recorded at less than 10 Hz is

interpolated between the maximum and minimum values in that range to create parametric records at 10 Hz. Should an event where a data spike or dropout occur, the data is interpolated to avoid gapfilling. Most occurrences of this are no more than 2 seconds and within the limit for interpolation.

The second stage in the RR process is to lump like regimes that occur sequentially together.

The third stage in RR is the consolidation logic. This portion of the code looks at the recently lumped regimes and determines how long the maneuver lasted. This allows compression and better damage mapping so that instead of 20 records stating the same regime, there is one 2 second record with the flight regime. Another benefit of the consolidation code is when parametric data of certain maneuvers border the threshold limits. Since it is possible that the RR code could identify different transient regimes for one maneuver based on where the parametric thresholds are set, the consolidation code has logic built in that identifies the actual maneuver occurring and lumps the like data together. For instance, this would cause a maneuver sequence to be counted as a 30 degree angle of bank turn for 3 seconds, even if the parametric data causes the RR code to identify it as a 30 degree turn followed by a 1.1 g pullup followed by a second 30 degree angle of bank turn. This is also a benefit where individual pilot technique may influence the data.

The fourth stage in the RR code is to identify all control reversals, their start time and duration. A control reversal is when a pilot inputs control completely in one direction, then fully reverses the input to the opposite direction. The aircraft weight is also used here to determine the damage increment incurred by the control reversals. The control reversal damage increment is only counted once and is not double counted when the RR process is complete.

The fifth stage is to identify all other damaging maneuvers that are counted based on the number of occurrences and not duration. Examples of such maneuvers are Ground-Air-Ground (GAG) cycles, hook loads, and torque cycles. The final stage for the RR code is the log file. The log file provides basic results on the quality assurance program. The log file records takeoffs, landings, rotor start and stop conditions, and the cause for flight rejection, if applicable.

The RR code was validated against flight test data, known as the 'HUMS flights'. The HUMS flights were a number of flights in which pilots flew to a known sequence of regimes at specific times. The RR code was then validated by

producing the expected results from the HUMS flights.

Once the RDF file is processed through the RR code, an output file is generated and a regime identifier is assigned to all regimes located in the file. This output file summarizes all the regimes that occurred in the RDF, as well as the time and duration of the regime.

## Gross Weight Estimation

As depicted in figure 5, component damage rates are impacted by aircraft gross weight (GW) and altitude. Without accurate gross weight estimation, the most conservative damage assumption must be utilized. In order to accurately monitor gross weight, IMDS requires crew input before a flight. This is deemed an impractical increase to pilot workload as well as a source of potential inaccuracy.




Figure 5: Gross Weight vs. Altitude

This initiated the need for a CH-53E specific Gross Weight Virtual Sensor. The program funded Naval Surface Warfare Center (NSWC) Carderock to develop a novel GW Virtual Sensor, similar to the one developed for the SH-60B [Ref. 10], based on recorded parametric HUMS data. In order to accomplish this task, NSWC Carderock gathered flight control system data, weight and balance reports, Naval Aviation Training and Operating Procedures Standardization (NATOPS), and OEM reports. The GW Virtual Sensor is a second generation sensor developed to predict aircraft gross weight at take-off once the aircraft has climbed to 30 ft above ground level (AGL) and has a working range of 43,000 lbs to 54,500 lbs. Additional test flights are needed to expand the weight range above 54,500 lbs. The main advantage of this sensor over first generation sensors is that it is no longer restricted to operate during steady hover or steady level flight. Since

hovers are infrequent with no way to measure airspeed and given that drag is difficult to account for in the higher speed regimes, this improvement is significant. In contrast, the new virtual sensor utilizes an energy approach to determine the gross weight at take-off by essentially calculating the integral of the engine torque and equating this quantity to the energy necessary to lift a given weight (in this case, the aircraft gross weight) to a prescribed altitude (in this case, 30 ft) in a finite amount of time that is related to both the energy input into the system as well as the weight of the body. Other than time and torque, the other inputs to the model are pitch attitude and density altitude (to account for air temperature and air pressure). The sensor currently operates during post flight analysis which allows the reconstruction of weight throughout the flight. Sample virtual sensor performance is shown with each take-off represented with a circle (figure 6).




Figure 6: Predicted vs. Actual Gross Weight

During the 40 flights selected for model development, weight was estimated in 38 with an average of 10 estimations per flight. The accuracy of the model was calculated using a five fold cross-validation approach, one of the latest statistical techniques for wide data. This technique estimates the expected error for data not previously seen by the sensor. This technique requires the development of five independent neural network models (the weight estimation is the average of the estimation from each of these models). Based on this analysis, the five model average has a root mean square (RMS) error of 831 lbs with a maximum over-estimation of 1,900 lbs and a maximum under-estimation of 2,229 lbs. The GW Virtual Sensor was also validated against weight and balance sheets provided by PMA-261. To account for the variation in estimation, the most conservative weight will be used. Once the RR process is



complete and reversals identified, and the gross weight is known, the RDF can then be mapped to the component damage table to calculate fatigue damage.

## Component Damage Table Generation

The component damage tables are a key component for SHUM. The tables are from the Original Equipment Manufacturer (OEM), in this case, Sikorsky Aircraft, and represent the amount of fatigue damage each component exhibits for a particular amount of time spent in a flight regime. The table also contains damage information for those maneuvers that are not time dependent, but rather the number of occurrences an event is recorded.

Once an RDF has been processed through the RR code and a gross weight identified for each regime, the results are then mapped to the damage tables for all experienced regimes. The damages from a flight of regimes are then summed to provide a unit of damage on the components for that flight. With no additional reliability adjustments, an FLE of 1.0 corresponds to end of life for the component. This process is carried out for all flight data to determine an FLE for all life limited dynamic components.

## Gapfill Methodology

Gapfill is a process in which statistical data are used to fill in missing or corrupt data. Data that are gapfilled are assumed to be more severe than average operations to account for the unknowns of the flight. Since the weight and regimes are unknown, worst case damage rates are used. Until the new fleet usage spectrum is developed, gapfill rates will be based on the design spectrum at the 95<sup>th</sup> percentile for worst case. The updated usage spectrum will be discussed later in this paper.

Gapfill is also used when the historical component configuration data are incomplete or inaccurate. Install and removal records are only sought for components from when IMDS was installed. The starting FLE will be based on the number of landings and flight hours to that point. Should a serialized component have missing install or removal records, the SAFE process assumes the worst case for that time and cannot use the IMDS data to map a fatigue damage.

Due to the six-nines reliability requirement (probability of failure of a dynamic component at the retirement life does not exceed one in a million,

i.e. a reliability level of 0.999999), the gapfill methodology will need to be revisited when the new usage spectrum is released. One thought is to use the 99<sup>th</sup> percentile instead of 95<sup>th</sup> percentile to account for the perceived reduction in reliability. Many parties in industry, government and academia are evaluating different methods to address this notion [Ref. 11 and Ref. 12]. For example, some proposals are to adjust the S/N curve or apply reliability factors.

## Components to be Tracked

The CH-53E has thirty-eight components that are identified to be prime life limited components, or components with a fatigue life of 10,000 flight hours or less. Once the SAFE process was developed, the first items to be tracked needed to be determined from the existing thirty-eight. Seven of the thirty-eight life limited components were selected to be inducted into SAFE first, based on criticality, perceived benefit, and expense. The components selected were: main rotor sleeve assembly, main rotor hub lower plate assembly, main rotor hub upper plate assembly, main rotor blade extender, main gear box housing, main gearbox shaft, and the main rotor spindle/sleeve assembly. The remaining thirty-one life limited components will be implemented into SAFE based on available funding and estimated return on investment.

## Ground Station Modifications

A challenge for current SAFE programs is the means to routinely produce real-time FLE updates to the squadron level. Delayed delivery of expended life computation to squadron maintainers can be cumbersome and requires backfilling due to the time lag required to execute the quarterly report. The fleet user downloads the SAFE report from the ASLS website on a quarterly basis. Updating the maintainers' ground stations with estimated FLE between published SAFE reports remains a challenge. During this time lag, the squadron must accrue damage to components at their most conservative (costly) rate. This rate is the basis for the Periodic Maintenance Information Card (PMIC) and is derived from the design spectrum. Fleet maintainers must plan their maintenance activities to correspond to these rates. The CH-53E team proposes two improvements to this scenario. First, the CH-53E OOMA configuration manager would implement a simple Fatigue Life Estimator calculation for each component. This estimator will calculate damage between SAFE reports based on statistics from existing fleet data and provide a

more accurate assessment than applying worst case according to potentially obsolete design data. Second, a means to automate the SAFE report distribution process is being investigated including the use of e-mail, website downloads, and automatic population of OOMA component damage fields to the users' ground station.

## Usage Spectrum Update

Another way to gain benefit from SHUM/SAFE is to update the aircraft flight spectrum. The initial design spectrum is usually developed in a few different ways; derivation from specifications such as Aeronautical Requirement 56 (AR-56), pilot surveys, data on similar T/M/S or the Navy/Marine Corps-provided requirements to the OEM. These requirements illustrate what the expected mission and mission mix will be for the aircraft. These requirements yield a design spectrum that drives component usage based on aircraft mission, weight, and mission frequency. During operation, it is common that any one of these aspects change, resulting in an inaccurate portrayal of maintenance requirements and component life. A flight spectrum based on actual aircraft usage, the usage spectrum, provides a more accurate account of what the dynamic components and aircraft structure are experiencing. From these data, fatigue rates and maintenance intervals could be adjusted accordingly. In order to maximize SHUM benefit, the CH-53E program will update the usage spectrum, in addition to providing SAFE FLEs.

As of the writing of this paper, the CH-53E usage spectrum method is still under development, however the process will be similar to that used on the Navy AH-1W in the 1990's to update their usage spectrum, using statistical cumulative frequency distribution of the usages [Ref. 13]. Traditionally, the usage spectra updates have been through usage surveys conducted using a paper questionnaire, which is filled out by the pilots for information on mission type, gross weight, altitude, velocity, flight maneuver and associated time, flight duration, and other information. As with the H-1's in the past, pilot surveys were not used for two main reasons, the pilot's account is not always a clear representation of the actual mission flown, and the availability of an established regime recognition algorithm to identify the experienced flight regimes [Ref. 13]. The CH-53E will be using the IMDS data and their regime recognition software to identify which regimes were flown, the durations, and remaining information to accurately model the usage.

The CH-53E has benefitted from new requirements for HUMS from lessons learned on previous aircraft. These new requirements are outlined in Reference 8. For usage spectrum development, 356 recognized regimes were condensed into 78 design spectrum regimes at 3 gross weights. NAVAIR has recommended having at least 150-200 data hours for 15-20 aircraft before fluctuations in individual operation stabilizes to a fleet usage. This is dependent on having sufficient data in each regime and to ensure all regimes are accounted for. This should not be an issue for the CH-53E program since many IMDS were installed in 2006 and have been in operation since. SAFE standup is scheduled for later this year.

## Conclusions

SAFE is a large part of SHUM and the overall CBM program being pursued by the US Navy/Marine Corps. With the implementation of SAFE, the CH-53E program hopes to achieve cost savings while ensuring safety is not compromised. Other studies have shown that smaller programs have been able to achieve 50% increase in component life using SAFE. Initial analysis has shown that if the CH-53E program achieves 25-50% savings in retirement time or maintenance burden, the program could save in the neighborhood of \$20M per year.

## Acknowledgements

The authors would like to acknowledge Capt. Richard Muldoon and Ms. Vicki Nagle of PMA-261 for their continued efforts in initiating, developing and establishing CBM for the H-53.

## References

- [1] Croisetiere, Col P., "CH-53 Heavy Lift Helicopter Program," Military Aviation Repair and Maintenance 2006 Conference, Arlington, VA, April 24-25, 2006
- [2] Condition-Based Maintenance (CBM) Policy, OPNAVINST 4790.16A, Office of the Chief of Naval Operations, 17 Dec 2007.
- [3] Department of Defense, Office of the Inspector General. "Condition Based Maintenance Plus," Report No. D-2003-125, pp 2-9, August 27, 2003.
- [4] Mullen, M ADM., "CNO Guidance for 2006 – Meeting the Challenge of a New Era", <http://www.navy.mil/features/2006CNOG.pdf>, accessed 29 December 2009.

[5] Muldoon, R CDR, and Hayden, R., "Improving Military Helicopter Supportability with the Integrated Mechanical Diagnostics (IMD) Health & Usage Monitoring System (HUMS)," 25<sup>th</sup> European Rotorcraft Forum, Rome, Italy, September 1999.

[6] Neubert, C., Tullos, R., Little, M., "Integrated Mechanical Diagnostic System (IMDS) Fleet Introduction For U.S. Navy/Marine Corps Helicopter," American Helicopter Society 61<sup>st</sup> Annual Forum, Grapevine, TX, June 1-3, 2005.

[7] Commander, Naval Air Systems Command. "Technical Directive for the Incorporation of the Integrated Mechanical Diagnostic System," H53 Airframe Change-519, August 11, 2005.

[8] Goodrich Corporation., "H53E Integrated Mechanical Diagnostics System Specification," Technical Document No. T1004-0101-0301, October 2009.

[9] Barndt, G., and McCool, K., "Development Efforts and Requirements for Implementation of Navy Structural Usage Monitoring," American Helicopter Society 58<sup>th</sup> Annual Forum, Montreal, Canada, June 11-13, 2002.

[10] Morales, M., and Haas, D., "Feasibility of Aircraft Gross Weight Estimation Using Artificial Neural Networks," American Helicopter Society 57<sup>th</sup> Annual Forum, Washington D.C., May 9-11, 2001.

[11] Moon, S., Phan, N., "Characterization of Rotorcraft Recorded Maneuver/Regime Usage Variability," 13<sup>th</sup> Australian International Aerospace Congress, Melbourne, Australia, March 2009.

[12] Adams, D.O., and Zhao, Dr. J., "Searching for the Usage Monitor Reliability Factor Using an Advanced Fatigue Reliability Assessment Model," American Helicopter Society 65<sup>th</sup> Annual Forum, Grapevine, TX, May 27-29, 2009.

[13] Moon, S., Simmerman, C., "The Art of Helicopter Usage Spectrum Development," American Helicopter Society 61<sup>st</sup> Annual Forum, Grapevine, TX, June 1-3, 2005.

[14] Barndt, G., Moon, S., "Development of a Fatigue Tracking Program for Navy Rotary Wing Aircraft," American Helicopter Society 50<sup>th</sup> Annual Forum, Washington D.C., May 11-13, 1994.