Hydrodynamics of the Nearshore

Robert A. Dalrymple and James T. Kirby Center for Applied Coastal Research University of Delaware Newark, DE 19716 phone: (302) 831-2440 fax:(302) 831 1228 email: rad@udel.edu Award #: N00014-98-1-0521

LONG-TERM GOAL

The goal of this project is to predict the wave-induced nearshore circulation and the low frequency motions that exist near shorelines. Two aspects of this hydrodynamic system are of particular interest: rip currents on barred shorelines and the analysis of edge wave and shear wave motions.

OBJECTIVES

To determine the mechanisms for the generation of rip currents on a shoreline with sand bars and rip channels. To discover the reasons that rip currents are unstable in position and in time.

To develop a framework for analyzing the spatial and temporal structure of shear waves and other unstable wave-induced flows in the nearshore zone. To construct a dynamical model for the coupling and evolution of the spatial modes of the flow field, and to compare the low-order dynamical framework to a weakly nonlinear formulation based on three-wave coupling of shear wave and edge wave modes, as determined from linear theory.

APPROACH

For the rip current problem, laboratory measurements in a 20 m x 20m directional wave basin have been conducted. Wave height and horizontal velocities were measured over the whole basin. Mean flows and water level set-up was obtained by averaging the data.

To augment the laboratory data, a theoretical/numerical model for the flow instability of rip currents has been developed. The model examines the instability of the rip current by treating it as a jet, subjected to an increasing water depth. The instabilities are due to the shear in the jet, much as in a shear wave.

For the shear waves, the approach is to analyze numerically simulated flow fields (such as the unstable shear wave climates described by Ozkan-Haller and Kirby (1998) using principal component analysis (PCA), as described by Holmes *et al.* (1996). This leads to a possible description of a complex flow field in terms of a (hopefully) small number of dominant modes. Following Aubry *et al.* (1988), a nonlinear model coupling these modes can be constructed and hopefully will shed light on the mechanisms for the growth of large scale structures such as vortices in the nearshore circulation pattern. The aim is to also apply the method to spatially

Report Documentation Page				Form Approved OMB No. 0704-0188		
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.						
1. REPORT DATE 1998	. REPORT DATE 998 2. REPORT TYPE			3. DATES COVERED 00-00-1998 to 00-00-1998		
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER		
Hydrodynamics of the Nearshore				5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NUMBER		
				5e. TASK NUMBER		
				5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Delaware, Center for Applied Coastal Research, Newark, DE, 19716				8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited						
13. SUPPLEMENTARY NOTES See also ADM002252.						
14. ABSTRACT						
15. SUBJECT TERMS						
16. SECURITY CLASSIFICATION OF: 17. LIMITATION OF				18. NUMBER	19a. NAME OF	
a. REPORT unclassified	ь. abstract unclassified	c. THIS PAGE unclassified	Same as Report (SAR)	of Pages 5	KESPONSIBLE PERSON	

Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std Z39-18 dense, measured flows in the field, such as those obtained using doppler radar techniques (Smith and Largier, 1995). Results of this approach will be compared to results obtained using a spectral, coupled-mode model for a combined field of weakly nonlinear edge and shear waves.

WORK COMPLETED

A series of experiments have been carried out in the Directional Wave Basin for waves over a sand bar with a rip channel. Figure 1 shows the directional basin with the 34 element wavemaker to the upper right and the sand bar system appears as the lighter areas at lower left; the beach is not shown (lower left). The rip current is moving towards the wavemakers through the rip channel, causing the waves to refract around the current and break on the current. Experiments have shown that the mean water levels induced between the sand bars and the beach by breaking waves provides a longshore hydrostatic gradient for longshore flows to the rip channels. The rip currents are unstable in time and space.

A numerical model has been written to predict the instability of these rip currents, based on previous works on the instability of plane jets. The rip current is modeled as a two-dimensional jet and the method of multiple scales is used to examine its linear (spatial) instabilities. The present model is based on the work of Nayfeh et al. (1974) and Saric and Nayfeh (1975), who applied the theory to boundary layer flows. The mean



flow in the rip current flows the model of Joshi (1982), which was developed for tidal ebb flows from inlets. The fact that the depth under the rip current increases in the offshore direction has been included in the model.

At first order, the rip current instability model reduces to the Orr-Sommerfeld problem for parallel flows. At the next order, the effects of the transverse velocity component due to non-parallel mean flow and streamwise variations of the mean flow are included. The model predicts the streamwise variations of the disturbance amplitude, wavenumber, and spatial growth rate and these results are compared to the laboratory measurements. In addition, the influence of viscosity, non-parallelism, and depth variation in the longitudinal direction and the associated vortex stretching are examined.

A numerical model for calculating a combined field of edge and shear waves has been developed (Ozkan-Haller and Kirby, 1997) and has been applied to the study of a circulation field dominated

by shear waves (Ozkan-Haller and Kirby, 1998). Development of the PCA techniques needed to analyse the resulting numerically-predicted flow fields is underway but incomplete at this time. The governing equations describing the mode-coupled, weakly nonlinear model for edge and shear waves have been developed (Kirby et al, 1998), and have been applied in a study of edge wave interactions on a planar beach.



Analytical (dashed lines) and Numerical (jagged lines) Results for Edge Wave Amplitudes in an Interacting Triad. Time is scaled by the edge wave period, T_{ν} , of Wave 1.

RESULTS

The most important result from this study is the discovery in the laboratory that the rip current system is unstable. The fast seaward flowing jet oscillates laterally in the channel and pulsates in time.

Numerical modelling for rip current instability predicts the most unstable mode of this instability. This instability is similar to the shear wave instability of the longshore current, however, is it is an independent mechanism. It is likely in the field that both mechanism occur simultaneously.

The laboratory results also have been put in SHORECIRC to predict the presence of the rip current and the presence of the instability. Results agree well.

A numerical model for calculating a combined field of edge and shear waves has been developed (Ozkan-Haller and Kirby, 1997) and has been applied to the study of a circulation field dominated by shear waves (Ozkan-Haller and Kirby, 1998). Development of the PCA techniques needed to analyse the resulting numerically-predicted flow fields is underway but incomplete at this time.

The governing equations describing the mode-coupled, weakly nonlinear model for edge and shear waves have been developed (Kirby *et al.*, 1998), and have been applied in a study of edge wave interactions on a planar beach.

IMPACT/APPLICATIONS

The main anticipated short-term impacts are a better understanding of the behavior of rip currents on a barred shoreline and an improved understanding of whether and how nonlinearities affect the balance of shear wave and edge wave energies on a given beach topography.

RELATED PROJECTS

The rip current laboratory data has also been used in FUNWAVE, a Boussinesq model developed with Army Research Office funding. By averaging output from this Boussinesq model, mean longshore and rip currents are obtained. Instantaneous vorticity calculations have been shown to be the same as the time-averaged vorticity. Finally the rip current data has been input to this model for comparison. A manuscript has been submitted to a journal on this topic.

REFERENCES

- Aubry, N., Holmes, P., Lumley, J. L. and Stone, E., 1988, "The dyanmics of coherent structures in the wall region of a turbulent boundary layer", J. Fluid Mech., 192, 115-173, 1988.
- Holmes, P., Lumley, J. L. and Berkooz, G., "Turbulence, Coherent Structures, Dynamical Systems and Symmetry", Cambridge University Press, 1996.
- Joshi, P.B., Hydromechanics of tidal jets, J. Waterways, Port, Coastal and Ocean Engineering, ASCE, 108, 1982.
- Kochergin, I. Y. and Pelinovsky, E. N., 1989, "Nonlinear interaction in an edge wave triad", Oceanology, 29, 669-672, 1989.
- Nayfeh, A.H., W.S. Saric, and D.T. Mook, Stability of non-parallel flows, Archives of Mechanics, 26, 1974.
- Özkan-Haller, H. T. and Kirby, J. T., ``A Fourier-Chebyshev collocation method for the shallow water equations including shoreline runup", Applied Ocean Research, 19, 21-34, 1997.
- Özkan-Haller, H. T. and Kirby, J. T., ``Nonlinear evolution of shear instabilities of the longshore current: A comparison of observations and computations", submitted to Journal of Geophysical Research, under revision, 1998.

Saric, W.S. and A.H. Nayfeh, Nonparallel stability of boundary-layer flows, Physics of Fluids, 18,

8, 1975.

Smith, J.R. and J.L. Largier, "Observations of nearshore circulation-rip currents," J. Geophys. Res., 100, 10967-10975, 1995.

PUBLICATIONS

- Haas, K., I.A. Svendsen, M.C. Haller, and R.A. Dalrymple, "Numerical Modeling of Nearshore Circulation on a Barred Beach with Rip Channels," Proc. 26th Intl. Conf. Coastal Engineering, ASCE, Copenhagen, 1998.
- Haller, M. C., Dalrymple, R. A., and I. A. Svendsen, "Rip Channels and Nearshore Circulation," Coastal Dynamics '97, 594-603, 1997.
- Haller, M. C., Dalrymple, R. A., and I. A. Svendsen, "Rip Channels and Nearshore Circulation," Waves '97, ASCE, 1997.
- Kirby, J. T., Putrevu, U. and Özkan-Haller, H. T., "Evolution equations for edge waves and shear waves on longshore uniform beaches", Proc. 26th Intl. Conf. Coastal Engrng., Copenhagen, June 1998, in press.