

Simulating the Detachment of Leading Edge Vortices on *Drosophila Melanogaster* using CFD

Alex Sabbatini
Stanford University

Gabriel Smith, Jeffrey S. Pulskamp, and Ronald G. Polcawich
Adelphi Army Research Lab

September 13, 2010

1 Motivation

Initial CFD simulations of quasi-steady hovering flight of the *Drosophila* sp. have studied the effects of delayed rotation of the wings at the end of each stroke and its effect on the resulting unsteady aerodynamic forces found throughout the wing [8]. Further studies were carried out using the same CFD model as before to determine the lift and power requirements for *Drosophila Virilis* [7]. To verify the validity of the simulation's results, the specific power that was calculated (the sum of aerodynamic and inertial power requirements normalized to the fruitfly muscle mass) was compared to the values retrieved by Dickenson on tethered fruitflies [1]. Although the periodic behavior of the 'translational' and rotational motions of the wing were heavily approximated, the comparison showed strong agreement. This lends support to the use of CFD models in the parametric design process used in the pioneering of microscale flapping wings [2]. It is of great importance to MEMs designers working on microscale flapping wing to study the detachment of Leading Edge Vortices (LEV). Solving the Navier-Stokes equations in the time-varying coordinates of the flapping wing proves a challenge computationally but offers the possibility of predicting the behavior of the LEV-shedding phenomenon to which flapping wings owe a majority of their lift. In addition to studying the shedding of LEVs, CFD simulations enable one to quickly assess the effect of wing shaping on vertical lift. Pre-

Report Documentation Page

*Form Approved
OMB No. 0704-0188*

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

| | | | | | |
|---|------------------------------------|---|-----------------------------|---------------------|---------------------------------|
| 1. REPORT DATE 13 SEP 2010 | 2. REPORT TYPE | 3. DATES COVERED 00-00-2010 to 00-00-2010 | | | |
| 4. TITLE AND SUBTITLE Simulating the Detachment of Leading Edge Vortices on Drosophila Melanogaster using CFD | | 5a. CONTRACT NUMBER | | | |
| | | 5b. GRANT NUMBER | | | |
| | | 5c. PROGRAM ELEMENT NUMBER | | | |
| 6. AUTHOR(S) | | 5d. PROJECT NUMBER | | | |
| | | 5e. TASK NUMBER | | | |
| | | 5f. WORK UNIT NUMBER | | | |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Stanford University, Army High Performance Computing Research Center, Mechanical Engineering Department, Stanford, CA, 94305 | | 8. PERFORMING ORGANIZATION REPORT NUMBER | | | |
| 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) | | 10. SPONSOR/MONITOR'S ACRONYM(S) | | | |
| | | 11. SPONSOR/MONITOR'S REPORT NUMBER(S) | | | |
| 12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited | | | | | |
| 13. SUPPLEMENTARY NOTES | | | | | |
| 14. ABSTRACT | | | | | |
| 15. SUBJECT TERMS | | | | | |
| 16. SECURITY CLASSIFICATION OF: | | | 17. LIMITATION OF ABSTRACT | 18. NUMBER OF PAGES | 19a. NAME OF RESPONSIBLE PERSON |
| a. REPORT unclassified | b. ABSTRACT unclassified | c. THIS PAGE unclassified | Same as Report (SAR) | 6 | |

liminary code was developed in MATLAB with these two potential studies in mind.

2 Governing Equations

The code that was developed to tackle the flapping wing problem solves the Navier-Stokes equations for a compressible fluid (written here in cartesian coordinate system):

$$\frac{\partial \hat{u}}{\partial t} = -\frac{\partial}{\partial x}(\hat{f} - \hat{f}_v) - \frac{\partial}{\partial y}(\hat{g} - \hat{g}_v) - \frac{\partial}{\partial z}(\hat{h} - \hat{h}_v) \quad (1)$$

$$\frac{\partial \rho}{\partial t} = \frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} + \frac{\partial w}{\partial z} \quad (2)$$

where \hat{u} , \hat{f} , \hat{g} , \hat{h} , \hat{f}_v , \hat{g}_v , \hat{h}_v

$$\hat{u} = \begin{pmatrix} u \\ v \\ w \end{pmatrix} \quad (3)$$

$$\hat{f} = \begin{pmatrix} p + u^2 \\ uv \\ uw \end{pmatrix} \quad (4)$$

$$\hat{g} = \begin{pmatrix} vu \\ p + v^2 \\ vw \end{pmatrix} \quad (5)$$

$$\hat{h} = \begin{pmatrix} wu \\ wv \\ p + w^2 \end{pmatrix} \quad (6)$$

$$f_v = \nu \begin{pmatrix} \frac{\partial u}{\partial x} \\ \frac{\partial v}{\partial x} \\ \frac{\partial w}{\partial x} \end{pmatrix} \quad (7)$$

$$g_v = \nu \begin{pmatrix} \frac{\partial u}{\partial y} \\ \frac{\partial v}{\partial y} \\ \frac{\partial w}{\partial y} \end{pmatrix} \quad (8)$$

$$h_v = \nu \begin{pmatrix} \frac{\partial u}{\partial z} \\ \frac{\partial v}{\partial z} \\ \frac{\partial w}{\partial z} \end{pmatrix} \quad (9)$$

A constant density/incompressible fluid assumption can be applied to equation 2 - the PDE for the conservation of mass - which sends the $\frac{\partial \rho}{\partial t}$ term to zero. The resulting PDE can also be written as:

$$\nabla \bullet \hat{u} = 0 \quad (10)$$

This statement is now equivalent to saying that the mass flux entering a finite volume must equal the mass flux leaving that volume. The reynolds number for the flow about the flapping wings of *Drosophila Melanogaster* was determined to be 115 [3]. The low-reynolds number for the flow allows an additional assumption to be made: the flow is in the laminar regime. This saves us from the added complexity of implementing a model for turbulent fluid flow. The following form of the Navier-Stokes equations is developed by Roger and Kwak [4]

$$[I_{tr} + (\frac{\partial \hat{R}}{\partial D})^{n+1,m}](D^{n+1,m+1} - D^{n+1,m}) = -\hat{R}^{n+1,m} - \frac{I_m}{\Delta t}(1.5D^{n+1,m} - 2D^n + 0.5D^{n-1}) \quad (11)$$

The derivative of the state vector with respect to time is discretized using a second-order three-point backward difference formula. The distinguishing feature of this equation is its implementation of artificial compressibility.

$$\frac{\partial p}{\partial \tau} = -\beta \nabla \bullet \hat{u}^{n+1,m+1} \quad (12)$$

This equation, although physically meaningless with the inclusion of the derivative of pressure on the left hand side, enforces the desired incompressibility assumption which lead us to equation 10. This is achieved through carrying the form of the Navier-Stokes equations forward in artificial time. This requires adding a pseudotime derivative (a derivative with respect to artificial time) to all four of the Navier-Stokes equations. The three other equations that complement equation 12 can be written in a similar fashion to the one reproduced below (in its discretized form).

$$\frac{1.5\hat{u}^{n+1,m+1} - 1.5\hat{u}^{n+1,m}}{\Delta t} = \frac{-\hat{r}^{n+1,m+1} - 1.5\hat{u}^{n+1,m} - 2\hat{u}^n + 0.5\hat{u}^{n-1}}{\Delta t} \quad (13)$$

Together, equation 12 and the three equations that take on the form of 13 can be written compactly in the delta form (equation 1) mentioned earlier:

where $D, R, E, F, G, E_v, F_v, G_v$ are

$$D = \begin{pmatrix} p \\ u \\ v \\ w \end{pmatrix} \quad (14)$$

$$\hat{R} = \frac{\partial}{\partial x}(F - F_v) + \frac{\partial}{\partial y}(G - G_v) + \frac{\partial}{\partial z}(H - H_v); \quad (15)$$

$$F = \begin{pmatrix} \beta u \\ p + u^2 \\ uv \\ uw \end{pmatrix} \quad (16)$$

$$G = \begin{pmatrix} \beta v \\ vu \\ p + v^2 \\ vw \end{pmatrix} \quad (17)$$

$$H = \begin{pmatrix} \beta w \\ wu \\ wv \\ p + w^2 \end{pmatrix} \quad (18)$$

$$F_v = \nu \begin{pmatrix} 0 \\ \frac{\partial u}{\partial x} \\ \frac{\partial v}{\partial x} \\ \frac{\partial w}{\partial x} \end{pmatrix} \quad (19)$$

$$G_v = \nu \begin{pmatrix} 0 \\ \frac{\partial u}{\partial y} \\ \frac{\partial v}{\partial y} \\ \frac{\partial w}{\partial y} \end{pmatrix} \quad (20)$$

$$H_v = \nu \begin{pmatrix} 0 \\ \frac{\partial u}{\partial z} \\ \frac{\partial v}{\partial z} \\ \frac{\partial w}{\partial z} \end{pmatrix} \quad (21)$$

and where dR/dD consists of the jacobians of the convective and viscous flux terms. The jacobian arises from a common technique used in solving the Navier-Stokes equations numerically. This technique linearizes the residuals of each equation so that one can write the equations in implicit form and

from this the systems of linear equations can be solved numerically using conventional methods.

3 Numerical Method

Equation 11 is written in a form that can be solved using an procedure called the Gauss-Seidel line-iteration. The viscous fluxes are discretized with a second order central difference scheme while the convective fluxes are discretized using a cell-centered scheme that treats the fluxes across each node (each finite volume) as conservative variables. This discretization proves much more stable as it provides numerical dissipation automatically. This discretization is formed as follows for the flux passing through the faces corresponding to x-ward normal vectors:

$$\frac{[\hat{f}_{i+1/2} - \hat{f}_{i-1/2}]}{\Delta x} = 0 \quad (22)$$

$$\hat{f}_{i+1/2} = \frac{1}{2}[f(q_{i+1}) + f(q_i)] - \frac{1}{2}[\Delta f_{i+1/2}^+ - \Delta f_{j+1/2}^-] \quad (23)$$

$$\Delta f_{i+1/2}^\pm = A^\pm(\hat{q})\Delta q_{i+1/2} \quad (24)$$

the last equation 24, is the flux difference term found in equation 23 and it can be calculated provided that one can find a matrix A that is the jacobian of the flux vector with respect to the state vector D. This jacobian must also carry with it other properties all captured by the so called 'property U'. Creating a jacobian matrix with 'property U' allows the jacobian to be representative of the change in flux with respect to state vectors at the interface between the two nodes it is responsible for. P. L. Roe developed a method to produce such jacobians that is implemented on the Euler equations [3] but can be partly extended toward the navier-stokes equations and its convective fluxes.

4 Results and Further Work

The main problem facing the code now in its development is that upon attempting to solve the linear system of equations according to the Gauss-Seidel line-iteration, the matrix cannot be numerically inverted because it is found by `linsolve()` in MATLAB to be singular. This prevents results from being produced for the simple 3D channel problem.

References

- [1] Fry, Steven N., Rosalyn Sayaman, and Michael H. Dickinson. *The Aerodynamics of Hovering Flight in Drosophila*. The Journal of Experimental Biology 208 (2005): 2303-318. Print.
- [2] Kroninger, Christopher M., Jeffery S. Pulskamp, Ronald G. Polcawich, Jessica R. Bronson, and Eric D. Wetzel. *Design and Characterization of Millimeter-Scale Flapping Wings*. AHS International - the Vertical Flight Society; 65th Annual Forum Proceedings (2009): 1348-359. Print.
- [3] Roe, P.L. *Approximate Riemann Solvers, Parameter Vectors, and Difference Schemes* Journal of Computational Physics Vol. 43 (1981): 357-372. Print.
- [4] Rogers, Stuart E., Kwak, Dochan *Steady and Unsteady Solutions of the Incompressible Navier-Stokes Equations* AIAA 29 (1991): 603-610. Print.
- [5] Rogers, Stuart E., Kwak, Dochan *Upwind Differencing Scheme for the Time-Accurate Incompressible Navier-Stokes Equations* AIAA 28 (1990): 253-262. Print.
- [6] Sane, Sanjay P., Dickinson, Michael H. *The Aerodynamic effect of wing rotation and a revised quasi-steady model of flapping flight* The Journal of Experimental Biology Vol. 205 (2002): 1087-1096. Print.
- [7] Sun, Mao, and Jian Tang. *Lift and Power Requirements of Hovering Flight in Drosophila Virilis*. The Journal of Experimental Biology 205 (2002): 2413-427. Print.
- [8] Sun, Mao, and Jian Tang. *Unsteady Aerodynamic Force Generation by a Model Fruit Fly Wing in Flapping Motion*. The Journal of Experimental Biology 205 (2001): 55-70. Print.