



John Sullivan  
Shelter Technology Engineering &  
Fabrication Directorate  
- Special Projects Team

# Evaluation of High Efficiency LED Lighting

2 NOV 2011



UNCLASSIFIED

## Report Documentation Page

*Form Approved*  
*OMB No. 0704-0188*

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE <b>02 NOV 2011</b>	2. REPORT TYPE	3. DATES COVERED <b>00-00-2011 to 00-00-2011</b>		
4. TITLE AND SUBTITLE <b>Evaluation of High Efficiency LED Lighting</b>		5a. CONTRACT NUMBER		
		5b. GRANT NUMBER		
		5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)		5d. PROJECT NUMBER		
		5e. TASK NUMBER		
		5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>US Army Research, Development and Engineering Command (RDECOM),US Army Natick Soldier RD&amp;E Center,Natick,MA,01760</b>		8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		10. SPONSOR/MONITOR'S ACRONYM(S)		
		11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>				
13. SUPPLEMENTARY NOTES <b>7th Bi-Annual DOD JOCOTAS Meeting with Rigid &amp; Soft Wall Shelter Industry &amp; Indoor &amp; Outdoor Exhibition, 1-3 Nov 2011, Panama City Beach, FL</b>				
14. ABSTRACT				
15. SUBJECT TERMS				
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>	<b>Same as Report (SAR)</b>	18. NUMBER OF PAGES <b>19</b>
				19a. NAME OF RESPONSIBLE PERSON

## Jameson Fluorescent Lights

- Electronic Ballast
- Illumination 1598.44 lux
- Length 32.8 inches
- Weight 4.5 lbs each
- 0.35 Amps
- Challenges
  - Heavy and Bulky
  - Expensive
  - Non-Repairable in the Field
  - Ballast Challenges
  - Lower Light Quality and Efficiency
  - Requires HAZMAT cleanup



## Fluorescent Lighting

- Emits light in all directions
- Light can be lost inside the fixture
- Light can be reabsorbed by the lamp
- Light is not directed to maximize its usefulness.



Source: Dept. of Energy



# Military Specifications




- MIL-PRF-44259D
- **Light Set** must:
  - be interconnected with up to 11 other lights
  - provide for the water resistant pass through of fixed external power cords
  - have fixed power cords with a NEMA 5-15 plug at one end and a NEMA 5-15 receptacle at the other
  - have an on/off switch on the NEMA 5-15 plug side
  - have a total length of no less than 113 inches and no more than 120 inches
- **Input voltage** must:
  - operate on a voltage of 120 volts alternating current at 50 to 60 Hertz
- **Input current** must:
  - be a maximum of 0.7 amps
- **Illumination** must:
  - provide a minimum of 1506.95 lux per each light when measured 18 inches from the light

## Shelter Illumination through Light Emitting Diodes (LED's)


### Benefits:

- Produces necessary illumination using less power
- Instant Blackout Capability
- Non hazardous materials
- High quality of light across all wavelengths (CRI)
- Compact, lightweight
- Optimized optomechanics for even, non-dazzling light
- All light is directed to the floor (no dispersed light)
- 10 times longer life than fluorescent light
- Instant on, with no warmup period
- Durability



- In ideal condition (~25°C), the life span of LED lights is around 100,000 hours
  - 100,000 hours < 20 years
  - The life span of current LED lights is longer than that of the shelter they will be used in
- Life span compared to other lighting systems:

	Incandescent	Fluorescent	Solid-State
Average Life Expectancy	1000 – 1500 hours	10,000 – 12,000 hours	<b>50,000 – 100,000 hours</b>



## Design Goal

The development of a solid state LED lighting system that is 1) equal to or greater than fluorescent lighting in efficiency (economy), while 2) producing an equivalent or better light output suitable for deployed military lighting needs



## SBIR Design Challenges

1. In FY2004, large, high output LEDs were inefficient ~ only 50-60 lumens/watt
2. High output LEDs clustered in a quantity equal to fluorescent generated significant heat.
3. Requirement for small housing + high heat required on-board cooling system
4. High output LED's were very expensive
5. Complex power management system
6. And many more...



## Flexible, Electroluminescent (EL) Lighting Surfaces:

- Provide general illumination for shelters
- Decreases deployment time, weight, and cube
- Polymer-based lighting surfaces are flexible, durable and safe
- Can be printed on multiple substrates (including fabric)
- Puncture of EL lamp does not cause failure





Physical Optics Corp.




Techshot

## Comparison of General Lighting Types Available Today

Deployed Shelter Lighting Needs	Incandescent	Fluorescent	Solid State
Light Output	504 lm (40 watt bulb)	3060 lm (36 watt T-8)	4320 lm (36 watt input)
Efficiency (lm/w)	12.6 lm/w	ave~ 85 lm/w	120+ lm/w
Standard Color Temperature	2700-3000 K	2700-6000 K	2500 - 6000 K
Ave Life Expectancy	1000-1500 hrs	10-12,000 hrs	50-100,000 hrs
Dimmer Capability	YES	NO	YES
Adjustable Color	NO	NO	YES
Perform in wide thermal range	YES	NO	YES
Robustness of Design	NO	NO	YES
Drop Shock/Concussion Tolerant	NO	NO	YES
Integrate into structure	NO	NO	YES
Immediate Blackout Capability	NO	NO	YES
Logistical Support	HI	HI	MED


➤ 231 lm/w LED recently demonstrated (driven at 350mA and color temperature of 4500K)

## DOE Estimates 11 Months Apart




The Luminous efficiency of white LED technology has been increasing at an unprecedented pace, with **231 lm/w** recently being demonstrated.


- Testing of systems with an efficiency of 120+ lm/W underway, representing a 40% reduction in energy use without accounting for the more efficient distribution of light by LEDs.
- Assuming a 170 watt LED system vs. fluorescent, a single shelter would save 125 gallons of fuel if run continuous for a year off of a 60kW TQG.



- Conducted Evaluations to prove the benefits of LEDs
  - Tests include:
    - Efficiency
    - Energy and light output
    - Current
    - Temperature of light output
    - Color of light (shown right)
    - Durability
- Tested prototypes of various color temperatures across the white LED range.



The many different LEDs and their respective color output




## Cognitive Performance Analysis

Recently, testing of the cognitive performance of Soldiers at Natick while subjected to various LED systems which feature different color temperatures took place in an attempt to find a correlation between color temperature and Soldier performance.


### Tasks

- Color recognition
- Visual acuity
- Cognitive tasks
- Mood assessment


**Average Change in Fatigue Score**



**Average Change in Depression Scores**




**Average Change in Vigor/Activity Score**




## Cognitive Tasks

**Cognitive Task 2 RT (verbal task)**



**Cognitive Task 3 RT (spatial task)**



Not significant:


- CT1 (auditory sequence monitoring) Accuracy
- CT2 (verbal event planning) Accuracy
- CT3 (spatial memory) Accuracy

\*\*\* =  $p < .01$   
 \*\* =  $p < .05$   
 \* =  $p < .10$




## Impact of higher color temperature

- Faster color recognition visual perception tasks
- Higher arousal states and lower depression ratings
- Faster reaction times on cognitive tasks
- Increased comfort level and willingness to spend time in lighting area



**Lighting → mood → task performance**



## Technical Readiness Level 8

- Systems available that are fieldable and can save 30+% energy compared with fluorescents
- Price is still a limiting factor despite ROI's that make them justifiable
- Working with PM-FSS to field test larger quantities for potential transition



- More testing of color temperature affects on cognitive performance
- Currently selecting Phase I SBIR proposals for a hybrid day lighting solution that'll utilize both concentrated daylight and supplemental LED lighting to significantly reduce energy use.
- Begin larger scale LED testing at Fort Devens SIL
- Completion of NSRDEC lighting test lab
  - Multiple switched circuits to compare systems
  - Integrated illumination, color temperature, and current sensors connected to a central data acquisition system





# Questions



**POC:**

John Sullivan

[John.sullivan32@us.army.mil](mailto:John.sullivan32@us.army.mil)

508-233-5569