



Innovation for Our Energy Future

Waste-to-Energy and Fuel Cell Technologies Overview



**Presented to:
DOD-DOE Waste-to-
Energy Workshop**

Dr. Robert J. Remick

**January 13, 2011
Capital Hilton Hotel
Washington, DC**


Report Documentation Page

Form Approved
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE 13 JAN 2011		2. REPORT TYPE		3. DATES COVERED 00-00-2011 to 00-00-2011	
4. TITLE AND SUBTITLE Waste-to-Energy and Fuel Cell Technologies Overview				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Department of Energy, National Renewable Energy Laboratory (NREL), 910 D St SW Suite 930, Washington, DC, 20024				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES presented at the DOE-DOD Waste-to-Energy using Fuel Cells Workshop held Jan. 13, 2011 in Washington DC					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 13	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Global Approach for Using Biogas



Anaerobic Digestion of Organic Wastes is a Good Source of Methane.

Organic waste + methanogenic bacteria → methane (CH₄)

Issues:

High levels of contamination


Time varying output of gas quantity and quality



Photo courtesy of Dos Rios Water Recycling Center, San Antonio, TX

Opportunities for Methane Production via Anaerobic Digestion

- Breweries (~73 Watts per barrel of beer)
- Municipal Waste Water Treatment Plants (~4 W/person)
- Industrial-scale Food Processing
- Landfills
- Dairy and Pig Farms (~200 W/Cow)
- Pulp and Paper Mills



Stationary Fuel Cell Products Currently on the Market are Configured to Operate on Natural Gas

UTC Power, Inc.

FuelCell Energy Inc.

Bloom Energy, Inc.

PureCell 400

DFC 300, 1500, and 3000

ES-5000 Energy Server

Waste processes that produce methane, like anaerobic digestion of organic matter, are most easily mated to these fuel cell systems.



Comparison by Generator Type

(based on 40-million SCF* of biogas per year**)

Generator Type	Megawatt-hours/year
PAFC	2,900
MCFC	3,300
Micro-turbine	1,800
Reciprocating Engine	1,500

* ~830 Btu/SCF (HHV)

** WWTP serving a community of about 110,000 people

This comparison ignores the fact that generators do not come in an infinite range of sizes.

Contaminants in Biogas are a problem.

Commercial stationary power plants of all types are configured to operate on pipeline quality natural gas. Additional cleanup is necessary to use biogas from anaerobic digesters or landfills with these generators.



Compressor Station



PSA Cleanup System

Photos courtesy of Guild Associates, Inc.

Landfill Gas Contaminants vs Fuel Cell Specs.

Contaminant	Landfill Gas	Fuel Cell Spec*
Carbon Dioxide	~30%	3%
Nitrogen	~10%	4%
Oxygen	~1%	0.2%
C ₄ ⁺ hydrocarbons	0.2%	0.5%
Sulfides (mainly H ₂ S)	300 ppm	6 ppm
Organic Chlorine	<50 ppm	0.05 ppm
Organic Silicon	<30 ppm	Trace to 0


* Based on fuel specifications for the PureCell®400

Gasification of wood wastes is another potential source of useful fuel gas.

Wood waste → Gasification → Cleanup → Fuel Cell

Gasification uses high temperature to convert cellulosic materials to fuel gas

- Hydrogen (H_2)
- Carbon monoxide (CO)
- Methane (CH_4)
- Carbon Dioxide (CO_2)



One technology we have been following is inductive gasification developed by a German company Pyromex.

In 2009 NREL Performed a Study for the Los Alamos Joint Forces Training Base

Project Goal

- Increase base sustainability by producing on-site power
- Provide base energy needs through renewable pathways
- Provide backup power functionality to mission critical loads
- Provide hydrogen for on-site and public fuel cell vehicle refueling

Resource Availability


- Biomass up to 300 tons/day
- Land available for energy conversion hardware

Technology Evaluated

- Inductive gasification (Pyromex, German technology, mfg in Carson City, NV)
- Molten carbonate fuel cell (Fuel Cell Energy, US Technology, mfg in Connecticut)

Study evaluated the cost of electricity, heat, and hydrogen produced by the system.

Cost of Energy vs. Incentive Levels



25 tons/day biomass consumption, 350 kg/day H₂ and 31.2 MWh/day electrical output and 200 MMBtu/day heat

Technology Overview Summary

- Stationary fuel cells operating on natural gas are commercial technology.
- Integration of stationary fuel cells with anaerobic digesters is a demonstrated technology.
- A reasonable business case can be made for both at current costs when federal and state incentives are available.
- Integration of stationary fuel cells with biomass gasification is a developing technology that is in need of demonstration.

For Information Resources on Fuel Cells & H₂ the Place to Start is www.hydrogen.energy.gov

