



POWER AND MOBILITY



EVALUATING VOLTAGE REGULATION COMPLIANCE OF MIL-PRF-GCS600A(ARMY) FOR VEHICLE ON-BOARD GENERATORS AND ASSESSING OVERALL VEHICLE BUS COMPLIANCE

Disclaimer: Reference herein to any specific commercial company, product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the Department of the Army (DoA). The opinions of the authors expressed herein do not necessarily state or reflect those of the United States Government or the DoA, and shall not be used for advertising or product endorsement purposes.

Wesley G. Zanardelli, Ph.D.
Advanced Propulsion Team
US Army TARDEC

CPT John Kelly
ARSC, DET 8
US ARMY RDECOM-TARDEC

Report Documentation Page

Form Approved
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE 16 AUG 2012		2. REPORT TYPE Briefing		3. DATES COVERED 16-07-2012 to 15-08-2012	
4. TITLE AND SUBTITLE EVALUATING VOLTAGE REGULATION COMPLIANCE OF MIL-PRF-GCS600A (ARMY) FOR VEHICLE ON-BOARD GENERATORS AND ASSESSING OVERALL VEHICLE BUS COMPLIANCE				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Wesley Zanardelli; John Kelly				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army TARDEC, 6501 East Eleven Mile Rd, Warren, Mi, 48397-5000				8. PERFORMING ORGANIZATION REPORT NUMBER #23263	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army TARDEC, 6501 East Eleven Mile Rd, Warren, Mi, 48397-5000				10. SPONSOR/MONITOR'S ACRONYM(S) TARDEC	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) #23263	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES FOR GVSETS 2012					
14. ABSTRACT Briefing Charts					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Public Release	18. NUMBER OF PAGES 30	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Presentation Overview

POWER AND MOBILITY

- Objectives
- Background
- Experimental Setup
- Characterization and Power Quality Test Procedures
- Experimental Results
- Modeling
- Simulation Results
- Modeling Parameter Variation
- Conclusions
- Future work

Objectives

- Component level compliance with MIL-PRF-GCS600A(ARMY)
- Identification of parameters on power generation components
- Electrical machine characterization
- Modeling
- System level power quality compliance
- Optimization of high-voltage bus capacitance



Background

Background MIL-PRF-GCS600A(ARMY)


POWER AND MOBILITY

3.1.3 Electrical Characteristics


Steady-state Voltage	565V – 635V (600V ± 35V)
Ripple Amplitude	9V
Distortion Factor	0.015

$$\text{Distortion Factor} = \frac{\sqrt{\sum_{h=1}^{\infty} V_h^2}}{V_{DC}}$$

- Normal Transients: 475V – 725V for 15ms




- Distortion Spectrum




Background MIL-STD-704F vs. MIL-PRF-GCS600A(ARMY)



- Normal Transients



- MIL-STD-704F (270VDC)




- MIL-PRF-GCS600A(ARMY) (600VDC)

Specification	MIL-STD-704F (270VDC)	% of Nominal	MIL-PRF-GCS600A(ARMY) (600VDC)	% of Nominal
Steady-State Voltage	250V - 280V (270V +10V / -20V)	11.1%	565V - 635V (600V ± 35V)	11.7%
Normal Transients	200V - 330V for 20ms (up) / 10ms (down), 40ms settling time	48.1%	475V - 725V for 15ms, 40ms settling time	41.7%
Ripple Amplitude	6V	2.2%	9V	1.5%

Background MIL-STD-704F vs. MIL-PRF- GCS600A(ARMY)


POWER AND MOBILITY

• Distortion Spectrum



- MIL-STD-704F (270VDC)
- Distortion Factor: 0.015

Frequency	Amplitude, dBV	Amplitude, V	% of Nominal
10	-10	0.316	0.12%
1000	10	3.16	1.2%
5000	10	3.16	1.2%
50,000	-10	0.316	0.12%
500,000	-50	0.00316	0.0012%



- MIL-PRF-GCS600A(ARMY) (600VDC)
- Distortion Factor: 0.015




Frequency	Amplitude, dBµV	Amplitude, V	% of Nominal
10	115	0.562	0.09%
1000	135	5.62	0.9%
5000	135	5.62	0.9%
50,000	115	0.562	0.09%
500,000	75	0.00562	0.0009%

Background: Typical Vehicle Architecture

POWER AND MOBILITY

• Vehicle Loads

- Motor Drives & Voltage Converters
 - Constant Power
 - Capacitive (dc-link)
 - Switching noise
- Resistive Loads
- Inductive Loads
 - EMI filters
 - Phase Margin Reduction




Background: Generator Control Theory


POWER AND MOBILITY

Active Rectification

- Inverter required for Voltage Control
- Unity Power Factor is possible at terminals




Generator Phasor Diagram



Motor Phasor Diagram

Vector Control






Experimental Setup

Electrical Diagram of Setup

POWER AND MOBILITY


- Generator, Inverter and Load Equivalent Circuit



Experimental Setup

POWER AND MOBILITY

- AC Dynamometer
 - Constant Torque: 1244N·m from 0-2,000rpm
 - Constant Power: 260kW from 2,000-10,000rpm
- DC Power Supply
 - 900V / 1000A / 250kW
- DC Load Bank
 - 250kW in 5kW Steps
- Temperature and Flow Regulated PGW cooling loops



Characterization and Power Quality Test Procedures

TARDEC's Standardized Tests and Evaluations

POWER AND MOBILITY

● Traction Motor ● Servo Motor ● Generator ● Alternator ● DC/DC Converter

Machine Characterization

● ● ● ●

- Winding Resistance Characterization
- Inductance Characterization
- Back EMF Measurement and Characterization
- Rotor Inertia
- Spinning Losses (Iron Loss, Friction, Windage) – Spin Down Test

Drive Performance Validation/Determination

- Maximum Electrical Speed ● ● ● ●
- Maximum Starting (Stall) Torque ● ●
- Torque Ripple ● ● ●
- Speed / Torque (Current) Envelope Continuous ● ●
- Efficiency ● ● ● ● ●
- Speed vs. Power Envelope (Continuous) ● ●

Drive System Controllability

- Speed Regulation / Response ● ●
- Torque (Current) Response ● ● ● ●
- Voltage Regulation / Response ● ● ● ●

System Robustness

● ● ● ● ●

- Fault Tolerance
- Reliability Evaluation
- Conducted EMI Evaluation

Drive System Integration Practicability

● ● ● ● ●

- Safety Evaluation / Testing
- SWaP-C Evaluation
- Power Quality Compliance (MIL-PRF-GCS600A(ARMY) / MIL-STD 704/1275)
- Current Harmonics

Drive System Technology Readiness Level (TRL)

Power Quality Testing Scenarios

POWER AND MOBILITY

- 4.2.1 Voltage Regulation to Step Load.
 - *All power sources shall be bench tested with a simulated load profile (equivalent to the worst case operation of the system) to verify that electrical characteristics meet normal transient performance.*
 - 19 → 88kW resistive load bank step, 1800rpm
 - 88 → 19kW resistive load bank step, 1800rpm
 - 0 → 50kW resistive load bank step + 19kW constant power (2700 μ F), 1800rpm
- 3.1.1.11 Distortion Spectrum.
 - *The distortion spectrum is defined as the maximum allowable limit of distortion expressed in decibels above 1 microvolt as a function of frequency.*
- 3.1.1.12 Distortion Factor.
 - *The distortion factor is defined as the ratio of distortion to the steady state voltage.*
 - 19kW resistive load bank, 1800rpm
 - 88kW resistive load bank, 1800rpm
 - 50kW resistive load bank + 19kW constant power (2700 μ F), 1800rpm




Experimental Results


Experimental Results – Voltage Transient Response

POWER AND MOBILITY

4.2.1 Voltage Regulation to Step Load



19 → 87kW resistive load bank step, 1800rpm




87 → 19kW resistive load bank step, 1800rpm

Experimental Results - Steady State


POWER AND MOBILITY




Bus Voltage, 18.7kW Load Bank, 1800rpm




Distortion Spectrum, 18.7kW Load Bank, 1800rpm




Bus Voltage, 87.8kW Load Bank, 1800rpm




Distortion Spectrum, 87.8kW Load Bank, 1800rpm



Bus Voltage, 18.7kW Power Supply, 50.1kW Load Bank, 1800rpm



Distortion Spectrum, 18.7kW Power Supply, 50.1kW Load Bank, 1800rpm





Distortion Factor
0.0012
0.0015
0.0010

Machine Characterization

POWER AND MOBILITY


- Voltage Constant $K_e = 0.253 \text{ V}_{ll(pk)} / \text{rpm}$
 - Negligible variation across speed (150rpm - 2700rpm) and temperature (30C, 46.7C, 63.3C, 80C)
- Phase resistance $R_s = 10.7 \text{ m}\Omega$
- Friction (combined Coulomb (static) and viscous (dynamic))




Electrical and Mechanical Response Estimation

POWER AND MOBILITY

19 → 87kW resistive load bank step, 1800rpm



Voltage Transient: ΔV 48V and 60 msec



Speed Transient: Δ 44rpm and 570 msec

Modeling

Modeling Effort

**POWER AND
MOBILITY**



Objectives:

- 1) Evaluate the required amount of bus capacitance need for bus stability
- 2) Assess the total vehicle electrical system's compliance to MIL-PRF-GCS600A(ARMY)

Procedure:


- 1) From test data develop a model of the generator/controller system
- 2) Compare simulation results with experimental results to validate the model
- 3) Adjust generator/controller model's dc-link and apply load transients
- 4) Incorporate the generator/controller model into a vehicle electrical system model

Modeling: Experimental Setup

POWER AND MOBILITY

Models:

- Generator Controller
 - Voltage
 - Current
- Power Stage
 - Inverter
 - Dc-link
- Generator
 - dq frame of reference
 - Speed input
- Loads
 - Switchable Resistance
 - Constant Power
- Dynamometer
 - Speed Command
 - Torque response





Simulation Results and Modeling Parameter Variation

Modeling: Experimental Validation

POWER AND
MOBILITY

Comparison between Experimental and Simulation Results: Voltage Transient

70kW Resistive Step Load


70kW Resistive Step Load +Constant
Power Load (Lab Power Supply)

Modeling: Evaluation of Generator/Controller Capacitance


POWER AND MOBILITY

Comparison between 100% and 50% dc-link capacitance: Voltage Transient

70kW Resistive Step Load



70kW Resistive Step Load +Constant Power Load (Lab Power Supply)




Modeling: Simulating a Vehicle Load Cycle

POWER AND MOBILITY

Simulation of a Vehicle's Electrical System

- Generator Startup
- Transition between Passive and Active Rectification
- Voltage and Speed Transients
- Generator Controller Current Limits





Conclusions and Future Work

Conclusions

- Compliance verification with MIL-PRF-GCS600A(ARMY)
 - Established the laboratory capability to validate the results
- M&S tools for power generation system analysis and optimization
 - Characterization of a black-box power generation system, and model development
 - Evaluation of system response with varying DC-link capacitance values and EMI filter parameters, controller gains, and driveline inertia

Future Work

- Combine component models with those of an engine and high-voltage bus architecture to assess power quality at the vehicle level
- FY13 power generation system SIL and vehicle integration
- Optimization of the bus capacitance for power generation systems
- Vehicle high-voltage bus capacitance allocation