Enhanced Query Data Recorder (EQDR)– Networked Flight Recorder for the Future

Mark Wigent

AIR FORCE FLIGHT TEST CENTER EDWARDS AFB, CA

2/19/13

Approved for public release; distribution is unlimited.

AIR FORCE FLIGHT TEST CENTER
EDWARDS AIR FORCE BASE, CALIFORNIA
AIR FORCE MATERIEL COMMAND
UNITED STATES AIR FORCE

| REPORT DOCUMENTATION PAGE | Form Approved OMB No. 0704-0188 | | |
|---|--|--|--|
| Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instruction data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 13 4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to con- | In s, searching existing data sources, gathering and maintaining the of this collection of information, including suggestions for reducing 215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202- | | |
| valid OMB control number. PLEASE DO NOT RETURN YOU'R FORM TO THE ABOVE ADDRESS. 1. REPORT DATE (19-02-2013) 2. REPORT TYPE Technical | 3. DATES COVERED (From - To) | | |
| 4. TITLE AND SUBTITLE | 3/12 5/12 5a. CONTRACT NUMBER W900KK-11-C-0028 | | |
| Enhanced Query Data Recorder (EQDR)– Networked Flight Recorder for the Future | 5b. GRANT NUMBER | | |
| | 5c. PROGRAM ELEMENT NUMBER | | |
| 6. AUTHOR(S) | 5d. PROJECT NUMBER | | |
| Mark Wigent | 5e. TASK NUMBER | | |
| | 5f. WORK UNIT NUMBER | | |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) | 8. PERFORMING ORGANIZATION REPORT NUMBER | | |
| SCIENCE APPLICATIONS INTERNATIONAL CORP, 1710 McLean VA 22102-3703 | AFFTC-PA-12343 | | |
| 9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) | 10. SPONSOR/MONITOR'S ACRONYM(S) N/A | | |
| Tom Young, EA | 11. SPONSOR/MONITOR'S REPORT NUMBER(S) | | |
| 12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release A: distribution is unlimited. | | | |
| 13. SUPPLEMENTARY NOTES CA: Air Force Flight Test Center Edwards AFB CA CC: 012100 | | | |
| 14. ABSTRACT The Test Resource Management Center's (TRMC) Spectrum Efficient Technol development of the Enhanced Query Data Recorder (EQDR), a network flight recorder that is networked telemetry environment. EQDR is designed to support the "fetch" of recorded test dongoing recording of data from the test article vehicle network. | intended to meet the future needs of the | | |
| EQDR advances the state of the art of recorder technology in several ways. First, it supports thigh rate. Second, EQDR provides native support of the iNET TmNS message format. Third, retrieval, based not only on time interval and data source, but also on the content of the recorde efficient retrieval of individual parameters using indexes derived from the actual values of recorders. | EQDR enables parametric-level data ed data messages. EQDR enables selective, | | |
| The key benefits of the network data recorder as implemented in EQDR are increased flexibility with increasing demands on spectrum available for telemetered data. | sy and efficiency of test in an environment | | |
| This presentation will describe the design of EQDR and the benefits of selective data storage a telemetry. | nd retrieval in the application of networked | | |
| 15. SUBJECT TERMS iNET, TmNS, networked telemetry, Enhanced Query Data Recorder (EQDR) | | | |

17. LIMITATION

OF ABSTRACT

None

18. NUMBER

17

code)

OF PAGES

16. SECURITY CLASSIFICATION OF:

b. ABSTRACT

Unclassified

c. THIS PAGE

Unclassified

Unclassified a. REPORT

Unclassified

19a. NAME OF RESPONSIBLE PERSON

412 TENG/EN (Tech Pubs)

19b. TELEPHONE NUMBER (include area









Test and Evaluation/Science and Technology Program Spectrum Efficient Technologies

Enhanced Query Data Recorder – Networked Flight Recorder for the Future

Mark Wigent, SAIC

The author would like to thank Tom Young, SET Executing Agent, and the Test Resource Management Center (TRMC) Test and Evaluation/Science and Technology (T&E/S&T) Program for their support. This work is funded by the TRMC T&E/S&T Program through the U.S. Army PEO-STRI under contract # W900KK-11-C-0029.

Any opinions, findings and conclusions or recommendations expressed in this material are those of the authors and do not necessarily reflect the views of the TRMC T&E/S&T Program and/or the U.S. Army PEO-STRI.

Approved for public release; distribution is unlimited.

AFFTC-PA No.: XXXX



Acknowledgement



The authors would like to thank the Test Resource Management Center (TRMC) Test and Evaluation/Science and Technology (T&E/S&T) Program for their support. This work is funded by the T&E/S&T Program through PEO-STRI the CCA, Orlando, FL. contract number W900KK-11-C-0028.



T&E Need



- Network data recorder that provides instantaneous access to recorded flight data without interrupting ongoing recording
- Parametric-level data retrieval for backfill of data dropouts and ad hoc requests
- Need for spectrally efficient retransmission



S&T Challenge




- Recording data at high rates while at the same time allowing for concurrent, rapid and selective data retrieval
- Developing approaches to data indexing, storage, and retrieval that optimize overall system performance
- Developing ways to retrieve data based on complex criteria, including values of the stored data itself and derived values such as minimum, maximum, average within a time interval
- Parallelizing storage and retrieval mechanisms to enhance performance



Project Description





The Enhanced Query Data Recorder (EQDR) will improve test efficiency and safety of flight during data dropouts, non-nominal modes of operation, and inter-maneuver periods



Project Description



- Data dropouts
 - Instantaneous retrieval and retransmission of lost test data or for backfill to improve completeness of control-room data for quick-look data analysis
- Non-nominal modes of operation
 - Efficiently retrieve recorded data not previously sent to ground to better understand "trends" of non-nominal behavior observed during the test
- Inter-maneuver periods
 - Retrieval of data for quick-look analysis to ensure test objectives met and data gathered before moving on to next test point



S&T Background (slide 1 of 2)



Network Data Recorder must:

- Record and retrieve data concurrently
- Record at high enough rate to capture all data onboard the test article
- For spectrum efficiency, retrieve individual measurands quickly, with specificity and selectivity, as retransmitted data competes with real-time telemetry stream for limited bandwidth



S&T Background (slide 2 of 2)



- Existing Chapter 10 recorders store data by time interval and channel only
- Implications
 - Retrieval also limited to time and channel
 - No other selection mechanism
 - No filtering based on values of measurands themselves
- Today's current approach does not meet needs of future network data recorder



Project Scope



| Phase | Brief Description | End TRL |
|-------|--|------------|
| 1 | Determine optimal approach for data storage and retrieval | 4 |
| | Develop underlying EQDR technology components | |
| | Demonstrate effectiveness and flexibility of EQDR components in lab-based prototype (e.g. desktop environment) | |
| 2 | Port EQDR components to embedded system hardware more representative of aeronautical test environment | 5 |
| | Optimize software performance | |
| | Increase multi-threading/parallelism in execution | |
| | Characterize performance of system on embedded hardware | |
| 3 | Port EQDR technology to flight-capable hardware | 6 |
| | Flight demonstration | |
| | | |



Performance Testing Setup



Test Configuration

- Intel i7 610 @ 2.53 GHz, 4 Threads
- 8 GB RAM
- Windows 7 Professional SP1 64 bits
- Java 7.0.3 64 bits



Photo taken by SAIC


Generated Load

- Each Data Source has 2000 Data Items, average size 20 bits, 500 Hertz -> 20 Mbits/sec
- We simulate 12 Data Sources -> 240 Mbits/sec
- Maximum TmNSMessage size 80 Kbits
- 20 TmNSPackages per Data Source
- 100 Data Items per TmNSPackage



Performance 260 Mbits/sec Recording Rate (Target)






| | CPU Load |
|--------------------|----------|
| System Total avg. | 27.8% |
| EQDR Recorder avg. | 17.7% |
| MySQL avg. | 3.9% |
| EQDR Total avg. | 21.6% |



Performance at 480 Mbits/sec Recording Rate (Maximum)






| | CPU Load |
|--------------------|----------|
| System Total avg. | 50.1% |
| EQDR Recorder avg. | 35.6% |
| MySQL avg. | 7.0% |
| EQDR Total avg. | 59.0% |



Performance at 600 Mbits/sec Recording Rate (Peak)





| | CPU Load |
|--------------------|----------|
| System Total avg. | 68.5% |
| EQDR Recorder avg. | 49.3% |
| MySQL avg. | 9.7% |
| EQDR Total avg. | 59.0% |



Retransmission Performance



| | 250 Kbits/sec Retransmission | 5 Mbits/sec Retransmission | 20 Mbits/sec Retransmission |
|-----------------------------|---------------------------------|-------------------------------|--------------------------------|
| System Total avg. CPU Load | 26.6% | 27.4% | 28.2% |
| EQDR Recorder avg. CPU Load | 16.2% | 17.6% | 18.0% |
| MySQL avg. CPU Load | 3.9% | 3.9% | 3.9% |
| EQDR Total avg. CPU Load | 20.1% | 21.5% | 21.9% |
| Percentile | msec | msec | msec |
| 90% | 176.9 | 177.3 | 179.6 |
| 95% | 185.9 | 186.6 | 187.0 |
| 99.9% | 344.0 | 283.2 | 283.1 |

Concurrent recording (250 Mbits/sec) and retransmission



Summary



- The Enhanced Query Data Recorder (EQDR) will improve test efficiency and safety of flight during data dropouts, non-nominal modes of operation, and inter-maneuver periods
- Spectrum efficiency necessitates retrieval and retransmission of <u>individual</u> parameters
- EQDR enables data retrieval based on complex criteria, including values of stored data itself and derived values and statistical data
- Performance on Intel i7 610: 480 Mbits/sec recording with 60 Mbits/sec concurrent retransmission



Disclaimer



Any opinions, findings and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the Test Resource Management Center (TRMC) and Evaluation/Science & Technology (T&E/S&T) Program and/or the U.S. Army Program Executive Office for Simulation, Training, & Instrumentation (PEO STRI).