

**An Architecture for
Enabling migration of
tactical networks to future
flexible Ad Hoc WBWF**

Wroclaw, 28-29 September 2010



Report Documentation Page

Form Approved
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE SEP 2010	2. REPORT TYPE N/A	3. DATES COVERED -	
4. TITLE AND SUBTITLE An Architecture for Enabling migration of tactical networks to future flexible Ad Hoc WBWF		5a. CONTRACT NUMBER	
		5b. GRANT NUMBER	
		5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)		5d. PROJECT NUMBER	
		5e. TASK NUMBER	
		5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) ETARE		8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		10. SPONSOR/MONITOR'S ACRONYM(S)	
		11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited			
13. SUPPLEMENTARY NOTES See also ADA568727. Military Communications and Networks (Communications et reseaux militaires). RTO-MP-IST-092			
14. ABSTRACT			
15. SUBJECT TERMS			
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	SAR
			18. NUMBER OF PAGES 20
			19a. NAME OF RESPONSIBLE PERSON

- Rationale
- Operational scenarios
- Wideband Waveform Architecture requirements
- Architecture of the Wideband Waveform
- Layers features
- An example : Handling flat and/or clustered network

Rationale

- Various applications, various QoS
 - Low to high data rate : rate granularity
 - Latency from real time to background
 - Block error rate (speech \neq data)
 - Packet or connection oriented
- Interoperability
 - Nations/Coalitions
 - Manufacturers
 - Standardised interfaces and protocols
- Development, production, maintenance and deployment cost
- Product confidence
- Scarce frequency spectrum → bandwidth usage flexibility
- Facilities for future progressive insertion of new technologies (WBWF evolutivity)

Operational scenarios

- OTM (On The Move)
 - Multi-hop mobile Ad Hoc Network (self organisation of the network)
 - Fleets of terminal types : portable, vehicular, aero-mobile
- ATH (At The Halt)
 - Some of the terminals are fixed or semi-fixed, e.g. a mobile stops and deploys a mast mounted gain antenna
 - Enhanced communication capability : data rate, coverage
 - Can be used as backbone to infrastructure or other OTM parts
- NLI (Naval and Land Interworking)
 - Communications between OTM terminals and boat mounted equipment
- *(WSW - Weapon System Waveform)*

Different scenarios – Different System characteristics

- Types of missions/coalition configuration : different security levels
- Terminals behaviour : power management, transmission capabilities, support of Classes of Service, etc.
- Types of traffic with varying QoS requirements (IP services, connection oriented services, connectionless short messages, etc.)
- Types of operational theatre
 - Propagation environments, interference conditions and needs for signal discretion.
 - Coverage areas : densely (up to 200 nodes) as well as sparse
 - Types of network topology
- Frequency bands "agnostic"
 - NATO UHF band in a first step as the core band for OTM scenarios
 - other frequency bands either static configuration (NATO UHF rescheduling easily supported, or dynamic during operation (cognitive radio).


WBWF Architecture Requirements

- Several multiple access schemes TDMA OFDMA SC-OFDMA, FH-CDMA, DS-CDMA, hybrid access schemes, transitions between them
- Dynamic physical layer configuration for transport format adaptation
- QoS adaptation with radio resource management algorithms for link adaptation
- Boost future standardization of the interfaces for inter-operability
 - Inherits a similar OSI and cross layer behaviour than relevant standards and developments from the civil telecommunication domain, with adaptation to ad hoc and military constraints → fasten standardisation
 - Flexible enough to accommodate
 - progressive insertion of future radio technologies
 - Keeps encapsulated proprietary algorithms
 - Keeps encapsulated proprietary strategic matters (security, ...)

WBWF Architecture Requirements (con't)


- Optimization of spectrum efficiency and signalling consumption : several resources management strategies and protocols
 - Flat routing and radio resource management
 - Clustering of the management of radio resources :
 - a node is Cluster Head and allocates resources to its neighbours
 - but the traffic is not concentrated to it : traffic remains distributed.
 - Cluster Gateways at interconnections
 - Hierarchical clustering : nodes are organised in a hierarchical tree topology, some of them centralize
 - traffic for their upper level
 - optionally radio resource management for their lower level
- Security with the protection of
 - intra-network protocol signalling (NETSEC)
 - traffic and signalling information that transit over the radio interface (COMSEC)
 - the physical signal (TRANSEC)

Architecture of the WBWF (perimeter)




- Protocols related to the radio interface → Access stratum
 - From PHY to radio Ad Hoc routing
 - IP and legacy compatible
 - Facilities for securing WBWF protocols
- Interfaces with OAM for local and remote (OTA) supervision
- Support of (optional) GNSS interface (positioning and synchronisation features)

Architecture of the WBWF (QoS Architecture)



- Cos converted into QoS parameters at NAS service negotiation
- QoS parameters converted into routing and transmission parameters
- two levels of QoS :
 - at the radio link level between two neighbouring nodes
 - at the routing level between border nodes

Architecture of the WBWF (protocol stack)



Architecture of the WBWF (planes)

- 3 levels of information : logical, transport and physical channels
- Support of the concept of transport format
- 4 planes
 - User Plane : OTA data and signalling exchanges. Primitives at Data SAPs
 - Control Plane
 - configures the User Plane through Control SAPs
 - handles radio resource allocation and routing algorithms
 - Security Plane : security feature
 - configured according to the security level of the mission
 - Secures protocol layers through Security SAPs
 - Management Plane :
 - Local and remote management of equipment, radio interface, network
 - guarantees proper configuration and supervision of layers
 - compatible with SDR requirements
 - accesses to the protocol layers through Management SAPs

Architecture of the WBWF - layers features

- Convergence Sublayer (CS) : interface with different types of services
 - manages the sessions (IP, connection-oriented, connectionless short messages, etc.)
 - makes use of AHMM services to access a coverage area
- Ad Hoc Mobility Management (AHMM) : complement to NAS MM and routing
 - If clustering, handling of mobility between clusters or groups of clusters that belong to different areas
 - Attachment, registration, paging, etc.
 - If hierarchical clustering, handling of Location areas
 - Under control of SCM for peer entities authentication procedures
 - Makes use of RSN for access to routes

Architecture of the WBWF - layers features (2)

- Radio Sub Network (RSN): Ad Hoc Radio Networking complement NAS
 - Routing : presence detection, neighbour construction, route selection
 - Support of reactive and proactive protocols
 - If clustering, handling of clusters (creation modification, deletion)
 - RSN makes use of RRC
 - to adapt routing decisions to radio conditions
 - to effectively activate a radio link associated to a virtual route.
- Radio Resource Control (RRC)
 - Configuration for access to radio resources according (carrier frequency, transmission mode : coding scheme, ARQ protection, etc.) / QoS
 - locally to a node if flat network
 - If clustering, Cluster Head (CH) RRC instance manages resources of the nodes in its cluster, and can collaborate with its peer adjacent CHs
 - Radio link state monitoring : collect and filter lower layers measurements and reconfigure radio link accordingly

Architecture of the WBWF - layers features (3)

- If clustering : CH collects measurement from its cluster members and reconfigure radio links accordingly
- load balancing between radio link (linked to routing)
- long term (slow) power control and fast power control parameters
- algorithms depend on the multiple access scheme
- If DS-CDMA : handling of macro-diversity (linked to cooperative routing)
- TDMA and/of OFDMA : sub network synchronisation and timing advance

AHMM, RSN, RRC : belong to Control Plane

Control Plane signalling (protocols) injected in the User Plane for OTA transfer

Architecture of the WBWF - layers features (4)

- Sub Network Data Convergence (SNDC)
 - IP traffic flow adaptation to WBWF radio interface
 - IPv4, IPv6, header compression
- Broadcast/Multicast Control (BMC)
 - Broadcasting/Multicasting data flows adaptation to coverage area
 - Service notification to the target audience
- Layer 2 Radio Tunnelling Protocol (L2RTP)
 - Regenerative relaying (possibility of different transmission format between Tx and Rx)
 - Possibility to avoid unnecessary duplications (cause multipath routing)


SNDC, BMC, L2RTP : belong to User Plane

Architecture of the WBWF - layers features (5)

- Radio Link Control (RLC)
 - Data transfer over 1 radio hop
 - Transparent, Unack and Ack modes, Segmentation/reassembly, ARQ, etc.
 - Link re-establishment for temporary link suspension (loss or Silent Mode)
- Medium Access Control (MAC)
 - Real time scheduling of PHY, Survey of neighbouring signals
 - Random Access/CSMA
 - TDMA and/or OFDMA : Timing advance
 - Quality, Traffic volume measurements, Fast adaptation of Transport format
- Ciphering @MAC/RLC level : SCM
- Physical layer (PHY) : signal processing (mod, FEC, etc)
 - CDMA : macro-diversity
 - CDMA, OFDMA : fast power control MIMO processing
 - TRANSEC : in PHY or externalised depending on security architecture


Handling of flat and/or clustered networks

■ Node's role state transition diagram




Handling of flat and/or clustered networks, ex

- Transition between flat, clustered and hierarchical mode
 - reconfiguration of RRC and RSN internal algorithms
 - Activation/inhibition of protocols



Handling of flat and/or clustered networks. ex (con't)



Thank you