

U. S. AIR FORCE
PROJECT RAND
RESEARCH MEMORANDUM

EXPECTED COVERAGE WHEN ALL BOMBS ARE AIMED
AT THE CENTER OF THE TARGET

H. H. Germond

RM-191

18 July 1949

Assigned to _____

This is a working paper. It may be expanded, modified, or withdrawn at any time. The views, conclusions, and recommendations expressed herein do not necessarily reflect the official views or policies of the United States Air Force.

Report Documentation Page

Form Approved
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE 18 JUL 1949	2. REPORT TYPE	3. DATES COVERED 00-00-1949 to 00-00-1949			
4. TITLE AND SUBTITLE Expected Coverage When All Bombs are Aimed at the Center of the Target		5a. CONTRACT NUMBER			
		5b. GRANT NUMBER			
		5c. PROGRAM ELEMENT NUMBER			
6. AUTHOR(S)		5d. PROJECT NUMBER			
		5e. TASK NUMBER			
		5f. WORK UNIT NUMBER			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Rand Corporation, Project Air Force, 1776 Main Street, PO Box 2138, Santa Monica, CA, 90407-2138		8. PERFORMING ORGANIZATION REPORT NUMBER			
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		10. SPONSOR/MONITOR'S ACRONYM(S)			
		11. SPONSOR/MONITOR'S REPORT NUMBER(S)			
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	Same as Report (SAR)	8	

7-18-49

EXPECTED COVERAGE WHEN ALL BOMBS ARE AIMED
AT THE CENTER OF THE TARGET

Summary

If N bombs of individual lethal area a are independently aimed with mean radial error MRE at the center of a circular target of area A_t , the expected proportional coverage is

$$P = 1 - \frac{1}{x} \left\{ \left[-Ei(-\rho e^{-x}) \right] - \left[-Ei(-\rho) \right] \right\}$$

where $x = A_t / 4(MRE)^2$, $\rho = Na / 4(MRE)^2$, and Ei denotes the exponential integral.

Situation

This deals with a circular target, with a great number (N) of bombs independently aimed at the center of the target, and with these bombs subject to a circular Gaussian distribution law. In that case the bomb density at a distance r from the center of the target is given by

$$\frac{N}{2\pi\sigma^2} e^{-r^2/2\sigma^2}$$

where σ is the standard deviation of aim. If the lethal area of a single bomb is a , then the probability of a point at a distance r from the center not being within the lethal area of any of the bombs is given by

$$\left[1 - \frac{a}{2\pi\sigma^2} e^{-r^2/2\sigma^2} \right]^N \longrightarrow \exp \left[- \frac{Na}{2\pi\sigma^2} e^{-r^2/2\sigma^2} \right] .$$

7-18-49

The expected proportional coverage for a target of radius R is given by the integral

$$P = \frac{E(\text{Coverage})}{\pi R^2}$$

$$= \frac{2}{R^2} \int_0^R \left[1 - \exp \left(- \frac{Na}{2\pi\sigma^2} e^{-r^2/2\sigma^2} \right) \right] r dr \quad .$$

The substitution

$$t = \frac{Na}{2\pi\sigma^2} e^{-r^2/2\sigma^2}$$

reduces this to

$$P = 1 - \frac{1}{x} \int_{\rho e^{-x}}^{\rho} t^{-1} e^{-t} dt$$

where

$$\rho = \frac{Na}{2\pi\sigma^2}$$

and

$$x = R^2/2\sigma^2 \quad .$$

7-18-49

The integral may be recognized as an incomplete gamma function, or as the exponential integral. Using the notation of the latter,

$$- \text{Ei}(-y) = \int_y^{\infty} t^{-1} e^{-t} dt,$$

and

$$P = 1 - \frac{1}{x} \left\{ \left[-\text{Ei}(-pe^{-x}) \right] - \left[-\text{Ei}(-\rho) \right] \right\}.$$

When the product ρe^{-x} is very small this takes on the approximate form

$$P = \frac{1}{x} \left\{ .577216 + \log_{e} \rho - \rho e^{-x} + \dots + \left[-\text{Ei}(-\rho) \right] \right\}.$$

For large values of ρ , $-\text{Ei}(-\rho)$ approaches 0.

If instead of N , the number of bombs and a , the lethal area per bomb, one writes the bomb tonnage W and the lethal area, g , per ton, then

$$\rho = Wg/2\pi\sigma^2.$$

If the expression be written in terms of the mean radial error (MRE),

$$\begin{aligned} \rho &= Na/4(\text{MRE})^2 \\ &= Wg/4(\text{MRE})^2 \end{aligned}$$

and

$$\begin{aligned} x &= \pi R^2/4(\text{MRE})^2 \\ &= A_t/4(\text{MRE})^2 \end{aligned}$$

where A_t is the area of the target.

7-18-49

APPENDIXIllustration

If the area of the target is 40 square miles and the mean radial error is 2 square miles, then

$$\rho = Wg/4(2)^2 = Wg/16$$

$$x = 40/16 = 2.5,$$

$$e^{-x} = 0.082085,$$

and

$$P = 1 - 0.4 \left\{ \left[-Ei(-0.082055 Wg/16) \right] - \left[-Ei(Wg/16) \right] \right\}$$

Figure 1 shows the relationship between the expected coverage and the potential coverage (Na or Wg) for a mean radial error of 2 miles and for target areas of 40, 10, and 5 square miles each. From this graph one may estimate the potential bomb coverage needed to achieve a given percentage coverage for each of these targets. These have been so estimated for coverages of 30, 50, 70, and 80 percent. These figures are given in Table I. This table also gives the total bomb coverages in these cases on the assumption that there are 4 of the largest targets, 52 of the intermediate targets, and 43 of the smallest targets. In these figures it is assumed that the bombs used are of such characteristics that the lethal area is 0.001 square miles per ton of bomb.

Comparison of these figures with those presented in the Report RM-170 "Bomb Requirements for Three Target Systems", (B. Brown, M. Halperin, and A. Mood - June 14, 1949 - Confidential) shows these requirements are all greater than for the case there presented.




Figure 1
 DEPENDENCE OF EXPECTED
 COVERAGE ON POTENTIAL
 COVERAGE FOR THREE TARGETS
 (Mean Radial Error = 2 miles)



Table I

Tons of Bombs Required per Target, and Total Tonnage, for Various Expected Coverage Percentages.

Potential Coverage of Bombs: 0.001 sq.mi. per ton

Mean Radial Error: 2 miles.

No.	Area, sq. mi.	30 %	50 %	70 %	80 %
4	40	16,800	36,000	71,700	112,300
52	10	7,700	15,200	26,400	35,700
43	5	6,600	12,800	22,500	30,300
Totals		751,000	1,480,000	2,630,000	3,610,000
(From RM-170)		735,000	1,420,000	2,470,000	3,300,000