

# Acoustic Tomography With Navy Sonars

John Spiesberger  
Scientific Innovations, Inc.  
6 Derring Dale Rd., Radnor, PA 19087  
phone: 610 293 0834 fax: 610 293 0834 email: [johnsr@sas.upenn.edu](mailto:johnsr@sas.upenn.edu)

Award Number: N00014-99-M-0265 and N00014-00-C-0317

Thrust Category: Long-Range Propagation

## LONG-TERM GOALS

The long-term goal of this contract is to determine if a wide variety of Navy sonars can be used to map the sound speed field by means of acoustical tomography for use in research and surveillance.

The Sound Surveillance Systems (SOSUS) have traditionally been used for obtaining acoustical tomography data. The Navy has many more sonars than these, and their use should significantly enhance the accuracy and resolution of the maps.

## OBJECTIVES

We will utilize different types of active and passive Navy sonars, and electronically controlled acoustic sources deployed by scientists, to determine if Navy sonars can be used to make tomographic maps using a Kalman filter. In particular, we will utilize data from towed arrays, which should provide a synthetic aperture for increasing the resolution and accuracy of tomographic maps (Spiesberger *et al.*, 1997). We need to determine if the data from towed arrays have sufficient signal-to-noise ratios, and if the acoustic paths can be identified from a model, as has been demonstrated with data collected at SOSUS stations (Spiesberger and Metzger, 1992, Norris *et al.*, 1998). Our objective is to compare tomographic maps from towed arrays with those from only SOSUS stations in order to compare the advantages and disadvantages of using towed arrays.

## APPROACH


To assess the efficacy of using SOSUS stations and fixed sources for mapping the sound speed field, a four-dimensional Kalman filter is used to map sound speed from hydrographic and tomographic data collected from May through September of 1987 (Figure). The tomographic data consist of nine sections between three source and three stations. This acoustical configuration is about as much as one could hope to afford. The dots indicate the locations of all available hydrographic data at that time. The same Kalman filter will be used to map tomographic data recorded on towed arrays. The principal investigator will collaborate with Andrew Jacobson on the tomographic aspects of this program.

# Report Documentation Page

*Form Approved  
OMB No. 0704-0188*

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE <b>SEP 2000</b>	2. REPORT TYPE	3. DATES COVERED <b>00-00-2000 to 00-00-2000</b>			
4. TITLE AND SUBTITLE <b>Acoustic Tomography With Navy Sonars</b>		5a. CONTRACT NUMBER			
		5b. GRANT NUMBER			
		5c. PROGRAM ELEMENT NUMBER			
6. AUTHOR(S)		5d. PROJECT NUMBER			
		5e. TASK NUMBER			
		5f. WORK UNIT NUMBER			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>Scientific Innovations, Inc,6 Derring Dale Rd.,,Radnor,,PA,19087</b>		8. PERFORMING ORGANIZATION REPORT NUMBER			
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		10. SPONSOR/MONITOR'S ACRONYM(S)			
		11. SPONSOR/MONITOR'S REPORT NUMBER(S)			
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>Same as Report (SAR)</b>	18. NUMBER OF PAGES <b>4</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			



*Nine tomographic sections between three fixed sources and three SOSUS stations in May-September 1987. The dots give the locations of available hydrographic data during this period.*

## WORK COMPLETED

The sound speed field in the northeast Pacific has been estimated using the data shown in the figure using a Kalman filter. This work was led by Andrew Jacobson at the Pennsylvania State University as part of his Ph.D. thesis.

## RESULTS

There appear to be three principal results ascertained from the Kalman filter applied to the data shown in the figure so far. First, the tomographic and hydrographic data separately yield statistically consistent results for the average speed of sound in the 1000 by 1000 km volume outlined in the Figure in the layers from 0-100 m and 100-300 m depth. The consistency of these values supports the interpretation of the acoustic data. Second, the average speed of sound within the volume is colder than predicted from climatology with a confidence of 95%. Third, the hydrographic data yield more accurate maps of the average sound speed within the volume than from the tomographic data. This came as a surprise to the principal investigator. Until further analysis is done, not much more can be proven, but it appears that the sound speed field has a spatial structure that is better sampled from ships than from this fixed tomography array. The structure of the sound speed field is probably dominated

by Rossby waves related to El Nino and the Southern Oscillation (Spiesberger *et al.*, 1998). It is not yet known what the relative merits of hydrographic and tomographic data are when average values of sound speed are made in volumes of larger extent than 1000 by 1000 km in the upper ocean.

## **IMPACT/APPLICATIONS**

If available hydrographic data can better map the large-scales in the ocean than tomographic systems consisting of fixed sources and SOSUS stations, then it appears that it may be necessary to rely on synthetic apertures from towed arrays or towed sources to obtain the desired accuracy and resolution. A goal of this contract to ascertain if towed arrays do indeed provide much better maps of the sound speed field than either hydrographic data or data obtained from SOSUS stations and fixed sources.

## **TRANSITIONS**

The results of this research are not yet utilized by the operational Navy.

## **RELATED PROJECTS**

## **REFERENCES**

Norris, D. E., Spiesberger, J.L., and Merdes, D. W., Comparison of basin-scale acoustic transmissions with rays and further evidence for a structured thermal field in the northeast Pacific, *J. Acoust. Soc. Am.*, 103(1), 182-194 (1998).

Spiesberger, J.L., Fabrikant, A., Silivra A., and Hurlburt, H. E., Estimating climatic temperature change in the ocean with acoustic tomography: Navigational requirements, *I.E.E.E. J. Ocean. Eng.*, 22(1), 128-142 (1997).

Spiesberger, J.L., Hurlburt, H.E., Johnson, M., Keller, M., Meyers, S., and O'Brien, J.J., Acoustic thermometry data compared with two ocean models: The importance of Rossby waves and ENSO in modifying the ocean interior, *Dyn. Atm. and Oceans*, 26(4), 209-240 (1998).

Spiesberger, J.L., and Metzger, K., Basin-scale ocean monitoring with acoustic thermometers, *Oceanography*, 5, 92-98 (1992).

## **PUBLICATIONS**

Spiesberger, J.L., An updated perspective on basin-scale tomography, submitted to *J. Acoust. Soc. Am.* (2000).