

Numerical Studies of Rough Surface Scattering Models

Shira Lynn Broschat
School of Electrical Engineering and Computer Science
Washington State University
P.O. Box 642752
Pullman, WA 99164-2752
phone: (509)335-5693 fax: (509)335-3818 email: shira@eecs.wsu.edu

Award Number: N00014-97-1-0079

<http://www.eecs.wsu.edu/~shira/>

LONG-TERM GOALS

To develop a practical set of rough surface scattering strength equations for use in real-world Navy applications.

OBJECTIVES

To examine and develop theoretical surface scattering models that accurately predict acoustic wave scattering at the air-sea interface and at the ocean-bottom interface.

APPROACH

We have focused our attention on the development and examination of two theoretical models for rough surface scattering, the small slope approximation (SSA) and the non-local small slope approximation (NLSSA). The SSA has been developed for scattering from the ocean bottom, and the NLSSA has been developed for scattering at the air-sea interface.

WORK COMPLETED

The SSA has been developed for Biot theory. Scattering equations have been derived, and numerical results have been obtained for the backscattering and scattering strengths. A heuristic approach has been used to approximate the NLSSA scattering cross section, and numerical results have been obtained for the scattering strength.

RESULTS

The SSA equations for rough surface scattering using Biot theory were derived. Numerical results for the lowest-order SSA were obtained for both backscattering and bistatic scattering using a modified power law spectrum, and these results were compared with those of lowest-order perturbation theory (PT). Frequencies ranging from 100 Hz to 3 kHz were used for surfaces with *rms* heights h of 0.1 m and 1 m and a correlation length l of 10 m. The angle of incidence for the bistatic results was limited to 45° . It was found that for the smaller surface height roughness ($h = 0.1$ m), the SSA and PT give the same results for frequencies up to almost 1 kHz for both backscattering and bistatic scattering. For $h = 1$ m,

Report Documentation Page			Form Approved OMB No. 0704-0188		
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 30 SEP 2001		2. REPORT TYPE		3. DATES COVERED	
4. TITLE AND SUBTITLE Numerical Studies of Rough Surface Scattering Models				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) School of Electrical Engineering and Computer Science,,Washington State University,P.O. Box 642752,,Pullman,,WA, 99164				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.					
13. SUPPLEMENTARY NOTES The original document contains color images.					
14. ABSTRACT To develop a practical set of rough surface scattering strength equations for use in real-world Navy applications.					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES 5	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			




Figure 1: Backscattering strengths for lowest-order PT and SSA. The surface parameters $h = 1$ m and $l = 10$ m, and the frequency is $f = 3$ kHz (or $kh = 12.57$, $kl = 125.66$, where k is the wavenumber).

the SSA and PT backscatter results are in good agreement at all frequencies for incident grazing angles up to approximately 45° . For the bistatic results, the SSA and PT results agree only at low grazing angles of scatter. Figure 1 shows numerical results for the backscattering strength when $h = 1$ m and $l = 10$ m at a frequency of 3 kHz. These results were presented in Newport Beach, California, at the meeting of the Acoustical Society of America in December 2000, and a paper has been submitted to the *IEEE J. Oceanic Engineering*.

Voronovich introduced the NLSSA as a generalization of the SSA to explicitly include non-local interactions [1]. He showed that the NLSSA generally accounts for double scattering in the high frequency limit. Broschat and Thorsos presented numerical results for the lowest-order NLSSA scattering strength for two-dimensional, pressure-release surfaces [2]. Their results agreed well with Monte Carlo integral equation results and, in particular, were better than the higher-order SSA results at low forward grazing angles. However, the computational cost was extremely high, and results were unobtainable at low grazing angles. We have made an *ad hoc* approximation to the lowest-order NLSSA scattering cross section that reduces the computational complexity of the integration substantially. In addition, the first term of this approximate form is identical to that of the lowest-order SSA. Numerical results for the scattering strength were obtained for 2-D, pressure-release surfaces, and for the cases examined, the NLSSA and its approximate form give virtually the same results. Results at low grazing angles are obtainable and accurate with the approximate form. These results were presented in Newport Beach, California, at the meeting of the Acoustical Society of America in December 2000. Figure 2 shows numerical results for the bistatic scattering strength for $kh = 1$ and $kl = 1.4$ where k is the wavenumber, h is the *rms* surface height, and l is the surface correlation length. The spectrum is Gaussian, and the incident angle is 45° . Results are presented for the integral equation method (courtesy of Eric Thorsos), the SSA (both lowest order and higher order), the NLSSA, and the approximate form of the NLSSA (ANLSSA). It is believed that the surface parameters of this example give rise to double scattering.




Figure 2: Scattering strengths for the integral equation, SSA, NLSSA, and approximate NLSSA. The normalized surface parameters are $kh = 1$ and $kl = 1.4$, where k is the wavenumber, h is the rms surface height, and l is the correlation length.

IMPACT/APPLICATIONS

The development of approximate models that accurately predict wave scattering from rough surfaces is important in a number of Navy applications. For example, rough surface scattering models are needed in the simulations used by torpedo guidance and control personnel to test torpedoes. Another application for which rough surface scattering is critical is the detection of underwater mines, especially those buried in soft sediments. Other applications include ship wake detection, communications, and anti-submarine warfare. Of particular importance is that the models be as simple as possible while retaining the physical information necessary for the application.

TRANSITIONS

Much of the knowledge we have gained has been disseminated via publications and conference presentations. A search of the Science Citation Index online shows that previous ONR-sponsored work published in the *Journal of the Acoustical Society of America* has been cited about 60 times; it is believed that the current work will also be of use to others.

RELATED PROJECTS

This work is related to research in shallow water acoustics, high-frequency acoustics, and long-range propagation. The SSA Biot work is especially relevant to high-frequency, shallow water acoustics where the question of acoustic penetration into sediment is of much interest. The NLSSA work is relevant to long-range propagation since it attempts to model accurately scattering in the forward direction. Additionally, this work is related to that of several other ONR-sponsored researchers including Eric Thorsos and John Schneider.

REFERENCES

1. Voronovich, A.G., "Non-local small-slope approximation for wave scattering from rough surfaces," *Waves in Random Media*, vol. 6, pp. 151-167, 1996.
2. Broschat, S.L., and E.I. Thorsos, "A preliminary numerical study of the non-local small slope approximation," *J. Acoust. Soc. Am.*, vol. 100, p. 2702, 1996.

PUBLICATIONS

1. Fetche, C., T.Q. Yang, and S.L. Broschat, "The small slope approximation for acoustic scattering from a rough interface between a fluid and a fluid-saturated porous solid," 140th Meeting of the Acoustical Society of America, Newport Beach, California, Dec. 2000; *J. Acoust. Soc. Am.*, vol. 108, no. 4, pt. 2, Nov. 2000.
2. Broschat, S.L., "Numerical results for an approximate form of the non-local small slope approximation scattering strength," 140th Meeting of the Acoustical Society of America, Newport Beach, California, Dec. 2000; *J. Acoust. Soc. Am.*, vol. 108, no. 4, pt. 2, Nov. 2000.
3. Hastings, F.D., J.B. Schneider, S.L. Broschat, and E.I. Thorsos, "An FDTD method for analysis of scattering from rough fluid-fluid interfaces," *IEEE Journal of Oceanic Engineering*, vol. 26, no. 1, pp. 94-101, Jan. 2001.
4. Yang, T.Q., S.L. Broschat, and C. Galea, "A comparison of perturbation theory and the small slope approximation for acoustic scattering from a rough interface for a Biot medium," submitted to *IEEE Journal of Oceanic Engineering*, Jul. 2001.