AUV-Based Measurements of Turbulence in the Oregon Coastal Ocean

Hemantha W. Wijesekera College of Oceanic and Atmospheric Sciences Ocean. Admin. Bldg. 104 Oregon State University Corvallis, OR 97331-5503 Phone: (541) 737-2568 fax: (541) 737-2064 email: hemantha@coas.oregonstate.edu

Timothy J. Boyd College of Oceanic and Atmospheric Sciences Ocean. Admin. Bldg. 104 Oregon State University Corvallis, OR 97331-5503 Phone: (541) 737-4035 fax: (541) 737-2064 email: tboyd@coas.oregonstate.edu

Grant Number: N000140210104

LONG-TERM GOALS

Our long-term goals are to understand the mechanisms of turbulence and mixing in the coastal ocean environment sufficiently well to be able to incorporate mixing processes in coastal circulation models as sub-grid scale parameterizations. We plan to achieve our long-range objectives by collecting concurrent data sets of microscale, finescale, and mesoscale variables from sensors mounted on an autonomous underwater vehicle.

SPECIFIC OBJECTIVES

The main objective of this study is to demonstrate the feasibility of simultaneously collecting microstructure, hydrographic, and velocity data from an autonomous underwater vehicle (AUV) platform and ancillary data from a small boat in Oregon coastal waters.

APPROACH

The approach is to collect data off the coast of Newport, Oregon using an AUV acquired from Bluefin Robotics in combination with a sensor payload section developed at OSU. Our field program has been delayed until November, 2002, due to delays in the delivery of the AUV from Bluefin Robotics.

WORK COMPLETED

Work this year has focused on several activities: (1) interacting with Bulefin Robotics to assure delivery of a platform from which we can obtain high-quality oceanographic data, (2) development of our own sensor-payload section, (3) integration of our sensor payloads with the Bluefin platform, and (4) developing and testing strategies for successful deployment of the platform from a small vessel in our local waters.

Report Documentation Page				Form Approved OMB No. 0704-0188		
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.						
1. REPORT DATE 30 SEP 2002	2. REPORT TYPE			3. DATES COVERED 00-00-2002 to 00-00-2002		
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER		
AUV-Based Measurements of Turbulence in the Oregon Coastal Ocean				5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NUMBER		
				5e. TASK NUMBER		
				5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) College of Oceanic and Atmospheric Sciences,,Ocean. Admin. Bldg. 104,Oregon State University,,Corvallis,,OR, 97331				8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited						
13. SUPPLEMENTARY NOTES						
14. ABSTRACT Our long-term goals are to understand the mechanisms of turbulence and mixing in the coastal ocean environment sufficiently well to be able to incorporate mixing processes in coastal circulation models as sub-grid scale parameterizations. We plan to achieve our long-range objectives by collecting concurrent data sets of microscale, finescale, and mesoscale variables from sensors mounted on an autonomous underwater vehicle.						
15. SUBJECT TERMS						
16. SECURITY CLASSIFIC	17. LIMITATION OF	18. NUMBER	19a. NAME OF			
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	ABSTRACT Same as Report (SAR)	OF PAGES 6	RESPONSIBLE PERSON	

Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std Z39-18 Working with the shell of a mid-body parallel section, provided by Bluefin, we designed and assembled instrument mounts and buoyancy elements to produce a neutrally buoyant payload section (Figures 1 and 2). Instrumentation in this section includes: an upward-looking 1200 kHz ADCP, an ac-9 optical spectrometer, a downward-looking backscattering sensor, an upward-looking irradiance sensor, and a downward-looking video camera system, as well as a data logger, battery packs, and a junction box for power and data transmission to/from the AUV's main electronic housing. Some of the payload section sensors use AUV power but record data internally (e.g. the 1200 kHz ADCP), while data from other sensors (e.g. ac-9) are recorded by the AUV main vehicle computer for convenience in merging with the vehicle CTD data.

The microstructure sensing package, MicroSoar, was updated and configured for mounting at the forward end of the AUV nose cone (Figure 2). This included removing a dc-dc power converter, replacing data storage devices to minimize power usage and making a new pressure case. In order to avoid possible flow distortion by the AUV, the MicroSoar sensors are located about one foot in front of the main body of the AUV (Figure 2).

OSU and Bluefin engineering efforts were coordinated in order to satisfy the requirement of highquality CTD data. In order to minimize the effects of conductivity cell thermal inertia, a CTD sensor mount was designed which incorporates a pumped flow-collar around the conductivity cell. This CTD sensor mounting was designed at OSU and implemented at Bluefin using common CAD software.

We developed and successfully practiced AUV deployment and retrieval methods, using a dummy AUV (with approximate AUV dimensions and weight) aboard OSU's 54-foot vessel R/V Elakha. These tests were conducted off the coast of Newport, OR in July 2002.

RESULTS

We have developed a sensor payload section for use with a Bluefin Robotics Odyssey III Autonomous Underwater Vehicle (AUV).

IMPACT/APPLICATIONS

None

TRANSITIONS

None

RELATED PROJECTS

None

REFERENCES

None

PUBLICATIONS

Wijesekera, H. W., J. S. Allen, and P. A. Newberger, 2002: Modeling study of turbulent mixing over the continental shelf: Comparison of turbulent closure schemes. J. Geophys. Res. (recommended for publication).

Wijesekera, H. and T. J. Boyd, Upper Ocean Heat and Freshwater Budgets, in Encyclopedia of Ocean Sciences, J. H. Steele, S. A. Thorpe, and K. K. Turekian, eds., Academic Press, 2001.

PATENTS

None



Figure 1. Payload mid-section of AUV



[Exploded view of payload mid-section of AUV, showing sensor layout]




Figure 2. AUV with assembled payloads

[view of entire AUV showing locations of various components]