

Long-Term Autonomous Measurement of Ocean Dissipation with EPS-MAPPER

Neil S. Oakey

Bedford Institute of Oceanography

Dartmouth, Nova Scotia

Canada B2Y 4A2

phone: (902) 426-3147 fax: (902) 426-7827 e-mail: oakeyn@mar.dfo-mpo.gc.ca

Award #: N00014-01-1-0264

<http://www.mar.dfo-mpo.gc.ca/science/ocean/epsonde/welcome.html>

LONG-TERM GOALS

The long-term goal of this project is to demonstrate the feasibility of making high-quality, autonomous microstructure measurements from an ocean mooring. Successful development of such an instrument would enable researchers to obtain information in situations not currently possible with ship-based systems.

OBJECTIVES

The objective is to develop a new proof of concept instrument called EPS-MAPPER (EPSONDE Moored Autonomous Programmable Profiling Epsilon Recorder). This will enable us to autonomously collect ocean microstructure profiles for periods of several weeks in both weak winds or in heavy weather conditions unsuitable for shipboard operations. This profiler merges two well-established instruments, EPSONDE (Oakey, 1988) and Seahorse™ (Hamilton et al, 1999). The EPSONDE ocean-microstructure technology will be repackaged with modernized electronics and data logging memory and used as the payload for the Seahorse™ moored profiler.

APPROACH

The approach of this proposal is to develop the EPSMAPPER ocean microstructure profiler as a payload for the SeaHorse™ (Figure 1) to obtain estimates of mixing parameters. This instrument includes microstructure sensors to measure the dissipation using shear probes plus temperature microstructure using both a fast thermistor (FP07) and a thin film thermometer. The microstructure profiler is cushioned in flooded open cell foam in a gimballed mounting to decouple the SeaHorse motions from the profiler.

SeaHorse™ uses wave energy to move the profiler down a mooring wire to a docked position, typically 100m deep for our experiments. On a timed schedule, the package is released to free-float at typically 0.5 m/s to the surface. It is during this vertically rising profile that we measure mixing quantities. In addition to the microstructure measurements from EPSMAPPER, the package records data from a SeaBird 19Plus CTD. Velocity measurements are presently being evaluated using a Nortek Acoustic Doppler velocimeter mounted on SeaHorse™ in a collaborative study with Dr. Barry Ruddick at Dalhousie University.

Report Documentation Page

*Form Approved
OMB No. 0704-0188*

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE 30 SEP 2002	2. REPORT TYPE	3. DATES COVERED 00-00-2002 to 00-00-2002			
4. TITLE AND SUBTITLE Long-Term Autonomous Measurement of Ocean Dissipation with EPS-MAPPER		5a. CONTRACT NUMBER			
		5b. GRANT NUMBER			
		5c. PROGRAM ELEMENT NUMBER			
6. AUTHOR(S)		5d. PROJECT NUMBER			
		5e. TASK NUMBER			
		5f. WORK UNIT NUMBER			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Bedford Institute of Oceanography,,Dartmouth, Nova Scotia,Canada B2Y 4A2, , ,		8. PERFORMING ORGANIZATION REPORT NUMBER			
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		10. SPONSOR/MONITOR'S ACRONYM(S)			
		11. SPONSOR/MONITOR'S REPORT NUMBER(S)			
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT The long-term goal of this project is to demonstrate the feasibility of making high-quality, autonomous microstructure measurements from an ocean mooring. Successful development of such an instrument would enable researchers to obtain information in situations not currently possible with ship-based systems.					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 5	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Information from 1000 microstructure profiles from a depth of 100 meters to within a few meters of the surface can be recorded internally during the field program and downloaded when the mooring is recovered. This instrument is capable of recording one to three profiles per hour over a two to four week period after which time it would be recovered. At the same time, the information from the SeaBird 19 Plus CTD (sampled at 4Hz) and the Nortek ADV (sampled at 64 Hz) is recorded on another CompactFlash card by the SeaHorse controller and data logger. The data streams for all three instruments are synchronized using the SeaHorse microprocessor clock.




Figure 1: The EPSMAPPER (1) is shown mounted on the profiling engine SeaHorse™ (2) in tests in the Bedford Basin. The payload also includes a Nortek Vector ADV (3) and a Sea-Bird 19plus CTD (4).

WORK COMPLETED

The design and fabrication of the EPS-MAPPER electronic and mechanical components has been completed. The output of the 12 analog channels are converted to digital signals, processed and logged to a 1 GB CompactFlash disk. The system is controlled with a Persistor Instruments CF1 microprocessor which, in turn, has been interfaced with the microprocessor on the SeaHorse™ to allow synchronization of the data collected with the Sea-Bird CTD. The microstructure profiler is cushioned in flooded open cell foam in a gimballed mounting to decouple the SeaHorse motions from the profiler. Shear probes of a new design have been constructed to enable month-long deployments.

In October 2002, EPS-MAPPER will be moored at Station 2 on the Halifax Section of the Scotian Shelf (Figure 2) to do final tests of the prototype. This deployment will be one month in duration and will also include the Nortek Vector velocimeter as a payload on SeaHorse. A nearby mooring will

include an upward-looking ADCP to be used for inter-comparison of velocity estimates with the Nortek velocimeter data. This field experiment will provide a unique data set of coincident CTD, velocity and TKE dissipation measurements. We will analyse the microstructure data to obtain profiles of dissipation, ϵ , and temperature variance, χ_θ , in vertical segments of about two meters averaged in time over one to two hours. For these same vertical segments, we will use the density and horizontal velocity data to calculate gradient Richardson Numbers. These quantities will be used to explore the relationship between mixing rates and velocity shear, density gradient and Richardson Number. The relationship of mixing to surface forcing will be studied using wind data collected with a Minimet surface buoy at the mooring site.




Figure 2: Station 2 (44.2677N, 63.317W, Depth 150 m). on the Halifax Section is the location of the October 2002 field experiment. The black arrows represent mean currents on the Scotian Shelf.

RESULTS

These shear microstructure sensors on the EPS-MAPPER profiler are able to measure viscous dissipation, ϵ , from levels less than 10^{-8} W/kg (limited by vehicle noise and vibration) to greater than 10^{-5} W/kg (limited by sensor size). This range of dissipations is suitable for studying mixing in the upper 100 meters on the continental shelf in all but the weakest mixing periods. The temperature sensors allow one to obtain the dissipation of temperature fluctuations, χ_θ . Temperature measurements will allow the measurement of dissipations less than 10^{-8} W/kg since they are not affected by vehicle vibration or noise.

IMPACT/APPLICATIONS

The potential impact for this novel instrument design is that it would provide a new way of making ocean turbulence measurements with potential for applications that are not feasible using the current ship-based systems. This would also be a much more economical method of making such measurements.

TRANSITIONS

RELATED PROJECTS

The October 2002 field program is being jointly funded by Fisheries & Oceans Canada and this ONR project. The inclusion of the Nortek Vector and Minimet buoy in the field program are being funded by a Canadian Foundation for Climate and Atmospheric Sciences (CFCAS) grant to Dr. Barry Ruddick at Dalhousie University.

REFERENCES

Hamilton, J. M., G. Fowler and B. Beanlands, 1999: Long-term monitoring with a moored wave-powered profiler. *Sea Technology*, **vol. 40, no. 9**, 68-69.

Oakey, N.S., 1988: EPSONDE: An instrument to measure turbulence in the deep ocean. *IEEE J. Oceanic Eng.*, **13**, 124-128.