



AFRL-RH-WP-TP-2015-0030

**TRUST-BASED ANALYSIS OF AN AIR FORCE COLLISION
AVOIDANCE SYSTEM**

Joseph B. Lyons

Air Force Research Laboratory

Nhut T. Ho

Gina Masequesmay

California State University, Northridge

Kolina S. Koltai

Walter W. Johnson

NASA Ames Research Center

Mark Skoog

NASA's Armstrong Flight Research Center

Artemio Cacanindin

*Global Power Fighters Combined Test Force
Edwards Air Force Base, California*

DECEMBER 2015

Interim Report

Distribution A: Approved for public release.

See additional restrictions described on inside pages

**AIR FORCE RESEARCH LABORATORY
711TH HUMAN PERFORMANCE WING,
HUMAN EFFECTIVENESS DIRECTORATE,
WRIGHT-PATTERSON AIR FORCE BASE, OH 45433
AIR FORCE MATERIEL COMMAND
UNITED STATES AIR FORCE**

NOTICE AND SIGNATURE PAGE

Using Government drawings, specifications, or other data included in this document for any purpose other than Government procurement does not in any way obligate the U.S. Government. The fact that the Government formulated or supplied the drawings, specifications, or other data does not license the holder or any other person or corporation; or convey any rights or permission to manufacture, use, or sell any patented invention that may relate to them.

This report was cleared for public release by the 88th Air Base Wing Public Affairs Office and is available to the general public, including foreign nationals. Copies may be obtained from the Defense Technical Information Center (DTIC) (<http://www.dtic.mil>).

AFRL-RH-WP-TP-2015-0030 HAS BEEN REVIEWED AND IS APPROVED FOR PUBLICATION IN ACCORDANCE WITH ASSIGNED DISTRIBUTION STATEMENT.

Joseph Lyons, Ph.D., Work Unit Manager
Human Trust and Interaction Branch
Human Effectiveness Directorate
711th Human Performance Wing
Air Force Research Laboratory

Louise A. Carter, Ph.D., Chief
Human Centered ISR Division
Human Effectiveness Directorate
711th Human Performance Wing
Air Force Research Laboratory

This report is published in the interest of scientific and technical information exchange, and its publication does not constitute the Government's approval or disapproval of its ideas or findings

REPORT DOCUMENTATION PAGE				<i>Form Approved</i> OMB No. 0704-0188	
The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YY) 1-Dec-15		2. REPORT TYPE Interim		3. DATES COVERED (From - To) 1 Dec 13 - 1 Dec 15	
4. TITLE AND SUBTITLE Trust-Based Analysis of an Air Force Collision Avoidance System				5a. CONTRACT NUMBER In-House	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER 62202F	
6. AUTHOR(S) ~Joseph B. Lyons *Nhut T. Ho, Gina Masequesmay **Kolina S. Koltai, Walter W. Johnson ***Mark Skoog ****Artemio Cacanindin				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER H0HE	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) ~711 HPW/RHXS 2215 First St, Bldg. 20033 WPAFB, OH 45433				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) ~Air Force Materiel Command Air Force Research Laboratory 711 th Human Performance Wing Human Effectiveness Directorate Human Centered ISR Division Human Trust and Interaction Branch Wright-Patterson Air Force Base, OH 45433				10. SPONSORING/MONITORING AGENCY ACRONYM(S) 711 HPW/RHXS	
				11. SPONSORING/MONITORING AGENCY REPORT NUMBER(S) AFRL-RH-WP-TP-2015-0030	
12. DISTRIBUTION/AVAILABILITY STATEMENT Distribution A. Approved for public release.					
13. SUPPLEMENTARY NOTES Clearance 88ABW-2015-2170, on 29 April 2015					
14. ABSTRACT This case study analyzes the factors that influence trust and acceptance among users (in this case, test pilots) of the Air Force's Automatic Ground Collision Avoidance System. Our analyses revealed that test pilots' trust depended on a number of factors, including the development of a nuisance free algorithm, designing fly-up evasive maneuvers consistent with a pilot's preferred behavior, and using training to assess, demonstrate, and verify the system's reliability. These factors are consistent with the literature on trust in automation and could lead to best practices for automation design, testing, and acceptance.					
15. SUBJECT TERMS trust in automation, automation reliance, CFIT, nuisance budget, test pilot, Auto-GCAS technology, design, automation design, human-machine interaction, automated system					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT: SAR	18. NUMBER OF PAGES 7	19a. NAME OF RESPONSIBLE PERSON (Monitor) Joseph Lyons 19b. TELEPHONE NUMBER (Include Area Code) N/A
a. REPORT U	b. ABSTRACT U	c. THIS PAGE U			

Trust-Based Analysis of an Air Force Collision Avoidance System

By Joseph B. Lyons, Nhut T. Ho, Kolina S. Koltai, Gina Masequesmay, Mark Skoog, Artemio Cacanindin, & Walter W. Johnson

FEATURE AT A GLANCE:

This case study analyzes the factors that influence trust and acceptance among users (in this case, test pilots) of the Air Force's Automatic Ground Collision Avoidance System. Our analyses revealed that test pilots' trust depended on a number of factors, including the development of a nuisance-free algorithm, designing fly-up evasive maneuvers consistent with a pilot's preferred behavior, and using training to assess, demonstrate, and verify the system's reliability. These factors are consistent with the literature on trust in automation and could lead to best practices for automation design, testing, and acceptance.

KEYWORDS:

trust in automation, automation reliance, CFIT, nuisance budget, test pilot, Auto-GCAS technology, design, automation design, human-machine interaction, automated system

In military aviation, controlled flight into terrain (CFIT) is a significant cause of the loss of life for pilots (Richardson, Eger, & Hamilton, 2015). CFIT occurs when a properly functioning aircraft collides with terrain because the pilot is unaware of or unable to avoid the danger before it is too late. These collisions may occur because of the pilot's spatial disorientation (which is a cognitive precursor to CFIT) or from G-force-induced loss of consciousness.

To mitigate the precursors of CFIT, the Air Force and its collaborators in the past three decades have developed the Automatic Ground Collision Avoidance System (Auto-GCAS), which has been successfully flight-tested and is being integrated into and used in operational F-16 aircraft. Auto-GCAS is a technology that assumes control of an aircraft when an imminent collision with the ground is detected and returns control back to the pilot when the collision is averted.

We describe a case study that analyzed Auto-GCAS from a human-machine trust perspective. In particular, we explain the role of trust as related to the development and acceptance of this technology by discussing the critical drivers of trust from the perspective of test pilots who have extensive experience with Auto-GCAS. We conclude with recommendations for automated system design to foster trust of future automated systems.

WHY TRUST MATTERS

Trust, one's willingness to accept vulnerabilities in relation to another entity (i.e., technology), is a critical driver of human-machine interactions (Chen & Barnes, 2014; Lee & See, 2004; Lyons & Stokes, 2012). An individual's trust of

Engaging test pilots in the analysis reveals the qualities of the system that can lead to increased trust and, as a result, fewer crashes into the terrain.

technology will influence how much he or she will accept that technology and rely on it (Lee & See, 2004).

Pilots' acceptance of Auto-GCAS has been an ongoing concern (Richardson et al., 2015) because it is a system that takes control away from the pilot, albeit briefly. Understanding pilot trust of Auto-GCAS is critical to its operational performance because pilots have the option to turn the system on or off during operations.

Although Auto-GCAS was designed to prevent up to 98% of historical incidents, and to work only in situations when the pilot is experiencing spatial disorientation or G-force-induced loss of consciousness, pilots can misuse the system if they overtrust it and believe that Auto-GCAS will always save them. This misbelief can motivate the pilot to fly more aggressively or brazenly and to misuse Auto-GCAS as a combat tool. Thus understanding pilot trust is a crucial step in preventing pilot complacency (i.e., misuse).

The vast majority of studies focusing on human-machine trust have been conducted in laboratory settings. These studies, along with limited field studies, have identified a number of consistent predictors of trust in automation (for reviews on the topic, see Hoff & Bashir, 2015; Lee & See, 2004; Onnasch, Wickens, Li, & Manzey, 2014; Rice, 2009). Key findings from this literature show that factors such as high reliability, low error rates (particularly low false-alarm rates), transparency, familiarity, and anthropomorphic features increase trust (Hoff & Bashir, 2015).

Similarly, Lee and See (2004) suggested that to increase trust, designers should show the system's past performance and how it works, simplify algorithms to make them

understandable, highlight the system's intent, and conduct training to demonstrate the system's reliability. Research also shows that in addition to performance-based beliefs, social beliefs and institutional norms are predictive of early trust of new technologies (Li, Hess, & Valacich, 2008); thus it is important to capture the full spectrum of trust antecedents during technology evaluations with users. Yet, it is unknown how well these factors will map onto trust of test pilots using an actual automated system that employs a high level of automation during high-risk operations.

DESIGN MOTIVATIONS FOR AUTO-GCAS THAT IMPACT PILOT TRUST

Auto-GCAS was designed with three ranked design principles meant to guide the development and acceptance of the system: (1) do no harm, which requires that Auto-GCAS not cause any harm to the pilot or the aircraft; (2) do not impede, which requires the system to be nuisance free and thus not interfere with the mission; and (3) avoid collision, which requires the system to avoid collision with terrain (Richardson et al., 2015). The principal goal of Auto-GCAS is to mitigate the problem of CFIT. It is designed to do so by taking over control of the aircraft, maneuvering it away from danger, and returning control back to the pilot. This functionality can be contrasted with previous collision avoidance technologies, which primarily used warning systems and proved insufficient for mitigating CFIT (Richardson et al., 2015).

Warning-based systems were not an ideal solution to the CFIT problem because (a) they are prone to false alarms, which can degrade trust (Geels-Blair, Rice, & Schwark, 2013); (b) they require the user to manually respond and thus are not effective when the pilot is incapacitated or spatially disoriented; and (c) the pilot may not always correctly recognize a warning or correctly make the terrain collision evasion maneuver.

To overcome these limitations, Auto-GCAS was developed with a number of innovative approaches and solutions. To address the nuisance problem, a nuisance threshold was determined that ensured that in the pilot's view, Auto-GCAS would not trigger too early. This solution was accomplished by conducting a flight-test program to define what would be the maximum acceptable time before CFIT to initiate a recovery maneuver that the pilot would not consider to be a nuisance. Considering only this problem from a temporal perspective was unique, as previous efforts had used distance above the ground as a metric for nuisance.

To determine the time to CFIT at which a fly-up maneuver would not be a nuisance, pilots flew aircraft toward terrain in different conditions and manually initiated a recover as they reached their own comfort threshold. They then rated their anxiety level at recovery initiation to capture whether they had accidentally initiated the recovery sooner or later than they had intended. The duration between the point at which a recovery initiation would no longer be considered a nuisance and the point at which the aircraft's maximum performance recovery would just clear the ground is called a *nuisance budget*.



Figure 1. Head-up display image with chevrons.

Auto-GCAS was also designed with a head-up display (HUD) anticipation cue for potential activation. Providing human operators with transparency into the system's capabilities, purpose, intent, and analytical underpinnings is another way to foster trust (Lyons, 2013). In the Auto-GCAS system, operators are able to see two chevrons (i.e., the two arrows shown in Figure 1) on the HUD that dynamically intersect as the aircraft approaches a possible CFIT situation. These chevrons allow the pilot to anticipate when the system is about to engage.

TEST PILOT EVALUATION

Our research occurred in the context of a larger case study of the Auto-GCAS technology involving engineers, test pilots, and managers engaged in the Auto-GCAS program. This article focuses solely on the test-pilot portion of that case study, and specifically the factors that influenced test-pilot trust. Our general strategy for assessing test-pilot trust of Auto-GCAS involved a qualitative review of the factors that influenced their trust development of the system. This assessment was accomplished through survey and interview techniques.

First, test pilots responded to an online survey that assessed their general attitudes toward Auto-GCAS, initial perceptions of the system, experiences with the system, and open-ended questions about the factors that influenced their trust or distrust with the system. (The majority of questions in the online survey involved perceptions of engineers and managers associated with the Auto-GCAS program and are out of the scope of this article.) The survey data formed the basis for follow-up interview questions relating to what factors influenced the pilots' trust over time.

Experimental test pilots ($N = 15$) from Edwards Air Force Base participated in a series of interviews. Two to four interviewers were present, and the interviews lasted approximately 20 to 60 min, depending on the availability of the pilots. The interview focused on revealing pilot attitudes toward Auto-GCAS, identifying the trust levels among test pilots of Auto-GCAS, and discussing reasons for trust or distrust of Auto-GCAS. The interviews were recorded and

transcribed using NVivo software. The interview team then reviewed the files and looked for common themes and trends using a grounded-theory approach.

SUBSET OF FACTORS SHAPING TEST PILOT TRUST OF AUTO-GCAS

The following sections represent the factors that influenced trust of Auto-GCAS among the test pilot community.

Avoiding false alarms. The primary driver of trust among test pilots was the demonstrated ability of Auto-GCAS to avoid false alarms (i.e., the creation of the nuisance budget). The nuisance criteria were found to be governed by two principles for an avoidance maneuver to be acceptable to a pilot: It must be both aggressive and timely – aggressive in the sense that the avoidance is using a significant amount of the aircraft’s available maneuvering capability, and timely in the sense that it does not begin the maneuver so early that it is deemed a nuisance or so late that the aircraft does not have sufficient maneuverability to avoid hitting the surrounding terrain.

The pilots apply a safety buffer based on their uncertainty of the situation (rapidly changing aircraft attitude or conditions, high turbulence, poor visibility, etc.) to determine when the aggressive avoidance maneuver should be initiated. Because the aggressive portion of the criteria embeds within it the aerodynamics unique to a vehicle, the timely portion of the criteria remains the same for all aircraft. We also found that the timely criterion could be approximated by a single equation, with the maximum acceptable time being the point at which the aggressive recovery will just miss the ground. This finding is consistent with research on trust in automation showing how false alarms can degrade trust (Geels-Blair et al., 2013; Hoff & Bashir, 2015; Rice, 2009).

Performance of the system. A second factor driving test-pilot trust was the knowledge of the system’s reliability. Auto-GCAS was designed to approach 98% reliability in preventing CFIT. The test pilots experienced this high reliability in operational testing, which was clearly to the benefit of their trust in Auto-GCAS. This finding is consistent with prior research showing that performance is a significant predictor of human-machine trust (Hancock et al., 2011; Hoff & Bashir, 2015; Lee & See, 2004).

Transparency. Automation transparency, in the form of chevrons, was an important topic that emerged in this study because it affects how pilots develop and calibrate their trust of Auto-GCAS. The test pilots reported that the chevrons enabled them to better anticipate the behavior of Auto-GCAS, consistent with prior views of transparency (Lyons, 2013).

However, we must approach this issue with some degree of caution given the context of Auto-GCAS. It is possible, for instance, given that Auto-GCAS is a safety system, that pilots (who are faced with situations that require intense aerial maneuvers) could use the chevrons to operate their aircraft with

greater risk, as the chevrons provide enhanced awareness of one’s relative proximity to the ground. Such behaviors would conflict with the overall intent and design of Auto-GCAS, both of which assume that pilots will fly their aircraft in the same manner that they had prior to the availability of Auto-GCAS. Authors of future research should explore the role of transparency within safety systems, specifically within the context of Auto-GCAS.

Familiarity of the maneuver. Test pilots reported strong positive perceptions of the Auto-GCAS maneuvering capabilities. Auto-GCAS was designed to engage a wings-level, 5-G pull-up, which is consistent with pilot training and behavior. This familiarity supported stronger trust perceptions among the test pilots.

CONCLUSION AND LESSONS LEARNED

In this article, we discussed the Air Force’s Auto-GCAS system and highlighted several of the drivers of trust of this system from the perspective of test pilots. All these factors correspond to variables noted in the trust literature; from a real-life context in which humans interact with automation, they lend applied support to the literature. Additionally, we described a few design features used by the Auto-GCAS program that resulted in higher trust perceptions among test pilots. Although the current results are qualitative in nature, they provide a rich set of inputs from an operational community regarding the factors that shape trust in automation.

The lessons learned in conducting this research are both methodological and design based in nature. The study reinforced the notion that flexibility and access to applied participants are keys to success in researching applied systems. The test pilots had rigorous schedules, and the research team had to adapt to the pilots’ constraints. Second, none of this research is possible without the support of key stakeholders to foster access to the applied participants.

From a design standpoint, it is clear that the issue of false alarms was paramount to the pilots. These individuals are at the “tip of the spear” of military operations, and the last thing they wanted was interference from an automated system. Once these concerns were subdued, the test pilots became much more accepting of the technology. This finding reinforces the importance of user-centered design, as the guiding principle for the collision avoidance algorithm was based on the pilot’s nuisance budget.

A second lesson learned involves giving users an opportunity to experience the system in action, as this appeared to be a key driver of test-pilot trust of the system. Third, designing the system to provide cues related to activations was useful. This form of real-time transparency was an important driver of trust in our study. Finally, the maneuver designed into the system was one familiar to pilots, which also contributed to their trust of the system. Designers of future automated systems might consider incorporating these elements into their design process, lest they be faced with a distrustful user base.

REFERENCES

Chen, J. Y. C., & Barnes, M. J. (2014). Human-agent teaming for multi-robot control: A review of the human factors issues. *IEEE Transactions on Human-Machine Systems*, 44, 13–29.

Geels-Blair, K., Rice, S., & Schwark, J. (2013). Using system-wide trust theory to reveal the contagion effects of automation false alarms and misses on compliance and reliance in a simulated aviation task. *International Journal of Aviation Psychology*, 23, 245–266.

Hancock, P. A., Billings, D. R., Schaefer, K. E., Chen, J. Y. C., de Visser, E. J., & Parasuraman, R. (2011). A meta-analysis of factors affecting trust in human-robot interaction. *Human Factors*, 53, 517–527.

Hoff, K. A., & Bashir, M. (2015). Trust in automation: Integrating empirical evidence on factors that influence trust. *Human Factors*, 57, 407–434.

Lee, J. D., & See, K. A. (2004). Trust in automation: Designing for appropriate reliance. *Human Factors*, 46, 50–80.

Li, X., Hess, T. J., & Valacich, J. S. (2008). Why do we trust new technology? A study of initial trust formation with organizational information systems. *Journal of Strategic Information Systems*, 17, 39–71.

Lyons, J. B. (2013). Being transparent about transparency: A model for human-robot interaction. In D. Sofge, G. J. Kruijff, & W. F. Lawless (Eds.), *Trust and autonomous systems: Papers from the AAAI Spring Symposium* (pp. 48–53). Menlo Park, CA: AAAI Press.

Lyons, J. B., & Stokes, C. K. (2012). Human-human reliance in the context of automation. *Human Factors*, 54, 111–120.

Onnasch, L., Wickens, C. D., Li, H., & Manzey, D. (2014). Human performance consequences of stages and levels of automation: An integrated meta-analysis. *Human Factors*, 56, 476–488.

Rice, S. (2009). Examining single and multiple-process theories of trust in automation. *Journal of General Psychology*, 136, 303–319.

Richardson, C. E., Eger, C. A., & Hamilton, T. R. (2015, January). *Automatic collision avoidance system testing*. Paper presented at the AIAA Modeling and Simulation Technologies Conference, Kissimmee, FL.



Joseph B. Lyons is technical adviser for the Human Trust and Interaction Branch within the 711 Human Performance Wing at Wright-Patterson AFB, Ohio. He received his PhD in industrial/organizational psychology from Wright State University in Dayton, Ohio, in 2005. His research interests include human-machine trust, interpersonal trust, leadership, and social influence. From 2011 to 2013, he served as a program officer for the Air Force Office of Scientific Research.



Nhut T. Ho is a professor of mechanical engineering at California State University, Northridge, where he is director of the Systems Engineering Research Lab. His research interests and projects include human-automation trust, modeling and creation of principles for designing transparency in human-automation teamwork systems, and case and field studies to determine how fighter pilots interact with and accept automatic collision avoidance systems. He obtained his MS and PhD from MIT.



Kolina S. Koltai is a research associate at the NASA Ames Research Center in the Flight Deck Display Research Laboratory under the tutelage of Nhut Ho and Walter Johnson. Her research focus is taking social-psychological principles and applying them to studying human-computer interaction issues. She is exploring the relationship between trust and automation transparency.

Her previous research examined how culture, organizations, and automation capability affect trust and reliance in automation.



Gina Masequesmay is chair of the Asian American Studies Department at California State University, Northridge. She filed her doctoral dissertation in sociology at the University of California, Los Angeles, in 2001.



Mark Skoog works for NASA's Armstrong Flight Research Center as the principal investigator for its Automatic Systems Project Office. He leads the Collision Avoidance Technical Stewardship Group for the Office of the Undersecretary of Defense for Personnel and Readiness. He graduated from California Polytechnic State University at San Luis Obispo. Over the past 34 years he has supported numerous NASA and Air Force fighter and unmanned aerial vehicle research efforts.



Artemio (Tim) Cacanindin is chief engineer at the Global Power Fighters Combined Test Force, Edwards Air Force Base, California, which is responsible for the development flight-testing of new capabilities for F-15, F-16, and T-38 aircraft, including Auto-GCAS on the F-16. He has worked on the flight test programs of many platforms during his career. He received his BS and MS degrees in aeronautics and astronautics from the University of Washington, Seattle.



Walter W. Johnson is a research psychologist with NASA's Human Systems Integration Division at the Ames Research Center and leads the Flight Deck Display Research Laboratory there. While at NASA, his research has focused on the development of new operational concepts for the U.S. air traffic management system and on the design of airside and groundside interactive displays and decision support tools that support those concepts.

Author(s) Note: The author(s) of this article are U.S. government employees and created the article within the scope of their employment. As a work of the U.S. federal government, the content of the article is in the public domain.

Funding statement: This research was funded in part by the Air Force Office of Scientific Research via NASA Armstrong Flight Research Center Contract No. NNX10AI62A.



DOI: 10.1177/1064804615611274