

NON-PARABOLIC MARCHING ALGORITHM FOR SOUND FIELD CALCULATIONS IN THE INHOMOGENEOUS OCEAN WAVEGUIDE

Alexander G. Voronovich

NOAA/ERL/ETL, R/E/ET1, 325 Broadway, Boulder, CO 80303
phone: (303)-497-6464 fax: (303)-497-3577 email: agv@etl.noaa.gov

Award #: N00014-96-F-0086

Long-range propagation

LONG-TERM GOALS

The long-term purpose is to develop a new effective algorithm for sound field calculations in the inhomogeneous ocean waveguide. This algorithm will not involve parabolic approximation and can be considered as principally exact (at least for 2-D inhomogeneities of the sound speed field). Thus, it can be used in cases when the phase of the acoustic field should be calculated accurately enough. It will be able to calculate not only acoustic field but the entries of scattering matrix for the modes of the ocean waveguide as well. The case of uneven fluid bottom with losses will be also considered. Thus, the algorithm will be able to provide exact solutions of the wave equation with two-dimensional inhomogeneities both for shallow- and deep-water situations.

SCIENTIFIC OBJECTIVES

To develop an algorithm effectively calculating Jost solutions (JS, see below) for the inhomogeneous waveguide in the deep water case without attenuation. To express the Green function of the wave equation and scattering matrix (S-matrix) for the ocean waveguide in terms of JS. Generalize the algorithm to the case of uneven bottom with losses (shallow water case). To incorporate into the algorithm calculation of travel times of different modes. To develop appropriate code for the acoustic field and S-matrix calculations and to check it with the help of suitable benchmark problems.

APPROACH

First, the solution of wave equation is expressed in terms of so called Jost solutions. The latter are specific solutions of the 2-D wave equation representing a generalization of normal modes for the case of inhomogeneous waveguide. JS can be calculated by "marching" which in contrast to PE methods starts from large distances and migrates towards the source. The crucial point of the approach is the way of recalculating the field at each step of backward "marching". In contrast to Evans's coupled-mode method appropriate vertical slices of the waveguide are not assumed to be horizontally homogeneous, and relatively weak mode interaction within each slice is taken into account in a perturbative manner. This allows one to increase the value of horizontal step

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 30 SEP 1997		2. REPORT TYPE		3. DATES COVERED 00-00-1997 to 00-00-1997	
4. TITLE AND SUBTITLE Non-parabolic Marching Algorithm for Sound Field Calculations in the Inhomogeneous Ocean Waveguide				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Oceanic and Atmospheric Administration (NOAA),Environmental Technology Laboratory,325 Broadway,Boulder,CO,80303				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 3	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

significantly. Energy conservation and reciprocity relation provide convenient means of checking the accuracy of calculation and choice of the step value.

WORK COMPLETED

The JS for the case of ocean waveguide were introduced, and the expression for the field and S-matrix for normal modes is expressed in terms of JS. The reciprocity relation and unitarity condition are formulated in terms of S-matrix. In particular, the resulting expression for the acoustic field is reciprocal. The method of recalculating of the field from a vertical cross-section to the following one is developed. Appropriate code for deep water case was successfully checked with the help of benchmark problem. During 1997 most of the efforts were made towards generalization of the algorithm to the case of penetrable lossy fluid bottom. Appropriate theory was developed and the expression for the scattering matrix in this case was obtained. This task is much more difficult computationally, as it is related to calculation of complex spectrum of acoustic modes at each step. Newton's iterations based on the previous step are ineffective in the vicinity of critical depths, and some modifications to the mode calculations were evoked. Appropriate code was developed and numerical simulations started.

RESULTS

It is shown, that for typical deep-water situations the value of horizontal step (which is chosen automatically) varies from a few kilometers (for slow-varying "adiabatic" parts of the waveguide) up to a few hundred meters (for extremely fast-varying parts of the type of frontal zones). Effectiveness of the approach (in terms of the number of CPU operations) as compared to Evans's couple mode method was estimated. It was shown, that for typical mesoscale inhomogeneities this approach appears to be more effective by a factor of few hundreds. The code seems to be much faster as compared to COUPLE and IFDPE codes. The objective criterium for numerical estimation of the accuracy of different methods based on comparison of S-matrixes is also suggested. The shallow-water case due to sharp discontinuities of density and sound speed requires for accurate treatment relatively large number of modes.

IMPACT/APPLICATIONS

Developed algorithm and code can be used for numerical simulations of the sound propagation in the inhomogeneous ocean waveguide. This algorithm is exact, and can be especially useful when precise values of complex acoustic field is required. It is very effective numerically and does not require extensive computational resources (can be successfully run on PC).

RELATED PROJECTS

The developed non-parabolic algorithm was used for numerical simulation for the project "A New Scheme for Acoustical Tomography of the Ocean".

REFERENCES

A.G. Voronovich (1996): Non-parabolic marching algorithm for sound field calculation in the ocean waveguide," J. Computational Acoustics, v.4, No. 4, 399-423.