



# Dual Media Filtration System for Reducing Pollutants in Storm Water Runoff

**Naval Facilities Engineering Service Center**  
1100 23<sup>rd</sup> Avenue  
Port Hueneme, CA 93043-4370

**Presenter:**  
Gary Anguiano  
805.982.1302  
[Gary.anguiano@navy.mil](mailto:Gary.anguiano@navy.mil)

# Report Documentation Page

Form Approved  
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE <b>MAY 2009</b>		2. REPORT TYPE		3. DATES COVERED <b>00-00-2009 to 00-00-2009</b>	
4. TITLE AND SUBTITLE <b>Dual Media Filtration System for Reducing Pollutants in Storm Water Runoff</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>Naval Facilities Engineering Command, Engineering Service Center, 1100 23rd Ave, Port Hueneme, CA, 93043</b>				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES <b>Presented at the NDIA Environment, Energy Security &amp; Sustainability (E2S2) Symposium &amp; Exhibition held 4-7 May 2009 in Denver, CO.</b>					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>Same as Report (SAR)</b>	18. NUMBER OF PAGES <b>36</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			

# Outline



- **Background**
- **Dual Media Treatment Technology Demonstration**
- **Technology Transition**

# Background



- The Navy is required to self-monitor their storm water discharges, identify and install best management practices (**BMPs**) appropriate to their facilities.
- The EPA is establishing guidelines for total maximum daily loadings (**TMDL**) for impaired water bodies. This will result in stricter discharge limits being placed on Navy storm water discharges.
- Navy industrial activities and other DoD components will be forced to implement storm water treatment systems in order to comply with stricter permit requirements.

# Background



Navy industrial sites have limited real estate and limited resources.

The ideal storm water treatment system concept should:

1. Have a low capital cost
2. Be easy to install
3. Require little land area
4. Be inexpensive to maintain
5. Enable sites to comply with permit requirements

# Storm Water Treatment Technology Demonstration



## Project Approach

- Identify Navy industrial site storm water runoff permit requirements.
- Analyze storm water runoff characteristics.
- Evaluate commercially available structural BMP treatment technologies.
- Demonstrate new storm water treatment technology to address Navy industrial site specific requirements.
- Transition technology.

# Navy Site Specific Storm Water Permit Requirements




The Naval Regional Recycling Center (**NRRC**) was selected because they must comply with an order from the California Regional Water Quality Control Board (**CRWQCB**) that requires them to:

- (1) pass a 96-hour acute toxicity test,
- (2) reduce copper discharges to less than 63 ppb, and
- (3) reduce zinc discharges to less than 117 ppb.

In the past, NRRC discharges significantly exceeded the metals discharge limits and failed the toxicity tests.

# Naval Regional Recycling Center (NRRC) San Diego



Location of demonstration

Storm drain system

Location of Test Site



# Previous Method of Handling Storm Water Runoff at NRRC



# Characterize Storm Water Runoff



## Simulated Rain Event at NRCC



# Storm Water Runoff from Simulated Rainfall Event



<u>Metals</u>	<u>Runoff Level (µg/L)</u>	<u>Hydrant Level (µg/L)</u>	<u>Permit Limit (µg/L)</u>
Antimony	138	7	
Arsenic	18	ND	168
Beryllium	ND	ND	
Cadmium	<b>136</b>	ND	<b>15.9</b>
Chromium	102	ND	
Copper	<b>3,350</b>	5	<b>64</b>
Lead	<b>1,200</b>	5	<b>82</b>
Mercury	ND	ND	2.4
Nickel	245	ND	1417
Selenium	14	6	238
Silver	4	ND	32
Thallium	ND	ND	
Zinc	<b>6,860</b>	<b>169</b>	<b>117</b>
Aluminum	<b>19,900</b>	9	<b>750</b>

# Evaluate Available Structural Best Management Practices



- Compliance with the CRWQCB order will require a significant investment by the Navy.
- Commercial off the shelf (**COTS**) technologies are expensive. (> \$57K per acre of drainage area)
- COTS technologies have not reliably passed toxicity test.

# Evaluate Available Structural Best Management Practices



## Large scale StormWater Management, Inc. Installation

This 165 cartridge SMI installation at NASSCO costs \$530K



# Storm Water Treatment Technology Demonstration




NFESC developed and tested a storm water runoff treatment system that meets the stated Navy industrial site requirements. The system is similar to a sand filter. However, instead of using sand as the filter medium, heavy metals from storm water are removed by flowing the runoff through a bed of special filter-adsorption materials.

# Storm Water Treatment System Overview



**Pollutants in storm water will be removed through an innovative three staged filter process.**



# Adsorption Media Tested



<u>Organic Materials</u>	<u>Active Minerals</u>	<u>Inert Minerals</u>	<u>Proprietary Materials</u>	<u>Others</u>
Loose peat moss	A-400 activated alumina	Perlite	Forager sponge cubes	Iron chips and filings
Hardwood chips	FS-50 activated alumina	Washed plaster's sand	Dynaphore granules	Sodium alginate beads
Bone char	DD-2 activated alumina	Washed concrete sand	Ancor M-20/80 zero valence iron	geotextile
Anthracite	Chabasite	Washed well-packing gravel	Stormwater Management Metal Rx	
Sulphonated peat moss	Manganese green sand		Environmental H2O, LLC White Karbon	
	Ilmanite			
	Glauconite			



# Treatment Media Test Stands



**Test Column Setup**



**Dual Chamber Test Device**

Tanks hold runoff water from NRRC; cylinders contain filter/adsorption media

# Media Selection



The performing media selected are: activated alumina with surface coating of iron oxide and bone char. Both are readily available and inexpensive.

- **Bone char** is used to adsorb heavy metals, fluorides, and iron .
- **Activated alumina** is commonly used to remove arsenic and fluoride.

# 1/20<sup>th</sup> Scale Model Test Setup



Scale model installed at NRRC

# 1/20<sup>th</sup> Scale Model Treatment Test Results



<b>Metal</b>	<b>Influent mg/L</b>	<b>Effluent, mg/L</b>	<b>Permit Limit, mg/L</b>	<b>Detection Limit, mg/L</b>
<b>Aluminum</b>	<b>.330 - .860</b>	<b>ND - 0.100</b>	<b>.750</b>	<b>0.04</b>
<b>Cadmium</b>	<b>ND - .012</b>	<b>ND</b>	<b>.0159</b>	<b>.008</b>
<b>Chromium</b>	<b>ND - .018</b>	<b>ND</b>	<b>.020</b>	<b>.008</b>
<b>Copper</b>	<b>1.90 – 4.70</b>	<b>ND – 0.021</b>	<b>.064</b>	<b>.006</b>
<b>Iron</b>	<b>3.00 – 8.20</b>	<b>ND – 0.170</b>	<b>1.0</b>	<b>.008</b>
<b>Lead</b>	<b>0.150 - .360</b>	<b>ND</b>	<b>.082</b>	<b>.014</b>
<b>Zinc</b>	<b>.680 – 1.70</b>	<b>ND – 0.041</b>	<b>.117</b>	<b>0.01</b>

**Test Method EPA 200.7**


**Below practical detection limit - ND**




# Basic Design Overview




Porous pavement curb acts as coarse filter

Pre-cast concrete vault



-  Sand
-  Bone char
-  Activated alumina

# Cell Water Level Control



Mechanical Level Control Valve

# Containment Cell Installation



# Drain Manifold Installation





# Backfilling and Pouring Concrete



# Sampler and Instrumentation Shed



- Samples are taken from influent and effluent.
- Takes first flush and composite samples.

# Completed System



• Installation completed  
4/22/2005.

# Results



Date	Total Rainfall (inches)	First Flush Intensity (in/hr)	Survival 100% Concentration (%)	First Flush Influent/Effluent Cu (µg/L)	Cu % Removal	First Flush Influent/Effluent Zn (µg/L)	Zn % Removal
3/28/06	0.35	0.17	95	1170 339	71	1480 343	77
4/14/06	0.16	0.07	85	550 201	63	981 711	28
4/23/06	0.11	0.08	60 <sup>3</sup>	351 228	35	1270 913	28
5/22/06	0.60	0.4	90	987 397	60	2620 1140	57
10/16/06 <sup>1</sup>	0.40	0.06	45 <sup>4</sup>	1070 401	63	4810 1330	72
1/29/07	0.85	0.11	85	488 85	83	1960 277	86
2/18/07 <sup>2</sup>	0.9	0.06	100	307 63	79	1170 180	85
2/22/07	0.2	0.19	100	143 29	80	572 102	82
2/27/07	0.24	0.07	97	356 34	91	1870 167	91
3/22/07	0.06	0.25	100	335 81	76	928 222	76
4/20/07	0.53	0.18	100	342 88	74	1260 251	80

# Results



	Influent / Effluent, Average Event Mean Concentration ( $\mu\text{g/L}$ ) <sup>1</sup>						
Date	Al	Cd	Cu	Fe	Pb	Ni	Zn
2/18/2007	893 / 141	10 / 1	150 / 24	1229 / 219	43 / 5	11 / 2	561 / 74
2/22/2007	651 / 92	7 / 1	116 / 20	826 / 106	28 / 2	9 / 3	515 / 71
2/27/2007	952 / 220	13 / 2	181 / 29	1242 / 285	51 / 5	14 / 3	865 / 129
3/22/2007	3180 / 265	11 / 3	335 / 81	5350 / 524	66 / 9	29 / 8	928 / 122
4/20/2007	739 / 142	7 / 1	210 / 45	1084 / 208	38 / 5	15 / 3	738 / 113
<b>Last 5 Storm Events Efficiency Ratio</b>	1283 / 172 (87)	10 / 2 (83)	198 / 40 (80)	1946 / 268 (86)	45 / 5 (88)	16 / 4 (75)	721 / 122 (83)

1. ER in parenthesis.

# Other Applications



# Other Applications



# Potential Sites



- **Industrial areas**

- Recycling Centers
- DRMOs
- Drydocks & Boatyards
- Maintenance Facilities
- Storage yards
- Facilities with copper gutters, galvanized roofs & fences.



# Benefits



1. Enable sites to comply with permit requirements.
2. Treatment system has a low capital cost. (\$20,000 per acre of watershed)
3. Virtually no operational/maintenance costs.
4. Requires little land area.
5. Installation similar to other commercially available systems.

# Technology Transfer



- Technology is patented and will be commercially licensed.
- The NAVFAC-ESC Technology Integration Team is actively identifying potential user of this technology.
- NAVFAC-ESC has published project results.

# Publications



## Publications:

- R.E. Kirts, M.E. Foreman, and G.D. Anguiano, *Removal of Toxic Metals from Storm water Runoff at Naval Installations*, NAVFAC Technical Report TR-2256-ENV, November, 2004.
- G.D. Anguiano, and M.E. Foreman, *Low Impact Technologies to Reduce Pollution from Storm Water Runoff*, NAVFAC Technical Report TR-2300-ENV, September, 2008.
- R. E. Kirts, et. al., *METHOD AND MATERIALS TO REDUCE POLLUTION CAUSED BY COPPER, ZINC, AND OTHER METALS IN WASTE WATER* , Patent application, November, 2004,

# Acknowledgements



## **Funding provided by:**

- Navy Pollution Abatement Ashore Technology Demonstration/Validation Program (0817) for BMP Pilot study.
- Environmental Security Technology Certification Program (ESTCP) for a large-scale demonstration of filter-adsorption storm water treatment technology.

## **Site support provided by:**

- Commander Navy Region Southwest
- Engineering Field Division Southwest
- San Diego Navy Regional Recycling Center San Diego

# Contact Information



**Naval Facilities Engineering Service Center (NFESC)**  
**1100 23<sup>rd</sup> Avenue**  
**Port Hueneme CA 93043-4370**

Gary Anguiano P.E. (Principal Investigator)  
(805) 982-1302  
gary.anguiano@navy.mil

Mark Foreman (Project Engineer)  
(805) 982-2644  
mark.foreman@navy.mil

Ron Tsumura (Technology Transfer)  
(805) 982-1679  
ron.tsumura@navy.mil