

SEISMIC SONAR TECHNOLOGY

Dr. Thomas Muir, PI
U.S. Naval Postgraduate School
Departments of Physics and Undersea Warfare
Spanagel Hall 146A and Root Hall 200A
Monterey CA 93943
ph (408) 656 2185, (408) 656 1017 fax (408) 656 3679 tgmuir@nps.navy.mil

Dr. Steven Baker, Co-PI
Department of Physics
Naval Postgraduate School
Spanagel Hall 145
Monterey CA 93943
ph (408) 656 2729 baker@physics.nps.navy.mil

Research Project 03201
97 PR 05429-00
Shallow Water Acoustics

LONG-TERM GOAL

Develop the basic concepts of an active, seismic sonar for the detection of mines and/or unexploded ordnance buried in the surf and near-surf zone.

OBJECTIVE

Test the hypothesis that seismic interface waves can be discretely excited and can be reflected off buried objects, producing detectable echoes.

APPROACH

Develop electromechanical transducers having two, controllable, degrees of vibrational freedom that can discretely excite seismic interface waves. (These are vector waves that require both a horizontal and vertical component in order to be excited.) Test and evaluate these transducers at the Navy beach on Monterey Bay (and elsewhere), after ground truth and noise measurements are made. Develop a rudimentary seismic sonar apparatus for echo ranging tests.

LT Frederick E. Gaghan, USN, an EOD officer, has undertaken this research topic for his MS thesis, which along with his other academic achievements, will earn him masters degrees in Physics and in Engineering Acoustics. LT Gaghan is well into learning the art of military seismology, the theory of elasticity, transducer engineering, and measurement science. He is at the top of his class at the Naval Postgraduate School, and he has also taken and passed the qualifying exam for a PhD in Physics.

Report Documentation Page

Form Approved
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE 30 SEP 1997	2. REPORT TYPE	3. DATES COVERED 00-00-1997 to 00-00-1997			
4. TITLE AND SUBTITLE Seismic Sonar Technology		5a. CONTRACT NUMBER			
		5b. GRANT NUMBER			
		5c. PROGRAM ELEMENT NUMBER			
6. AUTHOR(S)		5d. PROJECT NUMBER			
		5e. TASK NUMBER			
		5f. WORK UNIT NUMBER			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Postgraduate School, Departments of Physics and Undersea Warfare, Monterey, CA, 93943		8. PERFORMING ORGANIZATION REPORT NUMBER			
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		10. SPONSOR/MONITOR'S ACRONYM(S)			
		11. SPONSOR/MONITOR'S REPORT NUMBER(S)			
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 3	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

WORK COMPLETED

As of November, 1997, we have developed and tested one, two degree of freedom seismic source, utilizing accelerometer devices, both in a laboratory sand tank and on the NPS baseball diamond. This device utilized two small accelerometers in a transmit mode, mounted to a base plate at a 90 degree angle, the base plate being the coupler to the sediment. We have also developed and tested two other types of two degree sources: one, a bimorph ceramic design, and the other an electromagnetic actuator design. The bimorph consists of two oppositely polarized ceramic wafers, bonded together, and anchored at one end in a cantilevered configuration. The sediment is driven at the opposite end of the device's anchor, much like the motion of a diver's flipper. Bimorphs are capable of producing extremely wide band, short pulse length signals at force level weights measured in the tens of grams. Actuators are normally used to produce large scale movements for industrial applications, but their utility in micro-seismology is quite appealing, since they can a) produce excitations at constant forces, or b) at constant displacements, and c) at force level weights measure in kilograms.

As of this date we have also developed a seismo acoustic testbed at the Navy beach at NPS, where we have made ground truth measurement on seismic interface wave velocities, and on the ambient noise caused by crashing waves.

RESULTS

Although our evaluation of the aforementioned seismic sources is incomplete at the present time, we have enough preliminary data that indicates we will have more than enough amplitude output from the actuators to liquify (overdrive) the sediments, albeit with unknown bandwidth, and that we will have much less amplitude with the bimorphs, albeit with ample bandwidth.

Our ground truth measurements at the NPS beach on Monterey Bay indicate excellent sediment conditions for seismic sonar, with good propagation conditions, and acceptable wave noise conditions that can be dealt with by known signal processing techniques.

IMPACT/APPLICATIONS

This work is significant for the solution of the buried mine problem, for which the Navy now has to rely on the marine mammals, whose care, feeding and logistics is quite involved, costly, and whose sonar search rate is quite low. Seismic sonar is an option to this reliance (as are options developed at the Naval Coastal Systems Station), and these offer man made sonar solutions more appropriate to naval operations.

TRANSITIONS

It is obvious that the 6.1 work discussed here has applications of interest to the undersea and amphibious warfare communities in the 6.2 arena and beyond. The transition has been discussed at the flag level with CNO N85, N87, and with PEO MINES, and most importantly, with other ONR Program Managers, Specifically Dr. Douglas Todoroff.

RELATED PROJECTS

An important related project of the principal investigator is funded by ONR Code 342PS, Drs. Teresa McMullen, Harold Hawkins, and Robert Gisiner. The objective is to discover how Navy dolphins can so easily find buried mines, perhaps with nonlinear sonar, while human engineered systems have failed to so do. In research conducted by the present PI at the Naval Ocean Systems Center (NOSC, now SPAWARESCEN), in cooperation with Dr. Sam Ridgway, it has been found that both bottlenosed dolphins and white whales emit signals with frequency content some **five** times higher than previously measured. The mystery of the marine mammal sonar is yet to be unraveled, and much of the previously published literature is ripe for debate as to its veracity.

REFERENCES

- [1] "Beamforming on seismic interface waves with an array of geophones on the shallow sea floor," by James TenCate and Thomas Muir, et al, J. Ocean Engr., **20**, n4, 300-310, Oct. 1995.
- [2] "Scattering of interface waves from pointlike obstacles," by Eric Smith, accepted for publication, J. Acoust. Soc. Am., Oct. 1997.
- [3] "Measurement and localization of interface wave reflections from a buried target," by Eric Smith and Thomas Muir, et. al., accepted for publication, J. Acoust. Soc. Am., Oct. 1997