UNCLASSIFIED

AD NUMBER

ADA800632

CLASSIFICATION CHANGES

TO:

unclassified

FROM:

restricted

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to DoD only; Administrative/Operational Use; FEB 1943. Other requests shall be referred to National Aeronautics and Space Administration, Washington, DC. Pre-dates formal DoD distribution statements. Treat as DoD only.

AUTHORITY

NACA list dtd 28 Sep 1945; NASA TR Server website

THIS PAGE IS UNCLASSIFIED

Reproduction Quality Notice

This document is part of the Air Technical Index [ATI] collection. The ATI collection is over 50 years old and was imaged from roll film. The collection has deteriorated over time and is in poor condition. DTIC has reproduced the best available copy utilizing the most current imaging technology. ATI documents that are partially legible have been included in the DTIC collection due to their historical value.

If you are dissatisfied with this document, please feel free to contact our Directorate of User Services at [703] 767-9066/9068 or DSN 427-9066/9068.

Do Not Return This Document To DTIC



.

1



HEADQUARTERS AIR MATERIEL COMMAND WRIGHT FIELD, DAYTON, OHIO

1 The U.S. GOVERNMENT **IS ABSOLVED** FROM ANY LITIGATION WHICH MAY ENSUE FROM THE CONTRACTORS IN -FRINGING ON THE FOREIGN PATENT RIGHTS WHICH MAY BE INVOLVED.

Les de la sector d'Alexandre de la sector de l



RESTRICTEL



PESTRICTED D 13.3 Anemometers 2

TECHNICAL NOTES

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

RESTRICTED

No. 880

Air Documents Division, T-2 AME, Wright Field Microfilm No. RC-205F 7242

ATI No 242

A TRACE

JULSOICAT

METHODS OF MEASUREMENT OF HIGH AIR VELOCITIES

BY THE HOT-WIRE METHOD

By John R. Weske Case School of Applied Science

CLASSIFIED DOCUMENT

CLASSIFIED DOCUMENT This document contains classified information effecting the National Defense of the United States within the meaning of the Escionase Act. USC 50:31 and 32. In transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law. Information so classified may be imparted only to persons in the military and naval Services of the United States, appropriase civilian officers and employees of the Federal Government who have a legitimate interest therein, and to United States citizens of known loyalty and direction who of necessity must be informed thereof.

Washington February 1943

FILE COPY Return to WRIGHT FIELD LIBRARY Dayton, Ohio

• (

WATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

1-

「の認識におけ、ことの言語を読い

A STATES A STATES A PROPERTY

.

TECHNICAL NOTE NO. 880

METHODS OF MEASUREMENT OF HIGH AIR VELOCITIES

BY THE HOT-WIRE METHOD

By John R. Weske

SUMMARY

Results are presented of investigations conducted to ascertain the feasibility of measurements of high velocities including velocities in the lower sonic range by the hot-wire method.

Investigations of strengths of hot wires at high velocities were conducted with platinum, nickel, and tungsten at approximately 200° C hot-wire temperature. The results appear to disqualify platinum for velocities approaching the sonic range, whereas nickel withstands sound velocity and tungsten may be used at supersonic velocities. This conclusion applies to standard atmospheric conditions of the air.

「「「「「「「「」」」」

For measurements at high velocities, hot wires must be supported by rigid prongs to avoid breakage caused by vibration of the prongs. Tungsten wire may be soldered to the prongs with soft solder after a very thin film of platinum has been electrolytically applied.

Measurements of heating current of the hot wire for constant-temperature operation show agreement with King's relation up to a velocity of 300 feet per second. Deviations from this relation were observed as sonic velocities were approached, presumably because of the effect of impact temperatures. No numerical evaluation of this aspect was undertaken, however.

Galibration curves of measurements with a circuit adjueted for linearity of reading with velocity and of directional characteristics of hot wires adjusted for linear reading are given.

1

l

INTRODUCTION

The results which have been obtained to date of an investigation undertaken at Case School of Applied Science, under the auspices of the National Advisory Committee for Aeronautics, for the purpose of investigating the possibilities and limitations of hot-wire measurements at high velocities are given in the prasent report. A preliminary report on this subject, which was submitted on July 25, 1941, contained a general survey of the field. The invastigation has been continued and certain techniques discussed hereinafter have been developed which it is hoped may render measurements by the hot-wire method at high velocities practicable.

Topics under consideration were listed in the preliminary report as follows: (a) measurement by the hot-wire method of high velocities up to and above the acoustic velocity; (b) effect of compressibility on hot-wire measurements; (c) effect of ambient temperature as a factor entering into the measurements; (d) hot-wire measurements in a flow in which fluctuations of velocity of high frequency and large amplitude occur; and (e) hot-wire measurements in flow in which changes of direction of high frequency occur.

In the present report are presented the results of experimental investigations of (a) the strength characteristics of hot wires of various materials in an air stream of high velocity; (b) the variation of heating current with velocity for constant-resistance operation of the hot wire; and (o) directional characteristics of a hot wire in a circuit adjusted for linearity of reading and wind velocity.

TESTS OF HOT WIRES FOR STRENGTH IN AN

AIR STREAM OF HIGH VELOCITY

A considerable number of factors enter into the problem of the strength of hot wires at high velocity; namely, (a) the hot-wire material, (b) diameter of the hot wire, (c) length of the hot wire, (d) diameter and length of prongs, (e) method of attachment of hot wire to the prongs, (f) rigidity of mounting of the prongs in the hot-wire

holders, (g) temperature of the hot wire, (h) tension of the hot wire, (i) turbulence of the air stream, and (j) duration of the test. In the development of a technioue of investigation it was found exceedingly difficult to effect a clear separation of the influence of the various factors. For this reason an attempt has been made to obtain, by the use of hot wires of various materials, dismeter, and length in combination with prongs and helders of various designs, an answer concerning the practicability of hot-wire measurements in a high-velocity air jet as far as strength properties of the wire and design of the mounting are concerned.

Equation for Strength Characteristics of Hot Wires

In order to establish a general relationship for the strength characteristic of the not wires, it is assumed that breakage of the wire occurs as the serodynamic drag causes the tensile stress in the wire to exceed the safe maximum limit for the Letal. Let it be assumed further that the curves of the wires unler load are similar, that is, that the ratio of sag s to length 1 is constant. The following relation may be established by the approximation of the curve by a parabola:

$$S_D \frac{\rho V^B}{2} \operatorname{Id} \frac{1}{4s} = \sigma \frac{\pi d^B}{4}$$

where :

ないため、ないられ

- d diameter of wire
- length of wire
- maximum sag of wire
- 0_D drag coefficient
- σ tensile stress

Hence

$$\sigma = \frac{1}{\pi} c_{\rm D} \frac{\rho v^{\rm a}}{2} \left| \frac{l}{d} \right|_{\rm s}^{\rm L}$$

• • •

l

The drag coefficient varies in the range of Reynolds number (10 < R_e < 10²) approximately as $C_{D} = \frac{\text{constant}}{V}$.

If this variation of C_D with V is neglected, wires of equal length-diameter ratio can sustain, for equal sag, the same velocity pressure. It is seen further that, neglecting variations of C_D with velocity, the strength of the hot wire is a function of the product of mass density of the air and velocity squared; that is, of the velocity pressure, and not simply of the velocity, or it follows from the equation that other factors being equal, the maximum safe velocity increases inversely as the square root of the mass density.

Apparatus

<u>Vires</u>.- Flatinum, nickel, and tungsten were used as hot wires in the investigation. Data of strength characteristics and electrical properties of these metals are given in table I. A table similar to table I for a large number of metals is given in reference 1. Only very thin wires from 3 to 5 mils in diameter were tested because of the limited capacity of the regulator tubes that supplied the heating current. These sizes are either currently in use or are believed to be applicable to high-velocity work.

Method of fastening hot wires to prongs. - The platinum and nickel wires were factened to prongs by soft solder, a method which was found satisfactory. A mechanically and electrically satisfactory connection was produced in the case of tungsten wire by supporting prongs made of sewing needles, the eyes of which were ground open on one side to form a hook. The tungsten wire was then placed into this hook; the free end was wound around the prong and passed through the hook a second time. After the application of a drop of zinc chloride the wire was imbedded in soft solder which completely filled the The connections were tested by exposure to a higheye. velocity air stream and acceptsd as satisfactory, as it was found from the reading of the heating current before and after this test that the electrical resistance of the solder connection had not changed during the test. When the tungsten wire was imbedded in solder without being wound around the prong, it was observed that after expo-sure to the air stream the wire had slackened; therefore,

• (.

5

this way of fastening the wire was found unsatisfactory. Prongs with hooks, as used for tungsten, produce a larger aerodynamic interference than the pointed prongs used for platinum and nickel. This drawback is offset, however, by the possibility of using longer wires because of the greater strength of tungsten.

Experimentation with a small spot-welding apparatus in which an attempt was made to weld tungsten wire to nickel supports failed to produce positive results because of the difficulty of controlling the intensity of the current. It is understood that satisfactory results with the spot welding of small wires have been obtained at LMAL.

Although satisfactory connection between tungsten wire and the supporting prongs might be produced by the needle method previously described, it was found in the investigations of the directional characteristics of such wires that the increase in the diameter of the prongs required by this method is a source of harmful interference. For this reason further investigations of the soldering of tungsten were undertaken. There appeared to be a pos-sibility that tungsten might be soldered if a thin coat of another metal which soldered easily were electrolytically deposited upon its surface. The metal deposited would have to be corrosion proof and should exhibit characteristics similar to those of tungsten in regard to its temperature coefficient or resistance. Furthermore, it should be possible to deposit a very thin film in such a way that the resistance characteristics of the tungsten would not be greatly affected. The metal that best answers these various requirements undoubtedly is platinum.

A deposit of platinum upon thin tungsten filaments was obtained by exposing the wire for less than a minute to the action of an electrolytic bath. This period of time sufficed to produce a film of deposited platinum of such strength that it could be seen with a microscope in some places where a light metallio surface was produced in place of the dark surface of the tungsten wire. Tungeten wires of two sizes, 0.00042 and 0.00034 inch in diameter, were used for this test. With this coating of platinum, tungsten wire could be soldered without difficulty to steel supporting prongs. The soldering was done with a special tin-base solder containing 67 percent tin and with Schwerter's Superior Soldering Fluid (sold by Hammel, Riglander & Co., Inc., 209 W. 14th St., N.Y.C.).

L

6

The coldered joints thus produced are considered both electrically and mechanically equivalent to those obtained with platinum and nickel wire. Inasmuch as only short pieces of platinum-plated tungsten wire were available, accurate comparative measurements of resistance could not be made; the film of platinum appears, however, not to alter appreciably the resistance of the tungsten wire.

Nozzles. - The hot wires were tested by placing them normal to a jet of air discharging from a De Laval nozzle. A nozzle was first used that was designed for the expansion of air from a gage pressure of 90 pounds per square inch to atmospheric pressurs. The results with this nozzle, however, ware most erratic, partly because that air carried small solid particles and partly because of the high ratio of initial to final pressure for which it was designed. Because of this high ratio, the resulting temperature drop caused the moisture in the air to condenss and form a visible fog and under certain conditions On the basis of this experieven minute ice particles. ence a second nozzle was designed for expansion from a gage pressure of 30 pounds per square inch to atmospheric pressure. Previous to expansion in this nozzle, the preseure of the hir was reduced from tank pressure by a throttling process. No trouble from moisture was experienced with this nozzle. Freakage from impingement of solid particles upon the wire was reduced by a large chamber immsdiately ahead of the nozzle in which screens were placed to arrest these particles.

The nozzle was calibrated by an impact tube placed close to the outlet of the nozzle from which a curve of impact pressure against pressure difference across the nozzle was obtained. Exploratory measurements of the temperature of the air discharged from the nozzle were made by a thermozeter held in the air stream. These measurements proved most unreliable and in subsequent work no attempt was made to determine the temperature in a jet of small diameter.

Tests and Results

The hot wire mounted on a pair of prongs was placed into the circuit of a hot-wire instrument and a heating current, by which the temperature of the wire was raised to a desired value, was applied. The characteristics of

٠Ŀ

the hot-wire instrument were such that thereafter the resistance and therefore also the temperature of the hot wire were automatically kept constant at the value determined by the initial setting, irrespective of the velocity past the wire. Constancy of the resistance, and the temperature, could be checked at any time during the test by a galvanometer. A further check through correlation of the measurements of heating currents of various velocities by means of King's equation will be discussed later.

The tests ordinarily were of 2-minute duration and, during this time, the pressure across the orifice was increased stepwise up to the point at which breakage accurred. The duration of the test was limited by the capacity of the pressure tank and of the compressor. If no breakage occurred, the test was repeated when the tank pressure was reestablished. The results are presented in table II.

Flatinum may be used for relatively low velocities only as shown in table II. Nickel is regarded as a more satisfactory material because it exhibits satisfactory strength characteristics which make possible its use for velocities up to and including the velocity of sound. It may readily be soldered to supporting prongs. The high tensile strength of tungsten renders it desirable for measurements at sonic velocities; it is satisfactory, however, only if a connection to the prongs is achieved which is both mechanically and electrically reliable, such as has been obtained through application of a thin electrolytically deposited coat of platinum.

たれないでものないの

For a hot wire of a given material and diameter the maximum permissible velocity pressure is proportional to the length-diameter ratio. Satisfactory results were obtained with hot wires of length equal to 250 times the diameter. For this length the end effect due to thermal conduction may be neglected. (See reference 2.)

Table II shows that the rigidity of the prongs has a pronounced effect upon decreasing the strength of the wire. This effect of the rigidity of the prongs was investigated as follows: Two three-prong holders were tested, one with slim prongs 0.018 inch in diameter and the other with stiff prongs 0.032 inch in diameter. These prongs were spaced to permit the mounting of two wires, one twice as long as the other, which were connected in series. They were then placed into the air stream and exposed to a gradually increasing velocity until the current was interrupted. Inspection of the wires following

· (.

NACA Technical Note No. 880 .

the interruption of the circuit showed that in the majority of cases for the holder with slim prongs both wires wers broken, whereas only the longer one was destroyed in the case of the stiff prongs. Simultaneous breakage of both wires was attributed to vibration of the prongs. As seen from table II, these vibrations occur at a decreasing velocity pressure as the prongs extend across the air stream and at an increasing velocity pressure as the prongs are placed parallel to the air stream. It is concluded, therefore, that prongs should be as strong as permissible without causing undue aerodynamic interference. The most satisfactory performance was obtained when the pointed ends of No. 4 darning needles were used to support the wire.

On the basis of the observations of strength and rigidity of prongs, two holders were developed, one with prongs for attaching nickel wire, the other for unplated tungsten wire. These holders are shown in figure 1.

i

HOT-WIRE MEASUREMENTS AT HIGH VELOCITIES

Constant-Resistance Operation of the Hot Wire

The hot-wire measurements of high velocities taken for the experimental investigation were obtained under particular conditions of operation, namely, for constantresistance operation of the hot wire. Since the resistance is a function of only temperature, constant-resistance operation is at the same time constant-temperature operation. This method is believed to offer a number of advantages.

If considerations of measurements of high-frequency fluctuation are disregarded, these advantages are: relatively small variations with change of wind velocity of the physical ouantities affecting hot-wire measurements such as specific heat, conductivity, and mass density in the film of air surrounding the wire. Furthermore, constant-resistance operation leads to a larger variation of the measured electrical quantity, in this case the heating current, with velocity than would be obtainable with constant-current operation. This increased variation in current with velocity should render the measurements more accurate. It appears reasonable that, with constant-temperature operation, measurements could

.

• (.

8

و الغوير العالم ال

be obtained at a relatively low hot-wire temperature, a condition which naturally is desirable when high strength of the wire is required. In practical operation constanttemperature operation was found to reduce the danger of accidentally burning out the hot wire.

Constant-resistance operation of the hot wire was effected through the circuit shown in figure 2. The particular circuit shown has the advantage of requiring a minimum number of batteries. Because the measurement of only mean velocities is considered in the present investigation, the alternating-current impulses were shortcircuited by condensers, which were connected in the circuit but are not shown in figure 2. This measure considerably simplified the adjustment of the circuit.

Applicability of King's Equation

A relation between the heating current required for a hot wire and the wind velocity and certain other quantities entering into measurement by the hot-wire method has been derived by King in reference 3 from the condition that the heat supplied to the wire must equal the heat dissipated by the air stream. This ecuation may be stated (reference 4) as follows:

$$i^{2} R = 4.2 K (T - T_{o}) \left(1 + \sqrt{\frac{2\pi\rho c_{p} Vd}{K}}\right)$$

where

ł

「行き」の

÷

.

- i heating current, amperes
- R resistance of the wire, ohms
- T temperature of the hot wire, °C
- T_0 temperature of the ambient air, 0
- K thermal conductivity, calories per centimeter per ^OC per second
- ρ mase density of air, grams per cubic centimeter
- op specific heat at constant pressure, calories per gram per ^oC

· (

•

.

d diameter of the wire, centimeters

For air, Marks Handbook in reference 5 gives the following equation for R in Btu per foot per ^oF per hour:

 $K = 0.0129 \left[\frac{717}{T_0 + 225} \right] \left(\frac{T_0}{492} \right)^{\frac{3}{2}}$

where T_0 is the absolute temperature of the air in ^oF. The equation is valid from -312° F to $+212^{\circ}$ F and may be converted into cgs units by dividing the value of K in engineering units by 241.9.

The first quantity on the right-hand side of King's equation represents the heat dissipated by conduction and induced convection and the second quantity the heat dissipated by forced convection. Radiation losses are disregarded. The equation is applicable only above a certain low limit of velocity past the wire which, for standard atmospheric conditions, is defined by a value of Reynolds number, based upon wire diameter, of 0.108. A relation corresponding to equation (1) has been derived for velocities below this limit which, however, has no significance for the field of application under discussion.

For zero wind velocity the equation reduces to

 $i_0^2 R = 4.2 K (T - T_0)$ (2)

.......

the set of the set

where io is the heating current at zero wind velocity. The following conditions must be considered when equation (2) is used for numerical calculations. The value of the thermal conductivity to be used in the eouation is that of the film of air surrounding the wire, which is a function of the film temperature. The effective value of the film temperature is not known. It has been suggested that the conductivity corresponding to the arithmetic mean temperature of the wire and the ambient air temperature may be used.

the stand of the second of the

10

V

11

It should be noted, furthermore, that at high velocities the temperature rise due to compression resulting from impact of the air upon the wire must be considered and, if necessary, allowance for it must be made in the choice of T_0 .

Because of these uncertainties calculations of hotwire temperatures by equation (2) can lead to only approvimate values. At velocity approaching the sonic range, the impact temperature affects the heat dissipated from the wire by conduction and induced convection given by the first term on the right-hand side of equation (1). The effect of the impact temperature also enters the relation between wind velocity and heat current given by the second term on the right-hand side of equation (1). It is seen that the relation between heating current i and velocthat the relation between heating current V for a given current i_0 is uniquely defined only ity if the resistance is constant and if both the temperature and the mass density of the air are constant. For take reason velocity measurements by the hot-wire method are conclusive only if variations of temperature and case density remain within limits established by the stipulated accuracy of the results,

Experimental Check

P

Measurements were made to obtain an experimental check of the conformity of the method of measurement chosen with King's equation at high velocities. The results are shown in figures 3 and 4. A number of test runs were conducted with a nickel wire 0.0005 inch in diameter and 1/8 inch long for various initial heating currents io and for velocities from 0 to approximately 300 feet per second. The measurements for two runs obtained in connection with the tests for the strengths of the hot wires in the high-velocity jet are also shown in figure 4. The deviation from King's relation of these measurements is attributed to variations of effective impact temperature of the air with velocity. No attempt was made to evaluate these results further because this temperature was not known.

DIRECTIONAL CHARACTERISTICS IN A CIRCUIT

ADJUSTED FOR LINEARITY

Hot-Wire Instrument with Linear Characteristic

It has been shown, in the paragraph dealing with the variation of heating current with wind velocity for constant-resistance operation, that the relation between heating current and wind velocity in which the velocity appears in the fourth root according to King's equation is maintained within the range of velocities investigated. It is seen that in accordance with the nature of the fourthroot relation at high velocities, the accuracy of velocity determination from the measured heating current becomes very low. Leaving out of consideration for the moment certain aspects pertaining to the measurement of fluctuating flow, this decrease in accuracy of reading made it desirable to establish a linear relationship between the reading of the hot-wire instrument and the velocity. This relationship was established (reference 6) through the installation of a nonlinear amplifier stage, the exponent of which could be adjusted to be inversely proportional to the exponent relating heating current to wind velocity. This amplifier stage, shown on the wiring diagram (fig. 2), consists of T_3 and its immediate external circuit including battery \mathbb{B}_{γ} and meter M_{α} . calibration curve of measurements obtained with the hotwire circuit including a linearizing stage is shown in figure 5.

If the variation of heating current with wind velocity is known, for instance, through a curve such as is shown in figure 5, it is possible to adjust the lineariz-ing stage for the desired evenent by a simple electrical testing procedure which does not require the use of aerodynamic equipment, such as an air stream. The procedure is as follows: After the instrument is adjusted for a given heating current at zero wind velocity io, currents are impressed upon the bridge of various strengths - $(i - i_0)$ and of voltage opposite to that of the heating current, as indicated by the minus sign. The cathode bias of the linearizing stage is then adjusted to obtain readings that are proportional to the velocities corresponding to the values of $(i - i_0)$ chosen. A satisfactory

ł

• (

Galibration curve can be obtained by this out-and-try method using from four to six values of $(i - i_0)$ covering the desired range of velocities. A check of this calibration can be made at any time between tests by impressing upon the bridge a negative heating current - $(i - i_0)$ corresponding to the maximum velocity and, if necessary, adjusting the bridge balance and the amplifier.

この方法になったための

Calibration of the Directional Characteristics

of a Hot Wire Adjusted for Linear

Instrument Characteristic

Galibrations of the directional characteristics (reference 7) were undertaken for two hot wires, nomely, nickel wire 0.0005 inch in diameter and 1/3 inch long and nickel wire of the same diameter and 7/32 inch long. The short wire was tested in a stram of 3/4-inch diameter, the long wire in a stream of 6-inch diameter. In both curves the instrument operating on the basis of constant resistance of the hot wire was adjusted for linearity between reading and wind velocity. Galibration curves for linearity are given in figure 5 for the short wire and in figure 6, for the long wire. Test results showing the directional characteristics are given in figure 7 for the short and long wires. A sin curve is also plotted into the graph for comparison. These curves indicate that within the range of velocities from 50 feet per second to 300 feet per second, the change of reading with angle is quite pronounced, especially for angles of incidence of approximately 45°; it is suggested, therefore, that these characteristics might possibly form the basis of directional measurements by the use of two properly oriented wires without manual adjustment in the determination of the direction.

It will be seen that the directional characteristics of the long wire show much less sprend of test points with velocity for a given angle than the short wire. It was found that the variations of readings may be attributed largely to the drifting of the balance of the hot-wire instrument which, for the short wire is more critical than for the long wire. Other effects, such as interference with the flow past the hot wire caused by the prongs, did not show up clearly. Considerable trouble was caused by the accumulation of lint on the wire, which

produced fluctuations and faulty readings. In the second test (fig. 7(b)) greater care was taken than in the first test to maintain balance of the bridge and to keep the wire free from dust.

CONCLUSIONS

Tests of hot wires of platinum, nickel, and tungsten of various diameters and lengthe in combination with prongs and holders of various designs indicate the following conclusions:

1. For measurements at high velocities, hot wires must be supported by rigid prongs to avoid breakage caused by vibration of the prongs. Experimentation with various types of connection between hot wire and prongs indicate that, in high-velocity work, a mechanically satisfactory connection is as difficult to obtain as a connection that has a low electrical resistance which remains constant during the life of the hot wire. Satisfactory results can be secured with ateel prongs, however, by the use of soft solder for platinum and nickel and by the use of soft solder with tungsten on which a thin film of platinum has been electrolytically deposited.

2. Flatinum may be used for only low velocities, nickel may be used for velocities up to and including the velocity of sound, and tungsten may be used at supersonic velocities.

3. The general relationship established by King's equation for constant-resistance operation of the wire and constant pressure and temperature of undisturbed flow may be assumed to hold for velocities up to 300 feet per second. Deviations from King's relation, which were observed as sonic velocities were approached, were assumed to result from impact temperatures.

4. Decrease in accuracy at high velocities resulting from the fourth-root relationship between heating current and velocity in King's ecuation for constant resistance operation, made it desirable to establish proportionality between the reading of the hot wire instrument and the velocity.

•

Aerodynamics Laboratory, Case School of Applied Science, Cleveland, Ohio, April 1942.

.14

REFERENCES

「「「「「「「「」」」」というという。「「「」」」のないので、「」」」の「「」」」」

.:

ļ

- MacGregor-Morris, J. T.: The Electrical Measurement of Wind Velocity. Engineering, vol. 94, no. 26, Dec. 27, 1912, pp. 892-894.
- Harper, D. R., 3d, and Brown, W. B.: Mathematical Equations for Heat Conduction in the Fins of Air-Cooled Engines. Rep. No. 158, NACA, 1923.
- 5. King, Louis Vessot: On the Convection of Heat from Small Cylinders in a Stream of Fluid. Determination of the Convection Constants of Small Platinum Wires with Applications to Hot-Wire Anemometry. Phil, Trans. Roy. Soc. (London), ser. A, vol. 214, 1914, pp. 373-432.
- Dryden, H. L., and Keuthe, A. M.: The Measurement of Fluctuations of Air Speed by the Hot-Wire Anemometer. Rep. No. 320, NACA, 1929.
- Marks, Lionel S.: Mechanical Engineers' Handbook. McGrew-Hill Book Co., Inc., 4th ed., 1941, p. 395.
- Huguenard, Magnan, and Planiol, A.: Aèrodynamique -Sur un Anèronétre à Fil Chaud à Compensation. Comptes Rendus, vol. 176, no. 5, Jan. 29, 1923, pp. 287-289.

 Purgers, J. M.: Abkühlung eines Fadens, welcher nicht senkrecht von der Strömung getroffen wird Anwendung zur Bestimmung der Strömungsrichtung. Vol. IV, Hitzdrahtmessungen, soc. 6 of Handb. Exp. Phys. Akad. verlagsgesellschaft (Leipzig) 1931, fig. 5, p. 657.

•6

TABLE I

PHYSICAL PROPERTIES OF METALS USED FOR HOT WIRES

Temperature Tensile Melting Electrical Metal coefficient point resistivity strength of resistivity (°c) (oha-cm/°C) (microhm-cm) (lb/sq in.) ^ъо.003 ag.83 53,000 Platinum 1773.5 ^b7.8 °.00537 1440 70,000 to 85,000 Nickel d.0047 ^b5.5 215,000 Tungsten 3382 ^cFrom 20[°] C to 100° C. ^dFrom 0[°] C to 100° C. $^{\rm B}_{\rm At}$ 0° C. $^{\rm b}_{\rm At}$ 20° C. · · · · · · · • : • • Alexandra and a statistical statisticas sta statistical statistical statistical statistical statistical statistical statistical statistical statistical statisticae statist 5 d 5 d 5 • : • · · · · . Į

[Values taken from reference 8]

16 ²¹

TABLE II

1

l

REBULTS OF TEST OF HEATED BOT WIRES IN A HIGH-VELOCITY AIR JET

teete		Ameter of uire	101		Diameter of prougs	Free length of pronge	Position of prongs with respect	Heating Current at zero	Approx- imate temper- sture	Average velocity preseure at instant	Average velocity at instant of breaking at standard	Remarks
	(a11e)	(sicrons)	(ia.)	(an)	(10.)	(1n.)		(1	(°c)	(lb/sq in.)	conditions (fpe)	
							Platinum					
	6		-4 00	0.318					1	5.8	650	
8	¥. 		-12	.158				8	188	7.5	880	
	_		-40	.316	0.006	19	Tere!!el			6.5	825	
	•	4	ᆌ	.159		œ				8.5	028	
0			n	2				\$	CRT	5.4	9 9 2	3
			<u>ত্র</u> তি	366.						5.4	780	3
							rickel.					
68			- 1 0	0.318]allare			11.6	1065	
•	20.5	12.7	-	2	0.033	م [دء		52	192	8 ^ 28	>1400	(3)
ю			×	1			Perpendioular			8	>1400	(3,3)
							Tungaten					
10	10	4	~				Parallel			8~	>1400	(2)
10	;	5	-	0 476	210 0	10	Perpendicular	<u> </u>		 52 	>1400	(Ŧ)
ч			19	}	200.5	G	Parallel			88	1600	(3)

te o

17

Both wires tested simultaneously on a three-prong holder. Both wires broke simultaneously, presumably due to wibration of pronge. 3 Prolonged test. 4 Occasional breakagee, presumably due to vibration of pronge.

(3) (e)

1600 >1400

8 08 <

160

Perpendicular 65

10.7

. 43

ч

· (

í

Fig. 1

18-





6



· (

1

Ļ



....



-



. ~ -



TITLE: Metho	ds of Measur	ement of Hi	gh Air Velocities	by the	Hot Wire Meth	od	ATI- 7242
ORIGINATING	AGENCY: N	ational Advi	sory Committee	for Aer	onautics, Wash	ington, D. C.	TN-880
Feb '43	BOC. CLAIR	U.S.	Eng.	PAGES 22	ILLUSTRATIONS ph	oto, tabies, di	iagr, graphs
ABSTRACT:	and the second	Par . A.	1	*		12	

Investigations of strengths of hot wires at high velocities were conducted with platinum, nickel, and tungsten at approximately 200°C hot-wire temperature. The results appear to disqualify platinum for velocities approaching the sonic range; whereas nickel withstands sound velocity, and tungsten may be used for supersonic velocities under standard atmospheric conditions. Hot wires must be supported by rigid prongs at high velocities to avoid wire breakage. Heating current measurements for constant temperature show agreement with King's relation.

DISTRIBUTION: Request copies of this report only from Originating Agency

DIVISION: Wind Tunneis (17) SECTION: Equipment and Instrumentation (3) ATI SHEET NO.: R-17-3-9

> Air Materiel Command U.S. Air Force

AIR TECHNICAL INDEX

Wright-Pattersen Air Force Base Dayton, Ohio

SUBJECT HEADINGS: Anemometers, Hot Wire (10795)

Jassification cancelled

AUTH:

Signature and Grade

. APR 2 9 1949

Classification cancelled per authority of List NACA dd. 28 Sept 1945 Henry R. Jordan, USCO. 29 Apr 1949

	RESTRICTED ATI. 7242 TITLE: Methods of Measurement of High Air Velocities by the Bot Wire Method avances (None) AUTHOR(S): Weske, John R. ORIGINATING AGENCY: National Advisory Committee for Aeronautics, Washington, D. C.										
ł	DATE	DOC. CLARS	COUNTRY II S	LAROUAGE Engr	22	LUSTRATIO	nhoto, t	ables, di	iagr. graphs		
	ABSTRACT:	Investigatio platinum, ni The results range; wher for superso must be sup Heating cur with King's	ns of strengths ickel, and tung; appear to diag eas nickel with nic velocities u ported by rigis rent measuren relation.	of hot wires a sten at approxi- ualify platinum stands sound inder standard prongs at high ments for const	at higb ve imately 2 n for veh velocity, l atmosph (h velocit ant temp	elocities 00 ⁰ C ho ocities z and tun eric co ies to a erature	were condu- tt-wire tem approaching goten may t nditions. H void wire bu show agree	ucted wi perature the som e used ot wires reakage. ement	th 2, 10 3		
	DISTRIBUTION	. Request co	pies of this rep	port only from	Original	ing Age	ncy				
	DIVISION: W SECTION: IS ATI SHEET N	upment and C.: R-17-3	(17) Instrumentatio -9	m (3)	IECT HEA	DINGS:	Anemomete	ers, Hot	Wire (10795)		
	Ļ	Air Me U.	starial Command S. Air Forco	AID PECM RES	nical in Tricted	DUR	, Wright-Pat	Horson Alr Dayton, Ob	Forco Daso No		

ŀ