

UNCLASSIFIED

AD NUMBER
ADB019907
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Specific Authority; 01 JUN 1977. Other requests shall be referred to Naval Underwater Systems Center, New London Laboratory, New London, CN 06362.
AUTHORITY
CNO/N772 1tr CNO N772A/6U875630 20 Jan 2006 and ONR 1tr 31 Jan 2006

THIS PAGE IS UNCLASSIFIED


UNCLASSIFIED

AD NUMBER
ADB019907
NEW LIMITATION CHANGE
TO Distribution authorized to U.S. Gov't. agencies and their contractors; Specific Authority; 01 JUN 1977. Other requests shall be referred to Naval Underwater Systems Center, New London Laboratory, New London, CN 06362.
FROM Distribution authorized to U.S. Gov't. agencies only; Test and Evaluation; 01 JUN 1977. Other requests shall be referred to Naval Underwater Systems Center, New London Laboratory, New London, CN 06362.
AUTHORITY
NUSC, per DTIC Form 55

THIS PAGE IS UNCLASSIFIED

NUSC Technical Report 5635

2



Generic FACT

Henry Weinberg
Special Projects Department

1 June 1977

NUSC

NAVAL UNDERWATER SYSTEMS CENTER
Newport, Rhode Island • New London, Connecticut


Distribution limited to U.S. Government agencies only; Test and Evaluation;
1 June 1977. Other requests for this document must be referred to the
Naval Underwater Systems Center.

NUSC Technical Report 5635

AD B019902

DDC FILE COPY

DDC




PREFACE

This work was accomplished under NUSC Project No. B-650-02, "Underwater Acoustic / Environmental Modeling and Data Bank for Sonar Systems Design and Performance Prediction" (U), Principal Investigator, F. R. DiNapoli (Code 312), and Navy Subproject and Task No. SF-52-522-701. The sponsoring activity is the Naval Sea Systems Command, Program Manager, A. P. Franceschetti (SEA 06H1-4).


The Technical Reviewer for this report was Roy L. Deavenport (Code 312).

REVIEWED AND APPROVED: 1 June 1977



R. W. Hasse

Head: Special Projects Department



The author of this report is located at the New London Laboratory, Naval Underwater Systems Center, New London, Connecticut 06320.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NUSC-TR-5635	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TYPE (and Subtitle) GENERIC FACT	5. TYPE OF REPORT & PERIOD COVERED	
7. AUTHOR(s) Henry Weinberg	6. PERFORMING ORG. REPORT NUMBER	
8. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Underwater Systems Center New London Laboratory New London, Connecticut 06320	9. CONTRACT OR GRANT NUMBER(s) F52522 552522701	
10. CONTROLLING OFFICE NAME AND ADDRESS Naval Sea Systems Command (SEA 06H1-4) Washington, DC 20362	11. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS B-650-02 125-11	
12. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	13. REPORT DATE 1 June 1977	
	14. NUMBER OF PAGES 18	
	15. SECURITY CLASS. (of this report) UNCLASSIFIED	
16. DISTRIBUTION STATEMENT (of this Report) Distribution limited to U.S. Government agencies only; Test and Evaluation; 1 June 1977. Other requests for this document must be referred to the Naval Underwater Systems Center.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Bottom Loss Discontinuities Subsurface Channels False Caustics Generic Fast Asymptotic Coherent Transmission (FACT) Generic Sonar Model		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A Generic Sonar Model is used to investigate predictions generated by the Fast Asymptotic Coherent Transmission (FACT) Loss Model. Results indicate that FACT may produce questionable results in certain special situations. Possible improvements to FACT are suggested.		

TABLE OF CONTENTS

	Page
LIST OF ILLUSTRATIONS	11
INTRODUCTION	1
GENERIC SONAR MODEL	1
BOTTOM REFLECTION COEFFICIENT DISCONTINUITIES	2
FALSE CAUSTICS	3
SUBSURFACE CHANNELS	4
SUMMARY	5
REFERENCES	7

NOV 1967	
THIS	WHITE SPECTRUM ☐
IS	BATHY SPECTRUM ☒
UNCLASSIFIED	☐
CLASSIFICATION	
DISTRIBUTION/AVAILABILITY CODES	
DEL	ATL. 645/M SPECIAL
B	

LIST OF ILLUSTRATIONS

Figure		Page
1	FACT Bottom Loss Versus Frequency at 10° Grazing Angle for MGS Province 4	9
2	RAYMODE Bottom Loss Versus Frequency at 10° Grazing Angle for MGS Province 4	10
3	Sound Speed Versus Depth	11
4	Propagation Loss Versus Range Computed by Generic FACT	12
5	Propagation Loss Versus Range Computed by the Multipath Expansion	13
6	Ray Diagram for a 640 ft (195.072 m) Source	14
7	Ray Diagram for a 640 ft (195.072 m) Source, Including Source Angles from -20° to $+20^\circ$ in $1/2^\circ$ Steps . .	15
8	Propagation Loss Versus Range Computed by FFP	16
9	Propagation Loss Versus Range Computed by RAYMODE . . .	17

GENERIC FACT

INTRODUCTION

The Generic Sonar Model is a computer program designed to aid analysts predict the performance of sonar systems. Included in the Generic Sonar Model's library of subroutines is a modified version of the Fast Asymptotic Coherent Transmission Model¹ (FACT). The modified version, called Generic FACT, was found to be accurate in the majority of cases investigated, but not in all.

Three questionable predictions by Generic FACT documented in this paper pertain to bottom reflection coefficients, false caustics, and subsurface channels. The first prediction should be corrected by replacing the bottom reflection coefficient subroutine, and the second by changing one line of FORTRAN code. Correcting the third prediction, however, may require a substantial effort.

One of the desirable features of the original FACT Model is that predictions made at one installation can be reproduced at another. However, if the user makes the changes recommended in this report, he will lose consistency. A possible solution to this dilemma would be to implement the same changes at all installations, but this is presently impractical.

GENERIC SONAR MODEL

The Generic Sonar Model is a computer program designed to provide systems developers and technologists with a comprehensive modeling capability for evaluating the performance of sonar systems and investigating the ocean environment in which they operate. Specific uses of the Generic Sonar Model include the following:

- a. Analysis in which the relative performance of sonar systems are compared
- b. Optimization of individual sonar designs
- c. Support of sonar operational trainers
- d. Support of engagement models
- e. Comparison of existing acoustic models

f. Development of improved acoustic models.

Only a discussion of "e" follows because the main thrust of this report is to discuss the comparison of existing acoustic models.

Comparison of existing acoustic models is accomplished through modular design, adhering to a strict Generic format, and using overlaying techniques. For example, an option presently available in many propagation programs allows one to compare bottom reflection coefficient models by simply replacing the bottom reflection coefficient subroutine. The Generic Sonar Model allows the user to replace entire propagation loss programs as well. Thus, a sonar analyst can choose appropriate building blocks from a library of subroutines in order to obtain a best cost/accuracy configuration for the particular study at hand.

The Generic Sonar Model will not be ready for general distribution until it is documented. However, local usage at NUSC has uncovered some disturbing predictions by FACT that warrant dissemination now. These predictions were first discovered using Generic FACT and then verified against the standard version's output to ensure that Generic modifications were not a source of error.

BOTTOM REFLECTION COEFFICIENT DISCONTINUITIES

Most computer programs designed to model acoustic propagation in the ocean are optimized to predict propagation loss versus position at one frequency, whereas sonar system analysts require propagation loss versus frequency with position as the parameter. Errors are readily found by investigating discontinuities in plotted outputs. As a result, propagation loss models are "debugged" at a constant frequency, while analysts who are unfamiliar with the idiosyncrasies of an acoustic model inadvertently optimize their systems at frequencies where the computed propagation loss changes abruptly. Obviously, the design of a bottom bounce sonar should not be based on a bottom reflection coefficient model that displays significant discontinuities at frequencies within the operating band.

A useful feature of the Generic Sonar Model is the ability to display the output of its basic subroutines versus frequency. Upon applying this option to the Generic version of the FACT bottom reflection coefficient subroutine, one sees from figure 1 that the subroutine's output is riddled with discontinuities. Many of these discontinuities fall at sonar operational frequencies.

It is, therefore, recommended that the FACT bottom reflection coefficient model be smoothed by first removing the code that leads

to nonmonotonic discontinuities and, then, adding a linear interpolation between the remaining breakpoints. Alternatively, one could use the RAYMODE bottom reflection coefficient model that is coded by Yarger.² A sample output is illustrated in figure 2.

The bottom reflection coefficient discontinuities were apparent to many FACT users who proceeded to find the origin independently and without Generic-like models. However, the next questionable prediction to be discussed could not have been found so easily and serves to illustrate the power of the Generic Sonar Model.

FALSE CAUSTICS

Besides Generic FACT, a second propagation loss subroutine called the Multipath Expansion³ resides in the Generic library. The two subroutines agreed reasonably well in the majority of cases compared, although FACT was approximately 20 times faster. Both were exercised for the sound profile in figure 3. Agreement was satisfactory except when both source and receiver were placed at a depth of 640 ft (195.072 m). (See figures 4 and 5.) This section is concerned with differences within 10 kyd (9.144 km) in range; the next section will discuss the more significant differences beyond 10 kyd (9.144 km).

As stated earlier, abrupt changes in propagation loss tend to indicate error. Originally, Generic FACT did not show the bump of 4 kyd (3.6576 km), and so it was thought that the Multipath Expansion was at fault. The corresponding ray diagram (figure 6), on the other hand, revealed a strong focusing effect at the point in question, suggesting that the increase in intensity was real.

The Generic Sonar Model is structured so that individual contributions to the acoustic pressure, eigenrays, can be examined individually. It was soon discovered that Generic FACT generated a family of eigenrays corresponding to a false caustic not generated by the Multipath Expansion. This family of relatively high intensity masked the caustic phenomenon.

The reader may wish to omit the remainder of this section which requires a detailed knowledge of FACT.

According to the NUSC listing of FACT,¹ the FORTRAN card

```
15 IF ((THETC.LE.THMAX).AND.(THETC.GE.THMIN)) GO TO (30,35), IGTYP
INSTOR93
```

is responsible for the questionable eigenrays.

Here

THETC is the angle at which a caustic intersects depth Y(K2),

THMIN, THMAX are angular bounds of a group of rays, and

IGTYP equals 2, indicating that the range of the rays in the group is fit with the parabola,

$$R = A(1) + A(2)*DTHC + A(3)*DTHC**2$$

A necessary condition for caustics to occur is

$$DR/DDTHC = A(2) + 2.0*A(3)*DTHC = 0$$

so that

$$DTHC = -A(2)/(2.*A(3))$$

INSTOR96

and

$$THETC = THMIN + DTHC**2$$

INSTOR97

In order for the caustic to belong to the group, the inequality

$$0 < DTHC < (THMAX-THMIN)**0.5$$

must be satisfied. But, instead suppose that DTHC is small and negative. Then INSTOR 93 would incorrectly place the false caustic in the group. However, when the additional test that DTHC be positive was inserted in Generic FACT, the questionable eigenrays disappeared and the true caustic became visible.

SUBSURFACE CHANNELS

FACT incorporates asymptotic techniques in order to model low frequency diffraction effects not treated by classical ray theory. As this last example will demonstrate, this technique is inappropriate when the source and receiver lie within a weak subsurface channel.

Again consider the sound speed profile in figure 3. A weak subsurface channel lies below the 100 ft (30.48 m) surface duct and extends to a depth of 1265 ft (385.572 m). Figure 7 is a ray diagram for the 640 ft (195.072 m) depth source and consists of source angles ranging from -20° to $+20^\circ$ in $1/2^\circ$ steps. Bottom bounce rays were terminated at their second reflection in the ray diagram for

illustrative purpose. One sees that the 0° ray is trapped in the subsurface channel while the $\pm 1/2^\circ$ rays escaped.

By applying the eigenray printout option of the Generic Sonar Model to investigate the 45 kyd (41.148 km) region, we found that the Generic FACT was dominated by subsurface channel energy (figure 4) while the Multipath Expansion was bottom bounce limited (figure 5). Analytic investigation supported by FFP⁴ and RAYMODE⁵ predictions shown in figures 8 and 9, respectively, substantiate the Multipath Expansion.

Possible improvement to Generic FACT predictions could be achieved by smoothing weak subsurface channels out of sound speed profiles or by adding specialized logic similar to the FACT surface duct model.

SUMMARY

This report cautions the reader when using FACT in certain applications. Possible improvements are suggested, but there does not seem to be any practical way of implementing these modifications universally. Perhaps an interlaboratory committee such as the Panel on Standard Sonar Models (POSSM) could be tasked to distribute standard model updates at least throughout the Navy. Secondly, this report describes briefly a Generic Sonar Model and how it may be used to localize discrepancies in other acoustic models. Detailed documentation is in preparation.

REFERENCES

1. Computer Listing of Fast Asymptotic Coherent Transmission (FACT) Model, NUSC Acoustic Environmental Support Detachment, 1 April 1973.
2. D. F. Yarger, "The User's Guide for the RAYMODE Propagation Loss Program," NUSC Technical Memorandum 222-10-76, 9 August 1976.
3. H. Weinberg, "Application of Ray Theory to Acoustic Propagation in Horizontally Stratified Oceans," Journal of the Acoustical Society of America, vol. 34, 1975, pp. 97-109.
4. F. R. DiNapoli, Fast Field Program for Multilayered Media, NUSC Technical Report 4103, 26 August 1971.
5. G. A. Leiberger, "A Combined Ray Theory-Normal Mode Approach to Long Range Low Frequency Propagation Loss Prediction" (U), NUSC Technical Memorandum PA-0109-71, 13 August 1971 (CONFIDENTIAL).




Figure 1. FACT Bottom Loss Versus Frequency at 10°
Grazing Angle for MGS Province 4




Figure 2. RAYMODE Bottom Loss Versus Frequency at 10°
Grazing Angle for MGS Province 4




Figure 3. Sound Speed Versus Depth

TR 5635




Figure 4. Propagation Loss Versus Range Computed by
Generic FACT




Figure 5. Propagation Loss Versus Range Computed by the Multipath Expansion




Figure 6. Ray Diagram for a 640 ft (195.072 m) Source




Figure 7. Ray Diagram for a 640 ft (195.072 m) Source, Including Source Angles from -20° to $+20^{\circ}$ in $1/20$ Steps




Figure 8. Propagation Loss Versus Range Computed by FFP




Figure 9. Propagation Loss Versus Range Computed by RAYMODE.

INITIAL DISTRIBUTION LIST

Addressee	No. of Copies
COMSUBDEVGRUTWO (CDR Pugliese)	1
CRUDESDEVGRUTWO	1
ASN (R&D)	1
ONR, Codes 102-OS, 480, 481, 483, 102-OSC (LRAPP Manager)	5
AESD	1
CNO, OP-00, -090, -095, -098T, -23T, -942U, -96C1, -981	8
CNM, MAT-00, -03, -03L, -0302, SP-20, -24, ASW-14, -22, -23, -24	10
DDR&E (G. Cann) (2)	2
NRL (Dr. W. Kuperman, Dr. F. Ingenito)	3
OCEANAV	2
NAVOCEANO, Codes 02, 3000, 7200, 9320	4
NAVELEX, Code 03, PME-124	2
NAVSEA, SEA-03C, -037, -06H, -06H1, -06H1-1, -06H1-2, -06H1-3, -06H1-4, -06H2, -09G3 (4), -660C, -660F, -92	16
NAVAIRDEVCON (C. Bartberger)	1
NAVCOASTSYSLAB (T. Watson)	1
NELC	1
NUC (2), (Dr. H. Bucker, M. Pederson, D. Gordon, Dr. G. Deloreto, Dr. R. McGirr, E. Chaika, Dr. J. Stewart)	9
APL/UW, Seattle	1
ARL/PENN STATE, State College (Dr. Stickler)	1
ARL/Texas (G. Bardin)	1
CENTER FOR NAVAL ANALYSES (Acquisition Unit)	1
DDC, Alexandria	2
DEFENSE INTELLIGENCE AGENCY (DT-2C)	1
MARINE PHYSICAL LAB, Scripps	1
NATIONAL RESEARCH COUNCIL (Committee Undersea Warfare)	1
WOODS HOLE OCEANOGRAPHIC INSTITUTION (Dr. Porter, Dr. Hayes)	2
A. D. Little Co. (G. Miller)	1



DEPARTMENT OF THE NAVY

OFFICE OF NAVAL RESEARCH
875 NORTH RANDOLPH STREET
SUITE 1425
ARLINGTON VA 22203-1995

IN REPLY REFER TO:

5510/1
Ser 321OA/011/06
31 Jan 06

MEMORANDUM FOR DISTRIBUTION LIST

Subj: DECLASSIFICATION OF LONG RANGE ACOUSTIC PROPAGATION PROJECT (LRAPP) DOCUMENTS

Ref: (a) SECNAVINST 5510.36

Encl: (1) List of DECLASSIFIED LRAPP Documents

1. In accordance with reference (a), a declassification review has been conducted on a number of classified LRAPP documents.
2. The LRAPP documents listed in enclosure (1) have been downgraded to UNCLASSIFIED and have been approved for public release. These documents should be remarked as follows:

Classification changed to UNCLASSIFIED by authority of the Chief of Naval Operations (N772) letter N772A/6U875630, 20 January 2006.

DISTRIBUTION STATEMENT A: Approved for Public Release; Distribution is unlimited.

3. Questions may be directed to the undersigned on (703) 696-4619, DSN 426-4619.

A handwritten signature in black ink, appearing to read "B. F. Link", is positioned above the typed name.

BRIAN LINK
By direction

Subj: DECLASSIFICATION OF LONG RANGE ACOUSTIC PROPAGATION PROJECT
(LRAPP) DOCUMENTS

DISTRIBUTION LIST:

NAVOCEANO (Code N121LC – Jaime Ratliff)
NRL Washington (Code 5596.3 – Mary Templeman)
PEO LMW Det San Diego (PMS 181)
DTIC-OCQ (Larry Downing)
ARL, U of Texas
Blue Sea Corporation (Dr. Roy Gaul)
ONR 32B (CAPT Paul Stewart)
ONR 321OA (Dr. Ellen Livingston)
APL, U of Washington
APL, Johns Hopkins University
ARL, Penn State University
MPL of Scripps Institution of Oceanography
WHOI
NAVSEA
NAVAIR
NUWC
SAIC

Declassified LRAPP Documents

Report Number	Personal Author	Title	Publication Source (Originator)	Pub. Date	Current Availability	Class.
DASC 012-C-77	Unavailable	LRAPP PACIFIC DYNAMIC ARCHIVE (U) SEPTEMBER 1976	Daniel Analytical Services Corporation	770201	NS; ND	U
SAI-78-527-WA	Spofford, C. W.	NELANT DATA ASSESSMENT APPENDIX III-MODELING REPORT	Science Applications, Inc.	770225	ADA 0117680	U
PSI TR 036049	Barnes, A. E., et al.	OCEAN ROUTE ENVELOPES	Planning Systems Inc.	770419	ND	U
Unavailable	Unavailable	TAP II BEAMFORMING SYSTEM SOFTWARE FINAL REPORT	Bunker-Ramo Corp. Electronic Systems Division	770501	ADC011789	U
S01037C8	Unavailable	TAP 2 PROCESSING SYSTEM FINAL REPORT	Bunker-Ramo Corp. Electronic Systems Division	770501	ADC011790; NS; ND	U
Unavailable	Weinberg, H.	GENERIC FACT	Naval Underwater Systems Center	770601	ADB019907	U
Unavailable	Unavailable	TASSRAP II OB SYSTEM TEST	Analysis and Technology, Inc.	770614	ADA955352	U
Unavailable	Unavailable	LRAPP TECHNICAL SUPPORT	Texas Instruments, Inc.	770624	ND	U
Unavailable	Bessette, R. J., et al.	TASSRAP INPUT MODULE	Analysis and Technology, Inc.	770729	ADA955340	U
Unavailable	Unavailable	TAP-II PHASE II FINAL REPORT	Bunker-Ramo Corp. Electronic Systems Division	770901	ADC011791	U
Unavailable	Unavailable	LONG RANGE ACOUSTIC PROPAGATION PROJECT (LRAPP)	Xonics, Inc.	770930	ADA076269	U
SAI78696WA	Unavailable	REVIEW OF MODELS OF BEAM-NOISE STATISTICS (U)	Science Applications Inc.	771101	NS; ND	U
TRACORT77RV109	Unavailable	FINAL REPORT FOR CONTRACT N00014-76-C-0066 (U)	Tracor Sciences and Systems	771130	ADC012607; NS; ND	U
Unavailable	Unavailable	LONG RANGE ACOUSTIC PROPAGATION PROJECT (LRAPP)	Xonics, Inc.	771231	ADB041703	U
Unavailable	Homer, C. I.	SUS SOURCE LEVEL ERROR ANALYSIS	Underwater Systems, Inc.	780120	ND	U
Unavailable	Fitzgerald, R. M.	LOW-FREQUENCY LIMITATION OF FACT	Naval Research Laboratory	780131	ADA054371	U
Unavailable	Unavailable	MIDWATER ACOUSTIC MEASUREMENT SYSTEM - PAR AND ACODAC	Texas Instruments, Inc.	780228	ADB039924	U
ORI TR 1245	Moses, E. J.	OPTIONS, REQUIREMENTS, AND RECOMMENDATIONS FOR AN LRAPP ACOUSTIC ARRAY PERFORMANCE MODEL	ORI, Inc.	780331	ND	U
Unavailable	Hosmer, R. F., et al.	COMBINED ACOUSTIC PROPAGATION IN EASTPAC REGION (EXERCISE CAPER): INITIAL ACOUSTIC ANALYSIS	Naval Ocean Systems Center	780601	ADB032496	U
LRAPPRC78023	Watrous, B. A.	LRAPP EXERCISE ENVIRONMENTAL DATA INVENTORY, JUNE 1978 (U)	Naval Ocean R&D Activity	780601	NS; ND	U
TR052085	Solomon, L. P., et al.	HISTORICAL TEMPORAL SHIPPING (U)	Planning Systems Inc.	780628	NS; ND	U