

UNCLASSIFIED

AD NUMBER
ADB073873
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies only; Test and Evaluation; MAR 1983. Other requests shall be referred to Naval Electronic Systems Command, Washington, DC 20360.
AUTHORITY
ONR ltr, 31 Jan 2006

THIS PAGE IS UNCLASSIFIED



ADBO73873

ACOUSTIC EVALUATION OF SANDERS ASSOCIATES
ACODAC SENSORS

Robert DeChico
Sensors and Avionics Technology Directorate
NAVAL AIR DEVELOPMENT CENTER
Warminster, PA 18974

March 1983

PHASE REPORT

*Distribution Limited to U.S. Government Agencies only:
Test and Evaluation* JUN 1983
*Other requests for this document must be referred to:
NAVELECSYSCOM*

Prepared for
NAVAL ELECTRONICS SYSTEMS COMMAND
Department of the Navy
Washington, D.C. 20360

DTIC FILE COPY

DTIC
ELECTE
JUN 7 1983

A

83 06 06 0 72

NOTICES

REPORT NUMBERING SYSTEM — The numbering of technical project reports issued by the Naval Air Development Center is arranged for specific identification purposes. Each number consists of the Center acronym, the calendar year in which the number was assigned, the sequence number of the report within the specific calendar year, and the official 2-digit correspondence code of the Command Office or the Functional Directorate responsible for the report. For example: Report No. NADC-78015-20 indicates the fifteenth Center report for the year 1978, and prepared by the Systems Directorate. The numerical codes are as follows:

CODE	OFFICE OR DIRECTORATE
00	Commander, Naval Air Development Center
01	Technical Director, Naval Air Development Center
02	Comptroller
10	Directorate Command Projects
20	Systems Directorate
30	Sensors & Avionics Technology Directorate
40	Communication & Navigation Technology Directorate
50	Software Computer Directorate
60	Aircraft & Crew Systems Technology Directorate
70	Planning Assessment Resources
80	Engineering Support Group

PRODUCT ENDORSEMENT — The discussion or instructions concerning commercial products herein do not constitute an endorsement by the Government nor do they convey or imply the license or right to use such products.

APPROVED BY: E. Yannuzzi DATE: 5 MAY 1983

E. YANNUZZI
DIRECTOR, SATD

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NADC-83015-30	2. GOVT ACCESSION NO. AD-B073	3. RECIPIENT'S CATALOG NUMBER 873L
4. TITLE (and Subtitle) Acoustic Evaluation of Sanders Associates ACODAC Sensors		5. TYPE OF REPORT & PERIOD COVERED Phase
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Robert DeChico		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Sensors & Avionics Technology Directorate NAVAL AIR DEVELOPMENT CENTER Warminster, PA 18974		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Electronics Systems Command Department of the Navy Washington, D.C. 20360		12. REPORT DATE March 1983
		13. NUMBER OF PAGES 52
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Distribution Limited to U.S. Government Agencies Only; Test and Evaluation Other requests for this document must be referred to: NAVALELECSYSCOM		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES Appendix A		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Acoustic Evaluation ACODAC Sensors		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Two Sanders Associates Incorporated pressure gradient directional sensors capable of deep ocean operation were evaluated at the NAVAIRDEVCECEN'S Open Water Facility under simulated acoustical and environmental conditions. Measured acoustic performance was satisfactory except for narrow frequency bands where the directivity and receiving response were degraded.		

DD FORM 1473
1 JAN 73EDITION OF 1 NOV 68 IS OBSOLETE
S/N 0102-LF-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

TABLE OF CONTENTS

	<u>Page No.</u>
LIST OF TABLES.....	ii
LIST OF FIGURES.....	ii
SUMMARY.....	1
BACKGROUND.....	1
RESULTS.....	1
RECOMMENDATIONS.....	1
DISCUSSION.....	2
INTRODUCTION.....	2
SENSOR DESIGN AND DESCRIPTION.....	2
MEASURED DATA RESULTS.....	2
CONCLUSIONS.....	3
RECOMMENDATIONS.....	4
APPENDIX A – MEASUREMENT DATA ON ACODAC 1.....	A-1



[Handwritten signature or initials]



LIST OF TABLES

<u>Table</u>		<u>Page No.</u>
I	Required Performance for Sanders ACODAC Sensor	5
II	Directivity Pattern Summary for Sanders ACODAC Sensors (AC-2)	6

LIST OF FIGURES

<u>Figure</u>		<u>Page No.</u>
1	Basic Sensor	7
2	Measured Receiving Response Data for AC-2	8
3	Omnidirectional Receiving Response	9
4	Cosine-to-Sine Phase Response for AC-2	10
5	Close Directional-to-Omnidirectional Tracking	11
6	Response Relative to Pressure	12
7 thru 24	Directivity Patterns on the AC-2 Directional Channels	13-30

SUMMARY

BACKGROUND

The Naval Air Development Center was tasked by the Naval Electronic Systems Command (NAVELEX) (PME-124-30) to evaluate Sanders Associates, Incorporated, directional sensor (hydrophone) for compliance with NAVELEX Specification ELEX-B-409 of 17 June 1980. This report presents measured data on two redesigned Acoustic Data Capsule (ACODAC) sensors (AC-1, AC-2) and performance evaluation on one of these sensors (AC-2). These sensors, submitted by the contractor were acoustically measured at the NAVAIRDEVCON Open Water Facility.

RESULTS

Analysis of the measured data relative to the specification requirements indicates satisfactory acoustic performance with two exceptions: narrow frequency regions in the analysis band where response anomalies occurred and directivity performance was degraded with nulls depths of about -21 dB. The redesigned ACODAC sensors submitted by Sanders Associates, although displaying superior acoustic performance compared to units previously submitted, still have minor specification deficiencies in both the receiving and directivity responses.

RECOMMENDATION

It is recommended that Sanders investigate the sine/cosine response and directivity specification deficiencies and develop a positive approach to correct this hydrophone design problem area.

DISCUSSION

INTRODUCTION

This report presents the evaluation of two ACODAC sensors submitted by Sanders Associates, Incorporated. Acoustic performance evaluation criteria is based on table I. Both the directional and omnidirectional hydrophone elements within these sensors were evaluated for receiving voltage, phase, and directivity response. Environmental testing was conducted under ambient to 8000 psig pressure and at 6 degrees centigrade temperature.

SENSOR DESIGN AND DESCRIPTION

The basic sensor design is shown in figure 1 and consists of a neutrally-buoyant canister containing two orthogonal pair of electrodynamic geophones and one bottom-mounted ceramic disc element. The sensors were designated AC-1, 2 (NADC Code-225-1, 2) and represent a redesign of the original ACODAC sensor. Only AC-2, however, has the internal design improvements which Sanders is currently recommending. This unit, containing both the directional and omnidirectional sensors, has newer geophones and ruggedized machined aluminum straps and saddle to properly secure the geophones, thereby minimizing spurious resonances. A complete acoustic data package and evaluation are presented herein on this unit.

The AC-1 sensor contains only the directional sensors and utilizes 1/16 inch thick steel straps to secure the geophones. Sanders subsequently rejected this securing technique because of its susceptibility to in-band resonances. Although this unit was primarily submitted for sensor flow-noise evaluation, some acoustic calibration tests were initially performed indicating a defective cosine channel. It was decided to curtail further acoustic evaluation of this sensor and prepare it for the required flow-noise evaluation by replacing the defective geophones in the cosine channel. For completeness, the initial acoustic data taken on AC-1 is attached as appendix A.

MEASURED DATA RESULTS

Directional Receiving Response

Measured receiving response data for AC-2 is presented in figure 2. Measurements were made on the Maximum Response Axis (MRS) and at 80 deg off the MRA. Both the cosine and the sine channels displayed essentially flat response with a low frequency roll off starting at about 20 Hz and an upper resonance at 3300 Hz. The sensitivity at 100 Hz is nominally -204 dB/volt/uP with cosine to sine amplitude tracking within ± 1.0 dB. Evaluation of the off-axis response (80 deg) revealed narrow regions of response anomalies in the low (34 Hz), mid (170, 200 Hz) and upper (2000-2500 Hz) frequencies where the directivity performance was degraded.

Omnidirectional Receiving Response

The omnidirectional receiving response is presented in figure 3 and shows an essentially flat response over the analysis band with a minor resonance at 3500 Hz. The nominal sensitivity is -195 dB/volt/uP, without the internal preamplifier.

Phase Response

Cosine-to-sine phase response for AC-2 is presented in figure 4. Phase tracking is within the 15 deg. requirement over the analysis band. It was not possible to measure the phase response between the directional and omnidirectional sensors because of crosstalk induced from the amplified omnidirectional channel. To simulate this, phase measurements were taken comparing each directional channel with the output of a flat reference hydrophone with both sensors equidistant from the sound source. The results, presented in figure 5 show close directional-to-omnidirectional tracking ($\pm 7^\circ$) with no abrupt deviations. This implies that post sensor electronics can be utilized to achieve the 20 deg. directional to omnidirectional phase tracking requirement.

Directivity Patterns

Directivity patterns on the AC-2 directional channels are presented in figures 7 through 24 and summarized in table II. The analyzed data show that the required directivity performance is not met in the frequency regions of 34 Hz, 170 Hz, 200 Hz, and above 2000 Hz. Null depths in these regions do not meet the -30 dB relative to MRA requirement. Null depth in the degraded region is typically -21 dB.

Hydrostatic Pressure Testing

Hydrostatic pressure response data was taken on the directional and omnidirectional sensors of AC-2 up to 8000 PSIG. To minimize problems associated with entrapped air bubbles, a vessel pressure of 500 PSIG was used as the baseline reference with response changes noted at 1000 PSIG, 4000 PSIG, and 8000 PSIG. For the omnidirectional sensor this change is plotted in figure 6. The data shows no pressure-related changes in excess of 2 dB; therefore, the omnidirectional sensor is adequate.

Pressure response data on the directional channels was limited to specific frequency regions: nominally 25 Hz to 200 Hz and 600 Hz to 900 Hz. Frequencies outside these regions were contaminated by vessel structural resonances which tended to mask directional sensor performance. There were, however, no clearly discernible changes in the directional channel response as a function of hydrostatic pressure. This was expected since the geophone elements are mechanically isolated from the hydrostatic pressure.

Problem Areas Identified

The redesigned ACODAC sensor (AC-2) failed to meet the acoustic performance requirements in one critical area; hydrophone directivity. Null depth deficiencies were observed in narrow frequency regions within the analysis band.

One additional hardware-related problem area was identified. The plastic bulkhead electrical connector (BEACON, BRANTNER & Associates) failed twice and had to be replaced. Similar failures have been reported by Sanders personnel. Use of these inexpensive connectors on prototype hardware is not cost-effective; any repair becomes labor intensive and easily justifies the more rugged bulkhead connector planned for the production buoy.

CONCLUSIONS

The redesigned ACODAC sensor displayed superior acoustic performance over units previously evaluated at the NAVAIRDEVCON. Minor directivity deficiencies were noted in specific frequency regions of the analysis band for the directional sensors.

RECOMMENDATIONS

Sanders Associates should review the directional performance of the ACODAC sensor to insure that acceptable and consistent directivity is achieved over the analysis band. Assuming this is a geophone-related problem, two corrective approaches are recommended:

1. use a higher quality, anomaly-free geophone,
2. bench-test all geophones to enable selection of element pairs free of anomalies.

It is further recommended that additional prototype ACODAC sensors be fitted with ruggedized bulkhead connectors to minimize mechanical failures during contracto. in-house or NAVAIR-DEVCON evaluations.

TABLE I

REQUIRED PERFORMANCE FOR SANDERS ACODAC SENSOR

ACOUSTIC PARAMETERS EVALUATED	SPECIFICATION CRITERIA	ACCEPTABLE CRITERIA (INCLUDES CALIBRATION ACCURACY)
Receiving Response Shape at MRA	Figure 1	Smooth flowing and free of anomalies
Sine to Cosine Sensitivity Tracking	± 1.0 dB	± 2 dB
Mean Directional to Omni- directional Sensitivity Tracking	± 3.0 dB	Suitable for tracking via post-sensor electronic adjustment
Sine to Cosine Phase Tracking	15°	20°
Directional to Omnidirec- tional Phase Tracking	20°	Suitable for tracking via post-sensor electronic adjustment
Sensitivity Losses under 8000 PSIG pressure	-1.0 dB	-2.0 dB
Directional Patterns:		
a. Sensitivities for azimuth 70° from MRA	cosine ± 1.0 dB	cosine ± 2.0 dB
b. Sensitivities for azimuth 70° from MRA	*-8 dB/MRA	-7 dB/MRA
c. Null depths to MRA sensitivity	-30 dB	-28 dB
Omnidirectional Pattern	Omnidirectional ± 1.0 dB	Omnidirectional ± 2.0 dB

*This specification criteria is based on an ideal cosine pattern being -9.0 dB/MRA sensitivity at 70° degrees azimuth.

TABLE II

DIRECTIVITY PATTERN SUMMARY FOR SANDERS ACODAC SENSORS (AC 2)

FIGURE	FREQUENCY IN DB	MINIMUM NULL DB RELATIVE TO MAIN AXIS	SINE/COSINE NORMALITY DEVIATION IN DEGREES	ACCEPTABLE
Ideal	Analysis Band	-28	6 (± 3)	Yes
7	10	--	5½	Yes
8	30	-29	5½	Yes
9	34	-21	4½	No
10	50	--	5	Yes
11	100	--	6	Yes
12	135	--	5	Yes
13	150	--	5½	Yes
14	170	-21	6	No
15	180	--	6	Yes
16	200	-25	6	No
17	250	-32	3½	Yes
18	500	-30	4	Yes
19	750	-28	3½	Yes
20	1000	--	3½	Yes
21	1500	-33	3	Yes
22	2000	-20	2½	No
23	2300	-22	4	No
24	2500	-24	4½	No




Figure 1




Figure 2




Figure 3

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES
OPEN WATER FACILITY
PHASE REPORT




Figure 4

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES
OPEN WATER FACILITY
PHASE RESPONSE




Figure 5

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES
OPEN WATER FACILITY
RESPONSE RELATIVE TO PRESSURE





Figure 6

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN

MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 10
DATE 6/17/82
TST ENGR RAD

Figure 7

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 30
DATE 6/17/82
TST ENGR RAD

Figure 8

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 34
DATE 7/15/82
TST ENGR RAD

Figure 9

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 50
DATE 6/17/82
TST ENGR RAD

Figure 10

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE CW
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 100
DATE 6/17/82
TST ENGR RAD

Figure 11

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE CW
PLANE XY
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 135
DATE 7/15/82
TST ENGR RAD

Figure 12

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE CW
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 150
DATE 7/15/82
TST ENGR RAD

Figure 13

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 170
DATE 7/15/82
TST ENGR RAD

Figure 14

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT 225-2 (AC-2)
FREQ/HZ 180 Hz
DATE 6/17/82
TST ENGR RAD

Figure 15

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN




MODE CW
PLANE xy
DEPTH 9.2M
SEPARATION 1M

TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 200
DATE 7/15/82
TST ENGR RAD

Figure 16

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN

MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 250
DATE 7/15/82
TST ENGR RAD

Figure 17

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN




MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M

TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 500
DATE 6/17/82
TST ENGR RAD

Figure 18

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN

MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 750
DATE 7/15/82
TST ENGR RAD

Figure 19

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

**OPEN WATER FACILITY
RECEIVING PATTERN**



MODE	cw
PLANE	xy
DEPTH	9.2M
SEPARATION	1M


TEST UNIT	Code 225-2 (AC-2)
FREQ/HZ	1000
DATE	6/17/82
TST ENGR	RAD

Figure 20

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE CW
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 1500
DATE 6/17/82
TST ENGR RAD

Figure 21

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN




MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M

TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 2000
DATE 6/17/82
TST ENGR RAD

Figure 22

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN

MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 2300
DATE 6/17/82
TST ENGR RAD

Figure 23

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M

TEST UNIT Code 225-2 (AC-2)
FREQ/HZ 2500 Hz
DATE 7/15/82
TST ENGR RAD

Figure 24

NADC-83015-30

APPENDIX A
MEASUREMENT DATA
ON ACODAC 1




Figure A-1




Figure A-2





Figure A-3

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-1 (AC-1)
FREQ/HZ 10
DATE 6/22/82
TST ENGR RAD

Figure A-4

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN




MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 2M

TEST UNIT Code 225-1 (AC-1)
FREQ/HZ 10
DATE 6/22/82
TST ENGR RAD

Figure A-5

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN

MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-1 (AC-1)
FREQ/HZ 30
DATE 6/22/82
TST ENGR RAD

Figure A-6

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-1 (AC-1)
FREQ/HZ 30
DATE 7/13/82
TST ENGR RAD

Figure A-7

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-1 (AC-1)
FREQ/HZ 50
DATE 6/22/82
TST ENGR RAD

Figure A-8

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 2M


TEST UNIT Code 225-1 (AC-1)
FREQ/HZ 50
DATE 6/22/82
TEST ENGR RAD

Figure A-9

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-1 (AC-1)
FREQ/HZ 50
DATE 7/13/83
TST ENGR RAD

Figure A-10

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code-225-1 (AC-1)
FREQ/HZ 100
DATE 6/22/82
TST ENGR RAD

Figure A-11

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-1 (AC-1)
FREQ/HZ 100
DATE 7/13/82
TST ENGR RAD

Figure A-12

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-1 (AC-1)
FREQ/MZ 140 Hz
DATE 6/22/82
TST ENGR RAD

Figure A-13

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-1 (AC-1)
FREQ/HZ 190
DATE 6/22/82
TST ENGR RAD

Figure A-14

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-1 (AC-1)
FREQ/HZ 200
DATE 6/22/82
TST ENGR RAD

Figure A-15

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE CW
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-1 (AC-1)
FREQ/HZ 500
DATE 6/22/82
TST ENGR RAD

Figure A-16

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE CW
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-1 (AC-1)
FREQ/MZ 600
DATE 6/22/82
TST ENGR RAD

Figure A-17

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE CW
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-1 (AC-1)
FREQ/NZ 1000
DATE 6/22/82
TST ENGR RAD

Figure A-18

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M


TEST UNIT Code 225-1 (AC-1)
FREQ/HZ 1500
DATE 6/22/82
TST ENGR RAD

Figure A-19

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE CTV
PLANE xy
DEPTH 3.2M
SEPARATION 1M


TEST UNIT Code 225-1 (AC-1)
FREQ/HZ 2000
DATE 6/22/82
TST ENGR RAD

Figure A-20

NAVAL AIR DEVELOPMENT CENTER
SONAR DEVELOPMENT SIMULATION FACILITIES

RELATIVE DB

OPEN WATER FACILITY
RECEIVING PATTERN



MODE cw
PLANE xy
DEPTH 9.2M
SEPARATION 1M

TEST UNIT Code 225-1 (AC-1)
FREQ/HZ 2300
DATE 6/22/82
TST ENGR RAD

Figure A-21

DISTRIBUTION LIST

Report No. NADC-83015-30

	No. of Copies
NAVELEX	4
PME-124-30 (Cmdr. McCrumb) (2 copies)	
PMA-264 (1 copy)	
PM-4, R. Fabian (1 copy)	
NAVAIRDEVCEN	9
Codes: 1AA (1 copy)	
1 A511 (2 copies)	
3043 (3 copies)	
8131 (3 copies)	



DEPARTMENT OF THE NAVY

OFFICE OF NAVAL RESEARCH
875 NORTH RANDOLPH STREET
SUITE 1425
ARLINGTON VA 22203-1995

IN REPLY REFER TO:

5510/1
Ser 321OA/011/06
31 Jan 06

MEMORANDUM FOR DISTRIBUTION LIST

Subj: DECLASSIFICATION OF LONG RANGE ACOUSTIC PROPAGATION PROJECT
(LRAPP) DOCUMENTS

Ref: (a) SECNAVINST 5510.36

Encl: (1) List of DECLASSIFIED LRAPP Documents

1. In accordance with reference (a), a declassification review has been conducted on a number of classified LRAPP documents.
2. The LRAPP documents listed in enclosure (1) have been downgraded to UNCLASSIFIED and have been approved for public release. These documents should be remarked as follows:

Classification changed to UNCLASSIFIED by authority of the Chief of Naval Operations (N772) letter N772A/6U875630, 20 January 2006.

DISTRIBUTION STATEMENT A: Approved for Public Release; Distribution is unlimited.

3. Questions may be directed to the undersigned on (703) 696-4619, DSN 426-4619.

A handwritten signature in black ink, appearing to read "B. F. Link", is positioned above the typed name.

BRIAN LINK
By direction

Subj: DECLASSIFICATION OF LONG RANGE ACOUSTIC PROPAGATION PROJECT
(LRAPP) DOCUMENTS

DISTRIBUTION LIST:

NAVOCEANO (Code N121LC – Jaime Ratliff)
NRL Washington (Code 5596.3 – Mary Templeman)
PEO LMW Det San Diego (PMS 181)
DTIC-OCQ (Larry Downing)
ARL, U of Texas
Blue Sea Corporation (Dr. Roy Gaul)
ONR 32B (CAPT Paul Stewart)
ONR 321OA (Dr. Ellen Livingston)
APL, U of Washington
APL, Johns Hopkins University
ARL, Penn State University
MPL of Scripps Institution of Oceanography
WHOI
NAVSEA
NAVAIR
NUWC
SAIC

Declassified LRAPP Documents

Report Number	Personal Author	Title	Publication Source (Originator)	Pub. Date	Current Availability	Class.
NORDA35VOL.1BK 2OF3	Lauer, R.B.	THE ACOUSTIC MODEL EVALUATION COMMITTEE (AMEC) REPORTS, VOL. 2- APPENDICES A-D- EVALUATION OF THE FACT PL9D TRANSMISSION LOSS MODEL	Naval Ocean R&D Activity	810901	ND ADA034019	U
NORDA36VOL.3BK 2OF3	Lauer, R.B., et al.	THE ACOUSTIC MODEL EVALUATION COMMITTEE (AMEC) REPORTS, VOL. 3- APPENDICES A-D- EVALUATION OF THE RAYMODE X PROPAGATION LOSS MODEL (U)	Naval Ocean R&D Activity	810901	ND ADA034022	U
Unavailable	Hooper, M. W., et al.	MEASUREMENTS AND ANALYSIS OF ACOUSTIC BOTTOM INTERACTION IN THE NORTHWESTERN MEXICAN BASIN	University of Texas, Applied Research Laboratories	811005	ADA107551	U
Unavailable	Kirby, W. D.	FINAL REPORT FOR CONTRACT NUMBER N00014-78-C-0862	Science Applications Inc.	820201	ADA111000	U
Unavailable	Brunson, B. A., et al.	PHYSICAL SEDIMENT MODEL FOR THE PREDICTION OF SEAFLOOR GEOACOUSTIC PROPERTIES	Planning Systems Inc.	820701	ADA119445	U
Unavailable	Cavanagh, R. C., et al.	NORDA PARABOLIC EQUATION WORKSHOP, 31 MARCH - 3 APRIL 1981	Naval Ocean R&D Activity	820901	ADA121932	U
NORDA34VOL.1A	Martin, R. L., et al.	THE ACOUSTIC MODEL EVALUATION COMMITTEE (AMEC) REPORTS, VOL. 1A- SUMMARY OF RANGE INDEPENDENT ENVIRONMENT ACOUSTIC PROPAGATION DATA SETS	Naval Ocean R&D Activity	820901	ADC034017; ND	U
Unavailable	Bartberger, C. L., et al.	THE ACOUSTIC MODEL EVALUATION COMMITTEE (AMEC) REPORTS, VOLUME 2. THE EVALUATION OF THE ACOUSTIC MODEL EVALUATION COMMITTEE	Naval Ocean R&D Activity	820901	ADC034019	U
Unavailable	Deavenport, R., et al.	(AMEC) REPORTS, VOLUME 3. EVALUATION OF THE RAYMODE X PROPAGATION LOSS MODEL. BOOK 2. APPENDICES A-D	Naval Ocean R&D Activity	820901	ADC034022	U
Unavailable	Unavailable	1975-1982 SUMMARY REPORT	Analysis and Technology, Inc.	821217	ADA192591	U
Unavailable	DeChico, D.	ACOUSTIC EVALUATION OF SANDERS ASSOCIATES ACODAC SENSORS	Naval Air Development Center	830301	ADB073873	U
NRL-FR-8695; NRL-8695	Palmer, L. B., et al.	TRANSVERSE HORIZONTAL COHERENCE AND LOW-FREQUENCY ARRAY GAIN LIMITS IN THE DEEP OCEAN	Naval Research Laboratory	830809	ND ADA134916	U
Unavailable	Unavailable	ENGINEERING SUPPORT FOR ACOUSTIC AND ANALYSIS SYSTEM	Systems Integrated	840101	ADB091112	U
Unavailable	Unavailable	SEAS (SURVEILLANCE ENVIRONMENTAL ACOUSTIC SUPPORT PROGRAM) SUPPORT	Systems Integrated	840229	ADB091119	U