UNCLASSIFIED

AD NUMBER

ADB103813

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Foreign Government Information; MAY 1986. Other requests shall be referred to Canadian Embassy, 3100 Massachusetts Ave., NW, Washington, DC 20008.

AUTHORITY

DCIEM ltr 28 Nov 1986

THIS PAGE IS UNCLASSIFIED

THIS REPORT HAS BEEN DELIMITED AND CLEARED FOR PUBLIC RELEASE UNDER DOD DIRECTIVE 5200,20 AND NU RESTRICTIONS ARE IMPOSED UPON ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;

DISTRIBUTION UNLIMITED.





May 1986

DCIEM No. 86-R-24

PERFORMANCE OF SEVERAL AIRCREW LIFE-PRESERVERS IN CONJUNCTION WITH VARIOUS CLOTHING ENSEMBLES

N.A. Martin



Defence and Civil Institute of Environmental Medicine 1133 Sheppard Avenue West, P.O. Box 2000 Downsview, Ontario M3M 3B9

DEPARTMENT OF NATIONAL DEFENCE - CANADA

and the second second

TABLE OF CONTENTS

| | Page |
|--|------|
| ABSTRACT | ۷ |
| INTRODUCTION | 1 |
| METHODS | |
| - Subjects | 2 |
| - Mass of Subjects | 2 |
| - Clothing Ensembles | 2 |
| - Summer Ensemble | 2 |
| - Winter Ensemble | 3 |
| - Inmersion Suit Ensemble | 3 |
| - Life-Preservers | 3 |
| - Measurements | 4 |
| | |
| RESULTS | - |
| - Life-Preserver Buoyancy | 5 |
| - Flotation Angle | 5 |
| - Self-Righting Capabilities | 5 |
| - Mouth Above Water Level | 5 |
| - Statistical Analysis | 5 |
| - Performance Comparisons | 6 |
| A. 6. 6. 10. 7. 6. 1 | |
| DISCUSSION | |
| - Lite-Preserver Idlosyncrasies | 0 |
| CONCLUCTONS | - |
| CUNCLUSIONS | / |
| OF COMMENDATIONS | |
| RECOMMENDATIONS | 0 |
| DEEEDENCES | 0 |
| REFERENCES | , |
| ANNEY A - Etaura 1 Current CE Life-Dreserver let Aircrev | 10 |
| - Elaura 2 Cash-Scarla Life-December, dec Allerew | 11 |
| - Figure 2. Saab-Scalia Life-Preserver | 12 |
| - Figure J. Aerazur Lite-Preserver | 12 |
| - Figure 4. Jeculiar Aus-2 Lite-Freserver | 14 |
| - Figure 5. Electrice Acele Mergurement | 16 |
| - Figure 0. Flotation Angle neasurement | 16 |
| - Figure 7. Seriexigniting - Starting Position | 17 |
| ANNEY P - Table 1 Polovast Asthrogometric Data | 10 |
| - Table 2 Mars and linderwater Veight of Subjects | 10 |
| - Table 2. Puovancy of Selected 146-Decompose | 10 |
| - Table 8 life-December Comparison mached by | 19 |
| aute o. Lite-rreserver comparison, rankeu by | 10 |
| ANNEY C - Table A Elotation Angle | 20 |
| ANNEY D - Table 5. Solf-Dighting Times / Armor at Sider | 21 |
| ANNEY E - Table 6 Colf-Dighting Times/Armes at Stues | 21 |
| ANNEY E - Table 7 Subjects' Mouth Above Uster | 22 |
| ANNEA I TAUTE /. JULICLS HUULI MUVE WALE | 6.7 |

ABSTRACT

Three currently-available life-preservers were tested to evaluate their performances compared to the current jet aircrew model, when worn by five representative subjects wearing three different Canadian Forces flying clothing ensembles. Parameters tested were: maximum buoyancy provided, subject mouth-level above water, subject flotation angle, and time to self-right the inert subject. Results indicated that all but one of the lifepreservers tested met the ASCC Standard of 35 pounds buoyancy, two met the five-second limit for self-righting, although none would right the immersion-suited subject, and none achieved the optimum 45 degrees flotation angle.

| Acce | ssion For | |
|-------|------------|-------|
| NTIS | GRASI | - |
| DTIC | TAB | - |
| Unen | nounced | 0 |
| Jacob | ffication_ | anger |
| By | attration | |
| Dist | ritution/ | |
| Ava | lability | Codes |
| | Avail cad | 105 |
| Dist | Special | |
| - | 1 1 | |
| 14 | | |
| 10 | | |

- Y -

the second states and states and a second states and a second states and a second states and a second states a

INTRODUCTION

The three types of aircrew life-preserver currently in use in the Canadian Forces (CF) are modified versions of very old designs (1). There is little difference between the jet aircrew model, NATO Stock No. (NSN) 4220-21-871-6316, and the one used during the Second World War. and none of the current equipment meets the minimum specifications of recognized standards (1) such as the British Standards Institution (BS3595) (2), or the Air Standardization Coordinating Committee (ASCC) Air Standard (Air STD) 61/4 (3) which has been ratified by the CF.

In his review of incidents/accidents involving CF aircrew over the past twenty years, Brooks (4) found that the life-preservers in use have generally given good service, but that there is room for improvement and that one model used in Maritime Command, the Buaer, should be replaced.

The 1977 draft Statement of Requirement (5) outlined the shortcomings of the current life-preservers. This draft was superceded in 1984 with a SOR that includes the specifications of ASCC Air Standard 61/4. The following are required:

- a. inflation within five seconds;
- b. maximum self-righting time of five seconds;
- c. optimum flotation angle of 45 ± 10 degrees from vertical;
- d. minimum buoyancy of 16 kg (35 lbs);

CONTRACTOR CONTRACTOR CONTRACTOR

- e. a redundant bladder system;
- f. a slim profile when deflated, with no restriction to head movement while wearing helmet and oxygen mask;
- g. minimal heat buildup/retention in a hot cockpit;
- compatibility with harnesses of parachutes and/or seats of all CF aircraft; and
- j. easy to donn/doff.

As a result of complaints from the users, the latest being a UCR from 410 Squadron, Cold Lake (6), DCIEM was tasked to investigate and resolve (7) the reported incompatibility of the -6316 life-preserver and the CF-188 Simplified Combined Harness. MLSD's recommendations to NDHQ/DAS Eng in January 1984 were mainly to modify operating procedures to minimize the problems until a replacement life-preserver could be introduced.

Because of its long history of interest and involvement in lifepreserver problems and its mandate as Aviation Life Support specialists, MLSD subsequently started an in-house project to evaluate the lifepreservers currently available world-wide against the current international standards, and the draft SOR (8) A secondary goal was to determine their compatibility with current CF aircrew life support systems. Many test reports of other agencies, e.g. (9,10,11) were useful in identifying the best possible test procedures.

The results of the evaluation are given in this report. Three state-of-the-art life-preservers currently in use with national air forces were studied and compared with the current standard unit:

- a. NSN 4220-21-871-6316, Life-Preserver, yoke (CF) (-6316) (Figure 1);
- b. SECUMAR Model AUS-2 (Australian Air Force) (AUS) (Figure 2);
- c. Saab-Scania Model 601577-5 (Swedish Air Force) (S-S) (Figure 3); and
- d. Aerazur Model 35-2, (French Air Force) (Aer) (Figure 4).

METHODS

Subjects

Five subjects, three male and two female, were selected for these tests, in an attempt to cover most of the anthropometric range of aircrew sizes. Relevant anthropometric data of the subjects is recorded in Table 1. Gill (11) found that there is no significant relationship between flotation angle and chest circumference or buttock-heel length of subjects. Because all his subjects were male, however, it was deemed necessary to test the possibility that there is a significant difference between the flotation characteristics of male and female subjects.

Mass of Subjects

Each subject was weighed, dry, wearing each of the clothing ensembles worn in the tests, and then underwater, in bathing suit only. Underwater weight determines each subject's natural buoyancy. For this procedure, depicted in Figure 5, the subject was suspended from the scale by a web belt under the arms. The subject exhaled as much air as possible, submerged, and relaxed while the measurement was taken. Dry weight and lung capacity (Force Vital Capacity, (FCV)) were also measured, and the body density was calculated. The results of all weighings are found in Table 2, Annex B.

Clothing Ensembles

Each subject was fitted with the appropriate clothing ensemble for each test series and retained the articles for the duration of the tests.

Summer Ensemble

All subjects wore the following basic clothing for all of the test measurements done in summer ensemble:

INTER THE PARTY AND A DECEMPTOR AN

| a. | Underwear, light, | NSN 8415-21-870-5475; |
|----|------------------------------|--------------------------|
| b. | Turtleneck, cotton, | NSN 8415-21-870-5480; |
| c. | Socks, wool | NSN 8440-21-104-2860; |
| d. | Boots, summer flying | NSN 8430-21-868-7466; |
| | c/w zipper, boot | NSN 8430-21-840-3764; |
| е. | Coverall, summer flying | NSN 8415-21-876-5406; |
| f. | Gloves, flying, shell | NSN 8415-21-744-0140; |
| q. | Gloves, flying, insert, wool | NSN 8415-21-852-9129; |
| h. | Helmet, flying DH 41-2, | MSN 8475-21-868-3553; ar |
| 1. | Jacket, flying, | NSN 8415-21-859-0485. |
| | intermediate | |

Winter Ensemble

The winter clothing ensemble consists of items b,c,f,g,h above, plus the following:

| a. | Underwear, thermal, cotton | NSN 8415-21-859-0727; | 415-21-859-0727; | |
|----|-----------------------------|-----------------------|------------------|----|
| b. | Undershirt, thermal, cotton | NSN 8415-21-859-0732; | 415-21-859-0732: | |
| с. | Jacket, winter flying, | NSN 8415-21-859-0498; | 415-21-859-0498; | |
| | Type IV | | | |
| d. | Pants, winter flying, | NSN 8415-21-859-0472; | 415-21-859-0472; | |
| e. | Boots, flying, duffle | NSN 8430-21-878-1206; | 430-21-878-1206: | |
| f. | Socks, duffle | NSN 8440-21-103-7669; | 440-21-103-7669; | |
| g. | Insoles, felt | NSN 8335-21-857-8949; | 335-21-857-8949; | an |
| h. | Insoles, mesh | NSN 8335-21-872-4958. | 335-21-872-4958. | |
| | | | | |

Immersion Suit Ensemble

During the tests using the immersion suit, the following clothing items were worn:

a. summer items c,d,f,g,h;

WARMAN AND THE REAL PROPERTY AND THE REAL PR

- b. winter items a and b;
- c. Underwear aircrew (Hodges), NSN 8415-21-870-4658; and d. Coverall, immersion, NSN 8475-21-847-6777.
- constant-wear

Life Preservers

Each life-preserver was inflated by its standard CO2 bottle, weighted, and submerged in a tank of cold fresh water. The force (weight) measured by a spring scale was subtracted from the combined dry weight of the life-preserver plus ballast weights to determine the buoyancy. These figures are reasonably representative of the buoyancy that would be provided at 0 deg. C. The internal bladder pressure was measured with a "Magnehelic" pressure gauge, through a guick-disconnect in the oral inflation tube. To ensure the same bladder pressure was used for each subject, this pressure was duplicated, using compressed air, in the water trials using subjects. Only one life-preserver of each type was used in all the trials, and the

waist adjustment and any other straps were adjusted to the same degree of tightness as much as possible, for each subject.

Measurements

Measurements of each subject in each clothing ensemble, and in each life-preserver, were carried out in fresh water in the DCIEM static tank. Water temperature ranged from 11 to 33 deg. C. All measurements were taken four times to assess the reproducibility of the results. The subject entered the pool, swam around for approximately five minutes if the clothing was dry to start, and then all measurements were taken. The subject then left the tank, changed to the second life-preserver, and the procedure was repeated. This sequence continued until all life-preservers had been tested. Each of the subjects went through the same procedure. Finally, the trials were repeated as above, with each subject dressed in the other two clothing ensembles.

- a. Flotation Angle was determined by underwater photography of each subject, taken through the glass side in the tank. The subject was centered in the pool near a freely floating weighted pole which served as a vertical reference. The subject relaxed as completely as possible, was instructed to exhale all air, and was photographed. The flotation angle was obtained from the photographs, as follows (eg. Figure 6):
 - (1) The plane of flotation was taken as the plane of the trunk, represented by a line passing through the centres of the hip and shoulder joints. The centre of the shoulder joint was found by overlying the photograph with a "bull's eye" and matching it with the curve of the shoulder. The centre of the hip joint was taken as the midpoint of the greatest front-to-back width of the body at buttock level. The line joining these two points was taken as the plane of the trunk. Flotation angle was the angle between the plane of the trunk and the vertical.
- b. The self-righting times were determined by measuring in seconds the time taken by the subject to be returned to the face-up position in the water, starting from a face-down attitude flat on the water surface with feet held at the surface by a helper, as shown in Figure 7. The subject held his face out of the water until the surface was still, then took several deep breaths, let out half, and relaxed completely until his motion stopped. The helper released the feet, and the watch was started. The watch was stopped when the helper considered the subject to have achieved a "normal" steady-state flotation attitude, or at 30 seconds if the subject were still floating face down. Two selfrighting times were recorded: one with a starting position of arms extended at right angles to the body, the other with arms relaxed by the sides.
- c. Subject's mouth-above-water level was measured from the water surface to the lower corner of the mouth of the subject. lying

relaxed in still water. A bar, to which was attached a retractable tape measure, was suspended over the subject's head. With the subject and helper in the tank, the distances from the bar to the water, and to the subject's mouth were recorded. The difference is the level of the subject's mouth above water.

d. Because none of the life-preservers tested met all the ASCC standards, specific tests for compatibility with aircraft systems were not carried out. However, some observations on each item are recorded in the Discussion Section.

RESULTS

Life-Preserver Buoyancy

As can be seen from the results of the buoyancy tests, shown in Table 3., the CF -6316 was the only unit which could not meet the ASCC standard of 16 Kg buoyancy in 0 deg. C water.

Flotation Angle

As can be seen from the results in Table 4. (Annex C), only the -6316 provided near (37 deg.) the specified requirement of 45 ± 10 degrees flotation angle, and then only in flying suits. When in immersion suits the subjects floated parallel to the surface.

Self-Righting Capabilities

The self-righting capability results are shown in Table 5. (Annex B) and Table 6. (Annex E). Only the Aerazur and Secumar AUS-2 met the ASCC five-second standard with all subjects wearing flying suits; none of the life-preservers righted all subjects in immersion suits.

Mouth Above Water Level

The level-above-water measurements are shown in Table 7. (Annex F). From the mean height recorded, it can be seen that the Saab-Scania floated subjects slightly higher than did the others, except when the immersion suit was worn, when the Aerazur was the best performer.

Statistical Analysis

The independent t-test, based on a very limited population sample, indicated that there were no statistically significant (p < 0.01) male/female differences in the data. In a few cases, sex differences approached a marginal significance (p < 0.05), but these were too infrequent to warrant treating the data as two groups. Subsequent analyses were, therefore, performed by treating all five subjects as a single group.

Paired t-test analyses indicated no statistically significant differences between summer and winter clothing ensembles for any of the tests; however, since the rank order of the life-preservers was different between summer and winter ensembles in the Analysis of Variance (AOV) tests, these data were kept separate.

and the state of the second second and

Performance Comparisons

Comparisons between life-preservers were done with a (one-way) AOV test. The four life-preservers were "treatments" and the variables were mouth-level above water, self-righting time and flotation angle, for each clothing ensemble. From the AOV, the parameters which showed statistical significance (i.e.: p < .01) were given Ouncan's Test. From the resulting sample rankings, a comparison table was drawn up, shown in Table 8 (Annex B). As indicated in the table, even in cases where the results indicated a difference, no unit was best for all tests. Grouping those that were not statistically (p < .05) different, as shown by the underscoring, helps to clarify the results. For instance, the mean self-righting time, in winter clothing, by the Aerazur and the Saab-Scania was virtually the same. Overall, it could be said that the Saab-Scania or Aerazur would perform best at self-righting and at height above water, and that the -6316 is the best at providing a good flotation angle. At this point a relative weighting of the importance of each parameter for any intended role would help in making a recommendation of one unit over another.

OISCUSSION

Life-Preserver Idiosyncrasies

CF -6316. This unit has the lowest (uninflated) profile of all the items tested, and causes no interference with head movements. A well-known drawback of this type of bladder is that it covers most of the front of the abdomen, which makes it uncomfortable in a hot environment. Because of the low pressure in the inflated bladder, the subject's head is not well supported by the collar when in the water. For most subjects, when they were floating face-up, the back of their head and their ears were submerged, as shown in Figure 8. This permits a great heat loss in cold water. The position of the waist-belt is nearly ideal for most subjects, placing the centre of buoyancy coincident with the subject's centre of gravity. It was too low however, on both (75th percentile) female subjects, and also, the belt could not be adjusted enough by the ordinary buckle for them. The only problem encountered with the length (63 cm.) of bladder/stole is that the T-handle harness release of the CF-188 tends to slide under it when the subject is hanging in the harness. The glued-together rubberized nylon bladder has to be proof-tested every two months.

SECUMAR AUS-2. The short (35 cm) bladder stole has a very low profile, and the part behind the neck can be adjusted to move it farther from the nape of the neck. Instead of a vest, the bladder and pockets are attached to a strap suspension. The strap system would allow dissipation of body heat, thus preventing heat loading. However, it is somewhat complicated and requires precise adjustment for each subject. Further, it does not provide a good low attachment of the bladder to the subject's centre of gravity to give a good flotation angle. The female subjects experienced considerable discomfort from the tight straps crossing the breasts. The single Radio-Frequency (RF)-sealed bladder uses a German-made operating head and CO2 bottle which could be interchanged with current CF equipment.

SAAB-SCANIA. The stole of this unit has a very low profile, and is quite short (36 cm), providing little interference with oxygen mask, helmet or

harnesses. The suspension harness is very short, and on all subjects the waist strap came over the rib-cage. The female subjects found this uncomfortable for the same reason as with the SECUMAR. This shortcoming also allowed the whole assembly to slide up when in water, and resulted in the buoyant force being centered higher than the subject's centre of flotation. A poor flotation angle resulted. Adjusting the waist strap entailed pulling both ends of the strap to the rear, a somewhat awkward and difficult manoeuvre for the subject. The lack of a front opening and the small neck hole made the unit hard to donn and doff, especially when bulky clothing was worn. This unit uses a British Walter Kidde head and CO2 bottle, which were difficult to obtain from the U.K., and which could not be easily replaced with current CF items. The unit has two similar RF-sealed polyurethane bladders, one on top of the other, both inflated from one source.

<u>AERAZUR</u>. The 46 cm-long stole of this unit has a fairly low profile, especially behind the neck and over the shoulders, providing good clearance. The vest is fairly large and heavy, which could create heat loading. The waist strap is easily adjustable by pulling forward, but was above the waist on all but the shortest subjects, and could not be adjusted small enough to fit a small waist. Inflation times were slow, and the stole zipper did not break open completely on all inflations. The single bladder of gluedtogether polyurethane is one of the largest tested, and is shaped to provide a good self-righting moment. Unfortunately, the large buoyant force is not centered low enough to provide a good flotation angle. The operating head and CO2 bottle are French-built and are not easily replaceable with current CF items.

CONCLUSIONS

It is concluded that:

- a. because of the consistency of the results, the methods are reliable;
- based on a very limited population sample, the gender of the subject did not cause a significant difference in the performance of the units;
- c. the wearing of summer or winter flying ensembles did not produce significant differences in the results;
- d. for self-righting, the Aerazur and the AUS-2 performed significantly better than the other two, but none of the units would self-right all subjects within the five seconds maximum, and none would self-right any subject wearing the immersion suit ensemble; and
- e. for flotation angle, the -6316 performed significantly better than the other three units despite its low buoyancy; however, none of the units met the 45 deg. \pm 10 deg. criterion for all subjects.

RECOMMENDATIONS

This study reinforces earlier findings which suggested that designing a life-preserver to meet all the requirements is difficult, and design of the new CF life-preserver is expected to require considerable design effort. It is recommended that the information of this report be passed on the the designers to simplify the task to whatever extent possible. The points listed below are offered as guidelines:

- a. the bladder material should be of the smallest possible bulk consistent with adequate strength;
- a glued-together bladder is not acceptable in new designs; (radio frequency sealing is preferred)
- c. the bladder should have a large volume located directly above the subject's C of G, be quite slim over the shoulders, and with a head support behind the neck;
- d. the inflated bladder must render the face-down subject unstable in the rolling or the pitching plane, thus providing a positive righting moment;
- e. the bladder must be firmly anchored at its lowest point to the C of G area of any subject, e.g., with a snug, low waist-strap;
- f. the deflated bladder should be folded and encased in a short stole which lies flat all around, and which is attached to the vest/suspension only at the inside edges, the outside edges should be free to allow harness straps to pass under;
- g. the stole opening system must be simple and not allow hang-ups during inflation;
- the uninflated unit must be easy to donn/doff for this a front closure is recommended; and
- j. performance tests should be conducted, which will include 5th and 95th percentile CF male and female subjects.

REFERENCES

- FIRTH, J.A., R.W. SMITH, J.C. STEFFLER; July 1983, Evaluation Of Canadian Forces Life-Preservers To Determine Compliance With Air Standardization Coordinating Committee Air Standard 61/4, DCIEM Report No. 83-C-38.
- British Standards Institution; 1981, Specification For Life-jackets, BSI Specification BS3595:1981.
- AIR STANDARDIZATION CO-ORDINATING COMMITTEE; 5 September 1975, Flotation And Sea Survival, Test Methods and Requirements, AIR STD 61/4.
- BROOKS, C.J., J.A. FIRTH; May 1983, A Review of the Performance Of The Canadian Military Aircrew Life-Preservers Over The Last Twenty Years, DCIEM Report No. 83-R-29.
- PAISLEY, W.G., Colonel, DAR,; May 577, Statement Of Requirement -Aircrew Life-Preserver, 14220-100(DAR 3-2).
- ERHART, D.R. Capt.; 22 June 1983, UNSATISFACTORY CONDITION REPORT (UCR) On Life-Preserver 4220-21-871-6316, UCR No. D0134/3142FS.
- RANSON, R.G. Col.; 12 January 1984, CF Aircrew Life-Preserver Tasking, 14220-102 (DAS Eng 4).
- NATIONAL DEFENCE HEADQUARTERS (Ottawa); DIRECTORATE OF AIR REQUIRE-MENTS (DAR), 9 March 1984, Statement of Requirements, Aircrew Life-Preservers, 14220-100(DAR 3-2).
- .9. MACINTOSH, R.R., PASK, E.A.; 1957, The Testing Of Life-Jackets, Brit. J. industr. Med, 1957, 14, 168
- GABB, J.E., A.F. DAVIDSON, H.M. FERRES; 1 October 1964, Studies of the Principles of Flotation by Life-Jackets (Summary), Proc. R. Soc. Med., Vol 58, February 1965.
- GILL, P.H.R. (1975). The Flotation and Self-Righting Properties of Subjects Wearing A Mk 14 Life-preserver In Association With Various Clothing Assemblies. Aircrew Equipment Group Report #362. RAF/IAM.
- STEWART, LARRY E., "1985 Anthropometric Survey of CF Aircrew (Pilots and Navigators)", Human Element Inc., Tech Report 85-12-01 December 1985
- MACDONALD, G.A.A.H., K.A. SHARRARD, M.C. TAYLOR; July 1978, Preliminary Anthropometric Survey of Canadian Forces Women, DCIEM Technical Report No. 78X20.



Figure 1. Current CF Life-Preserver, Jet Aircrew



Figure 2. Saab-Scania Life-Preserver



Figure 3. Aerazur Life-Preserver



Figure 4. Secumar Aus-2 Life-Preserver

14 ANNEX A to 3614H11-19 (MLSD) 28 May 1986 Figure 5. Underwater Weighing

P. A. I

1.1.56

N. 8 4 4 4 4



Figure 6. Flotation Angle Measurement

SALAN STATISTICS

a constant of the second states of the second states of the



Figure 7. Self-Righting - Starting Position

CLEE

122



Figure 8. Minimal Head-Support of -6316 Life-Preserver

and a second second

Concernant and a second

のためのです。

1000000

| Cubicat | State | ure | Mas | 55 | Chest Circumference | | |
|---------|-------|-------|------|-------|------------------------|-------|--|
| SUDJECT | mm | %ile* | Kg | %ile* | mm | %ile* | |
| GG | 2850 | 90 | 89.8 | 85 | 1066 | 75 | |
| NM | 1828 | 80 | 79.3 | 55 | 1016 | 50 | |
| JS | 1727 | 25 | 72.4 | 30 | 965 | 25 | |
| LP | 1676 | 75 | 61.5 | 50 | 990 | 90 | |
| PR | 1650 | 75 | 53.3 | 25 | 863 | 25 | |

Table 1. Relevant Anthropometric Data

* Canadian Forces personnel (11, 12)

| 1 | [ab] | le | 2. | Mass | and | Underwa | ter | Weig | ht i | of | Sub | ects |
|---|------|----|----|------|-----|---------|-----|---|------|----|--------------------|-------------------|
| _ | | | | | | | | and the second se | | | the same same same | the second second |

| Cubicat | Ma | ass | Weight in | Body | Mass, dry, dressed in: | | | | |
|------------|------|------|-----------|-------|------------------------|------|------|--|--|
| Subject | Kg | %ile | Kg | Kg/L | Kg | Kg | Kg | | |
| GG | 89.8 | 85 | 3.6 | 1.059 | 95.8 | 98.0 | 97.1 | | |
| NM | 79.3 | 60 | 2.3 | 1.065 | 85.6 | 87.6 | 87.4 | | |
| JS | 72.4 | 40 | 2.2 | 1.058 | 79.4 | 80.1 | 80.2 | | |
| LP | 61.5 | 50 | 2.0 | 1.052 | 67.4 | 69.0 | 69.0 | | |
| PR 53.3 25 | | 2.2 | 1.060 | 59.1 | 60.7 | 61.3 | | | |

(TERRITARIA)

| Item | | Mass Kg | Standard CO2 Charge g | Bladder Pressure mm Hg | Water Temp deg.C | Buoyant Force Kg | |
|------|------------------|------------|-----------------------------|------------------------------|------------------------|------------------------|--|
| a. | CF -6316 (Irvin) | 1.23 | 2 x 12 | 2.2 | 0.2 | 15.7 | |
| b. | Secumar AUS-2 | 1.33 | 1 x 30 | 26 | 0.2 | 17.3 | |
| c. | Saab-Scania | 1.42 | 1 x 33 | 62 | 0.2 | 18.4 | |
| d. | Aerazur 35-2 | 1.72 | 1 x 40 | 60 | 0.3 | 23.2 | |

Table 3. Buoyancy of Selected Life-Preservers

Table 8. Life-Preserver Comparison, ranked by performance.

| Parameter | Poor | | > Good | | | |
|---|-------|-------|--------|-------|--|--|
| Level - Immersion Above Water | -6316 | AUS-2 | Aer | s-s | | |
| Self-Righting - Winter Arms Extended | -6316 | AUS-2 | Aer | s-s | | |
| Self-Righting - Summer Arms Extended | -6316 | AUS-2 | s-s | Aer | | |
| Self-Righting - Summer Arms at sides | -6316 | AUS-2 | s-s | Aer | | |
| Flotation Angle - Winter | Aer | AUS-2 | S-S | -6316 | | |
| Flotation Angle - Summer | Aer | s-s | AUS-2 | -6316 | | |

a a la contra de la c

のためのから

うべいろ

| Table 4. | Flotation | Angle | Degrees |
|----------|--|-------|---------|
| | and the second sec | | |

| SUBJECT | BJECT WINTER | | | | SI | JMMER | | | | INNE | RSION | |
|---------|----------------------|----------------------------|----------------------|-------------------|----------------------|----------------------|----------------------|----------------------|------|------|-------|-----|
| - | 6316 | s-s | Aer | AUS | 6316 | S-S | Aer | AUS | 6316 | S-S | Aer | AUS |
| 1. | 33 43 37 36 | 27 30 28 28 | 27 25 30 26 | 7 5 4 0 | 42 39 39 35 | 23 27 26 23 | 36 28 28 | 11 15 13 15 | near | hori | zonta | 1 |
| mean | 37.2 | 28.2 | 27.0 | 5.3 | 38.8 | 24.8 | 30.7 | 13.5 | | | | |
| 2. | 30 31 22 26 | 20 18 25 24 | 27 25 25 25 | 8 10 8 | 30 37 28 35 | 25 25 32 25 | 33 30 28 36 | 9 12 10 8 | | | | |
| mean | 29.8 | 21.8 | 25.5 | 8.7 | 32.5 | 26.8 | 31.8 | 9.8 | | | | |
| 3. | 48 40 42 45 | 29 21 27 19 | 37 39 31 38 | 0 10 8 8 | 35 37 37 40 | 33 27 26 36 | 31 26 28 33 | 2 2 5 | | | | |
| mean | 43.8 | 24.0 | 35.5 | 6.0 | 37.2 | 30.5 | 29.5 | 3.0 | | | | |
| 4. | 38 40 34 38 | 31 31 31 31 36 | 31 25 28 31 | 9 7 10 9 | 50 52 50 48 | 44 40 38 38 | 38 38 37 36 | 24 19 22 22 | | | | |
| mean | 37.5 | 32 | 28.8 | 9.2 | 50.0 | 40.0 | 37.2 | 21.8 | | | | |
| 5. | 39 34 40 42 | 34 34 34 32 | 30 27 28 37 | 8 10 5 7 | 45 44 45 44 | 34 36 36 32 | 26 23 23 27 | 15 21 16 19 | | | | |
| mean | 39.0 | 33.5 | 30.5 | 7.5 | 44.5 | 35.3 | 24.8 | 17.8 | | | | |
| mean | 37.4 | 27.9 | 29.5 | 7.3 | 40.6 | 31.5 | 30.8 | 13.2 | | | | |
| s.n. | 5.5 | 5.3 | 4.2 | 3.0 | 6.8 | 6.4 | 4.5 | 6.6 | | | | |

| SUBJECT | | WINT | ER | | S | UN114ER | | | | IMME | RSION | |
|---------|--------------------------|--------------------------|--------------------------|--------------------------|------------------------------|--------------------------|--------------------------|--------------------------|---------------------------------|----------------------------|----------------------------|---------------------------|
| | -6316 | s-s | Aer | AUS | 6316 | s-s | Aer | AUS | 6316 | s-s | Aer | AUS |
| 1 | 6.2 6.1 6.8 6.2 | 9.3 7.9 10.9 | 4.2 3.8 4.6 3.9 | 5.0 4.4 5.4 4.8 | 7.0 7.7 8.0 7.0 | 8.4 6.5 5.0 5.0 | 4.2 5.8 5.0 5.9 | 3.0 3.4 3.0 2.4 | DNR DNR DNR DNR | DNR ONR DNR DNR | 4.0 4.0 4.0 6.2 | ONR DNR DNR DNR |
| mean | 6.3 | 9.4 | 4.1 | 4.9 | 7.4 | 6.2 | 5.2 | 3.0 | - | - | 4.6 | - |
| 2 | 4.0 4.6 4.4 4.8 | 3.6 4.0 4.1 4.0 | 4.1 3.8 3.9 4.2 | 4.3 5.3 5.0 4.6 | 3.5 5.0 4.2 4.9 | 3.4 4.2 4.0 4.4 | 3.4 3.0 3.5 3.2 | 4.0 4.4 4.2 4.2 | DNR ONR DNR DNR | DNR DNR DNR DNR | 8.5 5.0 12.0 8.0 | 11.0 DNR DNR DNR |
| mean | 4.4 | 4.0 | 4.0 | 4.8 | 4.4 | 4.0 | 3.3 | 4.2 | - | - | 8.4 | - |
| 3 | 6.8 7.0 8.0 7.6 | 5.3 5.7 5.9 5.5 | 3.8 5.0 3.3 3.9 | 3.3 3.6 2.8 4.0 | 5.6 6.0 5.6 5.3 | 3.9 4.9 4.2 4.8 | 3.4 3.8 2.8 3.1 | 3.8 3.1 4.0 3.8 | DNR ONR DNR DNR | 6.8 11.0 DNR 12.3 | 4.0 4.2 12.8 11.0 | 7.0 ONR ONR DNR |
| mean | 7.4 | 5.6 | 4.0 | 3.4 | 5.6 | 4.4 | 3.3 | 3.7 | | 10.0 | 7.0 | - |
| 4 | 4.6 3.8 4.2 4.2 | 4.9 4.2 3.8 3.8 | 3.8 4.0 3.0 3.5 | 4.8 3.5 3.5 4.0 | 10.0 8.0 8.0 7.5 | 5.2 4.8 4.2 4.8 | 3.5 3.5 3.8 3.0 | 4.0 3.0 3.5 3.0 | DNR DNR ONR ONR | ONR DNR DNR ONR | ONR DNR DNR ONR | 18.0 DNR DNR ONR |
| mean | 4.2 | 4.2 | 3.6 | 4.0 | 8.4 | 4.8 | 3.4 | 3.4 | | - | - | - |
| 5. | 7.0 6.0 5.8 6.0 | 6.0 5.4 5.8 5.4 | 4.0 3.8 3.3 3.8 | 4.0 4.0 4.0 4.4 | 17.6 17.0 14.5 11.4 | 5.0 5.7 6.2 5.0 | 3.2 4.2 4.0 4.5 | 4.0 4.0 5.0 5.2 | DNR DNR DNR DNR DNR | DNR DNR DNR DNR | DNR DNR DNR ONR | DNR DNR DNR ONR |
| mean | 6.2 | 5.6 | 3.7 | 4.1 | 15.1 | 5.5 | 4.0 | 4.6 | | | - | - |
| mean | 5.7 | 5.8 | 3.9 | 4.2 | 8.2 | 5.0 | 3.8 | 3.8 | - | - | - | - |
| S.P. | 1.4 | 2.2 | 0.7 | 0.6 | 4.2 | 0.9 | 0.8 | 0.6 | | | | |

Table 5. Life-Saver Self-Righting Times (sec.) - Arms At Sides

* DNR - Did Not Right (within 30 sec.)

A LAND MARKAR AND A CALLER AND A

| | WINTER | | | | 51 | | | IMMERSION | | | | |
|------|--------|-----|-----|-----|------|-----|-----|-----------|------|-----|-----|-------|
| | 6316 | s-s | Aer | AUS | 6316 | s-s | Aer | AUS | 6316 | s-s | Aer | AUS |
| 1. | 7.2 | DNR | 4.6 | 5.6 | 10.0 | 7.0 | 6.0 | 4.0 | DNR | DNR | DNR | DNR |
| | 6.9 | 7.3 | 5.0 | 5.0 | 9.9 | 6.0 | 5.7 | 3.5 | 99 | | н | |
| | 7.2 | 8.5 | 5.7 | 5.0 | 8.7 | 6.2 | 6.0 | 3.0 | | | | |
| | 6.9 | 7.9 | 4.8 | 5.0 | 8.4 | 4.8 | 5.2 | 3.0 | ** | | | |
| mean | 7.0 | 7.9 | 5.0 | 5.2 | 9.2 | 6.0 | 5.7 | 3.4 | - | - | - | - |
| 2. | 3.8 | 5.1 | 4.5 | 4.5 | 4.0 | 3.6 | 4.2 | 4.0 | DNR | DNR | DNR | DNR |
| | 4.9 | 4.3 | 4.5 | 5.0 | 4.8 | 4.0 | 3.6 | 4.2 | | | | |
| | 5.4 | 4.0 | 3.6 | 5.5 | 4.9 | 4.0 | 4.2 | 3.8 | | 90 | | |
| | 5.1 | 3.6 | 4.1 | 4.8 | 4.2 | 4.2 | 3.8 | 4.0 | | | | |
| mean | 4.8 | 4.2 | 4.2 | 5.0 | 4.5 | 4.0 | 4.0 | 4.0 | | | | |
| 3 | 6.8 | 5.8 | 5.3 | 4.2 | 5.1 | 4.9 | 4 2 | 4.0 | | | | |
| | 7.1 | 5.9 | 4.3 | 4.1 | 5.8 | 4.9 | 3.9 | 4 0 | | | | |
| | 6.8 | 6.0 | 4.9 | 4.6 | 5.4 | 4.9 | 4.0 | 4.2 | н | | | |
| | 6.6 | 6.4 | 5.1 | 4.0 | 5.5 | 4.7 | 3.9 | 4.0 | H | | | |
| mean | 6.8 | 6.0 | 4.9 | 4.2 | 5.4 | 4.9 | 4.0 | 4.0 | - | - | - | |
| 4 | 7.0 | 5.0 | 4.0 | 5.0 | 10.0 | 6.0 | 4.0 | 4.2 | DNR | DNR | DNR | 36 |
| | 7.0 | 5.2 | 4.2 | 5.0 | 9.0 | 5.2 | 4.0 | 4.0 | H | H | H | |
| | 6.4 | 5.0 | 4.0 | 3.5 | 10.0 | 5.8 | 4.5 | 4.2 | | | н | |
| | 6.6 | 5.0 | 4.0 | 4.0 | 8.5 | 5.5 | 3.5 | 3.5 | - | | | |
| mean | 6.8 | 5.0 | 4.0 | 4.4 | 9.4 | 5.6 | 4.0 | 4.0 | | | | |
| 5 | 7.6 | 6.5 | 4.0 | 4.0 | | 8 2 | 4.0 | 4.8 | DND | DND | DND | DND |
| 3. | 7.0 | 5.6 | 2.8 | 4.6 | - | 9.2 | 3.8 | 5.0 | H | H | H H | UNIX. |
| | 6.8 | 5.5 | 4.0 | 4 0 | - | 7 4 | 4 7 | 5 5 | | | | 81 |
| | 6.6 | 5.8 | 3.8 | 4.1 | - | 8.4 | 4.9 | 4.6 | H | | н | н |
| mean | 7.0 | 5.8 | 3.9 | 4.2 | - | 8.0 | 4.4 | 5.0 | - | - | - | |
| mean | 6.5 | 5.8 | 4.4 | 4.6 | 7.1 | 5.7 | 4.4 | 4.1 | - | | - | |
| S.D. | 0.9 | 1.4 | 0.5 | 0.5 | 2.5 | 1.5 | 0.7 | 0.6 | | | | |

Table 6. Self-Righting Times (sec.) - Arms Extended

* DNR - Did Not Right (within 30 sec.)

いたちとこうの

いいの

| SUBJECT | | WINTER | | | 5 | SUMMER | 2 | | IMMERSION | | | | |
|---------|------|--------|--------|-----|------|--------|--------|-------|-----------|--------|--------|--------|--|
| •••••• | 6316 | s-s | Aer | AUS | 6316 | S-: | s Aer | AUS | 6316 | S-S | Aer | AUS | |
| 1. | 98 | 86 | 89 | 81 | 116 | 114 | 149 | 57 | 89 | 89 | 108 | 67 | |
| | 108 | 89 | 108 | 81 | 116 | 143 | 124 | 76 | 86 | 89 | 105 | 57 | |
| | 102 | 111 | 108 | 81 | 125 | 140 | 140 | 60 | 86 | 95 | 127 | 67 | |
| | 105 | 111 | 114 | 78 | 121 | 130 | 143 | 60 | 60 | 95 | 130 | 57 | |
| mean | 103 | 99 | 105 | 80 | 120 | 132 | 139 | 63 | 80 | 92 | 118 | 62 | |
| 2. | 67 | 67 | 60 | 60 | 68 | 59 | 62 | 41 | 76 | 103 | 130 | 129 | |
| | 65 | 76 | 73 | 67 | 68 | 67 | 84 | 43 | 73 | 100 | 121 | 118 | |
| | 65 | 67 | 73 | 67 | 68 | 68 | 86 | 44 | 76 | 79 | 138 | 113 | |
| | 65 | 67 | 76 | 67 | 71 | 67 | 86 | 65 | 73 | 92 | 132 | 118 | |
| mean | 66 | 69 | 70 | 65 | 69 | 65 | 80 | 48 | 74 | 94 | 130 | 120 | |
| 3. | 60 | 95 | 93 | 93 | 79 | 86 | 102 | 70 | 92 | 92 | 133 | 95 | |
| | 67 | 76 | 86 | 84 | 89 | 92 | 92 | 57 | 95 | 98 | 133 | 92 | |
| | 75 | 56 | 80 | 87 | 89 | 98 | 89 | 64 | 89 | 98 | 133 | 95 | |
| | 67 | 59 | 95 | 81 | 89 | 89 | 108 | 60 | 92 | 98 | 127 | 92 | |
| mean | 67 | 72 | 88 | 86 | 86 | 91 | 98 | 63 | 92 | 96 | 132 | 94 | |
| 4. | 60 | 89 | 73 | 64 | 79 | 95 | 92 | 76 | 60 | 89 | 137 | 117 | |
| | 95 | 95 | 73 | 67 | 79 | 114 | 95 | 76 | 60 | 83 | 140 | 133 | |
| | 67 | 95 | 92 | 73 | 79 | 114 | 95 | 76 | 60 | 83 | 121 | 127 | |
| | 67 | 95 | 89 | 67 | 79 | 114 | 95 | 76 | 60 | 83 | 114 | 118 | |
| mean | 72 | 94 | 82 | 68 | 79 | 109 | 94 | 76 | 60 | 84 | 128 | 124 | |
| 5 | 95 | 60 | 60 | 95 | 89 | 76 | 76 | 60 | 92 | 83 | 105 | 95 | |
| | 92 | 79 | 64 | 86 | 89 | 95 | 76 | 64 | 89 | 92 | 118 | 92 | |
| | 95 | 86 | 73 | 95 | 89 | 76 | 75 | 64 | 86 | 92 | 118 | 95 | |
| | 95 | 98 | 76 | 95 | 89 | 86 | 57 | 70 | 86 | 92 | 114 | 92 | |
| mean | 94 | 81 | 68 | 93 | 89 | 83 | 70 | 64 | 88 | 90 | 114 | 94 | |
| mean | 80. | 4 83 | 82.6 | 78. | 4 88 | .6 96 | 96.1 | 2 62. | 8 78. | 8 91.7 | 2 124. | 4 98.8 | |
| S.D. | 17 | 13. | 2 15.8 | 11. | 8 19 | .2 25 | .6 26. | 4 9. | 9 12. | 6 4.1 | 5 17. | 9 24.9 | |

Table 7. Subjects' Houth Level Above Water (centimeters)