# UNCLASSIFIED

# AD NUMBER

### ADB805760

### LIMITATION CHANGES

### TO:

Approved for public release; distribution is unlimited.

# FROM:

Distribution authorized to DoD only; Administrative/Operational Use; SEP 1943. Other requests shall be referred to National Aeronautics and Space Administration, Washington, DC. Pre-dates formal DoD distribution statements. Treat as DoD only.

# AUTHORITY

NASA TR Server website

THIS PAGE IS UNCLASSIFIED

# **Reproduction Quality Notice**

This document is part of the Air Technical Index [ATI] collection. The ATI collection is over 50 years old and was imaged from roll film. The collection has deteriorated over time and is in poor condition. DTIC has reproduced the best available copy utilizing the most current imaging technology. ATI documents that are partially legible have been included in the DTIC collection due to their historical value.

If you are dissatisfied with this document, please feel free to contact our Directorate of User Services at [703] 767-9066/9068 or DSN 427-9066/9068.

# Do Not Return This Document To DTIC



# The U.S. GOVERNMENT

# **IS ABSOLVED**

FROM ANY LITIGATION WHICH MAY

ENSUE FROM THE CONTRACTORS IN -

FRINGING ON THE FOREIGN PATENT

RIGHTS WHICH MAY BE INVOLVED.



# an and a second and a

MARKAN AL CANADA

-

# UNCLASSIFIED



### MEMORANDUM REPORT

### for the

### Department of Commerce

TESTS OF A 1/40-SCALE WING-HULL MODEL AND A 1/10-SCALE FLOAT-STRUT MODEL OF THE HUGHES-KAISER CARGO AIRPLANE IN THE TWO-DIMENSIONAL LOW-TURBULENCE PRESSURE TUNNEL

By Felicien F. Fullmer, Jr.

### INTRODUCT ION

At the request of the Department of Commerce, aerodynamic and hydrodynamic tests have been made of a 1/40scale wing-hull model and a 1/10-scale float-strut model of the proposed arrangement of the Hughes-Kaiser cargo airplane. The aerodynamic tests were made in the NACA two-dimensional low-turbulence pressure tunnel and the results are presented in this report. The hydrodynamic tests were made in the NACA tank and are being reported separately.

The aerodynamic tests were made primarily to study the drag characteristics of these models as originally designed and to determine, if possible, how the proposed designs could be improved. The investigation accordingly included tests of these models as received and after various modifications had been made. Some of these modifications were made as the result of hydrodynamic tests at the NACA tank. Whenever practicable, additional tests were made to study the lift characteristics of these models. The tests of the wing-hull model were made at a Reynolds number of approximately 22.5 million based on the model-hull length of 62.25 inches. The float-strut model was tested at a Reynolds number of approximately 7 million based on the model-float length of 23.00 inches.

#### MODELS

Wing-hull model. - The model arrangement tested is shown in figure 1 in the original condition and in figure 2 with the added chine-flare strips as recommended by the

The span of the model was 36 inches (tunnel NACA tank. test-section width); therefore, only the inboard portion of the wing (approximately 37.5 percent of the full span) was modeled. The airplane wing tapers from an NACA 63(120)-321 root section to an NACA 65,3-418 section at The airplane hull was developed from and is o the NACA model 84-F hull. The wing and hull the tip. similar to the NACA model 84-F hull. The wing and were constructed of mehogany and all surfaces were painted and sanded until aerodynamically smooth. dor some tests fillets made of modeling clay were added to the model at the wing-hull junction. These fillets were of the expanding-radius type and were very small were of the expanding-radius type and were very small forward of the maximum thickness of the wing. At the wing trailing edge the fillet radii were 1 inch and 0.503 inch., respectively, on the upper and lower wing surfaces. The fillets extended along the hull aft of the intersection for a distance of 2.25 inches. The step fairings used for some of the tests were made of modeling clay and extended approximately 3.5 inches aft of the step. Roughness was applied to the hull by two matheds first by gluing number 50 thread around the methods, first, by gluing number 50 thread around the hull 3.1 inches aft of the bow and later by shellacking 0.012-inch carborundum grains to the hull for a distance of 3.1 inches aft of the bow.

<u>Float-strut model</u>. - The model arrangement tested is shown in figure 3. The model was constructed of mahogany: all the surfaces were painted and sanded until aerodynamically smooth. For these tests the model was attached to a 36-inch-chord airfoil in such a manner that the strut leading edge, extended, intersected the quarter-chord point of the wing for all angles of incidence of the float. The 36-inch chord of the model approximates, to the same scale, the chord of the airplane wing at the juncture of the wing and float strut. The airfoil used was chosen only because of its availability and was an NACA 66,2-216 section. Figure  $l_4(a)$ shows the float-strut model and the 36-inch-chord airfoil mounted in the test section. The wing was mounted approximately 18 inches above the center line of the tunnel so that the float and lower portion of the strut would be within the working limits of the wakesurvey mechanism. As a result of tests in the NACA tank, a spray strip was added, the step was removed, and a cove was cut into the after section of the chine (fig.  $l_4(b)$ ).

### SYMBOLS

The defined	e coefficients and symbols used in this report are us follows:
c <sub>lm</sub>	model lift coefficient $\frac{L_M}{qs_M}$
∆C <sup>D</sup>	airplane-drag-coefficient increments $\frac{\Delta D}{qS}$
C <sub>DA</sub>	drag coefficients based on the maximum cross- sectional area of the hull $\frac{D_c - D_w}{qA}$
L <sub>M</sub>	total lift on the model
s <sub>M</sub>	wing area of the model
q	dynamic pressure of air $(\frac{1}{2}\rho V^2)$
۵D	drag of surveyed portion of the model scaled to full size
8	total wing area of the airplane
D <sub>c</sub>	drag of surveyed portion of wing-hull combination
D <sub>w</sub>	drag of surveyed portion of the wing alone
A	maximum cross-sectional area of the hull
۵	angle of attack of the model wing
G.o.	pitch angle (angle of attack of the hull)

### TEST METHODS

The lift coefficients were obtained by measuring the reaction of the lift on the floor and ceiling of the tunnel (reference 1). The lift data are presented as model lift coefficients  $C_{L_{M}}$ .

4.7

....

.....

•

. . .

The drag measurements were made by the wake-survey method (reference 1). The drag data are presented as airplane-drag-coefficient increments  $\Delta C_D$  because the differences in drag coefficient resulting from modifications of the arrangements represent directly the resulting change in drag coefficient of the actual airplane. The value of this drag coefficient also represents the contribution to the total airplane drag coefficient of the portion of the model surveyed.

Spanwise drag surveys were made over the central 20 inches of the model span. By intergrating these survey diagrams the airplane-drag-coefficient increments for the wing-hull model wire determined. The model wing area surveyed corresponds to 28.2 percent of the actual airplane wing area. A typical survey for one condition is presented in figure 5. The section drag coefficients shown in this figure are based on the mean geometric model chord of 13.72 inches.

The airplane-drag-coefficient increments for the float-strut model were obtained by the integration of drag surveys made over the float and lower 12 inches of the strut.

To compare the drag coefficients for this model with those of other hulls, the coefficients were also based on the maximum cross-sectional area and are presented as drag coefficients  $C_{D_A}$ .

#### RESULTS AND DISCUSSION

<u>Wing-hull model</u>. The important lift data obtained are presented in figure 6. Since minor modifications to the hull had little effect on the lift characteristics, these data are not presented. The incidence of the hull is shown to have an appreciable effect upon the angle of zero lift, the slope, and the maximum lift coefficient. These changes would have been much less if the total wing area of the airplane had been represented on the model.

The drag data for each model arrangement were obtained at lift coefficients corresponding approximately to the expected high speed, cruising, and elimb conditions for the airplane. The drag data obtained are

presented in figures 7(a) and 7(b). A comparison between these figures shows that the step fairing used with wing incidences of 2° and 4° appreciably lowered the drag coefficients of the model. The addition of wing fillets reduced the drag coefficients obtained with a wing incidence of 2° but gave a small increase in drag with the wing incidence increased to 4°. The increased chine. flare added to the model following hydrodynamic tests caused a small increase in the drag coefficients. Doors, mooring apparatus, and other protuberances would be expected to prevent extensive laminar flow over the actual airplane hull; therefore, roughness was added to the model to determine the drag coefficients of the hull with fixed transition. At a lift coefficient of 0.25, cementing 0.012-inch carborundum particles to the hull increased the drag-coefficient increment 9 percent at 4° incidence and gluing number 50 thread just aft of the bow increased the drag-coefficient increment 5 percent at 7° incidence.

The differences between the values for the wing-hull combination and those for the wing alone represent the drag and interference of the hull expressed directly as airplane-drag-coefficient increments. These data are chiefly remarkable for the unusually low drag increments caused by the hull. This is clearly indicated in figure 8 where a comparison of the drag coefficients (based on the maximum cross-sectional area) shows that the Hughes-Kaiser hull, a modified NACA model 84-F, with fixed transition gave considerably lower drag coefficients than were obtained with the NACA model 84-F (reference 2) with fixed transition. The more favorable results indicated by the present tests may be partially attributed to possible favorable interference between the wing and the hull. The Hughes-Kaiser hull with fixed transition gives lower drag coefficients than other comparable NACA hulls (references 3 and 4) in a smooth condition and the coefficients obtained with the hull in a smooth condition are much lower.

<u>Float-strut model.</u> The accuracy of the lift data obtained during the tests of this model was doubtful: therefore, no lift coefficients are presented.

The drag data are presented in figure 9 for the three float settings tested. The afterbody step is shown to cause an increase in drag for all three float positions. Changes in incidence of the float and strut to the wing did not affect the drag coefficients to any

appreciable extent. The addition of the spray strip and cove increased the drag of the model.

0

L

6

Tuft observations were made with and without the step in the afterbody and with the float keel line paralled to the chord line of the wing. The results of these tuft studies are presented in figures 10 and 11. With the step in the afterbody of the float, the air flow generally was steady except over the surface just aft of the step. The flow over the bottom of the float just aft of the step was separated. At a point midway along the bottom aft of the step the flow was intermittently separated, indicating that the air stream was closing back into the surface. With no step in the afterbody, the flow over the float was steady except near the rear of the chine line. The air separated locally as it flowed over the chine line, but returned to a steady condition over the remainder of the float.

### CONCLUDING REMARKS

Wing-hull model. The results show that, for the model tested, the incidence of the hull had an appreciable effect upon the angle of zero lift, the slope, and the maximum lift characteristics. Minor modifications to the hull had little effect on the lift characteristics of this model.

The model as originally tested showed unusually low drag coefficients for all angles of incidence, and the addition of a step fairing lowered these drag coefficients 7.5 percent. The addition of wing fillets caused only small changes in drag. The added chine flare caused small increase in the drag coefficients of this model in the high-speed condition. A moderate increase in the drag coefficients was obtained with transition fixed just aft of the bow.

<u>Float-strut model.</u> The results show that changes in incidence did not appreciably affect the drag coefficients of the model. An increase in drag-coefficient

a tang 7 increment of over 30 percent was obtained with a step in the afterbody of the float. The addition of the spray strips and the cove also caused an appreciable increase in drag. Langley Memorial Aeronautical Laboratory, National Advisory Committee for Aeronautics, Langley Field, Va., September 24, 1943. . Service . 100 150 - Sector ÷2. . . 18 See 1879 ģ. 2.14

### REFERENCES

- Jacobs, Eastman N., Abbot, Ira H., and Davidson, Milton: Preliminary Low-Drag-Airfoil and Flap Data from Tests at Large Reynolds Numbers and Low Turbulence, and Supplement. NACA A.C.R., March 1942.
- Farkinson, John B., Olson, Roland E., Draley, Eugene C., and Luoma, Arvo A.: Aerodynamic and Hydrodynamic Tests of a Family of Models of Flying-Boat Hulls Derived from a Streamline Body - NACA Model 84 Series. NACA A.R.R. No. 3115, Sept. 1943.
- Hartman, Edwin P.: The Aerodynamic Drag of Flying-Boat Hull Models as Measured in the N.A.C.A. 20-Foot Wind Tunnel - I. T.N. No. 525, NACA, 1935.
- 4. Truscott, Starr, Parkinson, J. B., Ebert, John W., Jr., and Valentine, E. Ployd: Hydrodynamic and Aerodynamic Tests of Models of Flying-Boat Hulls Designed for Low Aerodynamic Drag. N.A.C.A. Models 74, 74-A, and 75. T.N. No. 668, NACA, 1938.

3.00

























								100	
I TITLE: Tests of a 1/40-Scaie Wing-Hull Modei and a 1/10-Scale Fioat-Strut Model of the Hughes-Kaiser Cargo Airpiane in the Two-Dimensional Low-Turbulence Pressure Tunnel AUTHOR[S]: Fulimer; Felicien, F. ORIGINATING AGENCY: National Advisory Committee for Aeronautics, Washington, D. C. PUBLISHED BY: (Same)							АТІ- 9611 EFVISION (None) 0610. аденсу но. <u>MR-L-633</u> PUBLISHING AGENCY НО.	'	
DATE	BOC. CLASS.	COUNTRY -	LANGUA	GE PAGES	ILLUSTRATIO	INS			
Sept '43	Unclass.	Ų.S	Eng.	.   18	photos,	graphs, drwgs		<u> </u>	
Aerodynamic tests were performed to study drag characteristics of models as designed and to determine how proposed designs could be improved. Incidence of wing-hull model had appreciable effect upon angle of zero lift, siope, and maximum iift characteristics. Minor hull modifications had little effect on lift characteristics. Float-strut model incidence did not appreciably affect drag coefficients. Increase In drag coefficient increment over 30% was obtained è with step in float afterbody.									
						•			
DISTRIBUTION: Request copies of this report only from Originating Agency									
DIVISION: Aerodynamics (2) SUBJECT HEADINGS: Flying boats - Hulis - Aerodynamics									
SECTION: Pr	rasitic Comp	onents and In	erfer-	(41753); Wi	ngs - Aer	rodynamics (99150)			
	,	(	ences (7)						
ATI SHEET N	ATI SHEET NO.: R-2-7-10								
Air Document Ai	s Division, Intellig r Matarief Commo	enco Department nd	Air.	TECHNICAL I	IDEX ·	Wright-Pattorson Air Dayton, Oh	Force Baso io	1	

\_\_\_\_\_\_

------

TITLE: Tests of a 1/40-Scale Wing-Hull Model and a 1/10-Scale Float-Strut Model of the Hughes-Kaiser Cargo Airplane in the Two-Dimensional Low-Turbulence Pressure Tunnel AUTHOR(5): Fullmer; Felicien, F. ORIGINATING AGENCY: National Advisory Committee for Aeronautics, Washington, D. C. PUBLISHED BY: (Same)

Bent
BOC. CLASS.
COUNTRY
LAMPUAGE
PAGE
HUSTRATIONS

Sept '43
Unclass.
U.S.
Eng.
18
photos, graphs, drwgs
5

ABSTRACT:
Country
Countr

ATI- 9811

OTIO ACTIN'T IND

(None)

MR-L-633

PUBLISHING AGENCY MD.

INVISION

Aerodynamic tests were performed to study drag characteristics of models as designed and to determine how proposed designs could be improved. Incideoce of wing-hull model had appreciable effect upon angle of zero lift, slope, and maximum lift characteristics. Minor hull modifications had little effect on lift characteristics. Float-strut model incidence did not appreciably affect drag coefficients. Increase in drag coefficient increment over 30% was obtained è with step in float afterbody.

DISTRIBUTION: Request copies of this report only from Originating Agency

DIVISION: Aerodynamics (2)	SUBJECT HEADINGS: F13	ying boats - Hulls - Aerodyna	am
SECTION: Parasitic Components and Interfer-	(41753); Wings - Aerod	iynamics (99150)	
(ences (7)			
ATI SHEET NO. P.9.7 ID			
All Siler NO.: R-2-1-10			
Air Occuments Olvision, Intelligence Department AIR	TECHNICAL INDEX	Wright-Patterson Air Force Base	- 07
		boyren, Onte	
·		· · · ·	
•		-	

Ρ(), (3) \* Accodynamic Dang Flying Boat Hulls