



DEPARTMENT OF THE NAVY  
NAVAL UNDERSEA WARFARE CENTER  
DIVISION NEWPORT  
OFFICE OF COUNSEL  
PHONE: 401 832-3653  
FAX: 401 832-4432  
DSN: 432-3653



Attorney Docket No. 97629  
Date: 10 November 2008

The below identified patent application is available for licensing. Requests for information should be addressed to:

TECHNOLOGY PARTNERSHIP ENTERPRISE OFFICE  
NAVAL UNDERSEA WARFARE CENTER  
1176 HOWELL ST.  
CODE 07TP, BLDG. 990  
NEWPORT, RI 02841

Serial Number 12/287,155  
Filing Date 29 September 2008  
Inventor Kyrill V. Korolenko

Address any questions concerning this matter to the Office of Technology Transfer at (401) 832-1511.

DISTRIBUTION STATEMENT  
Approved for Public Release  
Distribution is unlimited

**20081119049**

REAL-TIME SYSTEM AND METHOD OF UNDERWATER DEPTH DISCREPANCY  
DETECTION, RECORDATION AND ALARM NOTIFICATION

STATEMENT OF GOVERNMENT INTEREST

[0001] The invention described herein may be manufactured and used by or for the Government of the United States of America for governmental purposes without the payment of any royalties thereon or therefor.

CROSS REFERENCE TO OTHER PATENT APPLICATIONS

[0002] None.

BACKGROUND OF THE INVENTION

(1) Field of the Invention

[0003] The present invention relates generally to underwater depth recording, and more particularly to a system and method of performing underwater depth discrepancy detection, recordation and alarm notification in real time.

(2) Description of the Prior Art

[0004] Ship personnel use depth charts generated by the National Oceanographic and Atmospheric Administration (NOAA) when navigating through coastal waters. In addition, most ships have an onboard fathometer (e.g., depth sounder) that monitors the depth in real-time. Unfortunately, actual water depths do not always correspond to chart depths. This can be a serious problem

if the actual depth is less than the chart depth. Currently, there are no automated systems or procedures in place that can record such discrepancies.

#### SUMMARY OF THE INVENTION

[0005] Accordingly, it is an object of the present invention to provide a system and method that can automatically detect, record, and notify when there is a discrepancy between an actual depth and a charted depth for an underwater location.

[0006] Other objects and advantages of the present invention will become more obvious hereinafter in the specification and drawings.

[0007] In accordance with the present invention, an underwater depth discrepancy detection, recordation and notification system and method are provided. In terms of a shipboard system, a comparator is coupled to a ship's depth measurement system (DMS) and electronic depth chart system (EDCS). The comparator compares an actual depth (provided by the DMS) with a chart depth corresponding to a current location of the ship (as provided by the EDCS). The comparator generates a first signal when the actual depth is greater than the chart depth. The comparator generates a second signal when the actual depth is less than the chart depth. The current location of the ship and actual depth are recorded whenever the first signal or the second signal is generated. In addition, one or more alarms are generated when the second signal is generated.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0008] Other objects, features and advantages of the present invention will become apparent upon reference to the following description of the preferred embodiments and to the drawings, wherein corresponding reference characters indicate corresponding parts throughout the several views of the drawings and wherein:

[0009] The sole figure is a schematic view of an underwater depth discrepancy system in accordance with the present invention.

#### DETAILED DESCRIPTION OF THE INVENTION

[0010] Referring now to the drawing, a system for detecting, recording and notifying of an underwater depth discrepancy is shown and is referenced generally by numeral 10. System 10 can be incorporated onboard any private, commercial or military ship. System 10 can include all of the illustrated elements or a portion thereof depending on the existing capabilities of a ship as will be explained further below.

[0011] At a minimum, depth discrepancy system 10 includes a comparator/processor 12, a recorder 14, and alarm(s) 16. Comparator/processor 12 is any conventional processing device capable of performing a real-time comparison between a current actual depth and a pre-recorded chart depth of the same location, and then generating a result of such comparison. Such comparators/processors are well known in the art. The current actual depth will be measured by an onboard depth measurement system 20 (e.g., depth sounder), the choice of which is not a

limitation of the present invention. Since most ships have an existing depth measurement system, depth discrepancy system 10 could be coupled to an existing system 20 or could include system 20 without departing from the scope of the present invention.

[0012] The pre-recorded chart depth is provided in an electronic form suitable for comparison with the actual depth measured by system 20. More specifically, an electronic depth chart 30 provides a database of pre-recorded depth data indexed to geographic position (e.g., Global Positioning System or GPS data). The particular pre-recorded chart depth data from chart 30 (that is then provided to comparator/processor 12) is "pointed to" by "own ship" GPS position data determined by a GPS receiver 32. Since a ship may already have an electronic depth chart 30 and GPS receiver 32, depth discrepancy system 10 could be coupled to existing components or could include electronic depth chart 30 and GPS receiver 32 without departing from the scope of the present invention.

[0013] In operation, comparator/processor 12 performs real-time comparisons between the actual depth (measured by system 20) and the pre-recorded depth (provided by chart 30) corresponding to the geographic location of the actual depth. If the two depths are equal, nothing happens and comparator/processor 12 awaits the next comparison. Since some level of discrepancy between the actual and pre-recorded depth might be acceptable, comparator/processor 12 can be provided with a tolerance parameter that specifies a range of acceptable discrepancy. The tolerance parameter can be pre-set or stored by comparator/processor 12, or

it can be manually provided thereto by a tolerance input 18. By allowing the tolerance parameter to be adjusted, system 10 can be configured for coastal operation where the tolerance may be lower or open-sea operation where the tolerance may be higher.

[0014] If the actual depth and pre-recorded depth do not "match" (e.g., as defined by the tolerance parameter), comparator/processor 12 triggers recorder 14 to record the actual depth and the current geographic position thereof (e.g., the ship's current GPS location and time of date determined by GPS receiver 32). This will occur if the actual depth is greater or less than the pre-recorded depth. Recorder 14 includes some form of removable data storage media 14A (e.g., floppy drive, CD, flash drive, etc.) that can be readily delivered to one or more organizations that produce and maintain electronic depth chart 30. In addition or alternatively, recorder 14 could be coupled to a transmitter 14B capable of wirelessly transmitting the actual depth and location thereof to the relevant organization(s) when a discrepancy is detected. Either way, the pre-recorded data can be updated to current conditions by the responsible organization(s).

[0015] In cases where the actual depth is less than the pre-recorded depth, comparator/processor 12 will also trigger alarm 16 that can be realized by one or more shipboard alarms. The alarms(s) could be audible (e.g., beeps, siren, etc.), visual (e.g., flashing lights, color change on computer screen, etc.), and/or tactile (e.g., vibrations delivered to shipboard controls continuously manned by personnel). The choice of number and type of alarms used are not limitations of the present invention.

[0016] The advantages of the present invention are numerous. Errors in pre-recorded depth data due to mistakes, technical errors, changing underwater conditions, etc., will be detected and automatically recorded in an accurate fashion so that the organizations charged with maintaining such depth data can update same. Further, shipboard operators will be notified of a depth discrepancy indicative of a potential grounding condition when an actual depth is less than the pre-recorded depth. Still further, since crowded coastal regions pose the greatest risk in the terms of a "grounding" incident, the present invention exploits existing private, commercial and/or military traffic to keep pre-recorded depth data current.

[0017] It will be understood that many additional changes in the details, materials, steps and arrangement of parts, which have been herein described and illustrated in order to explain the nature of the invention, may be made by those skilled in the art within the principle and scope of the invention as expressed in the appended claims.

REAL-TIME SYSTEM AND METHOD OF UNDERWATER DEPTH DISCREPANCY  
DETECTION, RECORDATION AND ALARM NOTIFICATION

ABSTRACT

An underwater depth discrepancy system and method are provided. A comparator compares an actual underwater depth with a predetermined/prerecorded chart depth corresponding to a current location corresponding to the location of the actual underwater depth. A first signal is generated when the actual underwater depth is greater than the chart depth while a second signal is generated when the actual underwater depth is less than the chart depth. The current location and actual underwater depth are recorded whenever the first or second signal is generated. In addition, one or more alarms are generated when the second signal is generated.

