UNCLASSIFIED

AD NUMBER

AD062045

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; JAN 1955. Other requests shall be referred to Ballistic

Research Laboratories, Aberdeen Proving Ground, MD.

AUTHORITY

BRL ltr dtd 22 Apr 1981

THIS PAGE IS UNCLASSIFIED



c.2A REPORT NO. 927

Jamary 1955

THE DRAG OF A 1/6 SCALE MODEL OF THE 3000-LB. BOMB MILS FROM A MACH NUMBER OF 0.7 TO 1.2 AS OBTAINED FROM FREE FLIGHT FIRINGS

L. C. MacAllister

DEVELOPMENT & PROOF SERVICES ABERDEEN PROVING GROUND MARYLAND

Department of the Army Project No. 503-03-002 Ordnance Research and Development Project No. TB3-0136

ABERDEEN PROVING GROUND, MARYLAND

••

÷

TABLE OF CONTENTS

. .

CONTENTS	٠	•	٠			٠	٠	٠	•	٠	•	٠	٠	٠	٠	٠	•	٠	٠	٠	٠	٠	•	٠	٠	٠	٠	2
ABSTRACT	•	•	•	•	٠	•	•	•	•	•	•	٠	٠	٠	•	٠	•	٠	•	•	٠	•	•	•	٠	٠	٠	3
INTRODUCT	ION	ł	٠	٠	٠	•	٠	٠	٠	•	٠	٠	٠	٠	•	٠	•	٠	•	٠	٠	•	٠	٠	٠	•	٠	5
TEST PROG	RAP	ſ	•	٠	•	•	٠	٠	٠	٠	٠	٠	•	•	•	•	•	•	٠	٠	•	•	٠	٠	٠	٠	•	5
REDUCTION	OF	Γ)A]	'A	•	•	٠	٠	٠	٠	•	•	٠	•	•	•	•	٠	٠	٠	٠	٠	٠	٠	٠	٠	•	6
RESULTS .	٠	•	٠	٠	•	٠	٠	٠	٠	٠	٠	٠	•	•	٠	•	٠	•	•	٠	•	•	٠	٠	•	•	•	7
ESTIMATES	OF	, I	U	L	S	CAI	E	PI	RI	OI	RM4	N	E	•	٠	٠	•	٠	•	٠	٠	٠	٠	٠	٠	٠	٠	8
CONCLUSION	NS	•	•	٠	٠	•	٠	•	٠	•	٠	٠	٠	٠	٠	٠	٠	•	٠	٠	•	٠	•	•	•	٠	٠	10
REFERENCE:	5	٠	•	•	٠	٠	٠	٠	•	٠	٠	٠	•	٠	٠	•	•	٠	•	٠	٠	٠	•	٠	•	٠	•	ц
FIGURES A	Ð	Œ	AI	PHS	5	•		•	•		•	•	•	•	•	•	•	•	•	•	•	٠	•	•	•	•	•	16

BALLISTIC RESEARCH LABORTORIES

REPORT NO. 927

LCMacAllister/psg Aberdeen Proving Ground, Md. January 1955

THE DRAG OF A 1/6 SCALE MODEL OF THE 3000-LB. BOMB M118 FROM A MACH NUMBER OF 0.7 TO 1.2 AS OBTAINED FROM FREE FLICHT FIRINGS

ABSTRACT

The drag coefficients of a 1/6 scale model of the 3000-pound Bomb Mil8 as obtained from free flight firings and full scale values as inferred from range drops are given for a Mach number range of 0.7 to 1.2. Comparison of the model and the full scale drag data indicate that the two are in good agreement only if the prevailing yaw levels of the full scale bomb are taken into account. This page Left Intentionally Blank

INTRODUCTION

The pertinent aerodynamic information on bombs which is necessary to prepare bombing tables is usually obtained from full scale drops. This procedure is both costly and lengthy. Hence it was thought important to explore the possibility of obtaining the necessary information by model firings. It should be noted that the variables that enter into the determination of the trajectory of a dropped bomb are probably too numerous and too interrelated with launching conditions to permit a highly accurate solution from knowledge of the bomb's basic drag properties along. A model program should be able to provide the basic drag information that could permit simplification of the necessary full scale program.

A primary question to explore is the importance of Reynolds number effects in the scaling of the bomb shape to a model size suitable for firing in the range. Therefore a model program to provide information on the aerodynamic properties of the 3,000-pound Mil8 bomb shape at transonic velocities was carried out in the Transonic Range facility⁽¹⁾.

The test considered of launchings of approximately one-sixth scale models through the range instrumentation to determine data that would yield the drag, stability, and damping properties of the models.

Since drag determinations are usually completed well in advance of the more complex yawing motion parameters only the drag results and their preliminary evaluation is given here.

TEST FROORAM

The test program consisted of two firings of twelve models each. Models of two types (Table I), differing in the position of the center of mass (Figs. 1, 2) were launched in wood-plastic sabots (Figs. 2, 3)⁽²⁾ from a tank mounted 155mm smoothbore gun tube (Fig. 4). The sabots were so constructed as to hold the models at one and a half degrees angle to the boreline of the launching tube. This arrangement insured that sufficient yaw would be developed to permit analysis of the yawing motion.

The model bomb disengaged from the sabot within the distance separating the gun from the blast shield protecting the range building. The fragmented parts of the sabot were collected and deflected by the shield; the model then passed through a series of eighteen-inch ports into the instrumented portion of the range.

At each of the range's twenty-five spark stations horizontal and vertical projections of the model were obtained. At twelve stations the respective times of flight were recorded by 1.6 megacycle counters. Twenty-two undamaged models successfully traversed the full range. Two of the models were damaged by sabot failure¹ in launching, although one of these flew through the range satisfactorily.

All models were provided with an inch-wide salt band on the nose to assure early development of a turbulent boundary layer. This was done since the full scale bomb usually operates at Reynolds numbers where a turbulent layer can be expected.

REDUCTION OF DATA

The two photographic plates of each timing station were measured on optical comparators. Spatial position of the center of mass was determined from these measurements geometrically. These data, together with the time of flight data, were fitted to the following form on high speed el ctronic computers. (3, 4)

$$t - t_0 = a\overline{s} + b\overline{s}^2 + c\overline{s}^3$$

Where $\overline{z} = z - z^*$

and z^{+} is an arbitrary point approximately in the center of timing data. The drag coefficient evaluated at the Mach number associated with z^{+} is given by:

$$C_{\rm D} = -\frac{8}{\pi} \cdot \frac{m}{\rho d^2} \cdot \frac{2b}{a} \equiv \frac{\text{Drag Force}}{\frac{\rho V^2}{2} \cdot \frac{\pi d^2}{1}} = \frac{8}{\pi} K_{\rm D}$$

The values for the drag coefficients obtained are given in Table II together with the statistical error, the Mach number, and the prevailing yaw levels. The yaw drag coefficient is defined by:

$$K_{\rm D} = K_{\rm D_0} + K_{\rm D_8^2} \cdot \delta^2$$

¹ Both failures occurred in the plastic base elements of the sabot. This probably was due to variability of properties in the initial plastic castings (used for the first time) since failures occurred at medium, rather than maximum, test loadings.

In order to establish the zero yaw drag curve, values of the drag coefficient obtained for lower yaw levels¹ were fitted as a function of Mach Number alone. This curve was used to adjust blocks of the data to a common Mach number so that the variation with yaw could be determined. This variation was, in turn, used to correct the data to zero yaw conditions so that a final variation with Mach number could be determined.

RESULTS

Model Drag

The model drag coefficients are given as a function of their Mach numbers in Table II and Figure 5 for zero yaw. A curve representing a constant yaw level of four degrees (sixteen squared degrees) is also given (accelerometer drop data indicated full scale yaws of 3 degrees or less). The effect of this level of yaw was to increase the drag coefficient about 14% at the lower subsonic test speeds. This percentage variation generally holds through the early part of the drag rise until approximately M = 0.97. In this latter region the yaw effects appear to decrease and between Mach numbers 1.0 and 1.075 the yaw drag coefficient

was not clearly determined but appeared to be small². Above M = 1.10 the percentage change of drag due to yaw effect was about half that at subsonic speeds and decreased with increasing Mach number. A plot of the yaw drag coefficient as a function of Mach number is given in Figures 3, 6 and 7.

Flow Pattern

The nature of the variation of the drag coefficient relates quite closely to observable features of the flow patterns about the projectiles.

The drag coefficient rises slowly from the lowest test Mach number of 0.7 up to approximately M = 0.85 with no observable disturbance in the flow field (Figs. 8, 9). This trend is probably due to flow compressibility effects and alters near a Mach number of .855 when local shocks appear on the corner of the ogive and at the boattail (Fig. 10). The onset of local shock patterns appear to disturb the viscous layer. The boundary layer and the wake seem more pronounced in the shadowgraphs, although the former does not separate under any of the observed yaw conditions. The dissipative effects of the shock formations and the disturbance of the viscous layer produce a higher rate of change of the drag coefficient with Mach number. The drag coefficient curve increases almost linearly with Mach number as the local shock formations grow

DEVELOPMENT & PROOF SERVICES ABERDEEN PROVING GROUND MARYLAND

¹ Mean squared yaws less than 3⁰².

² This behavior is determined from models with an average yaw level of 2 degrees. Since relatively large variations in the flow characteristics occur for minor changes in yaw or Mach number near sonic speeds it is questionable whether this trend can be extrapolated to yaw conditions other than those achieved in the test.

(Fig. 11) until a Mach number of 0.97 is reached. At this latter point the curve steepens sharply, coinciding with a general development of supersonic flow behind the ogive. A waist shock occurs about the body, the flow reaccelerates on the afterbody and a shock system is established ahead of the fins. Local shocks also begin to appear, associated with the fins and the wake (Fig. 12). It appears that the local flow about the model is mainly supersonic and the shock system seems general rather than localized.

A bow wave appears in the shadowgraphs at a Mach number of 1.00 (Figs. 13, 14) and the slope of the drag curve decreases with increasing Mach number to the end of the test data at M = 1.25 (Figs. 15, 16).

Two further points, or rather suppositions might be noted: The fin shock pattern appears to stabilize at M = 1.09 and the data might support a minor break in the slope of the curve at this point; secondly the aft and bow shock formations appear to stabilize at the highest test Mach numbers indicating that the drag curve may be near a maximum,

This discussion is summarized in Fig. 16 a.

ESTIMATES OF FULL SCALE PERFORMANCE AND COMPARISONS¹

In order to obtain estimates for the drag of the full scale bomb the difference in the surface skin frictional effects between the model and the full scale were computed using subsonic flat plate formulae⁽⁵⁾. Two conditions were considered: 1) the full scale bomb at zero yaw, equivalent Mach numbers and at essentially sea level atmospheric conditions; 2) the full scale bomb at zero yaw, and at the atmospheric conditions as recorded on a particular drop⁽⁶⁾. Curves representing these estimates are given in Figure 17 together with the model drag curve for 4 degrees average yaw to indicate the relative magnitude of yaw and scale effects. The curve corresponding to the atmospheric conditions prevailing for the drop is approximately 15% below the model curve in the lower subsonic portion and about 3% below it at M = 1.2.

Three determinations of the drag properties of the bomb are given in Figure 18. One is the drag curve obtained from accelerometer measur ments on a full scale drop test. The yaw records for this drop indicat d yaw levels of about two degrees just after launching and when the bomb neared sonic speed. The second is the drag curve being used for preparations of bombing tables by the Computing Laboratory. This latter curve was deduced, initially, from all forms of drag data on models and on full scale configurations and was then adjusted to a best match of

¹ Discussions with Mr. E. S. Martin, Bombing Tables Branch, Computing Laboratory, Dr. A. S. Galbraith and Mr. L. Maynard, Theory Branch, EEL, have be n very helpful in this s ction.

of impact and time of flight data for a wide variation of drop conditions. The full scale estimates obtained from the firing range model data are also replotted in Figure 18 for average yaw levels of zero and four degrees.

It appears that the model curve is comparable with the curve used for bombing tables up to a Mach of one if average yaw levels of one to two degrees are probable. Above M = 1 the bombing table curve disagrees with the model curve <u>unless</u> average yaws of about four degrees are assumed. The accelerometer data curve is best determined at the higher Mach numbers and in this region it essentially agrees with the model curve. Estimated errors⁽⁶⁾ for the lower portion of the accelerometer curve are such that it may be compatible with either of the other curv s.

In comparing overall results the source of the data should be considered. The free flight range test provides a highly accurate drag determination for the model fired; drag is usually determined for zero (or small) yaw. These results must be corrected for scale effects. The full scale drop test utilizing direct measurements, while frequently subject to instrumentational difficulties, gives a direct measure of the drag for the conditions of a particular flight. The curve finally utilized for the preparation of bombing tables is the result, generally, of all available data but is finally adjusted to give the best fit of impact and time of flight measurements of a large series of drops involving many release conditions. Hence, it is an average of some sort that represents, possibly, a wide variety of flight conditions.

The evidence indicates that the model data agree with the bombing table curve <u>only</u> if certain yaw conditions can be assumed. The question is then raised as to whether the actual bomb drops used in the trajectory calculations exhibited sufficient yaw, on the average, to explain the difference between the model data and the bombing table drag curve. If yaws of a proper level existed the data are compatible; if not, there would be an essential disagreement between the model and the full scale data that would seriously reduce the usefulness of model data in assisting the preparation of bombing tables.

The evidence of several accelerometer drop tests⁽⁶⁾ appeared to show that the prevailing yaw levels in a drop could explain, at best, only the discrepancies in the subsonic portion of the drag curve (it should be noted that these drops were made without bomb bay doors and with the bomb semi-externally slung). However a series of Askania yaw and drag determinations from drop tests which were used to determine the bombing table curve¹ were available. The results of 18 drops from B-36 and B-45 aircraft at altitudes of 25,000, 35,000, 40,000 and 45,000 feet were

This material was furnished by Mr. E. S. Martin of the Bombing Tables Branch of the Computing Laboratory.

investigated. The measured yaw was converted to plots of $\overline{\mathbf{5}}^2$ as a function of time; the drag coefficients and a function of the total drag were also plotted. These records indicated a higher yaw level than was anticipated from the accelerometer data, particularly in the higher Mach number regions. Yaw data of this nature has an accuracy level of, say, two degrees. The sample curves (Figs. 19, 20) show levels of yaw from 2^{o2} to over 10^{o2} along large portions of the trajectory².

Figure 21 shows a comparison of the measured drag function $(K_{\rm D} \rho V^2)$ on several full scale bomb drops; the bombing table curve; and the model curve with a yaw correction for 4 degrees, average yaw. It appears that either the table curve or the yaw corrected model curve represents the general trend of the actual drags quite well.

CONCLUSIONS

Drag data obtained from free flight range model firings at reasonably high Reynolds numbers appear sufficient to serve as the basis for bombing tables, provided that scale corrections are applied to the model data, and provided that the yaw level in the full scale drops is quite small.

When full scale drop conditions include significant yaws, agreement with model data can be achieved by determining the yaw level and adjusting the model data accordingly.

ACKNOWLEDGEMENT

The author wishes to acknowledge the assistance of E. J. Roschke who materially helped this investigation.

J C Mac allister

²Since the period of the bomb is on the order of a second the graphs are drawn to show gross overall variations in the yaw not detailed variations.

REFERENCES

- 1. Rogers, W. K., The Transonic Range, BRL Report 849.
- 2. MacAllister, L. C., <u>On the Use of Plastic Sabots in Free Flight</u> <u>Testing</u>, BRLM Report 782.
- 3. Karpov, B. G., <u>The Accuracy of Drag Determinations as a Function</u> of <u>Number and Distribution of Timing Station</u>, BRL Report 658.
- 4. Murphy, C. H., <u>Data Reduction for Free Flight Ranges</u>, BRL Report 900.
- 5. Prandtl, L., Tietjens, O. G., <u>Applied Hydro and Aero Mechanics</u>, McGraw-Hill Book Co.
- 6. Conlan, J., Galbraith, A. S., Lewis, J. V., Maynard, L. G., <u>Deter-</u> mination of Aerodynamic Coefficients Using Accelerometer Records from a Plane Yawing Bomb, BRL Report 885.

TABLE I

MODEL PHYSICAL DATA

Forwar Center of (rd Gravity	Mean Center of Gravity
Weight (lbs.)	31.32 (average)	19.57 (average)
Diameter (inches)	4.433 <u>+</u> .002	4.433 <u>+</u> .002
Length (inches)	33.8402	33.83 <u>+</u> .02
c.g. (inches from ba	se) 23.11	18.79
Axial Moment (1bin	n. ²)71.50	48.52
Transverse Moment (lb in ²)	2592.0	1779.1

TABLE II

RANGE DATA

				2
Mach No.	K _D	с _р	[%] Error	<u>ह</u>
1-226	.2091	•5325	•22	2.3
1.207	2061	5248	•07	3.12
1.196	.2062	.5251	•fo	7.25
1.189	2030	.5169	. 15	5.12
1.177	.2010	.5118	1.50	2.76
1.110	1938	·4935	•50	5.8
1.103	.1872	.4767	.24	4,83
1.096	1876	•4777	.10	2.2
1.093	1853	.4719	.13	3.32
1.085	.1841	•1688	•02	1 . 44
1.077	.1765	-4495	2.3	1.74
1.067	.1750	·hh56	2.6	1.77
1.058	· 1 735	<u>.</u> µµ18	.13	1.12
1.050	. 1739	<u>.</u> 4428	•65	. * •72
1.040	.1642	<u>-4181</u>	• 36	•2
1.024	.1 594	•4059	•11	•1
1.011	•1514	•3855	•59	•05
1.008	.1463	•3725	• <i>h</i> ħ	3.6
1.005	. 1365	•3476	•23	5.42
1.001	•1324	•3372	• 38	4.14
•998	.1375	.3501	.49	1.21
↓996	,1269	•3231	1.77	2.77
•992	.1317	•3354	•15	•09
•986	.1266	•3224	•78	•59
•982	•1272 ·	•3239	•79	6.96
•976	•1155	•2941	•71	4.17
•972	.1064	•2709	•45	2.0
•971	•1014	•2582	•54	•1
•958	•0931	•2371	•93	1.01
•954	•0918	•2338	•15	•98
•949	.0915	•2330	' •97	•56
•936	.0048	•2159	•20	2.02
•932	+093I	•2 <i>371</i>	1.0	11.17
•920 005	•0030	•2134	•TO	
•727	•U025		رو⊥	ン•ブ(コームビ
•ATT	●U [24 064r	•⊥OUUU.	· •2	1+07 2 K
● ⁰ 77	•0005 0401	1C03	•72 7 4	J.O 2 42
●007 9.91.	-0004 0500	●エフ <i>3</i> 0 コピクピ	T ●Q	2.0J 1 67
•004 ·	+U277	•1727 JCOC	•44 47	עס ר רפ ר
•002	• ₩ 2 X Y	+±727	+ > ⊥	T20T

	TABI		2	
Mach No.	K D ¹ · · · · ·	e (8 2€)) D	\$ Error	ঁত
•786	.0565	.14.39	.85	6.24
•786	. 0516	1314	1.35	2.66
•784	.0522	.1329	.27	1.80
• 782	.0518	.1319	1.3	1.25
•723	•0533	.1357	.28	1.4
•718	•0578	.1472	1.3	2.16
.716	•0497	.1266	.26	1.38
•713	•0490	. 1248	.24	•9
•700	• 0257	.1342	2.9	5.09
•698	.0524	133 4	•47	2.9
•69 6	÷0512	-1304	•73	1.59

٠

.

•

TABLE III

DRAG	COEFFICIENT	AT ZERO YAW
М	™ D _O	°Do
•70	<u>,</u> 0500	.1273
.80	• 0505	. 1286
.84	•0507	.1291
-85	.0510	.1300
•86	•0520	.1324
•07	+0540	•13/5 11-50
•00 80	+U5/U	۲۴۶۶ ۱۹۶۶
•00 •02	•0055 0710	-1000 -1881-
•72 _9}i	-0830	-2711
.95	.0870	-2215
.96	.0930	.2368
•97	.1000	•2547
•980	•1140	•2903
•990	.1280	• 3260
1.000	•1400	• 3565
1.01	•1500	• 3820
1,02	•1560	•3973
1.03	•1015 1442	•4113 1.225
1.05	-1705	+4235 Ju312
1.06	-17h5	مبريه. بابابابا
1.07	1775	·L1520
1.08	.1810	•4609
1.09	.1835	•4673
1.10	.1860	•4736
1.11	.1875	•4775
1.12	.1895	•4826
1.13	.1913	.1871
ד∙ד ו ד•דו	•1930	+4915
1015 116	•1945	+4753 1.007
1.17	•1900 .107¢	+477T
1.20 → 1	.22 .2033	.5177



FIG. 1. MODEL BOMB



FIG. 2. MODEL IN OPEN SABOT



FIG. 3. SABOT ASSEMBLED









FIG. 9 M = 0.78



FIG. 11 M = 0.96



FIG. 12 M = 0.98



FIG. 13 M = 1.00 +



FIG. 14 M = 1.005







FIG. 16 A CORRELATION OF FLOW FIELDS AND DRAG CHARACTERISTICS

													2	 				•		: · · ·			•			_
		••••• ••	0.5	• 	•••••••••	 :	0	 			С 0	 		 	2.0	 			1 Q	· · ·		() 			
				•			-+				.			. 3	•				•	; • • ;					2	
			1-					- - -			141	Г Ш	SN0	 		r					·····		1.2		E	
			Ì		- 			- 				H	L D	۵ ۵	•					.	·	•		به معر ۱ ۱		
					- : •					1		н 10	S		• • •			•			¦		1		• • • •	
				N							1	R.	<u>ل</u> ر ا	<u>9</u> 20	:;1								-	-		
								, , ,				le	TOR	9					; ;)				1	:		
				<u>)</u> 				11 - 11	•	•••••	• • • •	ţ,	JEC	DR				• 7		- F				****		
											•	FOR	TRA	ΘF.										· · ·		
										Ĩ		+											<u> </u>		:	
	a										$\pm f$	II		Ń					1					E B B		
	18		ΙT						AW	it r														IM B		
	 NE	F						ONS	N IO														0,9	N-H-		
ť	+							Ĩ	ZER		• • ••••					X		\mathbb{N}^+					+-+-	ACH		
僅								Ó					•		l.			\uparrow						N		
	E M J		+++												ΥA								8			
	i i i						- 14 - 14	EV					++++	17.1	-FN								0 Ŧ			
N.								Ā							STA											
NI	Y	۵.						SE							CON					1 1 1			2	· · · · ·		
Ŷ								OR	• • • • •	* * * * *	٦: I				•	+++							0		4	
																										:1; ;++++
										+ ++ + + +																
		C												111	Ò.		- <u> </u> 1			1.1			90			
															?			TIS .								
																						11 		е / Ц 1 г/	· · · ·	

] .	A W.																		<u> </u> .	L										
			Ч			•••		•	• •		L L L	12	+]]					••••				Val D			· ·			*	• • • •		18	
			VOTAN	, ,					• • • •			20'S)))		.							. u		 							FIG	••••
			g		Ĩ			-	• • • • •			111) 					••••				TAP		 	••••••••••••••••••••••••••••••••••••••					.		
						-1	-	•	· · · · ·	. C		<u>G</u>	0 0 1					• • •	····		 	N N C			 - -							
							-	Ţ			1	. F	<u>.</u>	 : : : :	 	†						- ă		 	 	••	┣ <i>╼</i> ╼╼ 	• • • • • •		· • • •		••••
					•				ľ						•••			•••		 				 	 .	• •						
						1	•		· · · ·				~					• • •	· • • • •	• • • • • •		· · ·•		 :	.,	·····		,				
ŝ	2								· · · ·			/< 	Z				┽							 							2	11 1
TAVAT]		;; ;;							 ;	••••	•••			1	and a						• • • • • • • •	•					JMBE	
5-												<u>.</u>								No.	Ż	5			••••				6.0			
NC	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		₹	T																			-3 \				••••		<u> </u>		ACH	
0				<u> </u>		1				61									:. 	- u											N	
N P						-					 			••••	*** ****					- ME	••••			 					: 0 8 8			
X			49 						. 										· · · ·												· • • •	.,
50				51												•••				U, V									7		· · · · ·	••••
B																· , ·		•••					:::						0			-
						1	1																									
					þ																 ខ			[r	1			90			
					7						F										р. 				2					· · · · ·		
	İ								┋┥╿					1444 1444					Υ.										· _ ·	;	•••	••••







••

FIG. 21

.



DISTRIBUTION LIST

No. of Copies	Organization	No. of Copies	Organization
3	Chief of Ordnance Department of the Army Washington 25, D. C. Attn: ORDTB - Bal Sec (1 cy) ORDTX-AR (1 cy) ORDTA (1 cy)	1	Commanding Officer and Director David W. Taylor Model Basin Washington 7, D. C. Attn: Aerodynamics Lab.
10	British Joint Services	1	Commander Naval Air Development Center Johnsville, Pennsylvania
	Mission 1800 K Street, N. W. Washington 6, D. C. Attn: Miss Mary Scott, Tech Services	2	Commander Naval Ordnance Test Station China Lake, California Attn: Technical Library
4	Canadian Army Staff 2001 Connecticut Avenue Washington, D. C.	2	Commander Wright Air Development Center Wright-Patterson Air Force
8	Chief, Bureau of Ordnance Department of the Navy Washington 25, D. C.		Base, Ohio Attn: WCLG
2	Commander Naval Proving Ground Dahlgren, Virginia	Ŧ	Air Force Armament Center Eglin Air Force Base Florida Attn: ACOL
3	Commander Naval Ordnance Laboratory White Oak Silver Springs, Maryland Attn: Mr. Nestingen Mr. May	1	Commander Arnold Engineering Development Center Tullahoma, Tennessee Attn: Deputy Chief of Staff, R&D
1	Superintendent Naval Postgraduate School Monterey, California	I	Commander Air Research and Development Command P. O. Por 1395
2	Commander Naval Air Missile Test Center Point Mugu, California		Baltimore 3, Maryland Attn: Deputy for Development

DISTRIBUTION LIST

.

.

•

•

.

No. of Copies	Organization	No. of Copies	Organization
5	Director Armed Services Technical Information Agency Documents Service Center Knott Building	1	Commanding General Redstone Arsenal Huntsville, Alabama Attn: Technical Library
	Dayton 2, Ohio Attn: DSC - SA	3	Commanding Officer Picatinny Arsenal Dover, New Jersey
4	ASTIA Reference Center Technical Information Division		Attn: Samuel Feltman, Ammunition Labs
	Library of Congress Washington 25, D. C.	1	Commanding General Frankford Arsenal Philadelphia, Pennsylvania
1	Director National Advisory Committee	_	Attn: Reports Group
	for Aeronautics 1512 H Street, N. W. Washington 25, D. C.	1	Commanding Officer Chemical Corps Chemical and Radiological Lab. Army Chemical Center
1	Director National Advisory Committee	_	Maryland
2	for Aeronautics Ames Laboratory Moffett Field, California Attn: Dr. A. C. Charters Mr. H. J. Allen	1	Commanding Officer Diamond Ordnance Fuze Laboratories Connecticut Avenue & Van Ness Street, N. W. Washington 25, D. C.
3	National Advisory Committee for Aeronautics Langley Memorial Aeronautical Laboratory Langley Field, Virginia Attn: Mr. J. Bird Mr. C. E. Brown	1	Operations Research Office 7100 Connecticut Ave. Chevy Chase, Maryland Washington 15, D. C.
	Dr. Adolf Buseman	2	Applied Physics Lab 8621 Georgia Avenue
1	Chief, Armed Forces Special Weapons Project Washington 25, D. C.		Silver Spring, Maryland Attn: Mr. G. L. Seielstad
	Attn: Capt. Bert F. Brown USN	1	California Institute of Technology Norman Bridge Laboratory of Physics Pasadena, California Attn: Dr. Leverett Davis, Jr.

DISTRIBUTION LIST

No. of Copies Organization 2 Cornell Aeronautical Lab., Inc. 4455 Genesee Street Buffalo, New York Attn: Miss Elma T. Evans, Librarian 2 Sandia Corporation Sandia Base P. 0. Box 5800 Albuquerque, New Mexico Attn: Mr. E. T. Clark 1 Aerophysics Development Corp. P. O. Box 657, Pacific Palisades, California Attn: Dr. William Bollay 1 Consolidated Vultee Aircraft Corp. Ordnance Aerophysics Lab. Daingerfield, Texas Attn: Mr. J. E. Arnold

1 Professor George F. Carrier Division of Applied Sciences Harvard University Cambridge 38, Massachusetts

1 Dr. A. E. Puckett Florence Ave. at Teal St. Culver City, California

Commanding Officer
Naval Aviation Electronics Service
Unit
Naval Receiving Station
Washington 25, D. C.
Attn: Mr. C. G. Moore