UNCLASSIFIED

AD NUMBER

AD092213

CLASSIFICATION CHANGES

TO:

unclassified

FROM:

confidential

LIMITATION CHANGES

TO:

Approved for public release, distribution unlimited

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; APR 1956. Other requests shall be referred to National Aeronautics and Space Administration, Washington, DC.

AUTHORITY

20 Jan 1958 per NACA list no. 124 dtd 10 Feb 1958; NASA Technical Reports Server website

A GGG DE CENTER Armed Services Technical Information Agency Reproduced by DOCUMENT SERVICE CENTER KNOTT BUILDING, DAYTON, 2, OHIO

This document is the property of the United States Government. It is furnished for the duration of the contract and shall be returned when no longer required, or upon recall by ASTIA to the following address: Armed Services Technical Information Agency, Document Service Center, Knott Building, Dayton 2, Ohio.

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

m m	CONFIDENTIAL	Copy RM L56
5		
RESEA	RCH MEMORA	NDUM
	WIND-TUNNEL INVESTIGATION OF A	
RAM-JET MISSI	LE MODEL HAVING A WING AND CANA	ARD SURFACES
OF DELTA	PLAN FORM WITH 70 ⁰ SWEPT LEADI	NG EDGES
FORCE AND MO	MENT CHARACTERISTICS AT COMBIN	IED ANGLES OF
PITC	H AND SIDESLIP FOR MACH NUMBER	2.01
By	Cornelius Driver and Clyde V. Hamilto	on
	Langley Aeronautical Laboratory Langley Field, Va.	
This m	LASSIFIED IN CUMENT terial contains information affecting the National Lefense of the United States within the	e meaning
	an unauthorized person is prohibited by law	
	FOR AFRONALITICS	
	WASHINGTON	
	April 26, 1956	
	CONFIDENTIAL	
		Inp99

NACA RM 156B21

CONFIDENTIAL

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

RESEARCH MEMORANDUM

WIND-TUNNEL INVESTIGATION OF A

RAM-JET MISSILE MODEL HAVING A WING AND CANARD SURFACES

OF DELTA PLAN FORM WITH 70° SWEPT LEADING EDGES

FORCE AND MOMENT CHARACTERISTICS AT COMBINED ANGLES OF

PITCH AND SIDESLIP FOR MACH NUMBER 2.01

By Cornelius Driver and Clyde V. Hamilton

SUMMARY

An investigation has been conducted in the Langley 4- by 4-foot supersonic pressure tunnel to determine the static stability and control characteristics of a ram-jet canard missile at a Mach number of 2.01. The missile had wings and canard surfaces of delta plan form with 70° swept leading edges. Two ram-jet nacelles were mounted in the vertical plane on unswept pylons near the rear of the body. The center of gravity of the model was at -19.5 percent of the wing mean aerodynamic chord. Force characteristics of the missile configuration and various combinations of its components were determined through an incidence angle range from -2° to about 26° and at various roll angles from 0° to -90°. The Reynolds number of the investigation was 3.47×10^6 based on the wing mean aerodynamic chord.

An analysis of the results indicated that the missile became unstable in pitch above a lift coefficient of about 0.4 as a result, primarily, of the large unstable moment of the body.

The maximum lift-drag ratio was reduced from 5.0 to 3.2 by the addition of the nacelle-pylon combination to the wing-body-canard configuration.

There was a decrease in the directional stability at small angles of sideslip with increasing angle of attack up to angles of attack near 14° .

For positive angles of attack, the missile had negative effective dihedral or positive rolling moment due to sideslip.

INTRODUCTION

Tests have been made in the Langley 4- by 4-foot supersonic pressure tunnel to determine the aerodynamic characteristics of a ram-jet canardmissile configuration. The tests were part of a coordinated program with the Pilotless Aircraft Research Division to provide preflight aerodynamic characteristics of a model of a missile to be flight tested. In addition, tests were required to determine certain interference effects not obtainable in flight.

The model had a wing and horizontal and vertical canard surfaces of delta plan form with 70° swept leading edges. Two ram-jet nacelles were mounted in the vertical plane on short unswept pylons near the rear of the body. The model was equipped with all-movable canard control surfaces for both pitch and sideslip control, and movable wing-tip ailerons for roll control. The various component parts of the model could be removed to permit the investigation of the complete configuration or various combinations of its component parts to determine interference effects. The results of previous tests of the missile at a Mach number of 1.6 are presented in references 1 and 2.

The present paper presents the results of an extension to the investigation in which the static stability and control characteristics of the complete configuration and various combinations of its component parts were determined at a Mach number of 2.01 and a Reynolds number of 3.47×10^6 based on the wing mean aerodynamic chord.

SYMBOLS

The results of the tests are presented as standard NACA coefficients of forces and moments. The data are referred to the stability-axis system (fig. 1) with the reference center of gravity at -19.5 percent of the wing mean aerodynamic chord.

- b wing span, 0.988 ft
- c wing section chord
- \bar{c} wing mean aerodynamic chord, $\frac{2}{S} \int_{0}^{b/2} c^2 dy$, 0.957 ft

D drag, 1b

NACA RM 156B21

- F body frontal area, 0.03875 sq ft
- 2 body length, 4.23 ft
- L lift, lb
- moment about X-axis, 1b ft Mx
- Mach number Μ
- moment about Y-axis, 1b ft My
- moment about Z-axis, 1b ft M_{7}
- q free-stream dynamic pressure, lb/sq ft
- total wing area, 0.6948 sq ft (see fig. 2) S
- longitudinal distance from mean geometric chord х
- distance along wing span from model center line measured У normal to the plane of symmetry
- Х force along X-axis, lb
- Υ force along Y-axis, 1b
- Ζ force along Z-axis, 1b
- lift coefficient, Lift/qS (where lift is -Z) C_{T.}
- longitudinal-force coefficient, X/qS (- $C_X = C_D$ when $\beta = 0$) CX
- pitching-moment coefficient, M'/qSc C_r
- lateral-force coefficient, Y/qS Cγ
- rolling-moment coefficient, L/qSb C_{l}
- yawing-moment coefficient, N/qSb Cn
- angle of attack of the body center line, deg α
- angle of sideslip of the body center line, deg β

4	CO	NFIDENTIAL,	NACA RM 156B21
i	incidence angle, deg (a relative wind or stin	angle between body center ng angle)	line and
ø	angle of roll about the wise as viewed from : in a plane 90° from : angle i	e body axis, deg (positiv rear). \emptyset is zero when t the plane containing the	re angles clock- he wings are incidence
δ _V	vertical canard deflect	tion, deg	
$\delta_{\rm H}$	horizontal canard defle	ection, deg	
δ_{a_R}	aileron deflection, ri	ght, deg	
δ _a L	aileron deflection, le	ft, deg	
Notation :	for configuration:		
В	body		
W	wing		
С	horizontal and vertical	l canard surfaces	
N	nacelles		

MODEL AND APPARATUS

A three-view drawing of the basic model is shown in figure 2(a). Details of the canard surfaces and the method of determining wing area included within the body are presented in figure 2(b). A photograph showing the details of the model is shown in figure 3. The geometric characteristics of the model are given in table I.

The model was composed of a cylindrical body with a nose formed by a parabolic section and a frustum of a cone. Coordinates for the body are given in table II. The canard surfaces were in both the horizontal and vertical planes and had delta plan forms with 70° swept leading edges. The canard surfaces were all-moving and were deflected about axes normal to the body center line.

The main wing was located in the horizontal plane and had a modified delta plan form with 70° swept leading edges. (See fig. 2(c).) The nacelles were mounted on short, unswept pylons near the rear of the

body and correspond to the position designated "aft inboard" in reference 1. Coordinates for the nacelle and nacelle center body are given in Table III. All components of the model were removable so that tests of various combinations of components could be made.

The model was mounted on a remotely controlled rotary-type sting so that tests could be made at various roll angles of the model. Force measurements were obtained through the use of a six-component internal strain-gage balance.

TESTS AND PROCEDURE

Tests were made through a sting angle range from -2° to about 26° at various roll angles from 0° to -90° . The sting angles and roll angles were resolved into the angles of attack α and sideslip β by means of the following relations:

$$\tan \alpha = \tan \mathbf{i} \cos \phi \tag{1}$$

$$\tan \beta = \sin i \sin \phi \tag{2}$$

The test conditions were

Mach number	2.01
Reynolds number, based on wing mean aerodynamic chord	3.47×10^{6}
Stagnation pressure, atm	1.0
Stagnation temperature, ^O F	100
Dewpoint, ^O F	below -25 ⁰

The model configurations tested are listed in the following table:

Incidence angle 1, deg	Roll angle, φ, deg	Model configuration	Horizontal canard deflection, $\delta_{\rm H}$, deg	Vertical canard deflection, by, deg	Aileron deflection ⁸ a, deg
-2 to 27	0 to -90	Commplete model (BWNC)	0, -8, -12	0, -10	0, ±10
-2 to 21	0, -45, -90	Body (B)			
0 to 26	0 to -90	Body-wing (BW)			θ
-2 to 12	0 to -90	Body-canards (BC)	0, -8, -12	0	
-2 to 27	0 to -90	Body-wing-canards (BWC)	Ó	0	0
-2 to 27	0 to -90	Body-wing-canards - lower nacelle	0	0	0
-2 to 27	0 to -90	Body-wing-canards - upper nacelle	0	0	0

For all the test runs the nacelles were open and the data include the effects of internal flow. The nacelles were designed for a Mach number of 2 and, for this test, were operated near their design massflow ratio of 1.0. (For one run a pressure-survey rake was installed at the base of one nacelle and the mass-flow ratio was determined to be about 0.97.)

CORRECTIONS AND ACCURACY

A limited calibration prior to these tests has shown that the flow in the test section is reasonably uniform. The Mach number variation in the test sections was ± 0.015 and the flow-angle variation in the horizontal and vertical planes was $\pm 0.1^{\circ}$. No corrections were applied to the data to account for these flow variations. The angles of incidence were corrected for deflection under load. No corrections were applied to the roll angles due to deflection under load; however, these deflections would be small due to the comparatively small rolling moments and the rigidity of the system.

The base pressure was measured and the drag data were corrected to a base pressure equal to the free-stream static pressure. Errors in the base pressure measurements are included in the estimated error of C_X . No corrections were made for sting interference.

The estimated errors in the individual measured quantities are as follows:

Cm	•	•	٠	٠	•	٠	٠	•	•	•	•	•	•	٠	•	•	•	•	٠	٠	•	•	•	٠	٠	•	•	•	٠	±0.0004
CN	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	٠	•	•	٠	•	•	•	٠	±0.004
с _х	•	•	٠	•	•	•	•	•	•	٠	٠	•	•	•	•	•	•	•	•	•	•	•	•	•	٠	•	•	•	٠	±0.002
Cn	•	•	•	•	•	•	•	•	•	•	٠	•	•	•	٠	•	•	•	٠	٠	•	•	•	•	•	•	•	•	٠	±0.0005
Cl	•	•	•	•	٠	•	•	•	•	•	•	•	•	•	•	•	•	•	٠	•	•	•	•	•	•	٠	٠	•	•	±0.0004
CY	•	•	•	•	•	•	•	•	•	•	•	٠	•	•	•	•	•	•	•	•	٠	•	•	•	•	•	٠	•	•	±0.001
i,	de	g	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		±0.1
φ,	de	g	٠	•	٠	٠	•	•		•	•	٠		•	•	•	•	٠	•	•	•	•	•	٠	•	•	٠	٠		±0.1
δ _H ,	đ	le	5	•	•	٠	•	•	•	•	•	•	٠	•	٠	•	٠	٠	•	•	•	•	٠	•	٠	•	٠	٠	٠	±0.1
δα,	đ	le	3	•	÷	•	•	•	•	•	•	٠	•	•	•	•	•	•	٠	•	٠	٠	•	•	•	•	•	٠	٠	±0.1

.

.

CONFIDENTIAL

RESULTS

The basic results presented as functions of the incidence angle i for various constant values of roll angle $\phi\,$ are shown in the following manner:

Configuration

BWCN, $\delta_{\rm H} = 0$	• •	•	٠	•	•	•	•	•	•	•	•	•	•	•	٠	•	•	•	•	•	•	•	•	4
BWCN, $\delta_{\rm H} = -8^{\circ}$.	• •	•	٠	•	•	٠	•	•	٠	•	•	•	•	•	•	•	•	•	•	•	•	٠	•	5
BWCN, $\delta_{\rm H} = -12^{\rm O}$	• •	•	٠	•	•	•	•	•	•	•	٠	•	•	•	•	•	٠	•	•	•	•	•	•	6
BWCN, $\delta_V = -10^\circ$	• •	٠	•	٠	•	٠	•	•	•	٠	•	•	•	٠	•	•	•	•	•	•	•	•	٠	7
BWCN, $\delta_{a_{T}} = 10^{\circ}$,	δaR	=	-]	LO ^C)	•	•	٠	•	٠	٠	•	٠	٠	•	•	•	٠	٠	•	•	•	•	8
BC, $\delta_{\rm H} = 0^{\circ}$.	•••	•	•	•	•	•	•	٠	•	•	•	•	•	•	•	•	•	•	٠	•	٠	•	•	9
BC, $\delta_{\rm H} = -8^{\circ}$.	• •	٠	٠	•	•	•	•	٠	٠	٠	•	•	•	•	•	•	•	٠	•	•	•	•	•	10
BC, $\delta_{\rm H} = -12^{\rm O}$.	• •	٠	٠	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	٠	•	•	•	11
BW	• •	٠	•	٠	•	٠	•	•	•	•	•	٠	٠	٠	•	•	•	٠	٠	٠	•	٠	•	12
BWC, $\delta_{\rm H} = 0$	• •	•	•	•	•	٠	٠	٠	٠	•	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	•	٠	٠	13

Analysis figures obtained from the basic data are presented as follows:

Aerodynamic characteristics in pitch for several constant

control deflections; $\beta = 0^{\circ}$	14
Effect of center-of-gravity location on the aerodynamic	
characteristics in pitch; $\beta = 0^{\circ} \cdot \cdot$	15
Aerodynamic characteristics in pitch of the complete model	
and various combinations of its components; $\beta = 0^{\circ}$	16
L/D ratios for the complete model and various combinations	
of its components; $\beta = 0^{\circ}$	17
Effect of nacelle location on the aerodynamic characteristics	
in pitch; $\beta = 0^{\circ}$	18
Aerodynamic characteristics in sideslip at vertical canard	
deflections of 0° and -10° ; $\alpha = 0^{\circ} \cdot \cdot$	19
Aerodynamic characteristics in sideslip for the complete model	
and various combinations of its components; $\alpha = 0^{\circ} \cdots \cdots \cdots$	20
Effect of nacelle location on the aerodynamic characteristics	
in sideslip; $\alpha = 0^{\circ}$	21
Effect of vertical canard deflection on the aerodynamic	
characteristics in pitch; $\beta = 0^{\circ} \dots \dots \dots \dots \dots \dots \dots \dots$	22
Effect of horizontal canard deflection on the aerodynamic	
characteristics in sideslip; $\alpha = 0^{\circ}$	23
Effect of aileron deflection on the aerodynamic characteristics	
in pitch; $\beta = 0^{\circ}$	24
Effect of angle of attack on the aerodynamic characteristics	
in sideslip	25

CONFIDENTIAL

Figure

Longitudinal Characteristics

Stability and control, complete model.- The pitching-moment curves for the complete model (fig. 14) indicate a large nonlinear moment variation with lift coefficient. Such nonlinear characteristics may lead to missile tumbling at higher angles of attack and may necessitate a restriction of the angle-of-attack range to angles below 12° . The results obtained at M = 1.6 (ref. 1) indicated a similar trend although the angle-of-attack range did not extend beyond 14° . A forward shift in center-of-gravity location of -0.30 x/c eliminated the unstable variation of pitching-moment coefficient at high angles of attack (fig. 15) but also increased the static stability $-C_m/C_L$ to such an extent that the maneuverability could be seriously hampered.

At a center-of-gravity location of -19.5 percent of wing mean aerodynamic chord, the maximum trim lift coefficient in the stable range $\delta_{\rm H}$ = -12°, was approximately 0.4 at α = 12° and the resulting longitudinal-force coefficient was -0.14.

Effects of component parts. - The longitudinal characteristics of the complete model and various combinations of its components are presented in figure 16. The nonlinear pitching moment appears to be primarily a body effect rather than a wake or upwash effect (fig. 16) since the model with the canards removed indicates the same nonlinear trends. The addition of the nacelle-pylon combination to the body-wing canard configuration caused a large increase in minimum drag (fig. 16) and lowered the maximum L/D from 5.0 to 3.2 (fig. 17). The addition of the upper nacelle only (fig. 18) produced a positive moment increment which resulted from the combined effects of the drag of the nacellestrut combination and the interference lift loss on the upper surface of the wing. Conversely, the combined interference and drag effects of the lower nacelle resulted in a negative moment increment. The addition of both nacelles produced a greater destabilizing effect on the complete configuration (fig. 18) than indicated by the results for the nacelles individually.

Lateral Characteristics

Directional stability and control, complete model.- The results for the complete configuration (fig. 19) indicate that the model is directionally stable up to sideslip angles near 14°. The pylons and nacelles provide greater lateral force and directional stability (fig. 20) than the wings provide normal force and longitudinal stability (fig. 16). As a result, potentially higher angles could be reached in the yaw plane before instability occurred. However, because of the greater stability and the decreased canard area, the vertical canard is less effective in producing trim angle changes than is the horizontal canard.

NACA RM 156B21

С

CONFIDENTIAL

Effects of component parts. - The lateral characteristics of the complete model and various combinations of its components are presented in figures 20 and 21. The differences in side force and yawing moment at the higher angles of attack between the configurations with only an upper or lower nacelle (fig. 21) are believed to result from small asymmetries inherent in the model and model support system. The directional stability for the complete model is somewhat less than that indicated by a summation of the individual nacelles as a result, probably, of a mutual interference of the nacelles on the body sidewash.

Induced effects of canard controls.- The induced effects caused by vertical and horizontal canard deflections on the aerodynamic characteristics in pitch and sideslip are presented in figures 22 and 23. The variation with angle of attack of the aerodynamic characteristics resulting from control deflection (figs. 22 and 23) are similar to those shown for other types of canard missiles (ref. 3, for example) and may lead to complicated flight control problems for such missiles. It should be pointed out, however, that the induced effects, for the most part, occur at angles of attack that are greater than those that would be reached before longitudinal instability occurred.

Lateral control.- The effects on the aerodynamic characteristics in pitch of deflecting the ailerons $\pm 10^{\circ}$ are shown in figure 24. There are small decreases in lift and pitching moment and a slight increase in longitudinal force. The ailerons provide a constant roll increment throughout the angle-of-attack range but are relatively ineffective in producing roll. It is indicated that a $\pm 10^{\circ}$ deflection would be required to overcome the induced roll produced by the vertical canard at an angle of attack of 12° (for example, fig. 22).

Effect of angle of attack on aerodynamic characteristics in sideslip.-Through the use of the equations for α and β given under "Tests and Procedure," it is possible to obtain sideslip data at various constant angles of attack. This procedure has been followed and, as an example, the results for the complete model have been obtained from the basic data (figs. 4 and 7) for various constant angles of attack through the sideslip range. The tabulated results are presented in table IV, and the variation of the coefficients with sideslip for various constant angles of attack is shown in figure 25. These results indicate a decrease in the directional stability at small sideslip angles with increasing angles of attack the variation of rolling moment with sideslip positive angles of attack the variation of rolling moment with sideslip indicates a negative effective dihedral (positive $C_{1\beta}$, fig. 25(a)).

Similar figures showing the variations of the various coefficients for combined angles of α and β can be made for each model configuration for which results were obtained through the roll-angle range.

CONCLUSIONS

A ram-jet canard missile model having a wing and horizontal and vertical canard surfaces of delta plan form with 70° swept leading edges was tested in the Langley 4- by 4-foot supersonic pressure tunnel. The center of gravity of the model was at -19.5 percent of the mean aerodynamic chord. The force characteristics of the model and various combinations of its components were determined at a Mach number of 2.01 and a Reynolds number of 3.47×10^6 based on the wing mean aerodynamic chord. A summary of the results of investigation indicated the following conclusions:

1. A nonlinear pitching-moment variation with lift for the complete model that is probably caused by the moment variation of the body alone may result in missile tumbling above a lift coefficient of 0.4. A forward shift in the center-of-gravity location would alleviate the tumbling but would result in lower maneuverability.

2. The maximum lift-drag ratio obtained for the complete model was 3.2. The removal of the nacelle-pylon combination increased the lift-drag ratio to 5.0.

3. The directional stability at small sideslip angles of the complete model decreased as the angle of attack was increased to angles of attack near 14° .

4. For positive angles of attack, the complete model had negative effective dihedral.

Langley Aeronautical Laboratory, National Advisory Committee for Aeronautics, Langley Field, Va., February 10, 1956.

REFERENCES

- 1. Hamilton, Clyde V., Driver, Cornelius, and Sevier, John R., Jr.: Wind-Tunnel Investigation of a Ram-Jet Missile Model Having a Wing and Canard Surfaces of Delta Plan Form With 70° Swept Leading Edges. Force and Moment Characteristics of Various Combinations of Components at a Mach Number of 1.6. NACA RM L53Al4, 1953.
- 2. Spearman, M. Leroy, and Robinson, Ross B.: Wind-tunnel Investigation of a Ram-Jet Missile Model Having a Wing and Canard surfaces of Delta Plan Form With 70° Swept Leading Edges. Longitudinal and Lateral Stability and Control Characteristics at a Mach Number of 1.60. NACA RM L52E15, 1952.
- 3. Spearman, M. Leroy: Effect of Large Deflections of a Canard Control and Deflections of a Wing-Tip Control on the Static-Stability and Induced-Roll Characteristics of a Cruciform Canard Missile at a Mach Number of 2.01. NACA RM L53K03, 1953.

•

-

TABLE I

GEOMETRIC CHARACTERISTICS OF MODEL

Maximum diameter, in. 2.660 Length, in. 50.832
Fineness ratio
Base area, sq in
Wing:
Span, in
Chord at body-wing intersection, in
Chord at aileron break line, in
Area (including that within body), sq in 100.05
Aspect ratio
Sweep angle of leading edge, deg
Thickness ratio at body center line 0.014
Thickness ratio at aileron break line
Leading-edge half angle normal to leading edge, deg 7.8
Trailing-edge half angle, normal to trailing edge, deg 7.8
Mean aerodynamic chord, in
Aileron:
Area, sq in
Mean aerodynamic chord, in
Horizontal canard surfaces:
Horizontal canard surfaces: Area (exposed), sq in

٠

.

.

•

-

*

TABLE II

•

BODY COORDINATES

Body station	Radius
$\begin{array}{c} 0\\ .297\\ .627\\ .956\\ 1.285\\ 1.615\\ 1.945\\ 2.275\\ 2.605\\ 2.936\\ 3.267\\ 3.598\\ 3.929\\ 4.260\\ 4.592\\ 4.923\\ 5.255\\ 5.587\\ 5.920\\ 6.252\\ 6.583\\ 11.542\\ 50.833\end{array}$	0 .076 .156 .233 .307 .378 .445 .509 .573 .627 .682 .732 .780 .824 .865 .903 .940 .968 .996 1.020 1.042 1.333 cylindrical section

TABLE III

NACELLE AND NACELLE-CENTER-BODY GEOMETRY



r	80.706 8.9966 8.9966 81.069
Х	0.963 7.603 13.712 14.962
æ	0 .325 .325 .402 .412 .413 .418 .418 .157 .157
×	0 893 1.200 1.500 1.575 1.575 7.500 7.200 6.208

⁸All internal contours are straight between the points noted.

CONFIDENTIAL

Ч	
TABLE	

.

.

TABULATED RESULTS FOR VARIOUS ANGLES OF ATTACK

AND SIDESLIP, COMPLETE MODEL

(a.) $\delta_{\rm H} = \delta_{\rm V} = 0^{\rm O}$

	ڻ ک	0010- 90010- 0010- 0010- 0010- 0010- 0010-	038 038 034 034 032	039 041 041 039	009 017 030	.037 .023 .008	.030 .0001
	сX	-0.052 -053 -053 -052 -052 -052	081 081 081 081 083	123 130 132 132	195 201 206	298 300 306	
	$c_{\rm L}$	0.125 .130 .131 .130 .130 .130 .125	.260 .265 .260 .260	.385 40 415 425	• 535 • 55 • 565	-70 -70 -70	.872 .880
	с _Y	0.023 046 .085 .130 .250 .250	.050 .111 .187 .30 .580	.085 .190 .330	.135 .30 .495	.265 .45 .65	•35 •565
	сı	-0.0001 0001 0001 001 001 002 008	002 014 012 019 019	009 019 028 035	120 - 140 - 140 -	034 046 056	-, 041 -, 055
	α C	-0.005 019 019 027 10	0085 041 041 068 122	014 0396 069 115	029 057 086	074 091 180	092
	β, deg	1-1-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2	2.5.5 2.5.5 2.5.8 2.5.8 2.1 2.1 2.1 2.1 2.1 2.1 2.1 2.1 2.1 2.1	-3.26 -5.66 -12.08 -12.08	-4.39 -7.62 -11.35 -16.00	-5.57 -9.63 -14.30	-6.80 -11.73
	1, deg	1.1.4 	8.28 8.28 9.74 9.74 11.24 15.70 22.54	12.01 13.20 14.55 16.73 23.03	16.54 17.56 19.29 22.07	20.65 21.88 23.96	24.75 26.16
And Annual and the state of the second	ø, deg	IJŶŶŶŶŶŶŶ ŶŶŶŶŶŶŶŶŶŶŶŶŶŶŶŶŶŶŶŶŶŶŶŶŶŶŶŶŶ	59 59 59 59 59 59 59 59 59 59 59 59 59 5	-15 -45 -45 -60	 	÷+ +5+ +5+	ų Υ
	a, deg	******	∞∞∞∞∞∞ ∞	នានានានា	16 16 16	ର ର ର	575

CONFIDENTIAL

NACA RM 156821

٠

.

TABLE IV.- Concluded

TABULATED RESULTS FOR VARIOUS ANGLES OF ATTACK

AND SIDESLIP, COMPLETE MODEL

(**b**) $b_{\rm H} = 0^{\circ}$; $b_{\rm V} = -10^{\circ}$

₹.	210.0	.093 041	-265			.080		-520	-330	200		.152		.370	<i>x</i> ?	.221		•515		542.	.658	•357
ರೆ	0.048	•036 021	- 010			6£0.		£00.	024	160		.018		+20		710	I	058			072	
C,1	-0.001	- 003 - 003				003		110	016	015		002		610 	•	001		027		010	039	023
٤	-0.020	017				035		030	034			032		034	()) -	600		038		100	- 022	.023
చ్	-0-057	051 056	059	<u></u>		086		061	087	960*-		-,126		120		200		-,100		705	133	744
г сГ	0.135	131.				762.		.232	•255	.267		e76.		865.	r 	543.		•559		zr7.	<u>5</u> 2.	.890
β, deg	-1.07 -1.87		-6-91	-10.88	6.43 - - - - - - - - - - - - - - - - - - -	-2.16	-3.75	-5.62	8°. 9	-13.68	-41-12-	-3.26	-5.66	9 . F0	-8-5-	-4-39	-7.62	-11-35	00-01-	-5.57	-14.30	-6.80 -1.73
1, deg	4.14 1.1.1	i ~i ∩ i ⊗ €	1.96	11.56	5-15	8.28	8.82	9.74	11.24	15.70	¥.	12.01	13.20	14.55	23.03	16.54	17.56	19-29	10.22	20.65 30.65	23.96 96.53	24.75 26.16
ø, deg	-15 8		18	6 1	- 8	-15	<i>א</i> ף	-35	5-1-2	8	0/-	-15	សុ	-35	<u>8</u>	-15	Ŕ	5	C T	-15	-35	5- 59 9
a, deg		+ - + - +	r	t	t -t	8	80	Ø	80 (ω ο	o	दा	ศ	<u>역</u> :	4 24	16	16	50	٩T	କ୍ଷ ହ	88	たた

CONFIDENTIAL

1







1



t

İ

ţ

CONFIDENTIAL

-001.4



(a) General arrangement of model.

œ

œ

-1.928 r-250

<u>4606-</u>

2.678-

417

-002-002-002-Section AA

Section BB

1700

Top view

-2700

2 926

-Honzontal canard hinge line

9,125-

-50.833 -

18



(b) Details of canard control surfaces.

Figure 2.- Continued.



Figure 2.- Concluded.



Figure 3. - Photograph of the model. L-74957

21



Figure L.- The variation of the basic coefficients with incidence angle i for configuration BWCN; $\delta_{\rm H} = 0^{\circ}$.

,

CONFIDENTIAL



Figure 4.- Continued.

+



Figure 4.- Concluded.

·C



Figure 5.- The variation of the basic coefficients with incidence angle i for configuration BWCN; $\delta_{\rm H}=-8^{\circ}$.

.

.

٠

.

٠



Figure 5. - Continued.

٠

1



Figure 5.- Concluded.



Figure 6.- The variation of the basic coefficients with incidence angle i for configuration BWCN; $\delta_H = -12^\circ$.

```
CONFIDENTIAL
```

٠



Figure 6.- Continued.

CONFIDENTIAL

•

۰.



Figure 6. - Concluded.



Figure 7.- The variation of basic coefficients with incidence angle i for configuration BWCN; $\delta y = -10^{\circ}$.

•



Figure 7.- Continued.

*

CONFIDENTIAL



Figure 7.- Concluded.

CONFIDENTIAL

33



Figure 8.- The variation of the basic coefficients with incidence angle i for configuration BWCN; $\delta_{a_L} = 10^\circ$; $\delta_{a_R} = -10^\circ$.



Figure 8. - Continued.

CONFIDENTIAL

*

•



Figure 8. - Concluded.



Figure 9.- The variation of the basic coefficients with incidence angle i for configuration BC; $\delta_{\rm H} = 0^{\rm O}$.

.



Figure 9.- Concluded.

CONFIDENTIAL

•



Figure 10.- The variation of the basic coefficients with incidence angle i for configuration BC; $\delta_{\rm H}$ = -8°.

CONFIDENTIAL

٠

•



Figure 11.- The variation of the basic coefficients with incidence angle i for configuration BC; $\delta_{\rm H}$ = -12°.



Figure 12.- The variation of the basic coefficients with incidence angle i for configuration BW.

•

CONFIDENTIAL

3

J.

٠



Figure 12.- Continued.

.

•



Figure 12.- Concluded.

CONFIDENTIAL

•

۰.



Figure 13.- The variation of the basic coefficients with incidence angle i for configuration BWC; $\delta_{\rm H} = 0^{\circ}$.

4 4



Figure 13.- Continued.

٠

45



Figure 13.- Concluded.

*

CONFIDENTIAL

.



Figure 14.- Aerodynamic characteristics in pitch for several constant control deflections; $\beta = 0^{\circ}$.

47

· ·



Figure 14. - Concluded.

5



Figure 15.- Effect of center-of-gravity location on the aerodynamic characteristics in pitch; $\beta = 0^{\circ}$.

٠.



Figure 16.- Aerodynamic characteristics in pitch of the complete model and various combinations of its components; $\beta = 0^{\circ}$.

i

;



Figure 16.- Continued.

1

CONFIDENTIAL

*



Figure 16. - Concluded.



Figure 17.- L/D ratios for the complete model and various combinations of its components; $\beta = 0^{\circ}$.

53

٠,



Figure 18.- Effect of nacelle location on the aerodynamic characteristics in pitch; $\beta = 0^{\circ}$.



Figure 18.- Concluded.

CONFIDENTIAL

.



Figure 19.- Aerodynamic characteristics in sideslip at vertical canard deflections of 0° and -10° ; $\alpha = 0^{\circ}$.



Figure 20.- Aerodynamic characteristics in sideslip for the complete model and various combinations of its components; $\alpha = 0^{\circ}$.

11

CONFIDENTIAL

,



Figure 21.- Effect of nacelle location on the aerodynamic characteristics in sideslip; $\alpha = 0^{\circ}$.

.











٩





ο δ_H = 0 °
□ δ_H = -8 °
ο δ_H = -12°



Figure 23.- Effect of horizontal canard deflection on the aerodynamic characteristics in sideslip; $\alpha = 0^{\circ}$.





Figure 24.- Effect of aileron deflection on the aerodynamic characteristics in pitch; $\beta = 0^{\circ}$.

,









Figure 24.- Continued.

CONFIDENTIAL

.





CONFIDENTIAL

- -



(a) $\delta_{\rm H} = 0^{\rm o}; \ \delta_{\rm V} = 0^{\rm o}.$

Figure 25.- Effect of angle of attack on the aerodynamic characteristics in sideslip.









Figure 25.- Continued.

CONFIDENTIAL

;

~

65

۰.

-

CONFIDENTIAL



Figure 25.- Continued.

·----

.

.

CONFIDENTIAL

,







Figure 25.- Concluded.

CONFIDENTIAL

į