UNCLASSIFIED



Reproduced by the

ARMED SERVICES TECHNICAL INFORMATION AGENCY ARLINGTON HALL STATION ARLINGTON 12, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

N.

MISS AS USED

54

ARL 64 269 539

STRONG INTERACTION WITH SLIP BOUNDARY CONDITIONS

J. AROESTY

UNIVERSITY OF CALIFORNIA

SEPTEMBER 1961

AERONAUTICAL RESEARCH LABORATORY OFFICE OF AEROSPACE RESEARCH UNITED STATES AIR FORCE





E i A

- 4			}	
		UNCLASSIFIED	UNCLASSIFIED	UNCLASSIFIED
There are a contracted as a co	University of California, Berkeley, Calif. STRONG INTERACTION WITH SLIP BOUN- DARY CONDITIONS by J. Aroesty, Septem- ber 1961. 35 p. incl illus. (Project 7064; Task 70169) ARL 64 Unclassified Report	A solution to the problem of strong inter- action between the shock wave and the boundary layer has been obtained for the case where velocity slip and temperature jump boundary conditions are consistent at the wall. It is shown that the addition of slip boundary conditions yields a correc- tion of order $[5/X]$ to the no slip solution. Estimates are made of the effect of slip on	induced pressures and skin friction for the case of the adiabatic wall. In addition, it is shown that the inclusion of slip boundary conditions does not change the energy trans- fer to the wall from the no slip values.	· [
		UNCLA.SSIFLED	UNCLLASSIFIED	UNCLASSIFIED
	University of California, Berkeley, Calif. STRONG INTERACTION WITH SLIP BOUN- DARY CONDITIONS by J. Aroesty, Septem- ber 1961. 35 p. incl illus. (Project 7064; Task 70169) ARL 64 Unclassified Report	A solution to the problem of strong inter- action between the shock wave and the boundary layer has been obtained for the case where velocity slip and temperature jurip boundary conditions are consistent at the wall. It is shown that the addition of slip boundary conditions yields a correc- tion of order $[5/X_1^{-1}c)$ the no slip solution. Estimates are made of the effect of slip on	induced pressures and skin friction for the case of the adiabatic wall. In addition, it is shown that the inclusion of slip boundary conditions does not change the energy trans- fer to the wall from the no slip values.	

STRONG INTERACTION WITH SLIP BOUNDARY CONDITIONS

J. AROESTY

UNIVERSITY OF CALIFORNIA BERKELEY, CALIFORNIA

SEPTEMBER 1961

CONTRACT AF 33(616)-6161 PROJECT 7064 TASK 70169

AERONAUTICAL RESEARCH LABORATORY OFFICE OF AEROSPACE RESEARCH UNITED STATES AIR FORCE WRIGHT-PATTERSON AIR FORCE BASE, OHIO

300 - January 1962 - 16-655 & 656

FOREWORD

This report was prepared at the Institute of Engineering Research, University of California, Berkeley, California, under Contract AF 33(616)-6161, Project 7064, "Research on Aerodynamic Flow Fields," Task 70169, "Thermo-Aerodynamic Characteristics at Hypersonic Mach Numbers." The work was administered under the direction of the Aeronautical Research Laboratory, Office of Aerospace Research, USAF, with Lt John Anderson as Task Scientist.

The theoretical analysis and experimental work were carried out by J. Aroesty under the supervision of Professor G. J. Maslach and Professor S. A. Schaaf.

ABSTRACT

A solution to the problem of strong interaction between the shock wave and the boundary layer has been obtained for the case where velocity slip and temperature jump boundary conditions are consistent at the wall. It is shown that the addition of slip boundary conditions yields a correction of order $[\delta/X]$ to the no slip solution.

Estimates are made of the effect of slip on induced pressures and skin friction for the case of the adiabatic wall. In addition, it is shown that the inclusion of slip boundary conditions does not change the energy transfer to the wall from the no slip values.

TABLE OF CONTENTS

Section		Page
1	INTRODUCTION	1
2	OGUCHI'S ANALYSES	3
3	EFFECTS OF SLIP	6
4	PRESENT ANALYSIS	9
	4.1 Derivation of the Zero & First Order Equations	10
	4.2 Solution	15
	4.3 Skin Friction and Heat Transfer	20
5	SUMMARY AND CONCLUSIONS	24
	REFERENCES	25
APPENDIX	A. EVALUATION OF SMALL PARAMETER	28
APPENDIX	B. THE EXPANSION OF PURELY X-DEPENDENT QUANTITIES	29
APPENDIX	C. BOUNDARY CONDITIONS	30

LIST OF SYMBOLS

M	Mach Number
С	Chapman Rubesin Constant = $M_{\rm es} T_{\rm es}$
Ž	Rypersonic Interaction Parameter - Mile
Rex	Reynolds Number = 102
T	Temperature
P	Pressure
ኛ	ce/cv
6	Boundary Layer Thickness
u	Velocity in x direction
v	Velocity in y direction
¥	Stream Function
£	Transformed Variable Defined by 5 - 5 1 M. 48 dx
η	Transformed Variable Defined by $\gamma = \frac{4s}{12t} \int \frac{1}{t} 1$
f	Defined by $\mathcal{Y}=\sqrt{2}\mathcal{F}$ in Boundary Layer
N	PH/R.M.
4	Shear Stress
2	Local Mean Free Path
ε	Expansion Parameter * Awe Us
ß	Pressure Gradient Parameter, $\beta = 2\frac{dus}{44}\frac{s}{f}\frac{H_s}{h_s}$
h	Enthalpy
н	h+== 12
P	Pressure
8	H/H3
5*	Displacement Thickness

.

 $\begin{array}{ccc}
\overline{C}_{F} & \text{Skin Friction Coefficient} & \overline{7}_{F/6/6}^{2} \\
\overline{C}_{F_{O}} & \overline{C}_{F_{O}} & \overline{C}_{F_{O}} & \overline{7}_{F/2}^{1/2} \\
\end{array}$ Momentum Thickness

Subscripts

£	Edge of Boundary Layer
4	Wall or Body
J.	Wall or Body
ω	Free Stream Values
0	Zero th Order quantities
1	First Order Perturbation

STRONG INTERACTION WITH SLIP BOUNDARY CONDITIONS

J. Aroesty

1 INTRODUCTION

The status of the hypersonic leading edge problem has not changed appreciably in the period since the earliest recognition of the shock waveboundary layer interaction phenomenon. The theoretical aspects of the problem have mainly been considered from the viewpoint of boundary layer theory, with few exceptions^[1,2,3]. There has been some work by $Charwat^{[4]}$ on the application of a near-free-molecule technique to the region very close to the tip. This approach, which actually considers the various types of collisions encountered by molecules which have been reflected off the plate surface, is similar to the "physical iteration" scheme used by Charwat and Baker^[5] in their consideration of near-free-molecule-flow over a sphere. This counting of collisions becomes quite complicated as more and more collisions occur and it becomes increasingly difficult to assign a mean free path to each type of molecular encounter.

Another attack on the problem, not within the scope of boundary layer theory, was carried out by Laurmann^[6], who considered the problem of slip flow over a short flat plate. The solution was based on a linearization of the full Navier-Stokes equations about the free stream velocity. The interesting possibility was raised that for this problem, with sufficient slip at the surface, the Oseen solution could be valid over the entire short plate. Although it is difficult to relate this problem of the short plate to that of the leading edge region of a long flat plate on physical grounds, Laurmann's^[6] result of a near linear displacement thickness is certainly suggestive of the possible effects of slip boundary conditions at the surface.

Except for a recent paper by Oguchi^[7], the remainder of the analytical attempts using the continuum approach have been within the framework of hypersonic similar solutions of the boundary layer equations. The earliest solutions ^[8] suggested the possibility of a strong-interaction region, where the pressure grows like $x^{-1/2}$ and the boundary layer grows like $x^{3/4}$. The important parameter in this region was shown to be $M^{3/4}$, and all solutions were given as functions of this hypersonic interaction parameter, χ .

Although the early measurements of the pressure distributions on the sharp leading edge flat plate in hypersonic flow seemed to confirm the existence of this strong interaction region, later work done at Berkeley and at Schenectady demonstrated clearly that this parameter alone is certainly not able to describe the pressures as the plate tip is approached. Starting from the downstream side, it becomes apparent that the pressures increase, at least qualitatively, as predicted by the strong interaction results until they reach a plateau of constant pressure, and then decrease. The level of the pressure plateau is a function of Mach number for sufficiently large values of \mathcal{Y} . Since the various data have been taken at a variety of wall temperatures, it is simplest to characterize the experiments done at Berkeley as the insulated case, and the experiments done at General Electric Company as the highly cooled case. ^[9,10]

Even the strong interaction theories suggest that the induced pressures increase with increased T_w/T_o , so that it is not surprising that the level of this pressure plateau is also a function of this temperature ratio. Examination of the available data suggests the possibility that the extent of the strong interaction region, where the pressure grows like $x^{-1/2}$, is probably quite small, if it exists at all.

Prior to the publication of the data which showed the existence of a pressure plateau near the tip, attempts to modify the early strong interaction

solutions were made by Oguchi and Stewartson [11, 12] using hypersonic small disturbance theory. On purely analytical grounds, these more recent solutions are attractive in that they provide a complete solution to the flow field between the shock wave and the boundary layer, whereas the early work, which utilized the tangent wedge formula, gave no information at all concerning the nature of the flow field external to the boundary layer.

2 OGUCHI'S ANALYSES

Recently Oguchi^[11] gave a more complete joining of the boundary layer and the inviscid flow, where the vorticity and temperature at the edge of the boundary layer are no longer taken to be zero, as in the earlier solutions, but rather at the values that obtain from the solution of the zero order inviscid equations. Thus, the complete similarity of the flow field enables one to obtain information which is not at all available in the tangent wedge approach, which yields p/p_{p_0} alone at the edge of the boundary layer.

However, the means necessary to achieve complete similarity is to assume that the shock wave grows like Ax^n , where $1 > n \ge 2/3$. With the application of the approximate conservation laws across the shock, this implies that the pressure and temperature approach a singularity as the leading edge is approached. Thus, this simple form of the shock shape, essential to a similar inviscid flow field, is then responsible for the high pressures near the leading edge, and also for the perhaps spuriously hot gas at the edge of the boundary layer.

edge of the viscous regions. For air, the small parameter is effectively of order \int_X , which introduces some question concerning its validity in a boundary layer solution. The additional consideration of the vorticity due to the curved leading edge shock wave yields pressure levels which are higher even than those of the earlier solutions.

In the light of experiments that seem to point to a pressure plateau as the leading edge is approached, it is possible that the leading edge shock wave is not very highly curved, and in fact, it is certainly possible that it is nearly straight. With this in mind, Oguchi has recently attempted to settle this problem of shock-boundary layer interaction in a manner which is similar to the viscous layer problem on a blunt body. Oguchi has assumed that the flow in the entire region between the shock wave and the body may be represented by the boundary layer equations. This implies that the entire pressure field in the very leading edge region is constant, since the assumption is also made that the shock wave is straight. In addition to the usual condition that $u = u_{n_0}$ at the shock, it is also required that the mass flow entering the shock wave is equal to the mass flow in the boundary layer. This is done by equating the boundary layer stream function at the still unknown shock wave height, y_{s} , to the stream function corresponding to the free stream at that height.

Using the nomenclature of reference [8], this new condition is

$$\gamma_{sl} = \gamma_{Fere} s_{TRemp} \qquad (1)$$

$$\sqrt{23} f(\gamma_s) = \rho_{so} U_0 y_1 \qquad (2)$$

where

$$\gamma_{s} = \frac{u_{\infty}}{\sqrt{2s}} \int_{0}^{y_{s}} \frac{dy}{dy} \qquad (3)$$

It is Oguchi's hope that the solution of the boundary layer equations, with this additional boundary condition, yield a zero value for the shear stress just behind the shock wave. This is critical to the justification of the use of the boundary layer equations in the entire field, since the shock wave is assumed to be a straight discontinuity, satisfying the appropriate Rankine-Hugoniot conditions. Since the shock thickness varies inversely as the strength, it is more likely that one is able to give an a priori justification for the neglect of the shock structure in the case of a very strong shock, such as a normal shock, than for this case of a comparatively weak shock.

In attempting to meet the boundary conditions for this problem, Oguchi utilizes an assumed form for the stream function which is inconsistent with the resulting equations, except for the region where $\gamma_S <</$, corresponding to the region closest to the tip. For larger values of γ_S , a numerical solution is proposed which is called a "local similarity solution". By means of these two solutions, one analytic and one numerical, the induced pressures over the entire leading edge region are predicted, and are shown to agree quite well with the more recent experiments.

However, if the value for the shear behind the edge of the shock is evaluated properly, i.e.,

$$\gamma = \frac{N_{AyA} - U_{0}^{2} F_{\gamma\gamma}(\mu)}{\sqrt{23}}$$
(4)

$$\frac{\sigma r}{T_{w}} = \frac{N F_{yy}(y_{s})}{F_{yy}(0)}$$
(5)

the solution for the limiting case of $\eta_s <<1$ yields the result that

 $\mathcal{F}_{w} = 1$ throughout the boundary layer. Similarly, for the case corresponding to the "locally similar" solutions, \mathcal{T}_{wall} is always greater than zero, and in fact, is always greater than 0.3. Thus, we see that the requirement of the vanishing of the shear behind the shock wave is not met, and an inconsistency develops at the shock wave. The way out of this inconsistency is certainly not clear, but it is apparent that the solution, as it stands now, is certainly open to question.

3 EFFECTS OF SLIP

Laurmann's suggestion that a linear displacement thickness is possible for large slip velocities, and the well known incompressible result, that small slip at the surface decreases the displacement thickness, all point to the likelihood that inclusion of first order slip boundary conditions in the strong interaction problem will tend to reduce the curvature of the boundary layer thickness, and consequently reduce the pressure levels from the no slip value as the leading edge is approached. Street^[1,3] and Laurmann^[14] have considered this problem, the latter using an integral technique, and the former using an expansion procedure somewhat analogous to the Oguchi procedure for matching the vorticity.

The procedure which Street and Laurmann used is the expansion of certain flow quantities in terms of a small parameter, which is related to the local mean free path at the wall. This technique is quite well known^[15], and is characterized as possessing solutions which are related to the y-derivatives of the zeroth order solutions.

Cassaccio^[15] has attempted to generalize this result to the case of a similar compressible flow, where no effect on the external flow is considered.</sup>

The solutions obtained are characterized by this linear dependence on the y-derivatives of the zeroth order solution.

If the expansion is cast in the Howarth-Dorodnitsyn variables $\begin{bmatrix} 8 \\ 8 \end{bmatrix}$, the appropriate expansion parameter becomes evident from the expression for $\frac{\partial u}{\partial Y}$ at the wall, i.e., slip boundary conditions.

$$4(0) = a \lambda \frac{\partial 4}{\partial \gamma} \qquad (6)$$

$$\sim 4(0) = \lambda w \rho \frac{4}{\sqrt{2}} f_{\gamma} \cdot a \qquad (7)$$

The appropriate expansion parameter becomes

$$\mathcal{E} = \frac{\lambda w \rho w \mathcal{U}_{s}}{\sqrt{2} s}$$
(8)

Expanding $\frac{u}{u_{J}} = for_{J} + \varepsilon f_{r}(r_{J}) + o(\varepsilon^{2}) + \cdots + \cdots$ (9)

(i.e., perturbing a similar solution), and inclusion in the momentum equation yields

$$N f_{\eta \eta \eta} + f_0 f_{\eta \eta} + f_0 (g_0 - f_0 \eta) = 0 \qquad \text{zero}^{\text{th}} \text{ order in } \mathcal{E} \qquad (10)$$

The requirement for similarity in the zeroth order solution was that

$$\beta = 2 \frac{du_{i}}{u_{i}} \frac{f}{df} \frac{H_{d}}{h_{f}}$$
(12)
$$\sigma_{r} \frac{U_{s}^{2}}{H_{j} - \frac{f}{2}} \frac{H_{d}^{2}}{H_{s}} = B \frac{g}{f} \frac{g}{h_{s}}$$
(13)

For the assumed first order expansion to be consistent, it is clearly necessary that \mathcal{E} must be of the form $\mathcal{B}\mathcal{F}^{\mathcal{K}}$ when \mathcal{K} is a constant. Since $\lambda \mathcal{A}\mathcal{A}\mathcal{A}$ is independent of \mathcal{F} , being determined only by the wall temperature, this is equivalent to requiring that \mathcal{U}_{i} vary like a power of \mathcal{F} . This is inconsistent with the requirement for the zeroth order solution, which is that

$$U_{i} = \left\{ \begin{array}{c} B \\ F \\ \hline i - \frac{1}{2} \\ \hline H_{i} \end{array} \right\}^{1/2}$$
(14)

Only for the special cases of $\beta = 0$, corresponding to a flat plate, $M_1^2 \approx 1$ corresponding to hypersonic flow, or $M_1^3 <<1$ corresponding to low speed flow, is the expansion procedure completely consistent. Maslen^[17] gave the complete solution for the case where $\beta = 0$, corresponding to compressible slip flow over a flat plate. Otherwise, it is possible to show that the only solution satisfying this assumed form for f is the one which drives the term in the brackets in equation (11) identially to 0, or $f_1 = Af_2 \beta_1$. However, this is certainly a very special case, since we have only given one solution to a third order differential equation for f_1 . In general, we can see that this assumed expansion is not satisfactory.

4 PRESENT ANALYSIS

The present analysis will consist of a perturbation about the strong interaction solution, in order to represent the effects of the slip boundary conditions.

The following assumptions will be made in order to obtain the familiar zero order equations given in [8], page 305.

- 1. The boundary layer equations are valid.
- 2. Pr = 13. P_{I} = N = (constant) 4. $M_{S} >> I$, H_{S} = constant

5. Tangent wedge formula is valid to describe the interaction between the displacement thickness and the induced pressure. The boundary layer equations, with first order slip, for Pr = 1 may be written as:

$$\frac{1}{3}\left(\begin{array}{c} \rho u \\ \overline{\gamma} \end{array}\right) + \frac{1}{3}\left(\begin{array}{c} \rho v \\ \overline{\gamma} \end{array}\right) = 0 \quad (15)$$

$$\mathcal{D}\mathcal{U} \frac{d\mathcal{U}}{d\mathcal{V}} + \mathcal{D}\mathcal{V} \frac{d\mathcal{U}}{d\mathcal{V}} = -\frac{d\mathcal{D}}{d\mathcal{V}} + \frac{d}{d\mathcal{V}} \left(\mathcal{M} \frac{d\mathcal{U}}{d\mathcal{V}} \right)$$
(16)

4.1 Derivation of the Zero & First Order Equations

The Howarth Dorodnytsin transformations are applied in order to render the equations amenable to a similar solutions analysis.

$$\begin{split} & \mathcal{G} = \int \mathcal{F} \mathcal{M}_{b} \mathcal{U}_{\delta} \mathcal{J}_{\lambda} \qquad (21) \\ & \mathcal{J} = \underbrace{\mathcal{U}_{\delta}}_{VZS} \int \mathcal{D} \mathcal{J}_{\gamma} \qquad (22) \\ & \mathcal{G} = \underbrace{\mathcal{H}}_{HS} \qquad (23) \\ & \mathcal{U} = VZSF(\gamma_{0}S) \qquad \text{where} \quad f_{\gamma} = \underbrace{\mathcal{U}_{\delta}}_{US} \qquad (24) \end{split}$$

The momentum equation becomes

-

$$NF_{\eta\eta\gamma} + ff_{\eta\gamma} + 2\frac{dl_{\eta}d_{1}}{dl_{\eta}s}\left(\frac{f_{i}}{\rho} - f_{\gamma}^{2}\right) = 25(f_{\eta}f_{j}s - f_{j}f_{\eta\gamma}) \qquad (25)$$

The energy equation becomes

$$N_{g\eta\eta} + f_{g\eta} = 25(f_{\eta}g_{g} - f_{g}g_{\eta})$$
 (26)

The momentum equation can be put in a somewhat different form for the case where the external flow is hypersonic-- i.e., $H_1^2 >> /$.

$$\frac{d h_{1} U_{3}}{d h_{2}} = \frac{\beta}{d \xi} \frac{d u_{1}}{d \xi} \qquad (27)$$

where
$$g = \int \rho_0 \mu_1 \, \mu_0 \, dy$$
 (21)

If we set $U_1 = \text{constant}$, in the integral,

(28) assuming a perfect gas.

Thus

$$\frac{dF}{dx} = \frac{M_{6} H_{6}}{RT_{6}}$$
(29)

or then

$$\frac{f}{ds}\frac{du_{\delta}}{u_{\delta}} = \frac{fp\,dx}{p\,u_{\delta}}\frac{d\,u_{\delta}}{dx} \quad (30)$$

Since we are assuming an isentropic external flow,

$$P_{s} \mathcal{U}_{s} \frac{\mathcal{U}_{s}}{\mathcal{U}_{x}} = -\frac{dp}{dx} \quad (31)$$

$$\therefore \quad \frac{\mathcal{F}}{\mathcal{U}_{s}} \frac{\mathcal{U}_{s}}{\mathcal{U}_{s}} = -\frac{\mathcal{F}_{s} \mathcal{U}_{x}}{\mathcal{F}_{s} \mathcal{U}_{s}} \frac{dp}{\mathcal{U}_{x}} \quad (32)$$

or

.

$$\frac{2f}{ds}\frac{Ju_{t}}{U_{t}} = -\frac{\int p dx}{p^{2}} \frac{dp}{dx} \frac{RT_{t}}{U_{t}^{2}}$$

$$= -\frac{\int p dy}{p^{2}} \frac{dp}{dx} \frac{r-1}{s} \frac{h_{t}}{\frac{H_{t}}{2}}$$

$$= -\frac{\int p dy}{p^{2}} \frac{dp}{dx} \frac{r-1}{s} \frac{h_{t}}{\frac{H_{t}}{2}}$$
for $M_{t}^{2} >>1$
for $M_{t}^{2} >>1$

Rewriting

$$\left(e_{p}^{2} - F_{y}^{2} \right)$$

$$\frac{J_{1}}{r} = \frac{h}{h_{5}} = \frac{T}{T_{5}} \qquad \text{for perfect gas}$$

$$\frac{J_{1}}{r} = \frac{H - u_{1}^{2} f_{1}^{2}}{h_{1}} - f_{1}^{2} \qquad (34)$$

$$= \frac{H - H_{5} f_{1}^{2}}{h_{1}} = \frac{H_{6} (g - f_{1}^{2})}{h_{6}} \qquad (35)$$

The momentum equation may then be written

$$Nf_{\eta\eta\eta} + ff_{\eta\eta} - \frac{f_{\mu}d_{\gamma}}{p^{2}} + \frac{g_{-1}}{g} (g_{-}f_{\eta}^{2}) = 2g(f_{\eta}f_{\eta}^{2} - f_{\eta}^{2}f_{\eta}^{2})$$
 (36)

The slip boundary conditions may be written, (to first order in λ) as

or

$$g(o) = g + b \lambda_{b} \left(\frac{\partial g}{\partial y} \right) = 0$$

$$g(o) = g_{b} + b \lambda_{b} \beta u_{s} g_{\eta}$$

$$(37)$$

$$(37)$$

$$(37)$$

$$(37)$$

$$(37)$$

Temperature Jump

or

$$\begin{array}{c}
\mathcal{U}(0) = \alpha \lambda_{1} \frac{\partial \mathcal{U}}{\partial y} \\
\mathcal{U}_{S}F_{\eta} = \alpha \lambda_{1} \beta \mathcal{U}_{S}^{2} F_{\eta} \\
\eta^{**} \quad \frac{\partial \lambda_{1} \beta \mathcal{U}_{S}}{\sqrt{2g}} F_{\eta} \\
\eta^{=0}
\end{array}$$

$$\begin{array}{c}
\text{Velocity} \\
\text{Slip} \\
(38)
\end{array}$$

The form of the slip boundary conditions suggests that the appropriate expansion parameter for a perturbation solution about the zero order strong $\mathcal{E} = \frac{\lambda_{0} f(\mathbf{u})}{\sqrt{2\pi}}$ interaction solution would be , where F- Hole Fodx Evaluation of this small E= 02-44 parameter in terms of M and Re shows that where $G = \left(\frac{M/C}{R_e}\right)^2 \sqrt{\frac{1}{10}} \left[\frac{1}{22}\right]$. (See Appendix A.) The expansion is applied directly to the transformed equations f=fo(y) + Efi(y) + ... (39) $g = g_0(\eta) + \varepsilon g_1(\eta) + \cdots -$ (40) $\beta = \beta_0 \left[1 + \varepsilon \beta_1 + \dots \right]$ (41) $f = f_{0} [1 + \epsilon f_{0} + \dots]$ (42)

At the edge of the boundary layer, as $\gamma \rightarrow \infty$, the following terms are expanded

Because the external flow is adiabatic, the stagnation enthalpy remains constant at H_{g} .

When these forms are placed in the transformed equations, the following sets of equations are obtained

$$\frac{2 \operatorname{ero}^{\operatorname{th}} \operatorname{order} \operatorname{in} \mathbf{E}}{\operatorname{N} \operatorname{F_{\eta} \eta}} + \operatorname{F_{0}}(\operatorname{g_{0}} - \operatorname{F_{\eta}}) = 0 \qquad (46)$$

$$Ng_{ij} + f_{ij} = 0 \tag{47}$$

At
$$\gamma = 0$$
; $g_{\bullet}(0) = g_{b}$; $f_{\bullet} = 0$, $f_{\bullet \gamma} = 0$ (48)

At
$$\gamma \rightarrow \infty$$
; $j_{\bullet} \rightarrow 1$, $f_{\bullet \gamma} \rightarrow 1$ (49)

The solutions of the zeroth order equations are tabulated in [18] <u>First Order in E</u>

$$NF_{\eta\eta\eta} + f_0 f_{\eta\eta} + f_0 f_{\eta\eta} + f_0 (g_1 - 2F_{\eta} f_{\eta}) + \frac{3}{2} F_0 F_1 (g_0 - f_{\eta}^2) = - f_{0\eta} f_{\eta\eta} + f_1 f_{\eta\eta}$$
(50)

and

(53)

Rewriting

$$Nf_{i}\eta\eta\eta + f_{0}f_{i}\eta\eta + f_{0}f_{i}\eta - 2\beta f_{0}\eta f_{i}\eta = -\beta(g_{i}) - \frac{3}{2}\beta \beta(g_{0} - f_{0}\eta)$$

$$(52)$$

and

Where B. C. are

$$f_{1}'(0) = a f_{0}'(0)$$

 $f_{1}'(0) = 0$
 $f_{1}(0) = 0$
 $g_{1}(0) = b g_{0}'(0)$
 $g_{1}(\infty) = 0$
(55)

4.2 Solution

The energy equation may be integrated immediately

$$g_{i} = Ag_{i}'(\gamma) + Bg_{i}'(\gamma) \int \frac{e^{-\int G_{i}' \gamma}}{(g_{i}')^{2}} d\gamma \qquad (56)$$

The perturbation velocity $f_{i}(\gamma)$ can be written $f_{i}(\gamma) = C f_{0}(\gamma) + D f_{0}(\gamma) \int_{0}^{\eta} \frac{e^{-\int_{0}^{\gamma} f_{0} d\gamma}}{(f_{0}^{\prime\prime})^{2}} d\gamma + V_{i} f_{i}^{\prime\prime}$ $+ V_{2} f_{0}^{\prime\prime} \int_{0}^{\eta} \frac{e^{-\int_{0}^{\gamma} f_{0} d\gamma}}{(f_{0}^{\prime\prime})^{2}} d\gamma \qquad (57)$

The condition at $\eta = 0$ permits the constants A and C to be evaluated, since all the other terms vanish there.

However, the condition at ∞ is identically satisfied by the functions, irrespective of the value of the constants B and D. It is then necessary to introduce some other requirement on the solution in order to establish a physically sensible solution. If the requirement is made that the various thicknesses which characterize the boundary layer possess finite dimensions, it is possible to evaluate the constants B and D. (See Appendix C).

When these constants are evaluated, the solution to the first order

energy equation becomes

The solution to the first order momentum equation can be written

$$f_{i}(r_{j}) = af_{o}''(r_{j}) + f_{o}''_{ij} \int \frac{e^{-\frac{\pi}{2}} \frac{e^{-\frac{\pi}{2}} \frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}{\frac{e^{-\frac{\pi}{2}}}{\frac{e^{-\frac{\pi}{2}}}{$$

Since the functions f_0 , f_0'' , g_0' and g_0 have already been calculated [18], it would be possible to evaluate the velocity and energy perturbations as numerical functions of γ .

numerical functions of 2. In order to calculate p₁, it is necessary to first calculate the displacement thickness, and then utilize the tangent wedge formula.

If we neglect terms of $O(\frac{1}{\sqrt{3}})$, the displacement thickness can be written

$$S^* \approx S = \frac{\sqrt{2F}}{P_{g} U_{J}} \frac{H_{J}}{h_{J}} \int (g - F_{J}^{2}) dy \qquad (62)$$

Expanding in the small parameter \leq , using the perfect gas law, and the results that $\int_{1}^{2} = 2p$, and $U_{1} = 0$, we may write

where

$$\delta_{0} = \int_{0}^{\infty} (g_{1} - f_{0}^{2}) d\eta \qquad (64)$$

$$\delta_{1} = \int_{0}^{\infty} (g_{1} - 2f_{0}^{2} f_{1}^{2}) d\eta \qquad (65)$$

The integral, \int_{1}^{1} , will be in the form $a' + p \beta$, since the perturbation velocity profile is given as a linear function of p_1 . Since $\int_{0}^{+} = p \sqrt{2f_c} T_c f_c$, $\int_{0}^{+} may$ be written $\int_{0}^{+} = \int_{0}^{+} \left[1 + \xi \int_{0}^{+} f_c \right]$ The use of the tangent wedge formula requires that the slope of the

displacement thickness be evaluated

$$\frac{d\delta^{*}}{d\chi} = \frac{d\delta^{*}}{J_{\chi}} \left[1 + \varepsilon \frac{di}{f_{0}} \right] + \frac{d\varepsilon}{d\chi} \int_{0}^{*} \frac{di}{f_{0}} \quad (66)$$

$$\frac{d\varepsilon}{J_{\chi}} = -\frac{d\varepsilon}{4\chi} \int_{0}^{*} \frac{df_{0}^{*}}{J_{\chi}} = \frac{3}{4\chi} \int_{0}^{0}^{*} \frac{d\varepsilon}{\chi} \quad (67)$$

$$\frac{d\delta^{*}}{4} = \frac{d10}{4} \left[1 + \varepsilon \left(1 - \frac{1}{3} \right) \frac{\delta}{10} \right]$$
(68)

or

$$\frac{d\delta^{*}}{dv} = \frac{d\delta}{dv} \left[1 + \frac{2}{3} \frac{\delta}{v} \right]$$
(69)

The tangent wedge formula, as given in reference [8] is

$$\frac{T}{R_0} = \frac{1}{2} \left(\frac{\tau}{\tau} \right) \left(\frac{1}{4s} \right)^2 M_0^2 \qquad (70)$$

or

$$f_{Ro}^{\prime} = f_{R}^{\prime} \left[1 + \epsilon_{R} \right] = \frac{1}{2} (r+1) \left(\frac{1}{2} \right) \left(1 + \frac{4}{3} \epsilon_{ro}^{\prime} \right) H_{ro}^{2} (71)$$

$$\widehat{Since} = \frac{1}{2} (+1) M_{uo}^{2} (+1) \frac{1}{2} (72)$$

then
$$h = \frac{4}{3} \frac{\delta_1}{\delta_2}$$

The calculation of p_1 for the general case is quite complicated, since the numerical evaluation of several integrals is required in order to evaluate f_1 ' and hence, f_2 . Although the complete calculation is possible in principle, it is of questionable utility, since the expansion parameter is of order f_2 . However, in order to give an estimate of the magnitude of p_1 , we shall consider the case of the adiabatic wall. In addition, we shall set $P_1 = 0$ whenever it appears in the velocity profile. This is equivalent to setting the non-homogeneous terms to zero in the differential equations. If we suggest, on intuitive grounds, that the primary effect of slip on the velocity profiles is not through the change in the external flow field (i.e., p) but rather directly through the change in the boundary conditions, we can write the approximate solution of the momentum equation as

(73)

$$f_i(\eta) = afo(\eta) \quad (74)$$

Evaluating S_{i} , since $g_{1} = 0$, for the adiabatic wall

$$s_{1} = -2 \int f_{1}' f_{0}' dy$$
 (75)
 $s_{1} = -2a \int f_{0}' f_{0}'' dy$ (76)

 $J_{1} = -a$ (77)

and

$$7_{1} = -\frac{9}{3} \frac{9}{50}$$
 (78)

From Oguchi's paper [11], & is evaluated from a solution of the zeroth order momentum equation. Oguchi's notation uses I_0 to represent our \mathcal{L}_0 .

$$I_{0} = 1.310$$
 for air (79)

Therefore, the nondimensional coefficient for the pressure perturbation is $p_1 = -a$. For the usual case of completely used constant a may be replaced by 1, since $a = \frac{2-6}{6} \times 2 \times 0.499$. As demonstrated in Appendix A, $E = \left(\frac{MVC}{VR_{e_v}} + \frac{T_W}{T_U}\right)^{1/2} (.22)$.

$$\vec{F}_{Ro} = \vec{F}_{R} \vec{\chi} \left[1 - .22 \left(\frac{MVE}{VRe_{Y}} \right)^{1/2} \right] (80)$$

or

$$P/R_0 = .555 \bar{\gamma} \left[1 - \left(\frac{MVC}{VR_{VY}} \right)^{1/2} .22 \right]$$
 (81)

This can be written

$$\frac{1}{P_{00}} = .555 \overline{\gamma} \left[1 - \frac{1}{M} \right]^{2} .22$$
 (82)

or

5 = .73 12 1/2 since

$$\frac{1}{7} = .555 \frac{1}{7} \left[1 - .3 \frac{50}{7} \right]$$
(84)

An examination of equation (61) suggests that this is a maximum estimate for the decrease in induced pressure from the zeroth order values.

(83)

4.3 Skin Friction and Heat Transfer

To boundary layer order, the shear stress at the surface is

$$T_{y=0} = \mu_{(y=0)} \frac{\partial 4}{\partial y} \Big|_{y=0}$$
(85)

Although it has been assumed that M = N in order to provide a better fit to the true viscosity-temperature behavior over the entire temperature range encountered in a hypersonic boundary layer, this approximation is used only in the differential equations, and is not used to evaluate shear and heat transfer at the wall.

In our transformed system, thus,

$$\gamma = \mu \underline{\mu}_{i} \frac{\underline{\mu}_{i}}{\sqrt{2}} F_{\eta \eta} \quad (86)$$

We approximate M(y=0) by $M_0 \frac{Tro}{T_0}$ where we have assumed that a linear fit is possible over the small temperature range Ta-Fa .

$$H(Y=0) = M_b [I + \varepsilon T_i] (87) \quad \text{where} T(0) = T_b (I + \varepsilon T_i)$$

The density at y = 0 is given by the perfect gas law,

$$P_{y=0} = \frac{B_{0}P_{0}(1+\epsilon p)}{RT_{L}(1+\epsilon T_{i})}$$
(88)

where P=PooPo(ItER) Tro)=To(ItETi)

$$\overset{\circ}{} \overset{\circ}{} \overset{\circ}{}$$

The shear stress can then be expanded in the form

$$\mathcal{T} + \mathcal{E}\mathcal{T}, = \frac{\mu_{b}\beta \, \mathcal{U}_{b}^{2}}{\sqrt{25}} \left[f_{0} \eta \eta + \mathcal{E}f_{0} \eta \eta \right]$$
(90)
ace $\mathcal{E} = \mathcal{L}p_{1}$.

since $\int_{I} = I_{P_1}$ The skin friction coefficient, defined by

$$C_{F} = \frac{\gamma}{2\rho_{0}} U_{0}^{2} \qquad (91)$$

is given by

$$C_{F} = G_{F_{0}} \left(1 + \mathcal{E} G_{F_{0}} \right) \quad (92)$$

.

$$= \frac{2 M_{b} \beta U_{b}^{2}}{R_{o} U_{b}^{2} f_{2} f_{o} \eta \gamma} \left[1 + \varepsilon \frac{F_{i} \eta \eta}{F_{o} \eta \gamma} \right]$$
(93)
$$= C_{F_{o}} \left[\frac{C}{R_{e_{x}}} \frac{\gamma}{\mu} V_{2}^{2} \left[1 + \varepsilon \frac{f_{i} \eta \eta}{F_{o} \eta \gamma} \right]$$
(94)

where

$$\overline{C}_{F_0} = C_{F_0} \sqrt{C_{Rex}} \overline{\chi}^{1/2}$$
(95)

Evaluating
$$f_{i\eta\eta\eta}$$
, we obtain
 $f_{i\eta\eta} = \frac{4}{6} \frac{6}{\eta\eta\eta} + \frac{4}{6} \frac{1}{6} \frac{6}{6} \frac{6}{2} + \frac{3}{2} \frac{6}{6} \frac{(g - f_0^{-2})}{g - 5} \frac{6}{6} \frac{1}{2} \frac{1}{2} \frac{1}{6} \frac{1}{6} \frac{1}{6} \frac{1}{2} \frac{1}{6} \frac$

If we attempt to estimate the magnitude of this slip correction to the skin friction on the same basis that we estimated the correction to the induced pressures, we can approximate the result for $f_{inp}(s)$ by

$$f_{i}\eta_{0}^{i} = -\frac{5}{2} = -286 \quad (97)$$

• $G_{F_{i}}^{i} = .568 \, \overline{\mu} \cdot \sqrt{\frac{2}{R_{ex}}} \left[1 - .245 \, \overline{e} \right] \quad (98)$

or since $\mathcal{E} = .22 \, \overline{\mu} \frac{V_{2}}{M}$

$$\bar{C}_{\mu} = .568 \, \bar{\chi}^{\mu} \left[= 1 - .05 \, \bar{\chi}^{\mu} \right] \left[= 1 - .05 \, \bar{\chi}$$

For this case of the adiabatic wall, it is possible to make an estimate of the magnitude of the second term in the expression for $f_{\gamma\gamma}$ by approximating f_{σ} " by its Blasius value, f_{σ} " f_{σ} .

Then, we may write

$$f_{i\eta\eta} = -\frac{\gamma+i}{2} \left[1 - \frac{3}{2} \frac{\pi}{6} \frac{60}{6} \right]$$
 (100)

where

$$\delta_0 = \int_0^\infty \left(\frac{1}{6} - \frac{1}{6} \right) d\eta \quad (64)$$

$$\approx$$
 1.310 for air

If we approximate p_1 by -1, as suggested earlier, the result is then

$$\begin{aligned} f_{i}\gamma\gamma_{0}^{i} \approx -.286 \int 2.97 \int (101) \\ \text{or} \quad f_{i}\gamma_{0}^{i} \approx -.85 \\ \text{or} \quad C_{F} = .568 \overline{\gamma}^{1/2} \int (1-.18) \overline{\gamma}^{1/2} \int (102) \end{aligned}$$

This also suggests that it may be possible to predict C_p from measured values of p_1 , which are obtained from the measurements of induced pressures on adiabatic plates. If the above procedure represents the phenomenon adequately, then the deviations from the strong interaction pressures could be used in a formula of the form

$$G_{SLIP} = G_{F_0} \int [-E_{*286}(1-1.97 \mu)] f (103)$$

where p_1 could be estimated from available data.

The heat transfer to the wall may be estimated more readily, but it should be noted that the energy transferred to a wall in slip flow is given by

where q is the Fourier heat conduction term

u₁ is the slip velocity

 \mathcal{T}_{w} is the shear at the wall.

In terms of our expansion parameter, Σ ,

The total energy transfer to the wall is then

$$\begin{array}{l}
\left(q + u_{1} T_{w} = -\frac{p_{0} M \cdot u_{0}}{P_{r} V \Sigma f_{0}} \right) \left(\frac{q}{2} \left(1 \right) - \mathcal{E} \left(\frac{q}{2} - \frac{2}{2} F_{0} \eta f_{0} \left(1 - \frac{p_{r}}{r} \right) \right) \right) \left(\frac{107}{r} \right)
\end{array}$$

For any wall temperature and Pr = 1, $g'_1| = 0$, since $g''_1| = \int_{-\infty}^{\infty} \int_{-\infty}^{$

Thus, for Prandtl No. = 1, the slip work term is exactly balanced by the change in the Fourier heat conduction to the wall, and there is no net change in the energy transfer to the wall.

5 SUMMARY AND CONCLUSIONS

The solution to the problem of the effects of slip boundary conditions in the strong interaction region has been presented. Since the appropriate expansion parameter is of $O(\frac{1}{2})$, the effects of slip, as obtained from this solution are only one of several possible higher order effects.

In view of the complexity of the general solutions, crude estimates of the slip effects on induced pressures and skin friction were made only for the adiabatic wall. These are presented in Figures 1 and 2. In addition, it was found that for the case of arbitrary constant wall temperature, and Pr = 1, there is no change in the heat transfer from zeroth order strong interaction solutions.

In order to evaluate the correctness of the estimates for induced pressure and skin friction, it would be necessary to integrate several functions of the zeroth order quantities. It would be desirable to do so, since this would show whether or not the significant departures from the strong interaction theory in the induced pressure can be attributed to slip at the surface. If it is decided that slip phenomena are present, and are important, then the use of the complete solutions would aid in the prediction of skin friction from pressure data.

Additional work is obviously necessary on the general problem of the hypersonic leading edge, both from the viewpoint of kinetic theory, starting from the tip, and also from the viewpoint of a set of continuum conservation equations such as the Navier-Stokes equations.

The apparent inadequacy of the hypersonic boundary layer equations in predicting aerodynamic quantities suggests that higher order effects may be both present and significant.

REFERENCES

- 1. Liu, V. C., J. Fluid Mech, 5, 481, 1959
- 2. Harris, E.L., UTIA Report #53
- 3. Nagamatsu, H., Phys. of Fluids, 3, 1, 140, 1960
- 4. Charwat, A.F., RAND Corp. Report P 2113, August 5, 1960
- 5. Charwat, A.F., and Baker, R. S., Phys. of Fluids, 1, 73, 1958
- Laurmann, J. A., Univ. of Calif. Eng. Project Report HE-150-152, December, 1957
- 7. Oguchi, H., ARL TN 60-133, Brown University, 1960
- 8. Hayes & Probatein, Hypersonic Flow Theory, Academic Press, New York, 1959
- 9. Aroasty, J., Univ. of Calif. Eng. Project Report HE-150-157, July 1958
- 10. Nagamatsu, H., and Sheer, R., ARS Preprint 1132-60, 1960
- 11. Oguchi, H., Univ. of Tokyo Aero Res. Inst. Report 330, 1958
- 12. Stewartson, K., J. Aero/Space Sciences, 22, 607-616, 1955
- 13. Street, R., Tach. Status Report 3, AF Contract 49(638)-440, Univ. of Washington
- 14. Laurmann, J. A., Univ. of Calif. Eng. Project Report HE-150=160, August 1958
- 15. Schaaf, S. A., and Chambre', P. L., "Flow of Rarefied Gases," <u>High Speed</u> <u>Aerodynamics and Jet Propulsion</u>, Vol. III, Section H, Princeton Univ. Press, 1958
- 16. Cassaccio, A., J. Aero/Space Sciences, 1960
- 17. Maslen, S., NACA TN-2818
- 18. Li, T.Y., and Nagamatsu, H., J. Aero/Space Sciences, <u>20</u>, 345-355, 1955
- 19. Cohen, C., and Reshotko, E., NACA Report 1293, 1956





APPENDIX A

EVALUATION OF SMALL PARAMETER

$$E = \frac{\lambda_{1}AU_{1}}{\sqrt{2f_{0}}} \qquad (A-1)$$

$$\int_{0}^{\infty} = \int \mathcal{H}_{k} R \, U_{5} \, d\mu = \frac{\mathcal{M}_{1} U_{1}}{RT_{0}} \int \mathcal{H}_{k} A \, d\mu \qquad (A-2)$$

$$= 2 \frac{\mathcal{M}_{1} U_{1}}{RT_{0}} \frac{\mathcal{M}^{3} VC}{\sqrt{R_{exo}}} \chi^{1/L}$$

$$\lambda_{k} = \lambda_{00} \frac{P_{0}}{P_{0}} \frac{\mathcal{M}_{k}}{T_{00}} \left(\frac{T_{1}}{T_{00}} \right) = \lambda_{00} \frac{\sqrt{R_{e}}}{M^{3} \sqrt{C}} \frac{\mathcal{M}_{k}}{\mathcal{M}_{00}} \left(\frac{T_{1}}{T_{00}} \right) \chi \qquad (A-3)$$

$$P_{b} = \frac{M^{3}\Gamma_{c}}{\Gamma_{Re}} \frac{1}{P_{T}} \frac{1}{\Gamma_{x}} \qquad (A-4)$$

For adiabatic flow, and Pr =/

$$\varepsilon = .22 \left(\frac{MVC}{VRey} \right)^2 . \qquad (A-6)$$

APPENDIX B

The expansion of the purely x-dependent quantities

$$f_{P_{SO}} = \beta_{o} \left[1 + \epsilon \beta_{i} + c \left(\epsilon^{2} \right)^{2} + \cdots \right] \quad (B-1)$$

$$\beta = \beta_{o} \left[1 + \epsilon \beta_{i} + c \left(\epsilon^{2} \right)^{2} + \cdots \right] \quad (B-2)$$
where
$$\beta = \frac{2}{d \ln 4i} \cdot \frac{h_{i}}{H_{s}} \quad \text{and} \quad \beta_{o} = \frac{r-4}{3}$$

$$U_{\varsigma} = U_{\varsigma o} \left[1 + \epsilon 4i + c \left(\epsilon^{2} \right)^{2} + \cdots \right] \quad (B-3)$$

$$f = \int_{o} \left[1 + \epsilon 5i + c \left(\epsilon^{2} \right)^{2} + \cdots \right] \quad (B-4)$$
where the coefficients , $\beta_{i}, \beta_{i}, 4i$, are constants

To first order in E.

$$f_{i} = U_{i} + 2 f_{i}$$
 from (21) (B-5)

$$f_{i} = \frac{3}{2} f_{i}$$
 from (33) (B-6)

$$U_{i} = O\left[f_{i} f_{i}\right]$$
 from $H_{f} = \text{constant}$ (B-7)

Therefore, to hypersonic order

$$f_{1} = 2 \phi_{1}$$
 (B-8)

$$\beta_1 = \frac{3}{2} \beta_1$$
 (B-9)

APPENDIX C

The evaluation of the arbitrary constants in the general solution requires two additional boundary conditions, since the general solution identically satisfies the conditions that $g_1 \notin f_1 \rightarrow c$ as $\gamma \rightarrow c$. On physical grounds, we can require that the displacement and momentum thicknesses be finite, since otherwise our entire approach, being based strictly on the boundary layer hypothesis, would be invalid. This requirement is also in keeping with our assumption that the effects of first order slip can be expressed as a perturbation on the no slip solution. In addition, this requirement guarantees that the only singularity in the vertical velocity, and hence pressure, will occur at the leading edge.

The displacement thickness, in hypersonic flow, can be written as

$$S^{+} = \frac{\sqrt{2}S}{S^{+}} + \frac{H_{S}}{h_{1}} \int (g - F_{3}) dy$$
 (63)

neglecting terms of $(\frac{1}{M_0})^L$ Expanding in \mathcal{E} yields $\int_{0}^{+} = \int_{0}^{+} \int_{0}^{+} + \mathcal{E} \delta_{1} \int_{0}^{+} (C-1)$

where

$$\delta_0^* = \left[\int_0^\infty (g_0 - f_0^*) dg_1 \right] \times \text{function of } x \quad (C-2)$$

$$S_{i}^{*} = \left[\int \left(\mathcal{G}_{i} - 2\mathcal{F}_{i} \mathcal{F}_{i} \right) dy \right] X \quad \text{function of } \mathbf{x} \quad (C-3)$$

The momentum thickness is

$$\Theta = \frac{12F}{R44} \int_{0}^{\infty} F_{y} \left(1 - F_{y}\right) dy \qquad (c-4)$$

which can be written similarly as

$$\Theta = \Theta_0 + \epsilon \Theta_1$$

where

$$\Theta_0 = \left[\int f_{O_1}(1 - f_{O_1}) dy \right] X$$
 function of x (C-5)

+
$$\left[\int f_{o} (1 - f_{o}) d_{y} \right] \times \text{function of x (C-7)}$$

The requirement of finite thickness at a station x thus requires

that the integrals

$$\int \left(\int \partial -f \partial f \partial f \partial g \right) dg (C-2), \quad \int \left(\int \partial f \partial f \partial f \partial f \right) dg (C-3)$$
all be bounded.

$$\int \left(f \partial f \partial g \right) dg (C-5), \quad \int f \partial f \partial f \partial f \partial f \partial f \partial g (C-6)$$

a

Since the results of the zeroth order solution are known to yield finite values for (C-2) and (C-5), we are then led to the condition that

 $\int_{and}^{\infty} (g_{i} - 2f_{0}f_{i}) dy$ and $\int_{and}^{\infty} f_{i}g_{i}(1-2f_{0}g_{i}) dy$

be finite.

Thus
$$\left| \int_{0}^{\infty} (g_{1} - 2f_{0}'f_{1}') dy \right| < \infty$$
 (C-8)

and
$$\left|\int_{-2}^{\infty}F_{i}(1-2f_{0})dy\right|<\infty$$
 (C-9)

Since the asymptotic expansion for f_0' is (from reference [19]) $f_{*}' = 1 \rightarrow \left[\alpha_{i} (q - F)^{-(2p+1)} + \frac{42}{2} (q - F)^{-1} \right] \exp \left[- \frac{(q - F)^{+}}{2} \right] + \frac{1}{(c-10)}$

we can write

$$\begin{aligned} & \int \mathcal{O}(g_{1} - 2f_{1}'(1 + (1, (\gamma - F)^{-(2F^{*})}) + \frac{\sqrt{2}}{2}(\gamma - F)^{-1} \int \mathcal{O}_{x} \rho(-\frac{(\gamma - F)^{2}}{2}) + \dots \int) d\gamma \\ & < \varpi \end{aligned}$$
(C-11)

ond

$$\int_{0}^{\infty} F_{r}'(1-\chi[x,(\gamma-F)^{-(\beta+1)} + \frac{1}{2}(\gamma-F)^{-1}] = \int_{0}^{1} \frac{F_{r}'(\gamma-F)}{2} + \dots \int_{0}^{1} \frac{1}{2} \frac{1}{$$

The nature of the general solutions for f_1^{-1} reveals that the exponential terms in the integral will yield only a finite contribution. Therefore, we may write

$$|\int_{0}^{\infty}(g_{1}-2f_{1})dy| < \infty$$
 (C-13)

and

This leads to the requirement that

$$\left|\int_{0}^{\infty}g_{i}dy\right|<\infty$$
 (C-15)

The general solution for g₁ is

As
$$\gamma \rightarrow \infty$$
, $f \rightarrow \gamma - F$, where F is a constant
 $f(\gamma \rightarrow 0) = Ae^{-\frac{(\gamma - F)^2}{2}} + Be^{-\frac{(\gamma - F)^2}{2}} \int e^{\frac{(\gamma - F)^2}{2}} d\gamma$ (C-17)

**



 $\mathcal{J}'_{(\gamma \to \gamma)} = \frac{B}{\gamma - F}$ + exponential terms (C-18)

The condition for finite $\int_{a}^{b} g_{i} dy$ then requires that B = 0. Thus

$$g_{i} = A e^{-5^{7} \frac{f_{i}}{f_{i}} dy}$$
 (C-19)

where A is determined by the temperature jump condition at $\gamma = 0$.

<u>APPENDIX C</u> - (continued)

The requirement that $\int f_i dy = f_i$ be finite as $\gamma \rightarrow \omega$ enables us to determine one arbitrary constant in the solution for f_1 . The general solution for f_1 is in the form

$$f_{i}' = f_{0}''(C + V_{i}(\eta)) + f_{0}''_{0} \int_{C}^{-5f_{0}} d\eta \left[D + V_{0}(\eta) \right]$$
where
$$(57)$$

۲

$$V_{i}(\gamma) = \underbrace{\underbrace{}}_{\delta} \int \frac{\left[\begin{array}{c} q_{i} + \frac{1}{2} \\ p_{i} \left(\begin{array}{c} q_{0} - f_{0} \end{array}\right) \right] \left[f_{0} \right] \left[\begin{array}{c} e^{-\int_{\delta} f_{0} \\ p_{i} \end{array}\right] \left[\begin{array}{c} f_{0} \end{array}\right] \left[\begin{array}{c} f_{0} \\ p_{i} \end{array}\right] \left[\begin{array}{c} f_{0} \end{array}\right] \left[\begin{array}{c} f$$

C is deter 7 by the behavior as $\gamma \Rightarrow \bullet$.

Knowledge of the asymptotic behavior of the zero order solution is essential in order to evaluate D.

Writing

$$V_2(y) = V_2 = \int_{y}^{\infty} \frac{\hat{y}_1 + \hat{z}_2 + \hat{z}_1 + (\hat{y}_2 - \hat{f}_2)^2}{e^{i\hat{x}_1 + y_2}} f_0^{\infty} dy$$
 (C-20)

since the integral V_{2} is finite.

For large values of η , the integral can be expanded asymptotically ^[19]

For the case where $\mathcal{E} \neq 0$, heat transfer case

$$V_2 C_{\gamma} = V_{\infty} - E_{\gamma}^{\infty} D e_{\gamma} p \left[-\frac{(\gamma - m)}{2} \right]^2 + \cdots d_{\gamma}$$
 (C-25)

For the case where E = 0, adiabatic wall.

$$V_{Z(\gamma)} = V_{00} - \int_{\gamma}^{\infty} a_{,} \frac{s_{,\varphi}(-G_{-F})^{2}}{(\gamma-F)^{2}F^{+\gamma}} d\eta + \cdots (C^{-26})$$

Since the expansions for the integrals are only of exponential order, and contribute finite quantities,

$$V_2(\gamma) = V_{00} - E \exp \left(\int -\frac{(\beta - E)^2}{2} \right)^2 + (c-27)$$

for y - 100

or

$$V_2(\gamma) = V_{00} - 2d$$
, $e_{\mu\rho}\left(-\frac{(5-F)^2}{2}\right) + -$ (C-28)

Similarly for V_1 , the expansion for large γ can be written

$$V_{i} \sim \int \frac{1}{y-F} \frac{dy}{dy} + \cdots \qquad (0.29)$$

or
$$V_{1} \sim ln(\gamma - F) + \cdots$$
 (C-30)
 $\gamma \rightarrow \omega$

Considering the leading terms in the expansion for f_{ij}

$$\int_{0}^{\infty} f_{i} dy = \int_{0}^{\infty} e^{-\frac{(g-F)^{2}}{2}} (1 + o(l_{\eta}(g-F))) dy + \int_{0}^{\infty} \frac{1}{\eta-F} (0 + V_{200} - q, e_{x,p} \cdot (g-F))^{2} dy \quad (C-31)$$

The requirement that $\int F_i dy$ be bounded is satisfied only be setting the arbitrary constant D equal to $-V_{2+0}$.

or
$$D = -\frac{1}{2} \int_{0}^{\infty} \frac{1}{c^{-\frac{1}{2}}} \frac{1}{c^{-\frac{1}{2}}} \frac{1}{c^{-\frac{1}{2}}} \int_{0}^{\infty} \frac{1}{c^{-\frac{1}{2}}} \frac{1}{c^{-\frac{1}{2}}} \int_{0}^{\infty} \frac{1}{c^{-\frac{1}{2}}}$$

		ductassified	UNCLASSIFIED	 UNCLASSIFIED
University of California, Berkeley, Calif. STRONG INTERACTION WITH SLIP BOUN- DARY CONDITIONS by J. Aroesty, Septem-	Task 70169) ARL 64 Unclassified Report A solution to the problem of strong inter- action between the shock wave and the boundary layer has been obtained for the case whener velocity slip and temperature	at the wall. It is shown that the addition of slip boundary conditions yields a correc- tion of order B/X to the no slip solution. Estimates are made of the effect of slip on	induced pressures and skin friction for the case of the adiabatic wall. In addition, it is shown that the inclusion of slip boundary conditions does not change the energy trans- fer to the wall from the no slip values.	
UNCLASSIFIED		UNC LA SSIFIED	UNCLASSIFIED	UNCLASSIFIED
University of California, Burkeley, Calif. STRONG INTERACTION WITH SLIP BOUN- DARY CONDITIONS by J. Aroesty, Septem-	her 1961. 35 p. incl illus. (Project 7064; Task 70169) ARL 64 Unclassified Report A solution to the problem of strong inter- action between the shock wave and the boundary layer has been obtained for the case where velocity slip and temperature	jump boundary conditions are consistent at the wall. It is shown that the addition of slip boundary conditions yields a correc- tion of order B/X_1° to the no slip solution. Estimates are made of the effect of slip on	induced pressures and skin friction for the case of the adiabutic wall. In addition, it is shown that the inclusion of slip boundary conditions does not change the energy trans- for to the wall from the nc slip values.	