

UNCLASSIFIED

AD NUMBER	
AD387058	
CLASSIFICATION CHANGES	
TO:	unclassified
FROM:	confidential
LIMITATION CHANGES	
TO:	Approved for public release, distribution unlimited
FROM:	Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; JAN 1968. Other requests shall be referred to Air Force Rocket Propulsion Lab., Edwards AFB, CA.
AUTHORITY	
31 Jan 1980, DoDD 5200.10; AFRPL ltr, 5 Feb 1986	

THIS PAGE IS UNCLASSIFIED

AD 387058

AUTHORITY:

AFRPL

1cc 5 Feb 86



THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

SECURITY

MARKING

The classified or limited status of this report applies to each page, unless otherwise marked.

Separate page printouts MUST be marked accordingly.

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 AND 794. THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

CONFIDENTIAL

AFRPL-TR-68-2
Part 2

19

(TITLE UNCLASSIFIED)
THROTTLING AND SCALING STUDY
FOR
ADVANCED STORABLE ENGINE

Report 68-C-0008-F

Part 2 of Two Parts
APPENDIX I
ARES SIZE SCALING DATA

S. R. Andrus
H. L. Bishop
J. A. Gibb
A. W. Nelson

AEROJET-GENERAL CORPORATION
ADVANCED STORABLE ENGINE PROGRAM DIVISION
LIQUID ROCKET OPERATIONS
SACRAMENTO, CALIFORNIA

FINAL REPORT AFRPL-TR-68-2, PART 2
January 1968

SPECIAL HANDLING REQUIRED

In addition to security requirements which must be met, this document is subject to special export controls, and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFRPL (RPPR/STINFO) Edwards, California 93523.

AIR FORCE ROCKET PROPULSION LABORATORY
RESEARCH AND TECHNOLOGY DIVISION
AIR FORCE SYSTEMS COMMAND
UNITED STATES AIR FORCE
EDWARDS, CALIFORNIA

GROUP 4 DOWNGRADED AT 3 YEAR INTERVALS; DECLASSIFIED AFTER 12 YEARS
THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 AND 794. ITS TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

1173

AEROJET-GENERAL CORPORATION
A SUBSIDIARY OF THE GENERAL TIRE & RUBBER COMPANY

CONFIDENTIAL

CONFIDENTIAL

LEGAL NOTICE

"When U.S. Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto."

CONFIDENTIAL

(This Page is Unclassified)

CONFIDENTIAL

(TITLE UNCLASSIFIED)
THROTTLING AND SCALING STUDY
FOR
ADVANCED STORABLE ENGINE

Report 68-C-0008-F

Part 2 of Two Parts
APPENDIX I
ARES SIZE SCALING DATA

G. R. Andrus
H. L. Bishop
J. A. Gibb
A. W. Nelson

SPECIAL HANDLING REQUIRED

In addition to security requirements which must be met, this document is subject to special export controls, and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFRPL (RPPR/STINFO) Edwards, California 93523.

GROUP 4 DOWNGRADED AT 3 YEAR INTERVALS; DECLASSIFIED AFTER 12 YEARS
" THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 AND 794. ITS TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW "

3224T

AEROJET-GENERAL CORPORATION
A SUBSIDIARY OF THE GENERAL TIRE & RUBBER COMPANY

CONFIDENTIAL

UNCLASSIFIED

Report 68-C-0008-F, Part 2, Appendix I

TABLE OF CONTENTS

	<u>Page</u>
I. Introduction	I-1
II. ARES Engine Description	II-1
III. Scaling Data	III-1

UNCLASSIFIED

Report 68-C-0008-F, Part 2, Appendix I

FIGURE LIST

	<u>Figure</u>
ARES Engine 100K, Throtttable	II-1-A
ARES Scaling Design Point Data	III-1-A
Nozzle Area Ratio Effect on Delivered Performance	III-2-A
Throttling Performance of Specific Engines	III-3-A
ARES Dry Weight vs Rated Vacuum Thrust	III-4-A
ARES Wet Weight vs Rated Vacuum Thrust	III-5-A
ARES Envelope Length and Outside Diameter vs Vacuum Thrust	III-6-A
RAO and 80% Bell Nozzle Dimension Ratios	III-7-A
ARES Gimbal Moment vs Vacuum Thrust	III-8-A
ARES Development Cost	III-9-A
ARES Production Cost	III-10-A

UNCLASSIFIED

UNCLASSIFIED

Report 68-C-0008-F, Part 2, Appendix I

I.

INTRODUCTION

(U) The Advanced Rocket Engine Storable (ARES), described in this appendix, is a throttlable-restartable advanced rocket engine using storable N_2O_4 /AeroZINE 50 propellants. The engine features high performance and simplicity in design. ARES is presently in the process of advanced development testing at Aerojet-General Corporation under contract to the USAF Rocket Propulsion Laboratory, Edwards AFB, California (Contract AF 04(611)-10830). Testing is at a fixed thrust of 100K.

(U) Parametric performance, size, weight, and cost scaling data for throttlable and restartable ARES liquid-propellant rocket engines over a range of engine sizes with rated thrust values from 25,000 to 500,000 lbf are presented in this report.

UNCLASSIFIED

UNCLASSIFIED

Report 68-C-0008-F, Part 2, Appendix I

II.

ARES ENGINE DESCRIPTION

(U) The ARES engine shown in Figure II-1-A consists of a turbopump assembly, a thrust chamber assembly, fuel and oxidizer suction valves, and boost pumps. The turbopump assembly includes the main pumps, the turbine, the primary combustor, and two fuel control valves, and forms the central structure of the engine. The turbopump is mounted on top of the thrust chamber, with thrust being transmitted through the turbopump housing to the gimbal and airframe. The entire engine is gimballed from a gimbal assembly which is attached to the thrust take-out pad of the engine.

(U) The turbine, oxidizer pump, and fuel pump are on a single shaft which is in line with the engine thrust axis and is supported in the housing by propellant-lubricated bearings. The single-stage turbine is on the lower end of the shaft and exhausts directly into the thrust chamber. The single-stage oxidizer pump is on the center of the shaft, with the two-stage fuel pump on the top end. Fuel and oxidizer enter the engine through vertical inlets on each side of the turbopump. In each suction inlet, a hydraulically driven boost pump is mounted with its shaft horizontal. A suction pre valve is located upstream of each boost pump.

(U) The primary combustor utilizes a radial inflow HIPERTHIN* injector consisting of a stack of thin platelet washers, with fuel and oxidizer fed between and metered by alternate washers.


(U) The secondary combustor, or thrust chamber, is transpiration cooled to the throat and downstream of the point where static pressure is 30 psia; from that point on the extension nozzle is cooled by the coolant-carryover boundary layer. The transpiration-cooled thrust chamber utilizes platelet washers for metering the required amounts of oxidizer into the thrust chamber wall. The nozzle extension is similar in design to the nozzle on the Apollo service module engine and the Transtage engine.

*Aerojet design denoting High Performance Throtttable Injector.

UNCLASSIFIED

CONFIDENTIAL

Report 68-C-0008-F, Appendix I



ARES Engine 100K, Throttlable (u)

Figure II-1-A

CONFIDENTIAL

III.

SCALING DATA

(C) Design scaling data have been determined for throttlable, restartable ARES engines at three rated thrust levels of 25K, 100K, and 500K, Figure III-1-A shows the predicted performance, weights, and dimensions for each of the three engines incorporating thrust chambers with 50:1 area ratio 80% bell contour and 150:1 area ratio RAO contour nozzles. The engine specific impulse values are based on the Contract AF 04(611)-10830 target performance of 91.7% of theoretical. Detailed thermodynamic analysis has shown that up to 94% specific impulse efficiency can be reasonably achieved in a development program. Therefore, the specific impulse data presented are conservative.

(U) Predicted engine performance (vacuum and sea level) versus nozzle area ratio is shown in Figure III-2-A for the three design thrust levels. Predicted engine throttling performance for the three engines over a 10:1 throttle range is shown in Figure III-3-A. The reduction in specific impulse as the engine is throttled results from: (1) increased combustion loss because of the lower liquid injection velocity and lower fuel vaporization rate, (2) increased friction because of greatly reduced flow over the same area, and (3) increased kinetic losses because of gas disassociation. Engine dry and wet weights versus rated vacuum thrust are shown by Figures III-4-A and III-5-A, respectively. It can be noted that the engines with 50:1 area ratio nozzles are slightly heavier than those with 150:1 area ratio nozzles. This results from the fact that as the area ratio is increased from 50:1, engine weight increases but thrust increases at a faster rate. Engine length and maximum diameter values versus thrust are shown by Figure III-6-A. The dimension ratios for RAO and 80% bell contour thrust chamber nozzles are presented in Figure III-7-A. Engine gimbal moment of inertia versus rated thrust is shown in Figure III-8-A. Estimated cost (1967 dollars) to develop man-rated, throttlable, restartable ARES engines is shown in Figure III-9-A. These costs are based on a four-year program involving three years through PFRT and one

CONFIDENTIAL

Report 68-C-0008-F, Part 2, Appendix I

III, Scaling Data

year for qualification. Propellant costs are shown separately. Fee is not included in the estimate. Estimated unit production cost (1967 dollars) for throttlable, restartable ARES engines is shown in Figure III-10-A. Costs shown do not include propellants or fee.

Page III-2

CONFIDENTIAL

(This page is Unclassified)

	25K			100K			500K		
	$\epsilon = 50$ 80% Bell	$\epsilon = 150$ RAO		$\epsilon = 50$ 80% Bell	$\epsilon = 150$ RAO		$\epsilon = 50$ 80% Bell	$\epsilon = 150$ RAO	
F, Vacuum Thrust, lbf	24,200	25,000		111,065	115,250		582,200	604,100	
I _s vac, sec	314.5	324.6		316.5	328.4		316.5	328.4	
I _s efficiency, %	91.1	90.3		91.7	91.2		91.7	91.2	
P _c , psia	2,800	2,800		2,800	2,800		2,800	2,800	
MR _{eng}	2.465	2.465		2.427	2.427		2.427	2.427	
L*	24.7	24.7		26.7	26.7		30.6	30.6	
N _T (speed), rpm	64,000	64,000		30,000	30,000		13,150	13,150	
NPSH oxid/fuel, ft.*	20	20		20	20		20	20	
Weight Dry, lb	207	209		869	883		6,110	6,130	
Weight Wet, lb	215	217		933	946		6,811	6,828	
L, Overall, in.	43.232	59.532		84.334	119.334		179.74	260.14	
L, Overall, in.	18.2	30.88		38.8	66.08		88.9	151.0	
d, in.	2.9	2.9		5.8	5.8		13.2	13.2	
L _a , in.	14.0	14.0		28.0	28.0		64.0	64.0	
L _b , in.	22.4	22.4		44.8	44.8		102.0	102.0	
Y ₁ , in. (Fuel)	5.1	5.1		10.25	10.25		23.4	23.4	
Y ₂ , in. (Oxidizer)	5.1	5.1		11.3	11.3		25.9	25.9	
X ₁ , in. (Fuel)	.65	.65		1.25	1.25		2.8	2.8	
X ₂ , in. (Oxidizer)	.65	.65		0.2	0.2		0.4	0.4	
D _t , nozzle throat, in.	2.43	2.43		5.214	5.214		11.9	11.9	
D _e , nozzle exit, in. (I.D.)	17.2	29.78		36.8	63.88		84.5	146.3	
L _n , in.	21.9	38.2		47.0	82.0		107.6	188.0	
Gimbal Moment of Inertia, Wet	10.0	13.9		176	250		4,531	6,563	

*With Boost Pumps

ARES Scaling Design Point Data (u)





Figure III-1-A

CONFIDENTIAL

Report 68-C-0008-F, Appendix I




Nozzle Area Ratio Effect on Delivered Performance (u)

Figure III-2-A

CONFIDENTIAL

CONFIDENTIAL

Report 68-C-0008-F, Appendix I




Throttling Performance of Specific Engines (u)

Figure III-3-A

CONFIDENTIAL

CONFIDENTIAL

Report 68-C-0008-F, Appendix I



ARES Dry Weight vs Rated Vacuum Thrust


Figure III-4-A

CONFIDENTIAL

(This page is Unclassified)

UNCLASSIFIED

Report 68-C-0008-F, Appendix I




ARES Wet Weight vs Rated Vacuum Thrust

Figure III-5-A

UNCLASSIFIED

UNCLASSIFIED

Report 68-C-0008-F, Appendix I




ARES Envelope Length and Outside Diameter vs Vacuum Thrust

Figure III-6-A

UNCLASSIFIED

UNCLASSIFIED

Report 68-C-0008-F, Appendix I




RAO and 80% Bell Nozzle Dimension Ratios

Figure III-7-A

UNCLASSIFIED

UNCLASSIFIED

Report 68-C-0008-F, Appendix I




ARES Gimbal Moment vs Vacuum Thrust

Figure III-8-A

UNCLASSIFIED

UNCLASSIFIED

Report 68-C-0008-F, Appendix I



ARES Development Cost


Figure III-9-A

UNCLASSIFIED

UNCLASSIFIED

Report 68-C-0008-F, Appendix I

1967 DOLLARS
Includes Acceptance Testing
and Support Through Launch
Man-Rated
Restartable
Throttleable
Propellant Costs Not Included



ARES Production Cost

Figure III-10-A

UNCLASSIFIED