

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

CATALOGED BY UDL

AS AD No. 451688

Technical Note N-651

A SIMPLE METHOD FOR CALCULATION OF GAMMA-RAY
SHIELDING PROPERTIES OF SHELTER ENTRANCEWAYS

BY

Charles M. Huddleston

26 October 1964

4 5 1 6 8 8

U. S. NAVAL CIVIL ENGINEERING LABORATORY
Port Hueneme, California

A SIMPLE METHOD FOR CALCULATION OF GAMMA-RAY
SHIELDING PROPERTIES OF SHELTER ENTRANCEWAYS
Y-F008-08-05-201 (DASA 11.026)

Type C

by

Charles M. Huddleston

ABSTRACT

An empirical equation is described for calculating the attenuation factor for gamma radiation within a ducted entranceway into a shelter. Some sample problems are worked, and a discussion is given of the accuracy of the formula.

This research was funded by the Defense Atomic Support Agency through the Bureau of Yards and Docks under DASA Subtask No. 11.026.

Qualified requesters may obtain copies of this note from DDC.

INTRODUCTION

A difficult calculational problem has been that of computing attenuation factors for gamma radiation within a two-legged duct in concrete.^{1,2,3} It has been found that the following formula can be used to obtain approximate answers

$$\frac{D}{D_0} = 0.25 \frac{\left(\frac{H}{W}\right)^{0.907} W^{2.864}}{L_1^{2.534} L_2^{2.667} E_0^{0.710}}$$

where

D_0 = dose rate in mr/hr outside the shelter

D = dose rate in mr/hr inside the shelter

H = height of entranceway in feet

W = width of entranceway in feet

L_1 = length in feet of first leg of duct

L_2 = length in feet of second leg of duct

E_0 = average energy of gamma radiation in Mev

This method of calculation can be used for fallout radiation. It does not consider penetration of radiation through the walls or ceiling of a shelter, but is concerned entirely with that radiation which streams through the shelter entranceway. The formula is valid when the following inequalities are true

$$0.662 \leq E_0 \leq 3.000 \text{ Mev}$$

$$1.0 \leq H \leq 6.0 \text{ feet}$$

$$1.0 \leq W \leq 6.0 \text{ feet}$$

$$2 \leq L_1 \leq 36 \text{ feet}$$

$$1 \leq H/W \leq 2$$

$$L_1/H \leq 6$$

$$L_2/H \leq 6$$

$$L_1/W \leq 2$$

$$L_2/W \leq 2$$

The formula has a safety factor already incorporated into it, so that one can be 95 percent certain that the actual attenuation factor, D/D_0 , is at least as small as the attenuation factor calculated by the formula.

USE OF THE FORMULA

The basic formula with which this note is concerned can be written in a slightly simplified version as follows

$$\frac{D}{D_0} = 0.25 \frac{\left(\frac{H}{W}\right)^{0.907}}{L_1^{2.534}} \frac{W^{2.864}}{L_2^{2.567}}$$

In this case, the energy term has been omitted. The reason for this simplification is that the mean effective energy of fallout radiation is approximately 1 Mev. Since unity raised to any power is still unity, the energy factor cannot appreciably change the final answer as long as only fallout radiation is considered. (If the higher energies of gamma-ray initial radiation are to be considered, the more complete equation shown in the Introduction must be used.)

Figure 1 shows an example of a two-legged duct leading into a shelter. The dimensions of the duct, as they are normally measured, are shown.

Consider a sample problem:

Calculate the dose rate attenuation provided by a shelter entranceway if the cross section of the duct is 6 feet high by 4 feet wide, the length of the first leg is 12 feet, and the length of the second leg is 14 feet. Assume the effective gamma-ray energy is 1 Mev.

Substitution of the values given above into the simpler version of the empirical formula gives

$$\frac{D}{D_0} = 0.25 \frac{\left(\frac{6}{4}\right)^{0.907}}{12^{2.534}} \frac{4^{2.864}}{14^{2.667}}$$

With a log-log sliderule, the above equation can be solved to give

$$\frac{D}{D_0} = 0.25 \frac{(1.445) (53)}{(545) (1130)}$$

$$\frac{D}{D_0} = 3.11 \times 10^{-5}$$

Another way of solving the equation is to use logarithms. The solution is then obtained as follows

$$\log (0.25) = 9.39794 - 10$$

$$\log (1.5^{0.907}) = 0.907 \log 1.5 = 0.907 (0.17609) = 0.15971$$

$$\log (4^{2.864}) = 2.864 \log 4 = 2.864 (0.60206) = 1.72430$$

$$\log (\text{numerator}) = 11.28195 - 10$$

$$\log (12^{2.534}) = 2.534 \log 12 = 2.534 (1.07918) = 2.73464$$

$$\log (14^{2.667}) = 2.667 \log 14 = 2.667 (1.14613) = 3.05673$$

$$\log (\text{denominator}) = 5.79137$$

$$\log (D/D_0) = (11.28195 - 10) - 5.79137$$

$$\log (D/D_0) = 5.49058 - 10$$

$$D/D_0 = 3.0945 \times 10^{-5}$$

Still another way to solve the given problem is to use the graphs given in Figures 2, 3, 4, and 5. The same problem is worked as follows:

(1) Note that $H/W = 1.5$. From Figure 2, read $(H/W)^{0.907} = 1.45$. This is the eccentricity factor corresponding to $H/W = 1.5$.

(2) From Figure 2, read the width factor corresponding to $W = 4$ feet. This value is 50.

(3) From Figure 3, read the first leg factor corresponding to $L_1 = 12$ feet. The factor is 500.

(4) From Figure 4, read the second leg factor corresponding to $L_2 = 14$ feet. One obtains 1200.

(5) Multiply the constant factor, 0.25, times the eccentricity factor and the width factor. Then divide by the product of the two leg factors. The answer is found to be

$$\frac{D}{D_o} = 0.25 \frac{1.45}{500} \times \frac{50}{1200}$$

$$\frac{D}{D_o} = 3.02 \times 10^{-5}$$

This answer is accurate enough for shielding calculations.

NOMOGRAM

A nomogram has been developed to solve two-legged duct problems, as shown in Figure 6. The sample problem can be solved nomographically.

The data given for the duct dimensions were

$$\begin{aligned} H &= 6 \text{ feet} \\ W &= 4 \text{ feet} \\ L_1 &= 12 \text{ feet} \\ L_2 &= 14 \text{ feet} \end{aligned}$$

The value of $H/W = 6/4 = 1.5$ is needed for the nomogram calculation. The solution is obtained as follows:

Draw a straight line from 14 on the L_1 scale to 12 on the L_2 scale. Note where this line intersects the vertical line between the L_1 scale and the L_2 scale.

Next, draw a straight line from 1.5 on the H/W scale to 4 on the W scale. Note where this line intersects the vertical line between the H/W scale and the L_2 scale.

Now, draw a straight line between the two intersection points determined above, and note where this line crosses the D/D_o scale.

Using the nomogram of Figure 6, one obtains for the answer to the sample problem

$$\frac{D}{D_o} = 3.5 \times 10^{-5}$$

Although this method is less accurate than the other methods for solution of the two-legged duct problem, the nomographic technique is still sufficiently accurate for most practical purposes.

SAMPLE PROBLEMS

Twelve sample problems are now given to allow an opportunity for practice with any or all of the three calculational techniques described in the previous section. Duct dimensions in feet are taken to be the following values:

L_1	L_2	H	W
11.	18.	5.2	4.8
16.	17.	4.1	3.0
20.	20.	3.7	2.9
19.	8.	4.2	2.2
29.	25.	5.1	2.6
25.	15.	5.2	4.0
14.	12.	2.9	2.9
30.	16.	5.7	4.1
24.	14.	5.1	3.0
18.	24.	4.5	3.6
8.	14.	3.3	3.0
17.	21.	5.8	5.0

The problems with their answers are shown in Table 1. In case the E-type notation is not familiar, it is explained by the following example:

$$0.4218\text{E-}04 = 0.4218 \times 10^{-4}$$

CONCLUSION

A simple empirical formula has been described for calculating the gamma-ray dose attenuation factor of fallout radiation within a two-legged duct with one right-angle bend. The formula can be used in the field as a guide in the design of entranceways, escape hatches, or air ducts leading into shelters.

ACKNOWLEDGEMENT

The author wishes to express his appreciation to Professor W. C. Ingold of Ventura College, Ventura, California, for his extensive work on the development of the empirical formula. Mr. Y. T. Song and Mr. J. S. Grant of the U. S. Naval Civil Engineering Laboratory were of great assistance in the development of the program.

REFERENCES

1. U. S. Naval Civil Engineering Laboratory. Technical Report R-264: Computer Calculation of Dose Rates in Two-Legged Ducts Using the Albedo Concept, by J. M. Chapman, Port Hueneme, California, October 1963.
2. U. S. Naval Civil Engineering Laboratory. Technical Report R-289: Gamma-Ray Streaming Through Ducts, by C. M. Huddleston and W. L. Wilcoxson, Port Hueneme, California, February 1964.
3. U. S. Naval Civil Engineering Laboratory. Technical Report R-349: An Empirical Formula for the Calculation of Gamma-Ray Dose Attenuation in Concrete Ducts, by W. C. Ingold and C. M. Huddleston, Port Hueneme, California, to be published.

Table 1. Attenuation Factors for Sample Ducts

L_1	L_2	H	W	Attenuation
11.	18.	5.2	4.8	.2476E-04
16.	17.	4.1	3.0	.3586E-05
20.	20.	3.7	2.9	.1126E-05
19.	8.	4.2	2.2	.9648E-05
29.	25.	5.1	2.6	.2616E-06
25.	15.	5.2	4.0	.3520E-05
14.	12.	2.9	2.9	.8705E-05
30.	16.	5.7	4.1	.2129E-05
24.	14.	5.1	3.0	.2625E-05
18.	24.	4.5	3.6	.1648E-05
8.	14.	3.3	3.0	.2862E-04
17.	21.	5.8	5.0	.6515E-05




Figure 1. Schematic diagram of 2-legged duct.




Figure 2. Graph showing $(H/W)^{0.907}$ versus H/W .




Figure 3. Graph showing $W^{2.864}$ versus W .




Figure 4. Graph showing $L_1^{2.534}$ versus L_1 .




Figure 5. Graph showing $L_2^{2.667}$ versus L_2 .




Figure 6. Nomogram for calculating two-legged duct problems.

Unclassified

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) U. S. Naval Civil Engineering Laboratory Port Hueneme, California		2a. REPORT SECURITY CLASSIFICATION Unclassified	
		2b. GROUP	
3. REPORT TITLE A SIMPLE METHOD FOR CALCULATION OF GAMMA-RAY SHIELDING PROPERTIES OF SHELTER ENTRANCEWAYS			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Interim report January 1964 through August 1964			
5. AUTHOR(S) (Last name, first name, initial) Huddleston, Charles M.			
6. REPORT DATE 26 October 1964		7a. TOTAL NO. OF PAGES 14	7b. NO. OF REFS 3
8a. CONTRACT OR GRANT NO. DASA 11.026		9a. ORIGINATOR'S REPORT NUMBER(S) TN-651	
b. PROJECT NO. Y-F008-08-05-201			
c.		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.			
10. AVAILABILITY/LIMITATION NOTICES Qualified requesters may obtain copies of this note from DDC.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY Bureau of Yards and Docks	

13. ABSTRACT An empirical equation is described for calculating the attenuation factor for gamma radiation within a ducted entranceway into a shelter. Some sample problems are worked, and a discussion is given of the accuracy of the formula. This research was funded by the Defense Atomic Support Agency through the Bureau of Yards and Docks under DASA Subtask No. 11.026.
--

11-173

0101-207-6400

Unclassified

Security Classification

Unclassified

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
EMPIRICAL EQUATIONS	8					
FORMULAS	8					
COMPUTATION	4					
ATTENUATION	9					
RADIATION	9					
GAMMA RAYS	9					
DUCTS	5					
SHELTERS	5					

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, &, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.

Unclassified

Security Classification

UNCLASSIFIED

UNCLASSIFIED