UNCLASSIFIED

AD NUMBER

AD488428

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited. Document partially illegible.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; 19 JUL 1966. Other requests shall be referred to Naval Ordnance Laboratory, Explosives Research Department, Explosion Dynamics Division, White Oak, MD. Document partially illegible. This document contains export-controlled technical data.

AUTHORITY

usnol ltr, 15 nov 1971

THIS PAGE IS UNCLASSIFIED



DEVELOPMENT OF THE MK 97 MOD 0 DELAY DETONATOR

19 JULY 1966

188428

NOLTR 66-134

UNITED STATES NAVAL ORDNANCE LABORATORY, WHITE OAK, MARYLAND

This document is subject to special export controls and each transmittal to foreign governments may be made only with prior approval of NOL.

DEVELOPMENT OF THE MK 97 MOD 0 DELAY DETONATOR

By

Vincent J. Menichelli

ABSTRACT: A nominal 0.3 second, flash-initiated, delay detonator has been developed for the AN-M173Al Fuze. A limited number of detonators were subjected to standard Navy rough handling and surveillance tests. These tests were successfully met. An independent evaluation of the detonator confirmed the soundness of the detonator. The detonator is completely documented with drawings and specifications.

> EXPLOSION DYNAMICS DIVISION EXPLOSIONS RESEARCH DEPARTMENT U. S. NAVAL ORDNANCE LABORATORY

> > i

12

19 July 1966

DEVELOPMENT OF THE MK 97 MOD 0 DELAY DETONATOR

This report discusses the design and development of a flash-initiated, delay detonator. The design of the detonator, the test program, and the test data are reported. The work was supported by "Fire Eye Fuzing", WepTask RM37-73066/W110-5H-03. The report will be of interest to fuze design engineers, explosive component designers, and explosive component users.

> J. A. DARE Captain, USN Commander

mar

C. **U**. ARONSON By direction

であった。

CONTENTS

Page

									Þ																			
INTRODUCTION	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1
DETONATOR DES	510	SN	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1
TEST PROGRAM	AN	D	RE	est	JLI	rs	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	2
DISCUSSION .	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	5
CONCLUSIONS	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•		6
REFERENCES .								•				•							•									6

ILLUSTRATIONS

Figure	Title	Page
1	Multi-Position Fuze AN-M173A1	7
2	Explosively Modified AN-M173Al Fuze	8
3	Detonator, Delay Mk 97 Mod 0	9
4	Functioning, Delay, and Output Test Fixture for the Mk 97 Mod 0 Delay Detonator	10
5	Engineering Test Schedule for the Mk 97 Mod 0 Delay Detonator	11

iii

* 義務 **

BLANK PAGE

INTRODUCTION

1. The multi-position fuze AN-M173Al shown in Figure 1, is stockpiled by the Navy for use in fire bomb weapons. A number of safety and reliability deficiencies exist in this fuze which has necessitated a program to develop a new fuze and in the interim to modify the existing fuze with a "quick-fix" program. Numbered amongst its deficiencies are (a) an in-line explosive train, (b) easy arming by careless manipulation, (c) a detonator (the M31) which contains lead azide loaded into a copper alloy cup^4 , and (d) a primer (the M26) which was found to deteriorate on long term storage.

2. A program (Fire-Eye) to replace the AN-M173Al Fuze with one which would meet current Navy safety and reliability criteria was established. In the interim, a quick-fix program (Fire-Eye Mother Hubbard) to modify and rework existing AN-M173Al Fuzes began. The quick-fix "Fire-Eye Mother Hubbard" program would result in a modified AN-M173Al Fuze. This modified fuze would have greater safety and reliability than the AN-M173Al Fuze. The program involved making mechanical and explosive modifications to the AN-M173Al Fuze. The explosive modifications consisted of replacing the M26 Primer with a more reliable primer (Mk 156 Mod 0 Primer) having good long term storage characteristics and replacing the M31 Detonator (instantaneous) with one which contains a short delay time (0.3 second). The delay time was required to allow the fire bomb fuel to disperse over a large area before fuel ignition occurred. This report covers the design and development of the delay detonator used to replace the M31 Detonator in the AN-M173Al Fuze.

3. The requirements for the replacement detonator were that:

- (a) It meet standard Navy rough handling and surveillance tests normally conducted on such devices.
- (b) It be dimensioned so as to be retrofitted into existing AN-M173Al Fuze hardware.
- (c) The sensitivity and output to be equal to or greater than that of the M31 Detonator.

Mr. Mr. -

1

(d) The delay time to be 0.3 ± 0.1 second.

The explosive modifications to the AN-M173Al Fuze are shown in Figure 2.

DETONATOR DESIGN

4. The external configuration of the detonator was dictated by the space available in the AN-M173Al Fuze. Since this detonator was to be a direct replacement for the M31 Detonator, it was designed with

* References are on Page 6.

a threaded body so that it could be screwed into the existing fuze body. The detonator metallic parts (body, baffles, and sealing discs) were made of aluminum. Aluminum was chosen for its compatibility with lead azide, which was used as an explosive in the detonator. A-LA igniter composition (Mil-P-22264), an iron oxide/zirconium metal mixture, was chosen as the flash charge. The delay powder was manganese delay composition (Mil-M-21383). Slotted baffles were placed on both sides of the delay column to keep the delay column under compression during burning. This results in more reliable and uniform delay times $\frac{3}{7}$. The output or detonating explosives consist of lead azide and RDX. Aluminum discs were crimped at both ends of the delay detonator and an epoxy resin was applied to the crimped area to seal the component. The loaded detonator, designated Mk 97 Mod 0, is illustrated in Figure 3. The delay composition is loaded into the detonator first to eliminate the possibility of contaminating the walls of the detonator body with the more sensitive igniter composition and detonating explosives. This helps prevent instantaneous or short delay times. The adequacy of the output charge was based on its ability to initiate, high order, the tetryl booster in the modified AN-M173A1 Fuze.

TEST PROGRAM AND RESULTS

After the design of the detonator parts was completed and checked 5. for dimensional compatibility with the fuze, a small number of detonators were loaded and tested for sensitivity, delay time, and output. The criterion for satisfactory sensitivity was that the detonator be initiated by the Mk 156 Mod 0 Primer (the primer to be used in the modified AN-M173Al Fuze as a replacement for the M26 Primer) over a one-inch air gap. The delay column length based on the measured delay times was adjusted to yield the desired time of 0.3 *0.1 second. The base charge or output was established by firing the detonator against the tetryl booster in the modified AN-M173Al Fuze and adjusting the weight until high order detonations were consistently obtained. Once the output of the detonator was satisfactory, the dent it produced in a steel witnes; block was used as the criterion for proper output. A test fixture to obtain sensitivity, delay time, and output was designed and is shown in Figure 4.

6. At the completion of the above tests, the detonator design appeared reasonable so a lot of 184 detonators was fabricated for engineering design tests. The test schedule is given in Figure 5. After the detonators were conditioned, they were functioned in the test fixture (Figure 4) which is used in conjunction with the Mk 136 test set (ball drop machine). A two ounce ball was dropped from a height of six inches onto the firing pin to initiate the Mk 156 Mod 0 Primer.

7. Functioning, delay time, and output testing over the temperature range -90° to $165^{\circ}F$ showed no significant shifts in delay time or output. The results of this testing are given on the following page:

		Delay Time (seconds)	
	165°F	RT	-90°F
N	25	25	25
x	0.337	0.348	0.322
S	0.024	0.022	0.055
	01	itput - Depth of Den (mils)	t
N	7	5	2
Ŷ	22.0	23.1	23.0
s	1.75	1.2	-

N = Sample size

 \overline{X} = Mean delay time

S = Standard deviation $\Psi = Mean Depth of Dent$ 8. X-ray examination of the detonators after transportation and aircraft vibration showed no apparent changes in the internal or external structures. When functioned at room temperature in the test fixture, the following results were obtained:

	Delay T	ime (seconds)
	Aircraft Vibration	Transportation Vibration
N	15	15
x	0.332	0.335
s	0.024	0.015

9. Jolt and jumble testing had no significant effect upon the detonators and subsequent functioning in the test fixture gave the following results:

	Delay Time	(seconds)
	Jolt	Jumble
N	15	15
x	0.342	0.340
s	0.011	0.014

3

and the state of

10. The 40 foot drop test was modified to guide the detonators (in a fixture) to impact in a given position. The guided drop test was conducted in three positions, vertical, 45°, and horizontal. Some deformation of the detonators was noted after this test, but none initiated and they were capable of being fired afterwards in the test fixture. The results were as follows:

	Delay Time (seconds)								
	Vertical	45°	Horizontal						
N	3	3	3						
x	0.337	0.332	0.376						

11. A sequential test in which the detonators were subjected to vibration, jolt, jumble, and 40 foot guided drop gave the following results:

$\left[\right]$	D (elay Time seconds)	
N	-	10	
x	=	0.320	
S	=	0,032	

12. It was not certain whether or not this detonator could pass the temperature, humidity cycling test (Mil-Std-304) because the device does not have a hermetic seal. However, it was of interest to know just how long a period of time could be tolerated by the detonator in this environment. Therefore, samples were withdrawn from the conditioning test chamber after 7, 14, and 21 days. Functioning in the test fixture after withdrawl gave the following results:

	Delay T	ime (seco	onds)
	7 Days	14 Days	21 Days
N	10	10	10
x	0.333	0.350	0.357
s	0.008	0,019	0.021

The results of this test were very encouraging in that it indicated that although the device was not hermetically sealed, the epoxy resin seal was adequate and the surveillance characteristics of the detonator appeared to be good.

DISCUSSION

13. The nature of this development program required a quick-fix in the shortest possible time. There is always an element of risk in such a program due to the lack of time to contemplate the design and an insufficient test program to uncover any weaknesses that may exist in the device. Employed in the design of this device were the latest techniques and materials of pyrotechnic delay construction. Experience and engineering judgment resulted in a design which appears to have met the requirements imposed. The delay detonator is readily initiated from the Mk 156 Mod 0 Primer which will be used in the AN-M173Al modified fuze. It is not known whether the manner in which the primer is used in the test fixture imposes a penalty on the initiation of the detonator. It appears to be a penalty when it is compared with the manner in which it is used in the fuze.

14. The output of the detonator was determined to be adequate by its ability to initiate the terryl pellet in the fuze high order. This was further confirmed in field tests. The engineering tests conducted on the lot of 184 detonators yielded very little output data because of an error when the lot of detonators was loaded. The delay composition and igniter composition are loaded at a pressure of 30K psi. The lead azide and RDX are loaded at a pressure of 10K psi. During the loading of the detonators (184) the lead azide was inadvertently pressed at 30K psi. This loading pressure is approaching the "dead press" region for lead azide which can result in low order initiation. On the other hand, if the lead azide initiates high order, the detonation velocity and pressure will be greater at the higher densities; hence, an expected higher dent value. Consequently, the depth of dents observed in the steel witness blocks varied from no dent to 26 mils. Properly loaded detonators are known to give dents approximately 23 mils deep.

15. While the engineering tests were in progress, an independent group in the Laboratory was loading a lot of 3000 detonators for field testing and Laboratory evaluation. The hardware and tooling used were based on the preliminary drawings generated during the development program. No problems were encountered in the loading. Uniform delay times and output values were obtained on samples drawn at random while this lot of detonators was being fabricated.

16. The drawings and specifications for the detonator are finalized and are covered in LD-549737 and WS-6491 respectively. A portion of the 3000 detonators loaded by NOL was evaluated by an independent group. It was determined that the detonator was adequate for use in the modified fuze, that it could be properly retrofitted, and that the requirements of the drawings and specifications had been met.

17. Some of the engineering tests conducted, such as jolt, jumble, and 40-foot drop are safety tests. The criteria for passing these tests are that the items shall not initiate or become unsafe to handle or dispose of. It is not required that they function after these tests. The fact that they did meet the requirements of the test and functioned properly afterwards, is indicative of the ruggedness of the design.

Star P.

.4

18. Throughout the testing of this detonator (engineering, evaluation, and field) there was no known case of an instantaneous detonation or of a detonator dudding.

CONCLUSIONS

19. A delay detonator, the Mk 97 Mod 0, has been developed and has met the standard Navy rough handling and surveillance tests normally applied to such items. It has been demonstrated from laboratory and field testing, that the detonator is suitable for use in the modified AN-M173Al Fuze.

REFERENCES

- 1. Encyclopedia of Explosives and Related Items, Volume 1, Picatinny Arsenal, Dover, New Jersey
- 2. The Journal of the JANAF Fuze Committee, 'Some Aspects of Pyrotechnic Delays', Serial No. 22-0
- 3. NOLTR 63-256, "The Development of the Detonator, Delay WOX-60A", V. J. Menichelli, C. L. Scott, Nov. 1963
- 4. Mil-Std 316, "Detonator Output Measurement by the Steel Dent Test"

1 25

E.



7

2.1



FIG. 2 EXPLOSIVELY MODIFIED AN-M173A1 FUZE

NOLTR 66-134 EPOXY SEAL BOTH ENDS SLOTTED BAFFLE 0. "002 THICK ALUMINUM DISK BOTH ENDS -IGNITER COMPOSITION A-IA - MANGANESE DELAY COMP 0. "600 -IGNITER COMPOSITION A-IA - SLOTTED BAFFLE - LEAD AZIDE - RDX 0."400 DIAM.

FIG. 3 DETONATOR, DELAY MK 97 MOD 0

9

7 1

-----!





FIG. 5 ENGINEERING TEST SCHEDULE FOR THE MK 97 MOD 0 DELAY DETONATOR

11



DOCUME	INT CONTROL DATA - R&D
(Security classification of title, body of abstract as	nd indexing annotation must be entered when the overall report is classified)
ORIGINATING ACTIVITY (Corporate author)	20 REPORT SECURITY CLASSIFICATION
Naval Ordnance Laborator	UNCLASSIFIED
White Oak, Maryland	- Zo SROUP
REPORT TITLE	
DEVELOPMENT OF THE MK 97	MOD 0 DELAY DETONATOR
DESCRIPTIVE NOTES (Type of report and inclusive du	(aiss)
FLSAL	
MENICHELLI, Vincent J.	
REPORT DATE	78. TOTAL NO. OF PAGES 75. NO. OF REFS
19 July 1966	13 4
8. CONTRACT OF GRANT NO.	SS. ORIGINATOR'S REPORT NUMBER(5)
5H-03	W110- NOLTR 66-134
c.	\$5. OTHER REPORT NO(\$) (Any other numbers that may be assign this report)
	-
This document is subjec	t to special export controls and each
This document is subjec transmittal to foreign supplementary works	t to special export controls and each governments or foreign nationals may be provel of NOL 12 sponsoring military activity
The supplement of the subject of the supplementary notes with supplementary notes of the supplementary notes	t to special export controls and each governments or foreign nationals may be proved of NOL 12 sPONSORING MILITARY ACTIVITY NOSC
AVAILABILITY/LIMITATION NOTICES T!.is document is subjec transmittal to foreign .supplement is subjec .supplement is supplement is subjec .supplement is supplement i	t to special export controls and each governments or foreign nationals may be proval of NOI 12 sPONSORING MILITARY ACTIVITY NOSC
AVAILABILITY/LIMITATION NOTICES This document is subjections transmittal to foreign supplementary notes ABSTRACT A nominal 0.3 second, fla developed for the AN-M17 were subjected to standa tests. These tests were evaluation of the detona detonator. The detonato and specifications.	sh-initiated, delay detonator has been Sh-initiated, delay detonator has been all Fuze. A limited number of detonator rd Navy rough handling and surveillance successfully met. An independe::t tor confirmed the soundness of the or is completely documented with drawing
AVAILABILITY/LIMITATION NOTICES This document is subject transmittal to foreign mode only with prior op supplementary notes ABSTRACT A nominal 0.3 second, fla developed for the AN-M17 were subjected to standa tests. These tests were evaluation of the detona detonator. The detonato and specifications.	t to special export controls and each governments or foreign nationals may be proval of NOL is sponsoning military activity NOSC sh-initiated, delay detonator has been 3Al Fuze. A limited number of detonator rd Navy rough handling and surveillance successfully met. An independent tor confirmed the soundness of the or is completely documented with drawing

ŧ

7

. . . .

••

KEY WORDS				LIN			N C
		AOLE	WT	ROLE	WT	ROLE	WT
Detonator Delay							
INSTRU	CTIONS						l
 Ordestrict in subcontractor, grantes, Department of Defense activity or other organization (corporate author) issuing the report. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included Marking is to be in accordance with appropriate security regulations. GROUP: Automatic downgrading is specified in DoD Directive 5200. 10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all capitals in parenthesis immediately follo wing the title. DESCRIPTIVE NOTES: If acyopriate, enter the type of report, e.g., interim, progress, sum ary, annual, or final. Give the inclusive dates when a specific reporting period is covered. AUTHGA(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If militory, show rank and branch of service. The name of the principal author is an absolute minimum requirement. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report. OF PAGES: The total page count abould follow normal pagination procedures, i.e., enter the number of pages containing information. NUMBER OF REFERENCES: Enter the total number of references ciled in the report. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report number, system numbers, task number, etc. ONGINATOR'S REPORT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the document will be identified and controlled by the origination grant which the document will be identified and controlled by the origination growed (sitter by the originator or by the o	imposed b such as: (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	y security Qualified port from Foreign a sport by D U. S. Gov his report sers shall U. S. milli sport direchall reque hall distri fied DDC All distri fied DDC for a popear a clean de clean de	classifie requeste DDC " innounces DC is no ernment : directly i request tary ager city from rest throug bution of users sho is been fur to form nter the g ARY NOT MILITAR bject offi h and dev Enter an a ument ind elsewhere space is irable this agraph, n itation on length is Key word security ment mod geographi Illowed by nt of link	cation, us rs may ob hent and of t authoriz agencies from DDC through incies may DDC. Oth this reposed all request mished to a erce, for orace, if k FES: Uso Y ACTIV ce or labor required, at the abir required, at the abir required, at the lenge from 150 s are tecl lerize a re the report classifici- lel design y an indices, rele, rele, the report classifici- lel design	dissemin. red." may obtain copy obtain cop	aird state ies of thin ation of the in copies qualified opies of i fied user trolled. (the public trolled. (the public tional exponsoring e address wrief and fort, even is e technical ation of the classified	ments in a second in a second
					TRIED		
			UN	Security	Classi	fication	

15

.....

100

Secting Chost Parts