

(Security slassification of sitte, be	POCUMENT CONTROL DA	l j A − K G U I must be antered when √	·· evali sepet is classified;			
1- OAISMATING ACTIVITT (Comercie auto	2	30. REPO.1	CURITY CLASSIFICATION			
Foreign Technolo	gy Division	UNC	UNCLASSIFIED			
IL S. Air Force	is command					
3. REPORT TITLE		<u>.</u>				
EFFECT OF SLIDIN	G FRICTION MODES O	N EXOELECTRO	N			
EMISSION PARAMEI	erd .					
4. DESCRIPTIVE HOTES (Type of report and	Inclusivo datos)		ومريوس معاد المحارب بالمحادث والمحاد المحاد والمحاد والمحاد			
'I'RANS LATION 8- AUTHOR:S) (First memo, addite initial, ia						
Konshunov I C	······					
Korshullov, D. G.						
S. REPORT DATE	TA TOT	AL NO. OF PASER	78. NG. OF REFS			
1969		5.	15			
SE. CONTRACT OR GRANT NO.	96. 9 RI	INATOR'S REPORT NU	MBER(\$)			
A PROJECT ND. 7343						
	F	FTD-HC-23-1844-71				
¢,	51. 07H	ER HEPORT HO(S) (AN	other numbers that may be seal			
ek.		•				
10. DISTRIBUTION STATEMENT						
Approved for put	lic release; distr	ibution units	nited.			
Approved for put	lic release; distr	Ibution unlin				
Approved for put	lic release; distr	ibution unlin HODAING MLITARY AC Foreign Tech	nited.			
Approved for put	lic release; distr	ibution unlin HEARKE MLITARY AC Foreign Tech Wright-Patte:	nology Division rson AFB, Ohio			
Approved for put	lic release; distr	Bution unlin BEARSE MLITARY AC Foreign Techn Wright-Patte:	nited. Tivity nology Division rson AFB, Ohio			
Approved for put	lic release; distr	ibution unlin HEERING MLITARY AC Foreign Techn Wright-Patte:	nology Division rson AFB, Ohio			
Approved for put	lic release; distr	Bution unlin Foreign Techn Wright-Patte:	nited. Tivity nology Division rson AFB, Ohio			
Approved for put	ated electron emis	ibution unlin BEARE MLITARY AC Foreign Techn Wright-Patte: sion of 40Kh:	nited. nology Division rson AFB, Ohio 10G1C steel			
Approved for put	ated electron emis	Sion of 40Kh	nited. Tivity nology Division rson AFB, Ohio 10G1C steel rent sliding			
Approved for put	ated electron emis ated sliding frict s studied in a vac	sion of 40Kh um using a s	10G1C steel rent sliding secondary			
Approved for put	ated electron emis d to sliding frict s studied in a vac ier. Also measure	Sion of 40Kh um using a side the main of the second	nology Division rson AFB, Ohio 10G1C steel rent sliding secondary agnitude of resistance.			
Approved for put 	ated electron emis d to sliding frict s studied in a vac ier. Also measure termediate contact of friction, and t	sion of 40Kh ion at diffe uum using a electrical he emf occur	10G1C steel rent sliding secondary agnitude of resistance, ring under			
Approved for put 	ated electron emis d to sliding frict s studied in a vac ier. Also measure termediate contact of friction, and t increases from 0.	sion of 40Kh ion at differ uum using a d were the ma he emf occur: 75 to 4.5 m/	10G1C steel rent sliding secondary agnitude of resistance, ring under sec, two maxima			
Approved for put 	ated electron emis ated electron emis d to sliding frict s studied in a vac ier. Also measure termediate contact of friction, and t increases from 0. ermally stimulated 70 and 270 degrees	sion of 40Kh ion at diffe: uum using a d were the m electrical he emf occur: 75 to 4.5 m/ electron emi C. A more	10G1C steel rent sliding secondary agnitude of resistance, ring under sec, two maxima ission curves intense thermal			
Approved for put 	ated electron emis d to sliding frict s studied in a vac der. Also measure termediate contact of friction, and t increases from 0. mermally stimulated 70 and 270 degrees fron emission is ob	sion of 40Kh ion at diffe uum using a d were the m electrical he emf occur: 75 to 4.5 m/ electron em C. A more served after	10G1C steel rent sliding secondary agnitude of resistance, ring under sec, two maxima ission curves intense thermall sliding with			
Approved for put	ated electron emis d to sliding frict s studied in a vac der. Also measure termediate contact of friction, and t increases from 0. ermally stimulated 70 and 270 degrees fron emission is ob- bec, and this also	sion of 40Km wright-Patter Wright-Patter wright-Patter d were the ma electrical he emf occur: 75 to 4.5 m/ electron emi C. A more served after produces great	10G1C steel rent sliding secondary agnitude of resistance, ring under sec, two maxima ission curves intense thermall sliding with ater wear.			
Approved for put 	ated electron emis d to sliding frict s studied in a vac der. Also measure termediate contact of friction, and t increases from 0. mermally stimulated 70 and 270 degrees fron emission is ob- bec, and this also	sion of 40Kh vere the main d were the main electrical the electron emin C. A more the served after produces great	10G10 steel rent sliding secondary agnitude of resistance, ring under sec, two maxima ission curves intense thermall sliding with ater wear.			
Approved for put 	ated electron emis d to sliding frict s studied in a vac der. Also measure termediate contact of friction, and t increases from 0. mermally stimulated 70 and 270 degrees fron emission is ob- bec, and this also	sion of 40Kh ion at diffe uum using a d were the m electrical he emf occur: 75 to 4.5 m/ electron emi C. A more served after produces grea	10G1C steel rent sliding secondary agnitude of resistance, ring under sec, two maxima ission curves intense thermall sliding with ater wear.			
Approved for put 	ated electron emis d to sliding frict s studied in a vac der. Also measure termediate contact of friction, and t increases from 0, mermally stimulated 70 and 270 degrees fron emission is ob- ac, and this also	sion of 40Kh ion at diffe uum using a d were the m electrical 75 to 4.5 m/ electron em C. A more served after produces grea	10G10 steel rent sliding secondary agnitude of resistance, ring under sec, two maxima ission curves intense thermall sliding with ater wear.			
Approved for put 	ated electron emis d to sliding frict s studied in a vac der. Also measure termediate contact of friction, and t increases from 0. mermally stimulated 70 and 270 degrees fron emission is ob ec, and this also	sion of 40Kh ion at diffe uum using a d were the m electrical he emf occur: 75 to 4.5 m/ electron em C. A more served after produces grea	10G1C steel rent sliding secondary agnitude of resistance, ring under sec, two maxima ission curves intense thermall sliding with ater wear.			
Approved for put IN SUPPLEMENTARY NOTES IN ABSTRACT Thermally stimuly samples subjected velocities Nu was electron multiply induced wear, in the coefficient friction. As Nu appear on the th in the regions for stimu .ted elector V equals 4.5 m/s [AR1024933]	ated electron emis d to sliding frict s studied in a vac der. Also measure termediate contact of friction, and t increases from 0, termally stimulated 70 and 270 degrees fron emission is ob- sec, and this also	sion of 40Kh ion at diffe uum using a d were the m electrical 75 to 4.5 m/ electron em C. A more served after produces grea	10G1C steel rent sliding secondary agnitude of resistance, ring under sec, two maxima ission curves intense thermall sliding with ater wear.			
Approved for put 	ated electron emis d to sliding frict s studied in a vac ier. Also measure termediate contact of friction, and t increases from 0. ermally stimulated 70 and 270 degrees fron emission is ob sec, and this also	sion of 40Kh ion at diffe uum using a d were the m electrical he emf occur 75 to 4.5 m/ electron em C. A more served after produces grea	10G1C steel rent sliding secondary agnitude of resistance, ring under sec, two maxima ission curves intense thermall sliding with ater wear.			
Approved for put 	ated electron emis ated electron emis d to sliding frict s studied in a vac der. Also measure termediate contact of friction, and t increases from 0, mermally stimulated 70 and 270 degrees fron emission is objec, and this also	sion of 40Kh ion at diffe uum using a d were the m electrical the emf occur 75 to 4.5 m/ electron em C. A more served after produces grea	10G10 steel rent sliding secondary agnitude of resistance, ring under sec, two maxima ission curves intense thermall sliding with ater wear.			

a starting

AND ADD ADD

HALLSREEMANDERSTREEM

ションションクレンドによった。

į

CONTRACTOR OF

1991 - DA

AREA INTERACTOR

an in georae our hear an STA and ATA AND AND LADE AND ATA AND ATA AND ATA AND ATA AND ATA ATA

έ.

EQ:

UNCLASSIFIED .

stémati

CARLESS IN MARCHER

の人にたちま

- A- P

2

	Lin	LINK A		LINK		LINE C	
KEY WORDS	ROLE		ROLE	=T	ROLE		
			[
Electron Emission		İ			1		
Metal Friction		Į					
Friction Coefficient							
Vacuum		j	j				
Electron Multiplier					Ì		
Wear Resistance	l l	, ·					
Electric Resistance			1		1		
Electromotive Force	ł	1			1		
Steel		1					
(U)40Kh10G10 Steel		Í					
•	ł	1			i		
	1	l			1		
	1]	}				
· ·		1					
		[
·							
			1				
			[
4							
			•				
	1						
				•			
	1				I		
	1						
	l l				1		
]				I		
•							
-							
•							
					1		
		1	1	í	- 1		

1.24

FTD-HC-23-1844-71

UNEDITED ROUGH DRAFT TRANSLATION

by Joint Publications Research Services

EFFECT OF SLIDING FRICTION MODES ON EXOELECTRON EMISSION PARAMETERS

By: L. G. Korshunov

English pares: 5

Source: Ural'skiy Folitekhnicheskiy Institut. Trudy (Ural Political Institute, Transactions) 1969, pp. 53-57

Approved for public release; distribution unlimited.

UR/0000-69-000-000

THIS TRANSLATION IS A RENDITION OF THE ORIGI-NAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES. ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DI-VISION.

PREPARED BY:

TRANSLATION DIVISION FOREIGN TECHNOLOGY DIVISION WP-AFB, OHIO.

FTD-HC-23-1844-71

Date <u>3 April 1972</u>

EFFECT OF SLIDING FRICTION MODES ON EXOELECTRON EMISSION PARAMETERS

/Article by L. G. Korshunoye; Sverlovsk, <u>Trudy Ural'skogo Politekhnicheskogo Institute imeni S. M. Kirova(Works of the Urals</u> Polytechnical Institute imeni S. M. Kirov), Russian, No 177, pp 53-57, 1969/

Friction of metals is a complex physical and chemical process. Plastic deformation occurs where friction exists in the surface layers of a metal with a high volocity due to intensive heating up of both submicro- and nicrovolumes and macrovolumes of the surface layers. The amount of heat liberated in friction encunts to almost 75% of all the external expended mechanical work /l/. High temperatures develop on the friction surface which reaches the melting points of the working metals /2/ or even exceeds them /3/.

Strain and strong heating up promotes high activity of the surfacelayers which leads to intensive interaction with the surrounding medium, to the occurrence of diffusion processes, phase transformations, etc., in them and to the development of a new structure in the surface layers which is different from the initial structure in chemical and phase composition /4, 5/. The friction process is also accompanied by electrical phenomena--thermoelectronic, thermoionic and excelectronic emissions as well as thermoelectrical processes /6-9/. Electrification of the working metals takes place as a result of the occurrence of these processes.

Excelectron emission with the surface of metals (Kramer's effect) is an energy characteristic of processes taking place during deformation /10/. The intensity and kinetics of excelectron emission for contact interaction have been linked with change of electron work function /10/ which for metals can essentially change during deformation due to phase transformations and processes of chemisorption, oxidation, etc. in the surface layers /11, 12, 13, 14/. Consequently, excelectron emission cerries in itself significant information about phenomena occurring in the surface layers of deformed metals.

Results are presented in this work of investigations into the effect of sliding friction modes on the parameters of thermally stimulated excelectron emission. Tests were conducted on a disk friction machine the element of which consisted of a calibrated rotating disk 70 mm in diameter and 9-mm thick. A sample 8 mm in diameter and 50-55 mm long was clamped to the disk surface under the action of an external lead with the plane. The calibrated disks were made of steel 4khl3 and after heat treatment has a hard-

1

FTD-HC-23-1844-71

alioenternen andread harinen etteren andreateria der tieden der tieden die het tieden die hette statigen statig

ness of R_c 50. The samples were made of steel 40Kh10G10 and had r purely fustenitic structure in the initial condition.

Tests were conducted with an external load of 2.5 kG in the range of slip rates of 0.75-7.5 m/sec. Friction path was 10,000 meters long. The following magnitudes were measured in the process of friction: weight wear, transient contact electrical resistance, average temperature on the sample friction surface and the emf forming during friction.

Thermally stimulated excelectron emission with the friction surface of a sample was recorded immediately after vacuum testing $(2r10^{-5} \text{ mm H g})$ with the aid of a secondary electron multiplier. The apparates and method of recording ex electron emission have been described in work /15/.



Fig. 1. Thermally stimulated excemission of steel 40Kh10G10 after friction at sliding velocities of: 1-4.5 m/sec; 2--7.5 m/sec; 3--0.75 m/sec; a--Pulses/sec; b--t, minutes.

Results of investigating the magnitude and nature of excelectron emission from a friction surface after testing steel 40Kh10Gl0 at different slip rates have been presented in Fig. 1. Analysis of the data shows that the intensity of excelectron emission and the nature of its change in heating depend on the friction mode. The temperature relationship of excemission for samples tested at slip rates of 0.75 m/sec has the form of a saturation curve. Upon heating, two maximums were discovered for samples having slip rates of 4.5 and 7.5 m/sec.

After comparing the obtained relationships it was possible to note that the change in slip rate leads to a difference in the maximum intensity of exoclectron emission as well as in the temperature position of the maximums. Moreover, it was established that heating the samples to 350 C and holding them at this temperature for one hour did not reduce the intensity of exocmission to a background level.

FTD-HC-23-1844-71

a the second second should be

Neasurement of the respective parameters was done to establish the interrelationship of excemission parameters with the characteristics of friction and wear. The nature of change in magnitudes of reduced wear Q_{rw} (1), transient contact electrical resistance R_c , kohm (2), friction coefficient K_f (3) and emf (4) which forms during friction in relationship to slip are shown in Fig. 2. (b)



Fig. 2. Change in the characteristics of friction and wear for steel 40KhlOGlO in relation to slip rate: a--Kr; b--Q, mg/1000 m; c--emf, mv; d--slip rate, m/sec.

Electromotive force, measured for friction in this case, is one of the integral characteristics of the processes occurring on the surface of metals. The magnitude and sign of it are determined not only by the physical nature of the contacting metals and temperature on the surface but also by the nature of interaction of the working metals with the surrounding medium. Development of oxidizing and other processes on the surface, associated with the formation of films on them, which differ in nature, are reflected in the changes of magnitude and then the sign of the emf formed during friction /8, 9/.

For a slip rate of 0.75 m/sec on the friction surface an oxide film is formed whose stability bears out the high values of transient contact electrical resistance and coefficient of friction as well as a comparatively small magnitude of reduced wear. The emf at this slip rate has the greatest values and a negative sign.

With increased slip rate up to 1.5 m/sec the transient contact electrical resistance and friction coefficient sharply drop while wear increases. This testifies that the oxide film forming on the surface is unstable. As a result of its rupture the area of purely metallic contact increases and grasping processes actively occur. Here the emf decreases by approximately 4 times. Upon subsequent increase in the slip rate the intensity of grasping is increased, no visible oxide film forms on the friction surface of the sample and wear achieves its highest value.

In the 4.5-7.5 m/sec range of slip rates, wear is reduced. On the friction surface an oxide film was noted. A lowering of FTD-HC-23-1844-71

emf in the examined range of slip rates can be associated with the fact that slip rates greater than 4.5 m/sec on the friction surface probably cause the formation of an oxide of another type which is thermoelectric and iriction properties (low coefficient of friction) and differs from those which posses oxides forming at slip rates below 4.5 m/sec. Conditions of oxide film failure on the friction surface renders a considerably greater effect on the exf magnitude than increased average temperature of the sample curface with an increased slip rate--emf with an increased temperature does not increase.

Comparison of the data in Figs. 1 and 2 makes it possible to make certain conclusions about the effect of sliding friction modes and the physical and chemical processes occurring here on the nature of thermally stimulated excemission. Formation of an oxide film on the friction surface at slip rates of 0.75-7.5 m/sec cauces a lowering of the emission intensity which was probably associated with the formation of chemisorbed and oxide layers leading to increased electron work function /12, 13/. Emission of the greatest magnitude can be observed on the surfaceof a sample the testing mode of which promoted the occurrence of grasping process and intense wear.

The presence of low-temperature maximum and point of discontinuity (at rates of 0.75 m/sec) on the emission curves can be caused by an $\leftrightarrow\gamma$ transformation occurring during heating. Hicrostructure studies showed that \leftarrow martensite is formed in the surface layers of steel 40Kh10G10 at slip rates of 0.75-7.5 m/sec.

Thus, these experiments indicate the existence of an interrelationship between excelectron emission and the most important processes taking place on the surface of metals for different friction modes.

BIBLIOGRAPHY

- 1. Kuznetsov, V. D., Fizika Tverdogo Tela (Solid State Physics), Tomsk, Vol 4, 1947.
- 2. Bouden, F. P. and Teybor, D., <u>Treniye i Smazka</u> (Friction and Lubrication), Moscow, 1960.
- 3. Thiessen, R. A., Gragert, E. and Meyer, F., Monatsber. Akad. Wiss., Berlin, Vol 6, No 8, 574-576, 1964.
- 4. Lyubarskiy, I. M., "Increasing Wear of Heavily Loaded Gears", <u>Kashinostroyeniye</u> (Machine Building), Moscow, 1965.
- 5. Golero, N. A., "Seizure in Machines and Methods of Its Elimination", Tekhnika (Engineering), Moscow, 1963.
- 6. Dubinin, A. D., Energetika Treniya i Iznosa Detaley Mashin

FTD-HC-23-1844-71

(Energetics of Friction and Wear of Machine Parts), Moscow, 1963.

- 7. Yevdokimov, V. D., <u>Izerciya Vysshikh Uchebnykh Zavedeniy-</u> <u>Fizika</u> (Reports of the iniversities--Physics), No 4, 23, 1968.
- 8. Korshunov, ... G. and Mints, R. T., FKhMM, No 4, 393, 1967.
- 7. Rudnits iy, A. A. Elektricheskiy Kontakty--Sbornik, Trudy Sovethel miya 26-28 Noyabrya 1956 (Electrical Contacts--Collection Jork of the 26-8 November 1956 Conference), Moscow, 1964
- 10. Mints, R. J. and R. M. V. S., Ibid. 7, No 3, 44, 1968.
- 11. Andreyev, ". A. for alige, Ya., Doklady Akademii Nauk SSSR (Reports of the A geomy of Sciences USSR), No 152, 1086, 1963.
- 12. Holmes, R., <u>ectrical Contacts</u>, Moscow, Foreign Literature Publishing Mouse, 1961.
- 13. Shaffs, I., <u>Excelectron Emission</u>, Moscow, Collection of articles edited by N. I. Kobozev, p 295, 1962.

14. Bogachev, I. N., Yegolayev, V. F., Kortov, V. S. and Mints. R. I., <u>Fizika Metallov i Metallovedeniye</u> (Metal Physics and Physical Hetallurgy), Vol 22, No 4, 674, 1967.

15. Fortov, V. 3., and Mints, R. I., Zavodskaya Laboratoriya (Plant Laboratory), no 9, 1144, 1906.